Characterization of Groundwater with Complementary Age Tracers

by

Monique Beyer

A thesis submitted to the Victoria University of Wellington

in fulfilment of the requirements for the degree of Doctor of Philosophy

Victoria University of Wellington

2015

Abstract

Groundwater age or residence time is the time water has resided in the subsurface since recharge. Depending on the application, this definition may or may not include travel through the unsaturated zone. The determination of groundwater age can aid understanding and characterization of groundwater resources, because it can provide information on e.g. groundwater mixing and flow, and volumes of groundwater and recharge. Groundwater age can be inferred from environmental tracers, such as SF₆ and tritium, that have a known input to groundwater and/or undergo known alteration processes in groundwater. The currently used age tracers face limitations regarding their application range and reliability. For example, some age tracers have local sources that can lead to contamination of groundwater. This contamination can result in misleading estimates of age. Other tracers have ambiguous inputs to groundwater, which can result in ambiguous age estimations. To reduce these limitations, it is now recognized that multiple tracers should be applied complementarily. There is also a need for new groundwater age tracers and/or new groundwater dating techniques to supplement the existing ones. Cost-effective and easily applicable tracers/techniques are preferred, since most established groundwater dating techniques are very costly and/or complex. Commonly measured hydrochemistry parameters¹, such as the concentrations of major ions and pH, have been suggested as cost-effective and easily determinable potential age tracers. To date, the use of commonly measured hydrochemistry parameters as independent age tracer has only been demonstrated for water recharged weeks to months ago relying on seasonal changes. Other studies applied commonly measured hydrochemistry complementarily to established age tracers to better constrain groundwater age and/or better understand and predict anthropogenic effects on groundwater quality. Further study is needed to assess the extent to which commonly measured hydrochemistry can be used to reduce uncertainty in tracer-inferred age as well as the extent to which commonly measured hydrochemistry can be used to extrapolate tracer-inferred age.

In addition to tracer specific limitations, quantification of uncertainty and ambiguity is not standard in age modelling. Although a few studies have attempted to quantify uncertainty in age modelling with the aid of probabilistic approaches, their methods are often relatively complex and not transferrable to the many cases with little available data. Uncertainties in the tracer's recharge estimate and identification of appropriate model components, such as the objective function, have not been considered. Studies in other areas of hydrological modelling, where probabilistic approaches are more commonly used, have highlighted the need for careful identification of model components.

¹ In this thesis, the term commonly measured hydrochemistry refers to relatively easily determinable and widely available parameters such as the concentrations of major ions, pH and conductivity. It does not include the concentration of isotopic compounds or other compounds that have been applied as groundwater age tracers.

This thesis aims to address the needs for additional complementary age tracers and a more comprehensive consideration of uncertainty in age modelling. This study is particularly concerned with improving the characterization of groundwater recharged a few months to ~100 years ago. Progress in three areas is made. Firstly, a new groundwater age tracer is presented, namely Halon-1301. Its discovery and the assessment of its performance as an age tracer against the established age tracers, namely tritium, SF₆, CFC-12 and CFC-11, in a range of groundwater environments are detailed. Secondly, age modelling is placed into a relatively simple and transferable probabilistic framework that allows for quantification of uncertainty in inferred age and the assessment of relevant model components and model uncertainties. The framework is applied to tritium, SF₆ and Halon-1301 data in a New Zealand gravel aquifer. Thirdly, the potential of commonly measured hydrochemistry for use as a complementary age tracer for groundwater recharged days to ~100 years ago (and as an age proxy and indicator for recharge sources and weathering processes) is demonstrated.

The main findings of this thesis include:

- Strong evidence is provided that Halon-1301 can be used as a (complementary) groundwater age tracer to date groundwater recharged after 1980. Age is reliably estimated with Halon-1301 in the majority of studied water samples from various groundwater environments. In a few relatively old anoxic waters reduced concentrations of Halon-1301 are observed which interfere with the age estimation. These were likely caused by degradation or sorption of Halon-1301 in the aquifer.
- When placing age modelling into a relatively simple, transferable probabilistic framework, each individual uncertainty in model input and its relevance towards uncertainty in the age estimate is assessed in detail. Guidance is provided on how to identify the most appropriate objective function and most appropriate and relevant model inputs and uncertainties by assessing their performance with quantitative criteria. It is demonstrated that uncertainty in inferred age can be significant (of the order of decades) and should be considered for robust groundwater dating. Application of the framework to Halon-1301 data enabled further assessment of its performance as an age tracer when used alone and in combination with tritium and/or SF₆.
- The complementary use of commonly measured hydrochemistry parameters and established age tracers is shown to be advantageous. With the aid of a single robust tracer-inferred age estimate, age information at the remaining sites were estimated purely using hydrochemistry. If used in combination with established age tracers, hydrochemistry also helped resolve ambiguity and reduce uncertainty in tracer-inferred age information. The complementary use of hydrochemistry and established age tracers also helped identify recharge source(s) and infer weathering rates, which can aid groundwater characterization.

Acknowledgements

This thesis is associated with the 'SMART aquifer characterization project', which aims to develop SMART (Save Money And Reduce Time) techniques which allow for the characterization of groundwater resources. Its objective is to improve the understanding of groundwater resources for sustainable groundwater management and protection. The focus of this study is on the determination of groundwater age and mixing, while other parts of the 'SMART' project focus on the remaining aims, such as the characterization of groundwater-surface water interaction.

This thesis contains excerpts of the following published work:

- Beyer, M.; Morgenstern, U.; Jackson, B. (2014) Review of dating techniques for young groundwater (<100 years) in New Zealand. *J. Hydrol. New Zealand* 53(2), 93-111. (Chapter 1 and 2 of this thesis)
- Beyer, M.; van der Raaij, R.; Morgenstern, U.; Jackson, B. (2014) Potential groundwater age tracer found: Halon-1301 (CF₃Br), as previously identified as CFC-13 (CF₃Cl), *Water Resources Research* 50, doi:10.1002/2014WR015818. (Chapter 4 of this thesis)
- Beyer, M.; van der Raaij, R.; Morgenstern, U.; Jackson, B. (2014) Assessment of Halon-1301 as a groundwater age tracer, *Hydrol. Earth Syst. Sci.* 19, 2775-2789, doi:10.5194/hess-19-2775-2015. (Chapter 4 of this thesis)
- Beyer, M.; Jackson, B.; Daughney, C.; Morgenstern, U., Norton, K. (2016) Assessment of hydrochemistry as a standalone and complementary age proxy, *J. Hydrol.* doi:10.1016/j.jhydrol.2016.05.062 (Chapter 6 of this thesis).

The following work is in preparation:

- Beyer, M.; Jackson, B.; Daughney, C.; Morgenstern, U. (under review) Quantifying uncertainty in age estimation from environmental tracers, *J. Hydrol.* (Chapter 5 of this thesis)

Due to prior publication of parts of this thesis and preparation for publication of other parts, the majority of figures are displayed in black and white. Effort was made to align the size and style of the figures throughout this thesis that had been created in various programmes and software. The author apologizes if this was not made to the full satisfaction of the reader.

I have received feedback and advice on this work from my supervisors Bethanna Jackson (VUW) and Uwe Morgenstern (GNS Science), and colleagues Chris Daughney, Rob van der Raaij (both from GNS Science) and Deborah Maxwell and Kevin Norton (both from VUW). The bulk of this work and the analysis have been carried out by me. I thank Uwe Morgenstern and the staff of Greater Wellington Regional Council (GWRC), in particular Sheree Tidswell, for their help with collection of groundwater samples (in 2013 and 2014). GWRC is also thanked for provision of aquifer material that I analysed on a microprobe with help of Ian Schipper (microprobe technician) and Stewart Bush (thin section

preparation) (both from VUW). I acknowledge Rob van der Raaij's introduction to the analytical system that I used for analysis of Halon-1301 and feedback I received on a GUI (graphical user interface) that I built to demonstrate the probability framework presented in this study from my colleagues at GNS Science, in particular Chris Daughney, Rob van der Raaij and Mike Toews, Mike Friedel and Mike Stewart. Stephen Mawdesley (mechanical engineering workshop at GNS Science) is thanked for building/repairing various field and lab equipment. Vanessa Trompetter (GNS Science) is acknowledged for the organization of lab equipment and accommodation for conference visits. I would also like to acknowledge Rowena Moss and Ross Martin (both from NIWA - National Institute for Water and Atmospheric research) for providing a Halon-1301 standard gas. GNS Science is thanked for access to tritium, SF₆, CFCs, excess air and recharge temperature data. GWRC is thanked for access to historical major hydrochemistry data.

This PhD would have not been possible with the financial support (and other resources) from GNS Science, MBIE (Ministry of Business, Innovation and Employment) and Victoria University of Wellington, in particular the Faculty of Science and the School of Geography Environment and Earth Sciences and the patience and support of my supervisors Beth and Uwe. I would also like to thank my colleagues at GNS Science (in particular Chris Daughney, Rob van der Raaij, Mike Toews, Mike Friedel and Mike Stewart) and colleagues at VUW (Deborah Maxwell, Martha Trodahl and the rest of hydrology group) for helpful discussions on various conference presentation drafts and a bicycle sponsored by Kurt McBeth (GNS Science) that allowed me to commute to GNS Science.

My colleagues from the PGSA (Postgraduate Students' Association at VUW) and 'Kaibosh - Food Rescue' as well as my rowing mates from the Wellington Rowing Club are thanked for helping me keep grounded. This PhD would have not been as enjoyable without the support of my friends and flatmates. In particular Angelique, Au, Denise, Fenty and Lydia are thanked for mental support and always having an open ear for me.

I would also like to thank the reviewers of this thesis, Peter Cook, Daren Goody and Dan Sinclair, for their valuable and constructive feedback.

Finally, I owe special thanks to my partner Eimantas Poskus and my family, particularly my Mom and Dad, for their endless support. Without them I would not have come this far.

Table of content

Abstract	i
Acknowledgements	iii
Table of content	v
1. Introduction.....	1
1.1 Background and context of this study.....	1
1.2 Aim and objectives of this study	3
1.3 Contribution of the thesis	4
1.4 Structure of the thesis.....	5
2. Background.....	7
2.1 Groundwater age definition	7
2.2 Determination of groundwater age distributions with Lumped Parameter Models.....	8
2.2 Tracer substances for dating relatively young groundwater (recharged < 100 y ago)	12
3. Study areas.....	19
3.1 Lower Hutt Groundwater Zone	23
3.2 Wairarapa and Wainuiomata aquifer	25
4. Halon-1301 a new groundwater age tracer	27
4.1 Introduction	27
4.2 Properties of Halon-1301 important for its use as a groundwater age tracer	27
4.3 Methods	30
4.3.1 Samples	31
4.3.2 Analytical procedure	33
4.3.3 Solubility	34
4.3.4 Calibration	35
4.3.5 Analytical uncertainty.....	35
4.3.6 Determination of recharge year.....	36
4.4 Results on the identification of Halon-1301 in groundwater.....	37
4.5 Results on the assessment of Halon-1301 as a groundwater age tracer	43
4.4 Chapter Summary and Conclusion.....	52
5. A probabilistic age (LPM) modelling framework.....	56
5.1 Introduction.....	56
5.2 General framework overview.....	57
5.2.1 Sources of uncertainty.....	57
5.2.2 General framework	58
5.2.3 Specific framework components used in this study.....	59
5.3 Study area specific framework components.....	63

5.4	Results	66
5.4.1	Most appropriate model components	66
5.4.2	Quantifying uncertainty in inferred age when using the most appropriate framework components.....	71
5.5	Chapter Summary and Conclusion	81
6.	Assessment of commonly measured hydrochemistry as a groundwater age tracer.....	86
6.1	Introduction.....	86
6.2	Methods	87
6.2.1	General method overview.....	87
6.2.2	Case study.....	92
6.3	Results	95
6.3.1	Identification of similarities/differences in hydrochemistry and sub-datasets	95
6.3.2	Inferring age information from hydrochemistry	97
6.4	Chapter Summary and Conclusion.....	107
7.	Main findings, conclusions and future research recommendations.....	112
7.1	Halon-1301, a new complementary groundwater age tracer.....	113
7.2	Achievements in LPM age modelling	115
7.3	Hydrochemistry, a (new) groundwater age proxy and complementary ‘age tracer’	117
7.3	Final summary	119
	References.....	122
	Appendix A – Available tracer data for studied groundwater sites	154
	Appendix B – for Chapter 4	158
	Appendix C – for Chapter 5	182
	Appendix D – for Chapter 6.....	237

1. Introduction

1.1 Background and context of this study

There is an increasing demand for access to sufficient quantities of ‘good quality’ groundwater, along with an increasing recognition of the importance of groundwater quality in maintaining ecological functioning (for freshwater and other ecological niches) [Gleeson et al., 2012]. However, groundwater has become subject to major human induced contamination and scarcity [Sampat, 2000]. Groundwater levels are decreasing due to ever increasing abstraction volumes driven by a growing population and industrialization, but also due to climate change. Groundwater recharge areas are increasingly impacted by e.g. land use, water supply and sewage system infrastructure. There are also natural sources of groundwater pollution such as heavy metals arising e.g. from geothermal processes or volcanic rock, or increased salinity levels as a result of saltwater intrusion into groundwater.

The complex and diverse recharge, mixing and flow processes need to be better understood in order to manage and protect groundwater resources [Dillon et al., 1989; White and Rosen, 2001; Close et al., 2001]. Two main approaches currently exist to characterize groundwater systems and their residence times, flows, recharge source, and aquifer volumes. In the first, hydrogeological models are developed based on lithology and hydrological data (e.g. water level, recharge area and porosity) to investigate groundwater flow, recharge and more recently to estimate groundwater age [e.g. Cornaton, 2012]. These models have shown to be very valuable as hypothesis testing tools, but these are ‘data hungry’ and complex to parameterize and set up [e.g. Castro and Goblet, 2005; Zuber et al., 2011]. In the second and more widely used, tracer substances, such as stable- and radio-isotopes and hydrochemical tracers, are used to infer groundwater age and/or recharge source [e.g. Małoszewski and Zuber, 1982; Nir, 1986].

Groundwater age, which is defined more formally in Chapter 2 of this thesis, is a measure of recharge year and residence time of a groundwater resource. Groundwater age information can aid assessment of not only recharge areas, flow paths and the amount of water that can be sustainably extracted, but also the lag-time and anticipated future loads of contaminants discharging from groundwater bodies [e.g. Visser, 2009]. For example, younger waters are generally more likely to be contaminated with man-made substances, due to recent leaching of pollutants (e.g. nitrate) into groundwater resources. A longer residence time of the water in the subsurface is likely to be associated with a lower risk of anthropogenic contamination. This is due to recharge at times with lower or no anthropogenic pollution, along with a higher potential of microbial (or other) degradation of pollutants with time which would have further impacts in future. However, these older groundwaters may be polluted with naturally occurring substances such as heavy metals leaching from the aquifer matrix.

Groundwater is usually sampled from a discharge point (e.g. springs or pumped wells) where groundwater from short and long flow paths in the aquifer mix. These samples therefore contain fractions of water of different ages rather than a single age [Maloszewski and Zuber, 1982]. Recent studies have stressed the importance of inferring the age distribution rather than the mean age, because mean age is misleading in many contexts e.g. contaminant breakthrough can occur much earlier than at mean age [e.g. McCallum et al., 2014; Suckow, 2014]. Several approaches exist to estimate the groundwater's age distribution. The most widely applied technique and the one used in this study makes use of natural or anthropogenic tracer substances with a known input to groundwater and/or known alteration processes in groundwater (e.g. radioactive decay), and a model that conceptualizes mixing of groundwater, also referred to as mixing models. The simplest mixing models, from which the age distribution is deduced, are Lumped Parameter Models (LPMs). LPMs conceptualize groundwater mixing based on the aquifer geometry and allow for estimation of the groundwater's age distribution with little tracer data. Since LPMs simplify groundwater flow and mixing and the model inputs, such as the tracer's recharge to groundwater, are uncertain and data are imperfect, the estimated groundwater age distributions are prone to uncertainty. Additionally, with insufficient tracer data and unknown aquifer geometry, often more than one LPM can fit observed tracer data leading to multiple possible (ambiguous) age estimates.

In contrast to other areas of hydrological modelling, quantification of ambiguity and uncertainty is not standard in LPM age modelling. Uncertainty perturbation techniques have been used within the age modelling community, but only a very few recent age modelling studies have demonstrated probabilistic approaches, which are known to be more robust than perturbation techniques. These recent probabilistic age modelling studies have been useful in quantifying uncertainty in the age estimates. However, the majority of these studies used relatively complex approaches that are inapplicable for the many situations with little available tracer data. Because there are only a few probabilistic age modelling studies, a discussion on relevant modelling components, such as the tracer's recharge estimate and most suitable objective function, has not been carried out. There is a need for relatively simple, easily applicable and widely transferable probabilistic age modelling approaches that allow for a more comprehensive quantification of uncertainty.

A further issue in groundwater age modelling is the limited application range of established age tracers. Each tracer can only robustly cover a limited age range depending on the tracer's input to groundwater and/or its alteration in groundwater [e.g. USGS, 1999; Zuber et al., 2011; Beyer et al., 2014]. Some tracers are degradable and/or have local sources in certain groundwater environments, which can result in misleading age estimates. Multiple tracer techniques generally need to be applied complementarily to reduce uncertainty and ambiguity in age estimates. However, even in

combination, ambiguities and high uncertainties can remain. Some tracers will also be of limited use in the future, because they are disappearing in the environment. For these reasons recent studies have stressed the importance of finding new complementary groundwater age tracers [e.g. Cook and Herczeg, 2000; Goody et al., 2006]. This study is not only concerned with finding new complementary age tracers for more robust groundwater dating, but also finding cost effective and easily determinable tracers to allow for groundwater dating when resources are limited. There is a specific interest in tracers for the characterization of relatively young groundwater recharged months to ~100 years ago. This age range is particularly important to understand, because groundwater for drinking and irrigation purposes in New Zealand and many other places around the world is abstracted primarily from shallow aquifers, due to their easier accessibility. Therefore shallow aquifers contain mainly younger groundwater and are highly prone to anthropogenic contamination. These younger groundwaters need to be studied for protection and sustainable management of drinking water resources.

1.2 Aim and objectives of this study

The focus of this study is on the characterization of relatively young groundwater in the many situations with limited available measurements and resources. In these situations the groundwater's age distribution can be inferred with the aid of simplified Lumped Parameter Models (LPMs). The aim of this study is to contribute to some of the most pressing needs related to the use of environmental tracers and age (LPM) modelling, which are:

- 1) The need for new groundwater age tracers to complement the existing tracers currently used for this purpose, while easily and cost effectively determinable tracers are preferred.
- 2) The need for a widely transferable, easily applicable framework that allows for a more comprehensive quantification of uncertainty and ambiguity in inferred age.

These needs are addressed with the following objectives (the first and second objectives relate to the first need and the third objective relate to the second need):

- 1) Identification of potential new groundwater age tracers applicable for dating of groundwater recharged a few months to ~100 years ago.
- 2) Demonstration and assessment of their performance as groundwater age tracers individually in relation to established age tracers, but also in combination with established tracers in a range of groundwater environments.
- 3) Demonstration of a relatively simple, widely transferable probabilistic groundwater dating framework that allows for quantification of uncertainty and identification of relevant model components.

1.3 Contribution of the thesis

Overall, this work contributes to more robust² determination of groundwater age (and mixing) which can aid better groundwater management and protection. Specifically the following was achieved:

- A new age tracer, Halon-1301, was discovered. Strong and conclusive evidence is provided that the signal formerly reported to have been caused by CFC-13 (a supposed groundwater age tracer) is caused by Halon-1301. Halon-1301 has never been considered as a groundwater age tracer. In this work, the applicability of Halon-1301 as a groundwater age tracer is assessed by means of its properties and demonstrated in various groundwater environments in New Zealand in relation to currently used age tracers. It is shown that Halon-1301 is a reliable groundwater age tracer at the majority of studied sites. At the remaining sites, reduced concentrations of Halon-1301 led to misleading age estimates. Possible reasons for reduced concentrations are discussed, but need to be validated in further study. Actual solubility measurements of Halon-1301 were not available, only estimates existed. Previous solubility estimates of Halon-1301 do not agree with its solubility determined from groundwater samples in this study. Further study is needed to robustly determine Halon-1301's solubility in groundwater to increase the precision of age estimates.
- An easily applicable, transferable groundwater age (LPM) modelling framework is demonstrated. The framework allows for quantification of uncertainty and ambiguity in age inferred from few tracer data. The framework also enables the identification of relevant model components such as the objective function and the tracer's recharge estimate. Application of the framework to Halon-1301 data allowed for further assessment of this new groundwater age tracer with regard to its ability to reduce uncertainty and ambiguity in estimated age when used individually or in combination with other tracers.
- The use of commonly measured hydrochemistry³ as a groundwater age tracer is demonstrated. Previous studies have successfully used commonly measured hydrochemistry to infer the age distribution of groundwater recharged days to weeks ago. In older groundwater, commonly measured hydrochemistry has only been demonstrated as an age proxy and indicator for the groundwater's mean age when used in combination with established age tracers. In this study, it is demonstrated that certain commonly measured hydrochemistry parameters can be used as complementary age tracers of water recharged months to ~100 years ago. Hydrochemistry helped in resolving ambiguity and reducing uncertainty in age information derived from established age tracers. Independent use of hydrochemistry resulted in relative age estimates. The addition of

² more reliable, more accurate and more informative (with regard to ambiguity and uncertainty in age estimates)

³ In this thesis, the term commonly measured hydrochemistry refers to relatively easily determinable and widely available parameters such as the concentration of major ions, pH and conductivity. It does not include the concentration of isotopic compounds or other compounds that have been applied as groundwater age tracers.

robust age estimate inferred with established age tracers at one site allowed deduction of the age distribution at the remaining sites purely using hydrochemistry. It is also shown that groundwater chemistry can aid inferring of weathering rates and hydrochemistry of recharge which can indirectly aid groundwater dating and/or groundwater characterization.

1.4 Structure of the thesis

This thesis is organized in seven chapters. In this chapter (Chapter 1) an overview of the problem along with the aims, objectives and contribution of this work were presented. In Chapter 2, more detailed background information is given, which includes a formal definition of groundwater age, a review of widely used groundwater age modelling approaches and age tracers applicable for dating of relatively young groundwater. In particular, the limitations currently faced in age (LPM) modelling are highlighted. In Chapter 3, the study areas are described, which serve for demonstration of the methods proposed to reduce the identified limitations. These methods include the use of Halon-1301 as a new groundwater age tracer presented in Chapter 4, the use of a relatively simple probabilistic groundwater age modelling approach presented in Chapter 5 and the use of commonly measured hydrochemistry as a groundwater age tracer presented in Chapter 6. Chapter 7 summarizes the main findings of this PhD and gives recommendations for future research. Appendices A, B, C and D contain detailed information on Chapters 3, 4, 5 and 6, respectively.

2. Background

2.1 Definition of groundwater age

The definition of groundwater age is complicated, as pointed out by Mazar (1996), Clark and Fritz (1997), Kendall and McDonnell (1998), Phillips and Castro (2003) and Kazemi et al. (2006) among others. Groundwater age cannot be measured directly, but is inferred from hydrological model simulations or from concentrations of age tracers by comparison of their measured input (recharge) and output concentrations and model process assumptions. Groundwater age or residence time indicates the time the water has resided in the subsurface since recharge normally excluding travel time through the unsaturated zone. Whether travel time through the unsaturated zone is included in the age estimate is method and tracer dependent. For example, groundwater age estimated from non-gaseous tracers includes travel through the unsaturated zone (and travel on the surface e.g. in streams). Groundwater age inferred from gaseous tracers does not usually include this time, because gaseous tracers are in equilibrium with atmospheric air during transport in the unsaturated zone or on the surface (except for deep and/or moist unsaturated zones [Cook and Solomon, 1995]). The age tracer dependent age estimation is not necessarily a disadvantage. One can take advantage of this by comparison of the ages derived from non-gaseous and gaseous tracers (or multiple gaseous age tracers) to study the passage of recharging water through the unsaturated zone in addition to studying saturated zone processes. Comparison of ages inferred from multiple age tracers can also allow for the assessment of contamination/degradation of one of the tracers (indicated by an elevated/reduced concentration of one of the tracers in comparison to the others).

Groundwater is usually sampled from a discharge point, such as springs or pumped wells, where groundwater recharged at different times and places converge and mix. These samples therefore contain fractions of different aged water rather than water of a single age [Maloszewski and Zuber, 1982]. The distribution of ages within a water sample is complex to represent and estimates are prone to uncertainty due to model assumptions and uncertain and imperfect data for age modelling (further discussed in the subsequent sections). Commonly the mean residence time (MRT) or apparent age⁴ is used for illustration, comparison and further modelling. However, this may lead to false interpretations, e.g. of contaminant breakthrough [e.g. McCallum et al., 2014; Suckow, 2014]. To overcome this issue, recent studies have stressed the importance of using the age distribution and/or distributional thresholds, e.g. as reflected by the New Zealand Ministry of Health (2008) drinking water standard, which requires less than 0.005 % of the water to be below one year old.

⁴ Apparent groundwater age is directly inferred from the concentration of the tracer in groundwater without modelling assumptions (i.e. assuming piston flow or no mixing). Apparent age often differs from mean age depending on mixing and input historic of the tracer [McCallum et al., 2014 and references therein].

2.2 Determination of groundwater age distributions with Lumped Parameter Models

Several approaches have been used to infer groundwater age and/or the age distribution. Particular locally applied groundwater dating techniques and still-developing groundwater dating approaches have been used. These include estimation of groundwater age by assessing the extent of damping of seasonally changing hydrochemistry [Stichler and Moser, 1979], tracking of an induced tracer such as dye or chloride [Flury and Wai, 2003; Moore, 2005] or inferring groundwater age from concentrations of major ions [e.g. Daughney et al., 2010]. More widely applicable techniques include the use of physics based groundwater models or environmental tracers.⁵

Physics based groundwater models have been used to infer groundwater age distributions with the aid of particle tracking or direct age simulation [e.g. Goode, 1996; Cornaton, 2012]. These models have proven very valuable as hypothesis testing tools. However, these are very ‘data hungry’ as well as being time consuming to set up and parameterise and can be prone to large uncertainties particularly under conditions with limited available measurements as mentioned previously [Castro and Goblet, 2005; Zuber et al., 2011].

Environmental tracers have been used to estimate groundwater age by making use of their well monitored (variable) input to groundwater and/or alteration in groundwater (e.g. radioactive decay) [e.g. Clark and Fritz, 1997; Phillips and Castro, 2003; Kazemi et al., 2006; IAEA, 2013]. If sufficient tracer data are available, the age distribution can be inferred without assumptions on groundwater mixing [e.g. Fienen et al., 2006; Cirpka et al., 2007]. However, a sufficiently large data set is rarely available to overcome the large degree of freedom introduced with this ‘shape free’, ‘non-parametric’ approach [e.g. McGuire and McDonell, 2006 and references therein]. Generally of the order of tens to thousands of data points are required. Simplified ‘parametric’ Lumped Parameter Models (LPMs) [Turnadge and Smerdon, 2014] are useful in the many situations with a limited number of tracer data where ‘shape free’ LPMs and more complex groundwater models cannot be applied. Simplified ‘parametric’ LPMs conceptualize groundwater mixing (i.e. assume the form of the age distribution *a priori*) based on the aquifer geometry and well construction [e.g. Małoszewski and Zuber, 1982; Nir, 1986]. Despite their simplicity, LPMs have been shown to 1) explain measured tracer concentrations in a range of hydrogeologic settings and 2) give similar age estimates to those obtained by particle tracking using detailed physics based groundwater models [e.g. Zuber et al., 2011; Eberts et al., 2011; Green et al., 2014; Basu et al., 2012; Scalón et al., 2003; Jurgens et al., 2012 and references therein]. Due to their wide applicability and simplicity, ‘parametric’ LPMs are used in this study to infer groundwater age

⁵ Steady state conditions are often assumed in both the simple and more complex modelling approaches. If sufficient tracer data are available, age tracers can be used to verify steady state or non-steady state conditions [Morgenstern et al., 2010]. Non-steady state (transient) approaches may be used to infer groundwater age, but require confinement (magnitude and direction) of the changes [Ozyurt and Bayari, 2005].

from tracer data. Estimating the age distribution with the aid of simplified LPMs from environmental tracers relies on the simplified relationship in Eqn. 2-1, also referred to as convolution integral.

$$c_{obs}(t) = \int_0^{\infty} g(t') * c_{in}(t - t') * e^{-(\lambda \times t')} dt', \quad \text{Eqn. 2-1}$$

where $c_{obs}(t)$ is the observed tracer concentration in groundwater; $c_{in}(t' - t)$ is the tracer concentration in recharge as a function of time; t' = transit time, t = observation time, $e^{-(\lambda \times t')}$ refers to radioactive/biological decay of the tracer with decay rate λ ; $g(t')$ is the mixing model or LPM from which the age distribution is deduced.

In general, 'parametric' LPMs are a function of mean residence time (MRT) and one or more mixing parameter(s). The most commonly applied LPMs are the Dispersion Model (DM), the Exponential Mixing Model (EMM), the Exponential Piston flow Model (EPM) and the Piston flow Model (PM). As an example, the EPM conceptualizing mixing of groundwater emerging from a partly unconfined aquifer is defined in Eqn. 2-2 and illustrated in Fig. 2-1. For a more detailed description of the most commonly used LPMs and further discussion on the use of 'parametric' LPMs, their advantages and limitations Maloszewski and Zuber (1996), Mook et al. (2001) and Jurgens et al. (2012) can be consulted.

$$\text{For } > MRT(1 - \frac{1}{n}): g(t') = f_{EPM} = \frac{n}{MRT} * \exp(-n * \frac{t'}{MRT} + n - 1); \text{ else: } f_{EPM} = 0. \quad \text{Eqn. 2-2}$$

f_{EPM} is one form of $g(t')$, the age distribution according to the exponential piston flow model, MRT is the mean residence time; t' is the transit time; t is the observation time; n refers to the reciprocal of the ratio of exponential to total flow defined by Maloszewski and Zuber (1982); $1/n$ is in the following referred to as E/PM.

Figure 2-1: Schematic diagram of an idealized aquifer in which the exponential piston-flow model can be applied - a partly confined aquifer with a recharge area of length x and a confined part of length x^* (LEFT). Example of an age distribution expected at Well X (RIGHT) assuming an EPM ratio (n) of 1 and mean age of 25 years [after Jurgens et al, 2012].

There are a number of widely accepted and commonly used programmes and codes⁶ which have been developed to infer groundwater age distributions from age tracers with the aid of simplified LPMs. These are summarized in Suckow (2014) and Jurgens et al. (2012). They are based on the convolution integral (Eqn. 2-1) and involve the generation of tracer concentrations by adjustment of the LPM type and its parameters (i.e. the MRT and mixing parameter(s)) until simulated tracer concentration(s)

⁶ These are most commonly spreadsheet programmes, but also include computer codes.

sufficiently match observed tracer concentration(s). The adequateness of the match is evaluated by eye or by evaluating the (average) relative difference between simulated and observed tracer concentration(s) in a least square minimization approach or similar. Additionally, information such as aquifer geometry or location of the studied groundwater in relation to aquifer recharge area is taken into account to infer a representative LPM. Studies that use these programmes/codes commonly only report the (visually) best fitting LPM and assume it to be most representative of age tracer observation(s) and groundwater processes. Ambiguity can easily be overlooked, due to the often manual assessment of the LPM parameter domain. In addition, uncertainty is not considered or quantified, because these programmes do not easily allow for this.

Understanding and quantifying uncertainty arising from model input uncertainties, model structural errors and uncertainty in observations is an important part of characterizing the performance of models and reducing uncertainty in model findings and predictions. This has become standard in other areas of hydrological modelling [e.g. Liu and Gupta, 2007 and Shrestha et al. 2009]. Ginn et al. (2009) noted that quantification of uncertainty in age modelling including all sources of uncertainty has not been fully carried out in literature. As part of this study, an extensive literature review through the Web of Science⁷ was performed which confirmed that a more comprehensive consideration of uncertainty in age modelling has only emerged in studies from 2010 onwards, although an earlier exception to this (Cirpka et al., 2007) is noted. A summary of the findings illustrated in Fig. 2-2 shows that, although a significant number of studies carried out sensitivity analysis of the age estimation towards model input uncertainties, these are still the minority of groundwater age studies (10 % of 400 assessed age modelling studies published between 1977 and 2014). Even fewer of the 400 age modelling studies published between 1977 and 2014 or between 2010 and 2014) attempt a more comprehensive uncertainty assessment in age modelling with the aid of more robust probabilistic approaches (2 % or 3 %, respectively). It is acknowledged that there may have been additional papers that address or take account of uncertainty in age modelling, but did not get identified in the literature search. The author went through references and citing articles of the papers identified in the literature search detailed in Appendix C1 to find additional papers. The author is confident that the number of publications that were not identified by the literature search is very small and these findings are representative.

⁷ Literature review (carried out on 29/04/2015) of the top 400 groundwater dating studies sorted by relevance that were identified by the keywords: 'water' or 'groundwater' and 'residence time' or 'age' or 'dating' and 'tracer' or 'lumped parameter model'; studies that address uncertainty (using sensitivity analysis or a more comprehensive uncertainty quantification) were identified by the keywords 'uncertain', 'sensitivity', 'error', 'probability', 'Bayes' or 'reali(z/s)ations'

Figure 2-2: Literature review (carried out on 29/04/2015) of the 400 groundwater dating studies published from 1977 to 2014 (LEFT) and 2000 to 2014 (RIGHT) identified by the keywords: 'water' or 'groundwater' and 'residence time' or 'age' or 'dating' and 'tracer' or 'lumped parameter model' and sorted by relevance; studies that address uncertainty (in a more comprehensive or sensitivity analysis approach) were identified by the keywords 'uncertain', 'sensitivity', 'error', 'probability', 'Bayes' or 'realizations'

The very few age modelling studies that were identified in the literature search as using a more comprehensive uncertainty analysis are summarized in Tab. 2-1. One additional paper highlighted (with '*' in Tab. 2-1), which did not get identified in the literature search, was found through assessment of references and citing articles of the papers that address uncertainty in age modelling.

Almost half of the studies listed in Tab. 2-1 use 'non-parametric' (shape free) LPMs. These have been useful in inferring the age distribution in particular to overcome model structural errors. However, the use of 'non-parametric' LPMs requires a large number of tracer data that are not readily available in many (non-extensive) studies as mentioned earlier. The remaining probabilistic age modelling studies use simplified 'parametric' LPMs, such as the piston flow model and the dispersion model, to conceptualize groundwater mixing. Although simplified LPMs introduce model structural uncertainty, these can be applied in studies with few available tracer data. A formal multi-model approach to assess model structural errors has not been addressed in the existing LPM age modelling literature.

The few studies that have attempted a more comprehensive uncertainty assessment in age modelling (listed in Tab. 2-1) take account of uncertainties in the tracer measurements in groundwater. Fewer studies also consider model structural errors (when using parameterized LPMs) and uncertainty in the tracer's retardation and decay rate. Uncertainty in the tracer's input to groundwater, e.g. due to variability of its atmospheric concentration or use of recharge estimates, has not been considered. In addition, a discussion on the appropriateness of objective functions for fitting of age tracer data and LPM calibration has not yet been carried out. Studies in other areas of hydrological modelling, where probabilistic approaches are more commonly used, have suggested careful identification of such metrics is required [e.g. Krause et al., 2005; Gelman, 2008; Beven, 2006; Stedinger, 2008 and references therein; Beven and Binley, 2014]. Implementing a more comprehensive uncertainty quantification in groundwater age modelling including all sources of uncertainty (as a standard procedure) is vital for robust groundwater dating. This is addressed in Chapter 5 of this thesis.

Table 2-1: Reference and specifications of probabilistic uncertainty quantification approaches in groundwater age modelling found in extensive literature review of 400 age modelling papers; *additional paper not identified in literature search, but found through a search of citing articles and references of the papers found in literature review

Reference	Data type and data quantity	Considered LPMs/ transfer function	Details on approach	Considered uncertainties
Cirpka et al., 2007*	Electrical conductivity in river (data points of order of 10,000)	Non-parametric, 1,000 realizations	maximum likelihood and variogram regularization	Uncertainty in tracer observations, model structure and possible numerical errors (totalling ca. 5%)
Liao and Cirpka, 2011 -builds on Cirpka et al., 2007	Synthetic, conservative & reactive tracer	Non-parametric in a transient-storage model	Truncated singular value decomposition, geostatistical smoothness criterion, maximum likelihood function	Uncertainty in tracer observations (as 5% noise)
McCallum et al., 2014 -builds on Cirpka et al., 2007	Synthetic age tracer data	Non-parametric in a groundwater box model, 100 realizations		Uncertainty in tracer observations (assumed to be 5 or 10% based on analytical errors and spatial variability of atmospheric concentrations)
Knee et al., 2011	Rn observations to characterize groundwater flow into sea	Piston flow model	'Classic' Monte Carlo simulation with 10,000 realizations	Uncertainty in tracer observation (analytical error + natural variability, normally distributed)
Massoudieh et al., 2012	multiple synthetic single point and time series age tracer data of environmental age tracers	Various parametric LPMs, hypothetical aquifer model	Bayesian approach with Markov Chain Monte Carlo Simulation and a likelihood function	Uncertainty in tracer observations (based on analytical errors and temporal and spatial variation of the tracers, heterogeneities and model structural error) assumed to be log-normally distributed (of 5% magnitude in 2014b paper); uncertainty in tracer decay and retardation (in 2012 paper)
Massoudieh 2013 (theoretical study)		simulated (non-parametric) LPMs inferred from hypothetical aquifer model are compared to parametric LPMs		
Massoudieh et al., 2014b				
Massoudieh et al., 2014a		Non-parametric, (histogram model)		
Timbe et al., 2014	Stable isotopes (O18 and H2), 2 year weekly data in catchment	Comparison of the performance of 7 parametric LPMs with regard to uncertainty in the MRT	'Classic' Monte Carlo (10,000); Nash Sutcliffe efficiency	Uncertainty in tracer observation (analytical error, normally distributed)
Green et al., 2014	Synthetic age tracer data	Comparison of parametric LPMs to non-parametric LPMs (inferred from a heterogeneous aquifer model)	'Classic' Monte Carlo, optimization routine in 'PEST')	Uncertainty in tracer observation (estimated from replicate tracer observations, normally distributed), model structural error

2.3 Tracer substances for dating relatively young groundwater

In the following section, more detail on those tracers that are commonly used for dating of relatively young groundwater is presented, with a particular focus on individual tracer limitations. Only the most commonly used age tracers that cover the age range that was of interest to this study (from months to ~100 years) are covered. In addition to most commonly used age tracers, information on the current

and potential use of commonly measured hydrochemistry as an age tracer is given. Summaries of other currently used age tracers and their limitations as well as further detail on the ones presented in the following can be found in e.g., Mazar (1996), Clark and Fritz (1997), Kendall and McDonnell (1998), Cook and Herczeg (2000), Phillips and Castro (2003), Kazemi et al. (2006), Bauer et al. (2001) and IAEA (2013).

Currently, the most widely applied age tracers for dating of relatively young groundwater are SF₆ (sulphur-hexa-fluoride), tritium and the CFCs (chlorofluorocarbons) CFC-12 and CFC-11 [e.g. Busenberg and Plummer, 2000, 2008 and 2010; Taylor et al., 2001; Stewart and Morgenstern, 2001; van der Raaij, 2003; Morgenstern et al., 2010].⁸ Groundwater dating with these tracers utilizes their atmospheric concentration records monitored over the last few decades (illustrated in Fig. 2-3) and well-examined radioactive decay (for tritium). The properties and limitations of tritium, SF₆ and CFCs are summarized in the following.

Tritium (³H), the heaviest hydrogen isotope, decays with a half-life of 12.32 years and occurs naturally, produced by spallation reactions in the atmosphere due to cosmic ray interaction with atmospheric gases. The atmospheric thermonuclear bomb tests (mainly occurring between 1954 and 1963) have led to global spike(s) in atmospheric tritium concentration, also referred to as ‘bomb peak’, with different magnitude and characteristics between the northern and southern hemisphere (Fig. 2-3). The estimation of tritium recharge to the groundwater system is complicated, since it is dependent on the amount and timing of recharging water. The seasonally varying tritium signal in the atmosphere can in some cases be amplified or dampened by seasonally varying recharge [Stewart and Taylor, 1981]. To estimate tritium recharge, atmospheric tritium concentrations have been weighting according to recharge estimates [e.g. Allison and Hughes, 1978; Stewart and Taylor, 1981; Engesgaard et al., 1996; Knott and Olipio, 2001, Morgenstern et al., 2010].

Tritium allows for dating of groundwater with a mean residence time of a few months to about 250 years, depending on detection limits, tritium recharge, sampling frequency and mixing assumptions. The rate of tritium’s radioactive decay and its decrease in the atmosphere has led to similar concentrations in groundwater recharged after the nuclear bomb tests. Due to this, ambiguous age estimations can be inferred, particularly in the northern hemisphere [Taylor et al., 1992; Morgenstern and Taylor, 2009; Morgenstern et al. 2010]. To overcome ambiguity, tritium time series measurements or the combination of a single tritium measurement with data of a complementary age tracer, e.g.

⁸ Please note that stable isotopes (ratios) of hydrogen and oxygen are also widely applied, but are not further assessed in this study, because these only robustly cover a small age range from a few months to < 5 years (relying on seasonal changes) and are mainly used to characterize the recharge source of groundwater [McDonnell et al., 1999; Rosen et al., 1999b; Stewart and Morgenstern, 2001]. Tracer tests facilitating the application of dye and other artificial locally applied tracers are also not covered here.

tritium's daughter product ^3He , CFCs, or SF_6 , are often used [Tolstikhin and Kamenski, 1969; Schlosser et al., 1988]. In areas where tritium is being emitted, e.g. at nuclear waste disposal sites, landfills or nuclear power plants, the atmospheric tritium signal can be significantly disturbed. In these cases the use of tritium can result in misleading age estimates and another tracer, such as SF_6 are necessary to robustly estimate groundwater age [e.g. Galeriu et al., 2005; Mutch and Mahony, 2008; Hughes et al., 2010].

SF_6 is widely used for electrical insulation, which has led to continuously increasing atmospheric SF_6 concentrations since the 1970s (Fig. 2-3). As a consequence of its characteristic atmospheric trend, SF_6 can be used to date groundwater recharged after the 1970s dependent on the limit of detection of the analysis. Despite SF_6 being a greenhouse gas, it is unlikely that SF_6 production and release will be limited soon because its atmospheric concentration in relation to its effect as a greenhouse gas is still relatively low compared to other greenhouse gases. The steadily increasing concentration in groundwater recharge is expected to allow for increasingly accurate dating of water younger than 40 years. SF_6 is not known to be biodegradable in groundwater even under anoxic conditions and does not sorb to organic matter [e.g. Watson et al., 1991; Wilson and Mackay, 1996]. There are also local (anthropogenic and natural) sources of SF_6 that can lead to higher concentrations or excess SF_6 . These can result in misleading age estimates with SF_6 . Natural sources of SF_6 include hot springs, volcanic areas, carbonate aquifers and silicigenous rock [Stewart and Morgenstern, 2001; van der Raaij, 2003; Koh et al. 2007; Bunsenberg and Plummer 2000 and 2008]. Anthropogenic sources, such as industrial areas where SF_6 is used [Santella et al. 2003 and 2008], are generally not a problem in New Zealand [van der Raaij and Beyer, 2015].

CFCs⁹ have gradually increased in the atmosphere since the 1930s due to their use as propellant and refrigerant gases (Fig. 2-3). They can be used to date groundwater recharged after the late 1940s depending on the limit of detection of the analysis. CFCs are still being released from industrial waste, e.g. old refrigerants and air-conditioning units. However, the restriction of the CFC emissions since the late 1980s, due to their ozone depleting effect (Montreal Protocol), led to a levelling out and subsequent decrease in atmospheric CFC concentrations (from about 2000, see Fig. 2-3 for detail). This has compromised the use of CFCs as groundwater age tracers, because often ambiguous age estimates are inferred [Bullister, 2011]. Further complications with the use of CFCs as groundwater age tracers are that they are biodegradable in anoxic groundwater and tend to sorb to organic matter in soils [Lesage et al., 1990; Bullister and Lee, 1995; Shapiro et al., 1997; Happell et al., 2003; Hinsby et al., 2007; Horneman et al., 2008]. Due to past and present release of CFCs, local anthropogenic CFC sources, e.g. in urban and industrial areas [e.g. Szabo et al., 1996], can lead to contamination of

⁹ The most commonly used ones are CFC-11, CFC-12 and CFC-113

groundwater. Such cases are known as 'excess' CFCs [e.g. Oster et al. 1996; Stewart and Morgenstern, 2001; Cook et al., 2006; Bunsenberg and Plummer, 2008 and 2010] can result in misleading age estimates with CFCs. However, with improving knowledge of CFC contamination sources it may be possible to use excess CFCs as indicator for recharge source [van der Raaij and Beyer, 2015]. In some cases, excess CFCs can also aid estimation of the extent and source of contamination plumes [e.g. Thompson and Hayes, 1979; Busenberg et al., 1993, Darling et al., 2010].

Further limitations of the gaseous tracers SF₆ and the CFCs may arise from excess air, e.g. entrapped air bubbles during recharge or sampling, and degassing, e.g. loss of tracer into gas phase created by biological processes such as methane or nitrogen. If not taken into account, both excess air and degassing can result in nonconforming, ambiguous age estimations when using SF₆ and the CFCs (and tritium/³He in northern hemisphere) [van Breukelen et al., 2003; Visser 2009].

As refer to in section 2.1, the use of gaseous and non-gaseous age tracers can result in different age estimations, depending on whether the age estimate includes or excludes travel time through the unsaturated zone. For tritium, a non-gaseous tracer, the age 'clock' starts counting as soon as the rain recharge infiltrates into the soil. Age estimates derived from tritium therefore include the passage of the water through the unsaturated zone. If water enters the aquifer, then re-emerges to the surface but again enters the aquifer after a short time, the tritium age 'clock' is not significantly altered during this surface contact, assuming additional recharge containing modern tritium concentrations is negligible. The tritium signal is not significantly affected during contact with air. Tritium can therefore be used to date ground- and surface water [e.g. Morgenstern et al., 2010]. In contrast, the gaseous tracers SF₆ and the CFCs are in equilibrium with the atmosphere in the unsaturated zone, hence their 'clock' does not start counting until the recharge has entered the saturated zone. When groundwater reappears at the surface, the dissolved gaseous tracers re-equilibrate with atmospheric air; hence their 'age clock' is reset to zero. In thick (>ca. 10m) and/or moist unsaturated zones a lag time needs to be taken into account for both gaseous age tracers and tritium, due to their slower diffusive transport [Cook and Salomon, 1997].

To overcome ambiguities and reduce the limitations generally encountered when using a single tracer, it is now recognized that multiple tracers (or the combination of a single tracer with another groundwater characterization technique) are essential. The use of multiple tracers/techniques enables more robust groundwater dating than feasible when using a single tracer/technique. However, even when using a combination of different dating techniques, robust age estimates are not always achievable. Some of the tracers, such as CFCs will become of limited use in the future as they are fading out in the environment. The development of further methods (e.g. new groundwater age tracers) is imperative to extend the application range of currently used groundwater dating methods, replace

those that will become less applicable, and to further reduce ambiguities and uncertainty in age estimates. In particular a combination of tracers with different input histories or transport parameters is preferred to also allow for the study of more complex groundwater processes such as double porosity transport. In addition easily and cost-effectively determinable (and widely available) tracers are preferred to aid groundwater dating in areas where the established techniques are of limited use.

Figure 2-3: Southern hemisphere (SH) and northern hemisphere (NH) atmospheric concentration of CFC-12, CFC-11, SF_6 , and tritium, using data from Sturges et al. (2000 and 2012), Busenberg and Plummer (2008), Bullister (2011) for the CFCs and SF_6 ; Morgenstern and Taylor (2009) for SH tritium data and Jurgens et al. (2012) for NH IAEA tritium data.

The use of commonly measured **hydrochemistry**¹⁰ as a groundwater age tracer bears significant advantages to the use of established age tracers. Firstly, the determination of commonly measured hydrochemistry is relatively cost-effective and simple. Secondly, major hydrochemistry is routinely determined and data are spatially widely available over the past decades in line with major national and regional groundwater monitoring programs such as the National Groundwater Monitoring Program (NGMP) in New Zealand, or the National Ground Water Monitoring Network (NGWMN) in the USA. The potential of commonly measured hydrochemistry for groundwater characterization has been discussed for decades [e.g. Freeze and Cherry, 1979; Drever, 1988; Langmuir, D. 1997; Robins, 1998]. However, its use as a groundwater age tracer has been shown to be difficult because groundwater chemistry can be influenced by many factors aside from residence time. Such factors include the

¹⁰ In this thesis, the term commonly measured hydrochemistry includes the concentration of major and trace elements, but does not include the concentrations of isotopic compounds, such as tritium and carbon, or other compounds, such as SF_6 , that have been applied as groundwater age tracers through employment of their known input to groundwater and/or well-studied decay.

abundance and type of minerals and microbes present and climatic conditions [Downes, 1985; Plummer et al., 1990; O'Brien et al., 1997; Kilchmann et al., 2004; Daughney and Reeves, 2005] but also anthropogenic factors such as land use and fertilizing practices [e.g. Morgenstern and Daughney, 2012].

The determination of the groundwater's age distribution purely based on commonly measured hydrochemistry has only been demonstrated for relatively young groundwater with a mean age of the order of weeks to a few months [Anderson, 2005; Cox et al., 2007; Cirpka et al., 2007]¹¹. The approach relies on significant (seasonal) variation of hydrochemistry in groundwater recharge. The use of anthropogenic commonly measured compounds, such as nitrate, for groundwater dating has also been suggested. However, reconstruction of its historic input to groundwater and determination of degradation rates are needed to utilize nitrate as an age tracer [e.g. Böhlke, 2002 and references therein]. Over a wider age range, where the time variable input of hydrochemistry has been dampened, the use of commonly measured hydrochemistry as an age proxy has been demonstrated which helped distinguish older from younger groundwater and/or support age information derived from environmental tracers with the aid of statistical tools or physical groundwater models [e.g. Allison and Hughes, 1978; Edmunds and Walton, 1980; Plummer and Sprinkle, 2001; Petrides et al., 2006; Lalbat et al., 2007; Daughney et al., 2010].

Relationships between mean or apparent age inferred from environmental tracer data [e.g. Downes, 1985; Katz et al., 1995; Morgenstern et al., 2009 and 2010; Rademacher et al., 2001 and 2005; Peters et al., 2013], flow path or well depth [e.g. Taylor et al., 1992; Edmunds and Smedley, 2000; Edmunds et al., 2003; Hofmann et al., 2010] and flow path length and groundwater velocity [e.g. Kenoyer and Bowser, 1992; Pacheco and van der Weijden, 2012]), and commonly measured hydrochemistry¹² have been established. These relationships can be used to estimate age purely using hydrochemistry as illustrated in Fig. 2-3. Further studies demonstrate the use of age - hydrochemistry relationships to help better understand groundwater systems, e.g. through determination of weathering rates, quantity and quality of recharge, and prediction/reconstruction of anthropogenic effects on groundwater quality [e.g. Boehlke, 2002 and MacDonald et al., 2003].

¹¹ The approach is similar to the use of stable isotope ratios for groundwater dating [e.g. McDonnell et al., 1999; Rosen et al., 1999b; Stewart and Morgenstern, 2001]. It relies on seasonal variation of hydrochemistry of recharge that is dampened over a period of months to a few years (depending on the groundwater environment and its signal dampening effect). The approach works well for inferring groundwater age distributions with a mean age of up to several months (e.g. has been used to characterize infiltration of river water into groundwater [Anderson, 2005; Cox et al., 2007; Cirpka et al., 2007]), but is of limited use for dating of water older than ~5 years. In addition, a large number (i.e. time series) data of hydrochemistry of recharge and hydrochemistry of groundwater are necessary for successful application of this approach.

¹² These relationships have been established for rock forming elements, such as Si, Na, Mg, and total dissolved solids (TDS) as well as constituents of microbial degradation, such as dissolved oxygen (DO) and pH.

Hydrochemistry–age relationships are generally formed using mean/apparent age (or age equivalent) inferred with established techniques and do not take account of groundwater mixing. These relationships do therefore not (necessarily) represent processes/kinetics at piston (i.e. unmixed or homogeneously mixed) flow as generally determined in lab environments. Deviation of observed hydrochemistry in groundwater from piston flow relationships may contain information on groundwater mixing. Inferring such information may allow for the use of commonly measured hydrochemistry as an age tracer to estimate the groundwater’s age distribution over a wider age range than possible with the established technique that relies on seasonal variations in hydrochemistry of recharge.

Chapter 6 builds on the findings of existing studies and assesses the potential use of commonly measured hydrochemistry as a complementary age tracer further. Specifically, it is assessed to what extent hydrochemistry can be used to 1) reduce uncertainty and ambiguity in age estimates inferred with established age tracers, and 2) extrapolate age inferred with established age tracers at sites with otherwise unavailable age information. In addition, the performance of commonly measured hydrochemistry for the use as an independent groundwater age proxy/tracer is also assessed.

Figure 2-4: Schematic of inferring residence time (RT) from commonly measured hydrochemistry. In this example the RTs of seven wells are available (estimated e.g. from age tracers) and for one well RT is unknown. A relationship between Ca concentration and RT at the seven dated wells was established. With the aid of this relationship RT at the eighth site can be estimated from its Ca concentration (assuming the established Ca-RT relationship is also valid at this site).

3. Study areas

The Wellington Region is one of the 16 local government regions of New Zealand. It is located in the southern part of New Zealand's North Island. The region covers a land area of ~8,000km² and has a population of ~470,000 [Statistics NZ, 2014]. The climate in the Wellington Region is temperate and marine with moderate temperatures all year round. Mean monthly temperatures, precipitation, sunshine hours and relative humidity recorded at two stations in the region are illustrated in Fig. 3-1. The location of the climate monitoring stations within the region is illustrated in Fig. 3-2. The seasonal pattern for the two stations is very similar, although absolute numbers differ. Generally precipitation is highest and temperature is lowest during winter months (Jun-Aug) resulting in higher water availability in winter.

Water use differs highly throughout the region. In Wellington city, water is mainly used for public supply. In rural areas, water is mainly used for irrigation with 70% being used for dairy pasture, 18% for non-dairy pasture and about 10% for horticulture and viticulture [GWRC, 2014]. Sources of water supply are local rivers, lakes and groundwater systems. Three of the region's groundwater systems serve as study areas in this thesis, as illustrated in Fig. 3-2. These are the Lower Hutt Groundwater Zone (LHGWZ), the Wairarapa groundwater system and the Wainuiomata aquifer. Water quality is generally good in the Region, but some surface water bodies are harmful for aquatic life during summer [GWRC, 2014]. Although water quality has been decreasing in some surface water bodies from 2006 to 2011, which can be attributed to intensification of agriculture and dairy/sheep farming, significant trends in groundwater quality have not been observed in the LHGWZ, the Wainuiomata aquifer and the Wairarapa groundwater systems from 2006 to 2011. However, the occurrence of droughts and the increasing water needs have impacted the groundwater systems in recent years and are expected to increasingly do so in the future [Keenan et al., 2012]. To manage and protect groundwater resources in the Wellington Region, groundwater quality and groundwater levels have been recorded in monthly intervals since 1993. In addition, physical groundwater models have been established and groundwater age modelling is increasingly used to characterize the region's groundwater systems, e.g. estimate volumes of groundwater and identify recharge sources and areas.

This study takes advantage of the rich datasets of (time series) tritium, CFC-11, CFC-12, and SF₆ data and historical records of major hydrochemistry in the LHGWZ, the Wairarapa groundwater zone and the Wainuiomata aquifer at 23 groundwater sites and one surface water site (Fig. 3-2 and Tab. 3-1). Detailed concentrations of the age tracers, kindly provided by GNS Science, are summarized in Appendix A along with further information on the studied sites, e.g. their geographic coordinates. Water samples have been collected and analysed following standard sampling and analysis procedures - for gaseous tracers see van der Raaij (2003) or van der Raaij and Beyer (2015), for tritium see

Morgenstern and Taylor (2009). Historical major hydrochemistry data records (time range 1993-2013) were provided by Greater Wellington Regional Council (GWRC). Available hydrochemistry parameters are summarized in Tab. 3-2. Water samples for analysis of hydrochemistry have been collected following standard sampling procedures described in Rosen et al. (1999a). Prior to 2003, unfiltered samples had been analysed (data reported as total concentration), after 2003 filtered samples (0.45 um) have been analysed (data reported as dissolved concentrations). Analytical methods (and sampling procedures) that have been used to determine major hydrochemistry in New Zealand aquifers can be found in Daughney and Reeves (2005).

The LHGWZ is the main study site in this thesis (providing data for Chapter 4, 5 and 6), therefore extensively described in the following. The Wairarapa groundwater system and Wainuiomata aquifer are only used to a minor extent (providing data for Chapter 4 only), so less detailed in the following.

Figure 3-1: Climate summary data for Kelburn and Masterton showing mean monthly data for 1981-2010 [CliFlo database (NIWA)]

Table 3-1: Lower Hutt Groundwater Wells, available age tracer and major hydrochemistry data and their time range, DO aquifer layer and depth, # median number of measurements is given since not all parameters were not determined every year; *monthly spaced observations; + SF₆ in 2013 determined in this study (details in Chapter 4); ^d groundwater samples showed considerable amount of methane and are considered as anoxic, despite relatively high oxygen concentration

Well #	Hydrochemistry data		Tritium data		SF ₆ data		CFC data		DO [mg/L]
	#	Time range	#	Time range	#	Time range	#	Time range	
	Lower Hutt Groundwater Zone								
6	57 [#]	1993-2012	4	1998, 2005, 2008, 2010	2	2007, 2013 ⁺	2	2007	4.82
2	52 [#]	1993-2011	2	2005, 2009	1	2007	-	-	1.72
13	9	1993-2013	1	2013	-	-	-	-	9.1
14	10	1993-1995	11	2002-2003*	-	-	-	-	-
5	38 [#]	1993-2013	9	1972-2013	2	2007, 2013 ⁺	-	-	0.17
1	11	1993-2013	2	2010, 2013	2	2010, 2013 ⁺	2	2010	3.84
4	58 [#]	1993-2013	9	1996-2010	3	2002, 2007, 2013 ⁺	3	2002, 2007, 2013	0.31
7	2	2008, 2013	2	2007, 2013	-	-	-	-	1.8
3	59 [#]	1993-2012	3	2002, 2005, 2011	2	2002, 2013 ⁺	1		0.22
9	2	2008, 2013	1	2013	-	-	-	-	0.94
10	3	1993, 2013	1	2013	-	-	-	-	1.58
8	2	2008, 2013	3	2007, 2x 2013	1	2013 ⁺	-	-	1.9
12	20	1993-2013	1	2013	-	-	-	-	0.14
11	10	1993-2013	1	2013	3	2002, 2x 2013 ⁺	2		0.11
15	18 [#]	1993-2012	1	2013	-	-	-	-	10.8
26	-	-	4	1996; 1998; 2001; 2007	3	2005, 2007, 2013 ⁺	2	2005, 2007	0.29
27	-	-	3	1998; 2001; 2002	2	2002, 2013 ⁺	1	2002	4.19 ^d
	Wairarapa groundwater zone								
16	-	-	1	2005	2	2005, 2013 ⁺	1	2005	0.02
17	-	-	1	1983	1	2013 ⁺	-	-	0.22
18	-	-	2	1983, 2005, 2013	2	2005	-	-	2.84
19	-	-	3	2005, 2009, 2011	2	2007, 2013 ⁺	1	2007	0.26
20	-	-	2	2005, 2009	2	2005, 2013 ⁺	1	2005	0.02
21	-	-	1	2008	2		1	2005	5.52
22	-	-	3	2005, 2008, 2011	2		1	2005	1.16 ^d
23	-	-	1	2009	2		1	2005	2.28 ^d
24	-	-	-	-	2		1	2005	6.12
	Wainuiomata aquifer								
25	-	-	2	2005, 2008	2	2007, 2013 ⁺	1	2007	4.17

Table 3-2: Available hydrochemistry parameters for wells in the Lower Hutt Groundwater Zone

Available hydrochemistry parameter	unit
Measured	
Br, Na, F, Fe, SO ₄ , Ca, Cl, B, SiO ₂ , DO, NO ₃ -N, NO ₂ -N, Mg, K, Al, Mn, NH ₄ -N, tot. alkalinity. (CaCO ₃), PO ₄ -P, dissolved reactive phosphorous (DRP), Cr, Cu, Cd, Ni, Zn, As	mg/L
Conductivity (field and lab)	uS/cm
pH (field and lab)	pH units
Calculated	
total dissolved solids (TDS), Bicarbonate, hardness, total cations, total anions	mg/L

Figure 3-2: The Wellington Region and three of its groundwater systems, Lower Hutt Groundwater Zone (A), Wainuiomata aquifer (B) and Wairarapa groundwater zone (C); the groundwater systems outline are indicated by dashed ovals; the Wairarapa groundwater zone can be split into upper, middle and lower valley as indicated by the dashed lines, the arrow indicates the general groundwater flow direction; groundwater wells and sampling locations in the Wellington Region New Zealand are displayed as points. ZOOM IN (RIGHT) shows the Lower Hutt Groundwater Zone, its outline is indicated with a dash-dotted line, the Hutt River is indicated as a dotted line, the arrow indicates the general groundwater flow direction, pentagons indicate groundwater sampling location and crossed circles indicate aquifer material sampling locations. Well 7 and 9, and 4 and 26 have the same location (upper, lower well, respectively).

3.1 Lower Hutt Groundwater Zone

The Lower Hutt Groundwater Zone (LHGWZ) is an alluvial gravel aquifer system located in the Hutt Valley, a sedimentary basin (Fig. 3-2). The LHGWZ is composed of multiple layered aquifers that are interconnected in a small unconfined area of ca. 5 km² [Gyopari, 2013]. Layers of aquifers and aquicludes have been formed during changing climatic periods and sea-level fluctuation in the last 50,000 years in concert with constant deposition of gravel from the Hutt River [O'Callaghan, 1996; McConchie et al., 2011]. Table 3-3 summarizes the layering of aquifers and aquicludes in the LHGWZ and their composition and time of formation after Brown and Jones (2000).

The water bearing material in the LHGWZ is composed of greywacke gravel, which has been transported by the Hutt River from the ranges located further north (Taraia Ranges) or slopes surrounding the area which are all part of the Torlesse Composite Terrane [Begg and Johnston, 2000]. The composition of the water bearing gravels is expected to be similar to the rock it is originating from, but may be partly altered, possibly depleted in reactive minerals, due to weathering during wind and rain erosion and transportation in the Hutt River. Rowe (1980) determined the bulk composition of greywacke rock in the aquifer region by XRF (X-Ray Fluorescence) and XRD (X-Ray Diffraction) analysis in an extensive study using rock samples of ~700 kg at six sampling locations each. Rowe found 24% quartz, 25% plagioclase (90% albite and 10% anorthite) and smaller amounts of K-feldspar (4%), biotite (4%), chlorite (5%) and muscovite (1%), further detailed in Appendix D1. The general evolution of major hydrochemistry with residence time in the LHGWZ (Fig. 3-3) illustrates increasing Na and HCO₃ concentrations with increasing groundwater age, suggesting increasing effects of mineral weathering on groundwater quality with increasing residence time.

The main recharge source of the LHGWZ is the Hutt River. The remaining recharge originates from infiltrating rain [Phreatos, 2003; Gyopari, 2013]. The amount and timing of recharge from the river have not been extensively studied because it is difficult to measure. Butcher (1993) estimated average monthly rainfall recharge in the LHGWZ, summarized in Tab. 3-5, using precipitation data and a simple soil moisture model (Eqn. 3-1). Estimated horizontal hydraulic conductivity values (K_h) for the main aquifers are summarized in Tab. 3-4 [Gyopari, 2014]. These indicate decreasing flow, therefore increasing residence time of the water from the upper to the lower aquifers.

$$\text{Recharge} = \text{Rainfall} - \text{Actual Evapotranspiration} - \text{Soil Moisture Deficit} \quad \text{Eqn. 3-1}$$

The groundwater zone's geometry and groundwater flow are believed to be relatively simple, due to three relatively homogeneous main (interconnected) aquifers (i.e. the Taita alluvium and the two Waiwhetu artesian gravels) [e.g. Phreatos, 2003]. Time series measurements of tritium and SF₆ and relatively long records of major hydrochemistry (1993-2012) are available at 14 groundwater sites and one surface water site (Fig. 3-2 and Tab. 3-1). CFC data (CFC-12, CFC-11 and few CFC-113) are also

available, but are of limited use, because elevated and reduced concentrations¹³ have been observed in the majority of sites compared to SF₆ and tritium further detailed in Chapter 4. This prevents the use of CFCs as reliable age tracers in the LHGWZ. All 14 groundwater wells with available major hydrochemistry and age tracer data are water supply wells¹⁴ that tap into the two Waiwhetu aquifer layers. These aquifer layers are the main sources of water supply from the LHGWZ and in the following referred to as upper and lower aquifer. For further detail on the LHGWZ the following references can be consulted: Grant-Taylor (1967), Butcher (1993) and Gyopari (2013).

Table 3-3: Strata summary of Hutt aquifer (after Brown and Jones, 2000), * the artesian Waiwhetu aquifer is composed of two layers, upper and lower Waiwhetu aquifer; + B.P. refers to before present

Aquifer layer	Type	Origin	Material	Time evolved ⁺
Taita Alluvium(1)	Unconfined aquifer	(Hutt) river fluvial deposits	Grey brown gravel; yellow brown silt; poorly sorted rounded to sub-angular, up to 30/ 50mm	4 ka B.P - present
Melling Peat	Aquiclude		Wood fragments	4.0 ka B.P.
Taita Alluvium(2)	Aquifer	(Hutt) river fluvial dep.	Grey blue gravel; poorly sorted round to sub-angular, < 30 - 50mm	6.5-4.0 ka B.P.
Petone Marine Beds	Aquiclude	Marine deposits	Sand, shells	6.5 ka B.P.
Taita Alluvium	Aquifer	(Hutt) river fluvial deposits	In some places hard to distinguish, mainly gravel clasts, sandy gravel, silty gravel, silty clayey gravel, gravelly sand, sand; poorly sorted, round to sub-angular <50 - 100mm	Older than 6.5 ka B.P.
Waiwhetu artesian gravel two layers*	Aquifer			Last glaciation (Otira) 22-15ka B.P
Willford shell bed	Aquiclude	Marine deposits	Silt, clay, sand, shells	High sea level, last interglac.(Kaihinuwa)
Moera gravel	Aquifer	(Hutt) river fluvial deposits	Weathered gravel (brown with rust brown & black staining), yellow silt & sand; poorly sorted rounded/ sub-rounded to sub-angular/ angular gravel < 50 to 80mm	Penultimate glaciation (Waimea), >40ka BP
Deeper strata	mix	two glacial and three interglacial deposits		
Greywacke	Greywacke basement rock			Permian 220-300Ma BP

Table 3-4: Modelled hydraulic conductivity data in horizontal direction (K_{hx}) for the main aquifer strata in the LHGWZ [Gyopari, 2013]

Aquifer layer	Taita Alluvium (2)	Upper Waiwhetu	Lower Waiwhetu	Moera
K _{hx} [m ³ /m ² /d]	1000	1400	336	200

Table 3-5: Recharge estimate for the Lower Hutt Groundwater Zone from precipitation, evapotranspiration and soil moisture data [Butcher, 1993]

Calendar month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
Mean Recharge [mm]	18	8	36	58	117	135	138	108	73	72	41	45	833

¹³ Elevated concentrations can be associated with contamination (from anthropogenic sources) and reduced concentrations can be associated with degradation (usually only occurring in anoxic water).

¹⁴ These include public and private, artesian and pumped wells. Well screens had generally been constructed to sample the entire aquifer layer.

Figure 3-3: Piper plot of selected wells in the LHGWZ, errors indicate general evolution of major hydrochemistry with increasing residence time (RT) showing an increase in HCO_3^- and Na with increasing RT suggesting mineral weathering.

3.2 Wairarapa and Wainuiomata aquifer

The Wairarapa groundwater zone is located in the Wairarapa Valley in the eastern part of the Wellington Region (Fig. 3-2). The groundwater zone's formation and composition is similar to that of the LHGWZ. It is an alluvial gravel aquifer system that formed during glacial and interglacial periods during the Holocene and Pleistocene. The water bearing strata are composed of greywacke gravel. Marine deposits formed aquicludes. The aquifer system is unconfined and recharged by both rain and river infiltration (with rain recharge equalling about 35% of the total recharge) [Jones and Gyopari, 2006]. The groundwater zone is compartmentalized into various smaller interconnected aquifers by numerous fault lines that cross the Wairarapa Valley. For reference, the aquifer system is subdivided into the three main aquifer zones - the upper (located furthest north), lower (located furthest south) and middle valley (located between the upper and lower valley) [Jones and Gyopari, 2006] as illustrated in Fig. 3-2. Hydraulic conductivity varies greatly throughout the groundwater zone due to a complex mosaic of sedimentary layers penetrated and lifted or subducted by the traversing fault lines [Jones and Gyopari, 2006]. Further detail on the Wairarapa groundwater system can be found in Begg et al. (2005) and Jones and Gyopari (2006).

The Wainuiomata aquifer is located in the south of the Wellington region and is considerably smaller than the Wairarapa groundwater zone and the LHGWZ. The Wainuiomata aquifer has formed in an alluvial valley filled with alluvial gravel and sand [WRC, 1993]. The aquifer is shallow and unconfined and recharged by both rain and river infiltration. Little data and information on the Wainuiomata aquifer are available as the aquifer is not significantly used for water supply of the Wellington Region [Jones and Barker, 2005].

For both the Wairarapa and the Wainuiomata aquifer tritium, SF₆ and CFC (CFC-12, CFC-11 and for some wells also CFC-113) data are available (see Tab. 3-1 for details). Similar to the LHGWZ, CFCs have a limited use as groundwater age tracers in the Wairarapa and the Wainuiomata aquifer. Elevated and reduced concentrations of the CFC were found at the majority of sites which resulted in misleading age estimates further detailed in Chapter 4.

4. Halon-1301 a new groundwater age tracer

4.1 Introduction

As extensively discussed in Chapter 2, additional tracers (or alternatively other groundwater dating techniques) are needed to reduce the limitations faced with currently used age tracers and to ultimately allow for more robust age estimates. Busenberg and Plummer (2008) suggested the use of CFC-13 (CF_3Cl) as a complementary age tracer. Following their suggestion, the initial intent of this study was to determine CFC-13 in various groundwater environments to further assess its performance as an age tracer. To analyse groundwater samples for CFC-13, the analytical system developed by Busenberg and Plummer (2008) composed of a gas chromatography with electron capture detector (GC/ECD) was used. While analysing a range of standard gases and modern water¹⁵, it was discovered that the signal formerly reported to be caused by CFC-13 is actually caused by Halon-1301 (both compounds have an extremely close retention time on Busenberg and Plummer's analytical system). This discovery raised the question of whether Halon-1301 (CF_3Br) can be used as a groundwater age tracer (instead of CFC-13). The behaviour of Halon-1301 in water and its potential use as a groundwater age tracer had not been previously investigated.

This chapter provides the strong evidence behind the discovery of Halon-1301 in groundwater. Its potential use as a groundwater age tracer is assessed by means of its properties and through testing of its performance against already established tracers (SF_6 , CFC-12, CFC-11 and tritium) taking advantage of the relatively well defined age information of New Zealand groundwater estimated from time series tritium and SF_6 data [Morgenstern and Taylor, 2009; van der Raaij and Beyer, 2015]. The analysed samples included oxic and anoxic groundwater that had been recharged recently¹⁶ to over 100 years ago. This allowed for assessment of Halon-1301's performance as an age tracer under different groundwater conditions.

4.2 Properties of Halon-1301 important for its use as a groundwater age tracer

Generally for a groundwater tracer it is important that a) it has a resolved atmospheric input, b) it is easily detectable in water, c) the tracer is stable in the atmosphere, d) it is conservative in groundwater (or the reactions/processes the tracer undergoes are well-studied and taken into account when inferring age from its concentration) and e) the tracer lacks local anthropogenic or natural contamination sources which would interfere with the age estimation from its concentration [Plummer et al., 2006]. As shown in the following, the established properties of Halon-1301 satisfy many of these key properties required for its use as a groundwater age tracer.

¹⁵ Modern water refers to water recharged a few weeks to months ago. River water samples and equilibrated tap water samples (equilibrated with atmospheric air at time of analysis) were used as modern water samples.

¹⁶ Recharged weeks to months ago

Halon-1301 (CF_3Br) was used as a refrigerant gas and fire suppressant agent in the mid-90s. At present it is still used in rare cases (due to recycling procedures) as an effective fire suppression agent in high-value facilities, like airports (fuelling of planes), telecommunication and large scale data centres. A small amount of Halon-1301 is also released during preparation of the pesticide Fipronil (mainly produced in China and France) [HTOC, 2012]. Halon-1301 was shown to be stable and inert when stored in gaseous form [Fraser et al., 1991; Peacock et al., 1994] and also in the atmosphere (with a lifetime of 400-10000 years) [Burkholder et al., 1991; Newland et al., 2013].

Halon-1301's atmospheric history has been well monitored in air samples covering the recent decades by NOAA (National Oceanic and Atmospheric Administration) and AGAGE (Advanced Global Atmospheric Experiment), and data from 1969 to 1977 were reconstructed by Butler et al. (1999). The results of these programmes showed that the concentration of Halon-1301 in the atmosphere prior to 1970 was not detectable. Its entirely anthropogenic nature was confirmed by analysis of Arctic and Antarctic firn air [Butler et al., 1999] showing absence of Halon-1301 prior to 1960.

As illustrated in Fig. 4-1, Halon-1301's atmospheric concentration had started to increase after the 1970s until about 2000 following a pattern similar to that of SF_6 . From about 2000 atmospheric Halon-1301 concentrations started to slowly level out because of production restriction due to its ozone depleting effect (Montreal Protocol in 1987) [e.g. Montzka et al., 2011]. Atmospheric Halon-1301 concentrations are projected to start declining between 2020 and 2030, depending on the model parameters used such as its atmospheric lifetime [e.g. Newland et al., 2013]. With its specific atmospheric trend Halon-1301 is expected to be useful for dating groundwater recharged from the 1970s onwards, depending on the limit of detection of the analytical procedure.

Figure 4-1: Records of Halon-1301 and SF_6 atmospheric mixing ratios in the southern hemisphere (Cape Grim, Australia) [Newland et al., 2013; Butler et al., 1999; Thompson et al., 2004; Miller et al. 2008; Maiss and Brenninkmeijer, 1998]

Since Halon-1301 has not been commonly used (compared to the CFCs) and is restricted by the Montreal protocol, local emissions and thus local atmospheric excess may be quite rare. Although comprehensive analysis of potential local sources has not been carried out, studies such as that by Barletta (2011) in Los Angeles, US, did not find local enhancement of Halon-1301 in city environments. Only one study found unusual fluctuations of Halon-1301 in the atmosphere in two stations in Poland, at Krakow and Kasprowy Wierch stations. The research group is still investigating reasons, but speculate it may be attributed to local sources from close-by city/industry environments [Bartyzel, 2015].

Halon-1301 is soluble in water (saturation: 30 mg/L at 20°C, in contact with modern air with 3.15 pptv Halon-1301: 7.4 fmol/L at 20°C, 10 m elevation) [Deeds, 2008]. In contrast to the solubility of SF₆, which had been well studied and directly measured [Wilhelm et al., 1977; Bullister et al., 2002], the solubility parameters of Halon-1301 had only been estimated by Deeds (2008) using the solubility estimation methods of Meylan and Howard (1991) and Meylan et al. (1996). Actual solubility measurements of Halon-1301 were not available in literature (according to extensive searches and further backed up by personal communication with Daniel Deeds, 06/03/2015). Robust and precise solubility measurements are important for inferring groundwater age from aqueous concentrations of Halon-1301.

Overall, these properties meet many of the key properties required for its use as a groundwater age tracer. However, little was known considering Halon-1301's conservativeness and contamination potential in groundwater and its performance in groundwater for the use as an age tracer relative to other tracers. To fully assess the potential of Halon-1301 as a groundwater age tracer the following questions needed to be answered:

- Is Halon-1301 easily determinable in groundwater and what is its application range (depending on the LOD of the analysis)?
- Does Halon-1301 degrade like the structurally similar CFCs in anoxic water [Plummer and Busenberg, 1999] or due to hydrolysis [Butler et al., 1991; Sturges et al., 1991; Kanta Rao et al., 2003]?
- Does Halon-1301 sorb to organic material in soil or elute from sampling material as suggested for CFCs [Reynolds et al., 1990; Cook and Solomon, 1995]?
- Does its use as a fire suppression agent and by-product during pesticide (Fipronil) production lead to 'local' contamination of groundwater resulting in misleading age estimates, similar to CFCs?
- Do CFC-13 and Halon-1301 signals (and potentially additional co-eluting compounds) interfere during groundwater analysis, which may lead to overestimated Halon-1301 concentrations (e.g. in case of CFC-13 contamination)?

- Most importantly, how does Halon-1301 perform (both alone and in combination with other tracers) as an age tracer relative to other tracers in any groundwater environment?

To answer these questions, 17 New Zealand groundwater samples and various modern (river) water samples were analysed for Halon-1301 as part of this study. As shown subsequently, the analysis for Halon-1301 allowed for the simultaneous determination of SF₆. Both SF₆ and Halon-1301 are gaseous substances and were expected to have similar behaviour in water. Their simultaneous determination therefore allowed for the identification of problems such as contamination, due to contact with air during sampling or local sources, or degradation (indicated by elevated/reduced concentrations of one of the compounds with respect to the other).

Modern (equilibrated tap and river) water samples were used with the initial aim of validating the previously determined solubility estimates for Halon-1301. On seeing inconsistencies, they were instead used to estimate Halon-1301's solubility. All groundwater samples had been previously dated with tritium, CFC-12, CFC-11 and SF₆. Piston and exponential piston flow ages were determined for Halon-1301 and SF₆, inferred by matching their historic input (i.e. atmospheric concentrations) to their determined concentrations in the groundwater samples. Comparison of Halon-1301-inferred piston flow and exponential piston flow mean residence times (MRTs) to relatively robustly tritium- and SF₆-derived MRTs enabled direct assessment of the performance of Halon-1301 as a groundwater age tracer. Comparison of age information estimated from tritium and four different gaseous tracers (SF₆, Halon-1301 and CFC-12 and CFC-11) in this study allowed for assessment of unsaturated zones processes of Halon-1301 and its potential degradation/contamination. Since some of the anoxic groundwater samples clearly have shown evidence of CFC degradation, comparison of Halon-1301 from these samples enabled a first understanding of the potential for degradation of Halon-1301 in anoxic groundwater systems.

4.3 Methods

Since the methods used to identify Halon-1301 in groundwater and assess its potential use as a groundwater age tracer were similar, these are presented together in the following. Firstly, the standard gases and water samples used in this study are listed. Secondly, details on the sampling procedure of the groundwater samples are given and the analytical procedure for determination of Halon-1301 in water is presented. Subsequently the methods for estimation of solubility, calibration of the analytical procedure, estimation of the analytical uncertainty and determination of the recharge year from concentrations of Halon-1301 are described.

4.3.1 Samples

Standard gases

A calibrated air standard (prepared by Scripps Institution of Oceanography in 2011, containing mainly SF₆, CFC-12, CFC-13, Halon-1301 and SF₅CF₃) and a custom made standard gas (prepared by NOAA containing CFC-12, CFC-13, SF₆ and SF₅CF₃ and smaller amounts of other halocarbons, but not containing Halon-1301) were analysed. The analysed gas volumes were usually 9.97±0.02 ml (in the following referred to as 10 ml) at pressures up to 1 bar at room temperature. In a few cases a larger amount (approximately 100 ml samples from ~1 bar to ~20 bar) of the custom made standard gas, which contained CFC-13, but lacked Halon-1301, was analysed to assess the analytical sensitivity for CFC-13. Additionally, using the same analytical setup, 0.502 ± 0.001 ml (in the following referred to as 0.5 ml) of a standard gas mixture prepared by New Zealand Industrial Gases (NZIG) containing only Halon-1301 and SF₆ was analysed. The detailed composition of the three analysed gases can be found in Tab. 4-1. It was believed that there were no detectable traces of Halon-1301 in the CFC-13 only standard (custom made NOAA standard) or CFC-13 in the Halon-1301 only standard (custom made NZIG standard). There may have been detectable traces of compounds with similar retention time to Halon-1301 and CFC-13 in the analysed gases, which may have interfered with the Halon-1301 signal (potential interfering candidates are further evaluated in Appendix B1). However, analysis of these standard gases, calibrated air and modern water demonstrated this was not a likely problem.

Table 4-1: Compounds and their concentrations in calibrated air standard and two custom made standard gases used in this study, * standards were gravimetrically prepared, because absolute standards for these compounds are not available

Compound	Calibrated air (Scripps)	Custom made standard gas (NOAA)	Custom made standard gas (NZIG)
SF ₆	7.53 (±0.81) ppt	10.70 (±0.02) ppt (analysed)	1.02 (± 0.1) ppb
CFC-13	Not reported, but approx. as atmospheric concentration at time of filling (5.3 ppt)	10.1 (±0.1) ppt (gravimetric blend*)	None
Halon-1301	3.27 (±1.55) ppt	None	3.16 (± 0.3) ppb
SF ₅ CF ₃	Not reported, but determined from atm. conc. (0.16ppt)	21.5 (±0.4) ppt (gravimetric blend*)	None
CFC-12	530.80 (± 0.06) ppt	544.5 (±1.5) ppt (analysed)	None
others	Other CFCs and Halon gases usually contained in air	~ 10.1 ppt of HFC-32, HFC-23, HFC-125, HFC-143a, CFC-115	None

Water samples

River water and a variety of equilibrated (at close to constant temperature) tap water samples were taken as representative modern water samples, to verify concentrations of Halon-1301 and CFC-13 in modern water and to confirm estimated solubility data. This method presupposed no contamination of CFC-13, SF₆ or Halon-1301 from air in the lab facilities, surrounding environment or river sampling locations, which seemed reasonable, due to the absence of sources of these compounds in these areas. To confirm the absence of elevated SF₆, CFC-13 and Halon-1301 concentrations in the lab facilities, air samples were regularly analysed. To enable a relatively comprehensive assessment of the use of Halon-

1301 as a groundwater age tracer, groundwater samples previously dated with tritium, SF₆, CFC-12 and CFC-11 covering a wide range of mean residence times and including anoxic and oxic samples and samples with apparent contamination/degradation of the CFCs were chosen.

Simultaneous analysis for Halon-1301 and SF₆ in 35 groundwater samples and eight river and equilibrated tap water samples was carried out. The groundwater samples were taken from 17 different sites in the Wellington region from three different aquifer systems (the Lower Hutt and the Wairarapa Groundwater Zone and the Wainuiomata aquifer described in Chapter 3). The sampling sites, number of samples taken for Halon-1301 analysis and corresponding aquifer systems are summarized in Tab. 4-2. Table 4-2 also includes the previously determined recharge temperature and amount of excess air (determined by Ar and N₂ analysis) [Stewart and Morgenstern, 2001; Jones and Gyopari, 2006; Tidswell et al., 2012], the number of previously determined CFC -11 and -12, SF₆ and tritium data and the waters' oxygen content (anoxic/oxic¹⁷). The location of the sampling sites is illustrated in Fig. 3-2 in Chapter 3.

Table 4-2: Summary of water samples analysed in this study: site number, amount of duplicates analysed, recharge temperature and excess air determined from noble gas analysis, oxygen content^b and number of available CFC, tritium and SF₆ data; ^a no data are available for this site - average NZ recharge temperature of 12.1°C ± 1.8 and average NZ excess air 12.1 ± 1.8 ml(STP)/L [van der Raaij and Beyer, 2015] are used; ^b oxic or anoxic water (distinguished according to dissolved oxygen (DO) concentration), detailed DO data and tracer sampling times can be found in Tab. 2-2 in Chapter 2.

Site #	# of water samples analysed for Halon-1301	recharge temperature [°C]	Excess air [ml(STP)/L]	oxic/anoxic water ^b	# of SF ₆ data	# of CFC data	# of tritium data
25	3	10.7 ± 1.8	0.6 ± 0.9	oxic	2	1	2
6	3	14.2 ± 1.9	-0.7 ± 0.9	oxic	1	2	4
4	3	12.3 ± 1.9	1.0 ± 0.8	anoxic	4	3	9
3	3	15.8 ± 2.1	2.3 ± 0.9	anoxic	2	1	3
15	4	15.4; 12.3	2.9 ± 1.8 ^a	oxic	1	1	1
26	3	10.4 ± 1.5	0.8 ± 0.8	anoxic	3	2	4
27	3	12.1 ± 1.8 ^a	2.9 ± 1.8 ^a	anoxic	2	1	3
11	3	9.7 ± 1.5	0.3 ± 0.8	anoxic	3	2	1
1	3	10.8 ± 1.2	0.6 ± 0.6	anoxic	1	2	2
23	1	14.0 ± 0.1	2.1 ± 0.2	anoxic	2	1	1
22	1	10.7 ± 1.6	2.0 ± 0.8	anoxic	3	2	3
20	1	20.0 ± 2.4	5.5 ± 0.9	anoxic	2	1	2
16	1	20.7 ± 1.5	-3.4 ± 0.8	anoxic	2	1	1
17	1	9.4 ± 1.8	3.0 ± 1.0	anoxic	1	0	1
19	1	10.3 ± 1.8	0.1 ± 1.0	anoxic	2	1	3
24	1	14.2 ± 1.5	-0.3 ± 0.8	oxic	2	1	0
21	1	12.7 ± 1.5	-0.4 ± 0.8	oxic	2	1	1
18	1	11.4 ± 1.7	2.4 ± 0.8	oxic	1	0	2
equilibr. water	4	14.4; 19.8	n/a	oxic	1	1	0

¹⁷ Water that contained > 0.5 mg/L DO was considered as oxic (≤ 0.5 mg/L was considered as anoxic). The threshold of 0.5 mg/L was chosen based on recommendation of McMahon and Chapelle (2008) and Jurgens et al. (2009) and because the variation in major ion concentrations ≤ 0.5 mg/L DO was significantly larger than > 0.5 mg/L (see Appendix D2 for detail).

To collect water for determination of Halon-1301 (and CFC-13), the standard sampling procedure used for collection of water for determination of other water soluble gaseous tracers such as SF₆ and CFCs was followed. To ensure the sampling of fresh unexposed groundwater (i.e. not the water stagnating in the dead volume of the well), the well was flushed at least three times of its volume and until conductivity, pH and dissolved oxygen (DO) stabilized [Daughney et al., 2006]. To avoid alteration of Halon-1301 (and CFC-13) concentrations with UV light and contamination or adsorption of Halon-1301 and SF₆ (and CFC-13) from/onto the sampling material (assuming Halon-1301 behaves similar to structurally similar CFCs), only brown borosilicate glass bottles and nylon tubing were used and the use of PTFE/Teflon or other fluorine bearing plastics was avoided [Reynolds et al., 1990; van der Raaij and Beyer, 2015]. To avoid contamination of the samples with modern air, sampling was carried out under rigorous exclusion of air by inserting a nylon tube to the bottom of the sampling bottle and filling it from the bottom. Then the bottle was let to overflow, so the water volume was replaced by several bottle volumes. The bottle was quickly capped and checked for presence of bubbles and if necessary the sampling process was repeated until no bubble was present. Groundwater samples in the Lower Hutt Groundwater Zone (LHGWZ) and river water samples were collected as triplicates, of which two were analysed directly after sampling and one was analysed after seven weeks storage at 14°C to assess potential degradation of Halon-1301 in water during storage. One river water sample was analysed after 1.23 years of storage at 14°C. The simultaneous determination of SF₆ and Halon-1301 allowed for isolation of Halon-1301 degradation, since SF₆ was not known to degrade in oxic or anoxic environments. An isolated reduced concentration in Halon-1301 can indicate Halon-1301 degradation, in contrast to a combined reduced concentration (of both Halon-1301 and SF₆) that can indicate e.g. escaping of gas into headspace (i.e. degassing).

4.3.2 Analytical procedure

Busenberg and Plummer's (2008) analytical setup consisting of a gas chromatography (GC) including a mole sieve 5A pre-column, a 3 m long column packed with 60-80 mesh Carbograph 1AC coated with 1% AT-100, and attached electron capture detector (ECD) was used. For the purpose of this study, the author is confident that the analytical setup was similar enough to their approach to give comparable results, and many replicates under varying conditions were taken to ensure representativeness of the results (detailed in Appendix B2).

To extract the trace gases from the water samples, 1 L water samples were purged in a vacuum-sparging extraction system similar to that developed by Busenberg and Plummer (2000). Details on the exact apparatus and methodology are given in van der Raaij and Beyer (2015). The GC/ECD signals obtained when analysing the purged gas from the 1 L water samples were interpreted by using calibration curves established with the gas standards. The solubility relationship, detailed in the following, was then used

to determine equivalent atmospheric molar ratios at time of equilibrium/ recharge from aqueous concentrations of CFC-13, Halon-1301 and SF₆ (which were used to infer age). If applicable, the amount of Halon-1301, CFC-13 and SF₆ in the water sample was corrected for headspace (as measured in the sampling bottle) and/or excess air (as previously determined by dissolved Ar and N₂ analysis after Heaton and Vogel (1981), further detailed in Appendix B3).

Please note the sample extraction procedure used in this study was different to the spray equilibrium technique used by Busenberg and Plummer (2008). Their technique implies sampling of hundreds of litres of water until equilibrium between a headspace (of approximately 100 ml) and the water phase is reached. The concentration of tracers is essentially equivalent to their atmospheric concentration at time of recharge of the analysed water. The concentrations of extracted tracers in the purge gas (this study) and the equilibrated headspace (Busenberg and Plummer's study) were determined on a similar analytical setup [Busenberg and Plummer, 2008]. This implied that concentrations and limit of detection determined when using standard gases and present day air in Busenberg and Plummer's (2008) study and this study were relatively comparable, but may have differed for concentrations determined in water, dependent on the extraction method used.

4.3.3 Solubility

To confirm whether the signal determined in water relates to Halon-1301 or CFC-13, their equivalent atmospheric concentration was determined using the solubility relationship (also referred to as Clarke-Glew-Weiss fit) in Eqn. 4-1 [Warner and Weiss, 1985] and solubility parameters given in Tab. 4-3. Since only solubility estimates for Halon-1301 were available [Deeds, 2008] and solubility is important for inference of the recharge year from Halon-1301 concentrations in groundwater, modern (equilibrated tap and river) water was used to validate the previously determined solubility estimates for Halon-1301. On seeing inconsistencies, solubility was estimated using modern (equilibrated tap and river) water and relatively young oxic groundwater samples (with a MRT <2 years)¹⁸ at temperatures ranging from 280 to 300 K. To estimate the robustness of the estimated Halon-1301 solubility, the solubility of SF₆ was also determined in these samples.

Table 4-3: Reported solubility parameters for Halon-1301 and CFC-13 and resulting Henry coefficient at 12.5 °C and 10 m elevation; * estimated solubility parameters for Halon-1301 in this study with an uncertainty of 10%

Compound	Reference	Solubility parameters for Henry/Bunsen/Ostwald coefficient			
		A	B	C	Solubility Coefficient
CFC-13	Scharlin and Battino (1995)	-157.11	229.8978	67.90798	Ostwald [L/L]
CFC-13	Deeds (2008)	-34.7447	53.1175	11.9348	Bunsen [L/L]
SF ₆	Bullister et al. (2002)	-96.5975	139.883	37.8193	Henry [mol/L/atm]
Halon-1301	Deeds (2008)	-92.9683	140.1702	36.3776	Henry [mol/L/atm]
Halon-1301	this study*	-91.878	139.001	35.478	Henry [mol/L/atm]

¹⁸ These modern waters were specifically collected for estimation of the solubility of Halon-1301.

$$\text{Solubility relationship: } \ln K_x = A + B \frac{100}{T} + C \ln \frac{T}{100}, \quad \text{Eqn. 4-1}$$

with K_x as the solubility - estimated as one of Henry's (K_H), Bunsen (K_B) or Ostwald (K_O) coefficient, T as the recharge temperature (in K) and A , B , C as the solubility fit parameters, given in Tab. 4-3. A salinity term can be added to Eqn. 4-1, but this is negligible for most groundwater applications, so was ignored here. The Ostwald and Bunsen coefficients can both be expressed as Henry coefficient according to the following relationships given in Eqn.4- 2 A and B [Emerson and Hedges, 2008].

$$\text{Solubility coefficients: A: } K_H = \frac{K_O}{R \times T} \quad \text{and} \quad \text{B: } K_H = \frac{K_B}{R \times 273.15 K}, \quad \text{Eqn. 4-2}$$

where R as the gas constant (8.314 J/K/mol).

4.3.4 Calibration

The amount of Halon-1301, CFC-13 and SF₆ in water was determined by establishing a calibration curve (least square fit, forced through 0/0)¹⁹ with approximately 10 ml certified air standard at various pressures. A calibration curve was established every day before measurement commenced, since the performance of the GC/ECD could change from day to day, due to fluctuations in the environment (e.g. temperature) or aging of the GC material (e.g. column fill). Because Halon-1301 concentrations in 10 ml calibrated air standard did not sufficiently cover concentrations obtained in modern water samples, another standard gas containing larger amounts of Halon-1301 and SF₆ prepared by NZIG (composition stated in Tab. 4-1) was used in a smaller standard loop of approximately 0.5 ml at various pressures. Additionally tap water samples ranging from ~1 to ~15 L volume and 10 ml modern air samples at pressures from ~1 to ~3.5 bar were analysed to assess the linearity of the ECD signal towards Halon-1301 concentrations in the concentration range obtained in old to modern 1 L groundwater samples. If linearity was found, then previously determined calibration curves (using the calibrated air standard) were linearly up-scaled to estimate Halon-1301 concentrations in groundwater.²⁰ The additional uncertainty introduced by this approach was taken into account when interpreting the findings (see section 4.5).

4.3.5 Analytical uncertainty

To determine the overall relative uncertainty arising from the analytical procedure, the EURACHEM/CITAC Guide CG4 [Ellison and Williams, 2012] was followed. This guide recommends the

¹⁹ The analysis of blank samples (only containing N₂) indicated no observable signal for SF₆ and Halon-1301. In addition, the statistical difference between the intercept of the calibration curves for SF₆ and Halon-1301 (when not forced through 0/0) were not significant (at 99% confidence). The intercept of the calibration curve was therefore considered insignificantly different from 0, hence the calibration curve was forced through 0/0 to simplify the calibration procedure and to ensure 0 signal was interpreted as a concentration of 0 (fmol/L, e.g.). This procedure was following the suggestions of Helsel and Hirsch (2002) and Caulcutt and Boddy (1983).

²⁰ This was relevant for all groundwater samples for which calibration curves were established at the time of measurement with calibrated air only.

method described in Kragten (1994), which also implies a sensitivity analysis. The standard measurement error was determined as the total of the following (independent) uncertainties:

$$u_{total}(x) = \sqrt{u1^2 + u2^2 + u3^2 + u4^2 + u5^2 + u6^2 + u7^2} . \quad \text{Eqn. 4-3}$$

- u1: Uncertainty from least square regression (calibration curve)
- u2: Uncertainty in standard gas concentration
- u3: Repeatability error from relative standard deviation of replicates
- u4: Uncertainty related to correction for headspace
- u5: Uncertainty related to correction for excess air
- u6: Uncertainty in recharge temperature
- u7: Uncertainty in solubility

Replicate samples were analysed to determine the repeatability standard deviation of the analysis. The

absolute standard deviation was defined as: $ASD_i = \sqrt{\frac{\sum[(a_i - \bar{x}_i)]^2}{n-1}}$, Eqn. 4-4

where $a_i - \bar{x}_i$ is the difference between the concentrations obtained for one of the replicate samples a_i with overall mean value $\bar{x}_i$ for n samples and m number of replicates.

The overall relative standard deviation can then be determined as mean of all replicate samples:

$$D_i = \sum \left(\frac{ASD_i}{\bar{x}_i} \right) . \quad \text{Eqn. 4-5}$$

The limit of detection (LOD) and limit of quantification (LOQ) were determined using the slope and standard deviation (SD) of the calibration curve [Shrivastava and Gupta, 2011]:

$$LOD = 3.3 \frac{SD}{slope} \text{ and } LOQ = 10 \frac{SD}{slope} \quad \text{Eqn. 4-6}$$

4.3.6 Determination of recharge year

To assess the performance of Halon-1301 as an age tracer against established age tracers, the recharge year or residence time of the groundwater was inferred. For that the equivalent partial pressure of Halon-1301 and SF₆ in the atmosphere at time of recharge (determined as described in the previous sections) was compared to their historic southern hemisphere atmospheric records illustrated in Fig. 4-1. It was assumed that Halon-1301 concentrations were well mixed across the atmosphere of the southern hemisphere as suggested by Montzka and Fraser (2003) and Butler et al. (1998) and local sources of Halon-1301 were lacking as indicated by regular analysis of local air in this study, so that southern hemisphere atmospheric concentrations could be used to estimate concentrations of Halon-1301 in recharge in this study.

The piston flow recharge year can be found when observed (equivalent) atmospheric tracer concentrations match historic atmospheric tracer concentrations. However, misleading age estimations can be obtained when assuming piston flow, which does not take account of mixing processes of groundwater that are usually occurring during discharge or sampling [e.g. Eberts et al.,

2012]. As discussed in Chapter 2, lumped parameter models (LPMs) are often used to conceptualize groundwater mixing and to infer an age distribution and the mean residence time (MRT) of a groundwater sample [Maloszewski and Zuber, 1982; Jurgens et al., 2012]. In this study, the commonly used exponential piston flow modelling (EPM) was used, which had previously been found to best represent tritium and SF₆ (time series) data at the studied groundwater sites (as also shown in Chapter 5). Age (LPM) modelling was carried out using TracerLPM, a commonly used spreadsheet approach to fit LPMs to tracer data using a deterministic single ‘best fit’ approach (USGS) [Jurgens et al., 2012]. Generally a range of EPMs with various exponential to total flow ratio (in the following referred to as E/PM)²¹ can be fit to single tracer measurements, as obtained for Halon-1301 and SF₆ in this study. Since the mixing parameter could not be adequately constrained with a single measurement of Halon-1301 and SF₆, in this study their E/PM was constrained to the E/PM previously (relatively robustly) inferred from tritium time series data. It was assumed that this approach was adequate under the assumption of steady state at each sampling location, which had been indicated by assessment of time series hydrochemistry data (using trend and seasonality analysis, further detailed in Chapter 6). The MRTs estimated from SF₆ and Halon-1301 in this study were subsequently compared to previously determined MRTs inferred from tritium. Halon-1301 concentrations were also assessed with regard to previously observed degradation or contamination with the CFCs (CFC-12 and CFC-11) in these waters. Since the main interest of this study was to assess how Halon-1301-inferred MRTs compared to MRTs derived from other tracers, uncertainty in the inferred MRTs was estimated in a relatively simple error propagation approach²². For a more robust uncertainty assessment a probabilistic approach can be used as presented in Chapter 5.

In the following, the findings supporting the identification of Halon-1301 (instead of CFC-13) with the analytical method developed by Busenberg and Plummer (2008) are presented. Thereafter the assessment of Halon-1301’s performance as an age tracer in comparison to tritium, SF₆ and the CFCs (-11 and -12) is presented.

4.4 Results and discussion on the identification of Halon-1301 in groundwater

Analysis of the custom made standard gases revealed that for the gas containing CFC-13 but lacking Halon-1301 (Fig. 4-2) there was no signal peak where Busenberg and Plummer (2008) reported CFC-13 (at about 2.9 min retention time). However, for the gas containing Halon-1301 (and SF₆), but lacking CFC-13, the peak at retention time of 2.9 min was present (Fig. 4-3). This clearly identified the peak with retention time of 2.9 min in calibrated air as Halon-1301. This also indicated absence of (other)

²¹ E/PM = 1/n. n had been defined as ratio of total to exponential flow by Maloszewski and Zuber (1982).

²² Where the upper/lower uncertainty limit of the inferred MRT was determined by interpreting the measured concentration ± 1 SD using TracerLPM.

co-eluting compounds present in the custom made NOAA standard. For comparison please see the chromatogram published by Busenberg and Plummer (2008) (Fig. 4A in their publication).

Because CFC-13 was not detectable at ambient atmospheric concentrations (Fig. 4-2) with the analytical setup used in this study, the sensitivity of the setup towards CFC-13 was assessed by analysing 100 ml of the custom made standard gas (NOAA) containing 10.1 pptv of CFC-13, but lacking Halon-1301, up to ~20 bar (STP equivalent of around 2 L standard gas or 4 L 2013 air containing 5.3 pptv). This resulted in the chromatogram illustrated in Fig. 4-4 and showed what may be a very small CFC-13 peak at retention time of around 2.9 min. Assuming that the entire signal of this small peak had been caused by CFC-13, the detection limit (LOD) for CFC-13 in this study was estimated to be around 800 fmol (800×10^{-15} mol). This LOD estimate was equivalent to the amount of CFC-13 in 50 L modern water (equilibrated at 12.5°C with atmospheric air in 2013, no headspace, no excess air), or around 4 L of 2013 air. This implied to adequately quantify CFC-13 concentrations in water recharged in 2013, one would need to analyse at least 50 L of water using the vacuum purge system (this study) or around 4 L of equilibrated headspace using the headspace equilibrium technique (used in Busenberg and Plummer's study). Larger sample amounts would be necessary for water recharged before 2013.

Figure 4-2: Chromatogram of 10 ml custom made NOAA standard containing CFC-13 (almost two times the amount compared to ambient air), SF_5CF_3 , CFC-12 and SF_6 and 10 ml calibrated air standard showing a missing peak where we expected CFC-13 to appear according to Busenberg and Plummer (2008)

The use of relatively large volume of gas at high pressure (i.e. ~100 ml gas at a pressure up to ~20 bar) may have overloaded the pre-concentration traps, resulting in insufficient cooling of the gas sample being pushed through them. This may have resulted in insufficient trapping and pre-concentration of the tracer and a low to no ECD signal²³. To assess whether the low to no CFC-13 signal had been caused by overloaded traps rather than poor detectability of CFC-13, the extended calibration curves for SF_6

²³ This is particularly relevant for compounds with low boiling point. For comparison, the boiling point of CFC-13 is -81.5 °C, that of SF_6 is -68.25 °C and that of SF_5CF_3 is -20.4 °C.

and SF_5CF_3 (both can also be determined on the analytical setup developed by Busenberg and Plummer (2008)), illustrated in Fig. 4-5, were assessed. The nearly linear signal response towards both compounds indicated that both SF_6 and SF_5CF_3 could be adequately determined using ~ 100 ml gas at pressures up to ~ 20 bar. It was believed that CFC-13 was similarly well trapped, due to the similar boiling points of CFC-13 and SF_6 , although full evidence of this is subject to further study. If CFC-13 was less well-trapped, the LOD may actually be slightly higher than the estimated LOD in this study. Overall the ECD appeared to be significantly less sensitive to CFC-13 than most other detected compounds²⁴, supporting that the peak is actually caused by Halon-1301.

Figure 4-3: Chromatogram of a 0.5 ml gas sample containing Halon-1301 and SF_6 (custom made NZIG standard gas) using the analytical setup developed by Busenberg and Plummer (2008)

Figure 4-4: Chromatogram of approximately 100 ml custom made NOAA standard gas containing SF_6 , SF_5CF_3 , CFC-12 and CFC-13, but lacking Halon-1301 at 20 bar. The very small peak at 2.9 min retention time is potentially CFC-13

As an additional test to examine whether the signal as detected by Busenberg and Plummer (2008) with retention time of 2.9 min relates to Halon-1301 or CFC-13, it was assessed whether calculated

²⁴ Sensitivity is a function of electron affinity, which is dependent on the number and type of halogenated atoms in the molecule [e.g. Landowne and Lipsky, 1962; Poole, 2013 and references therein]. Electron affinity generally increases with increasing amount of halogen atoms and halogen type (increasing with F, Cl towards Br [Plummer et al., 2008]), which explains that CFC-13 (CF_3Cl) showed a significantly lower (mol specific) ECD signal compared to Halon-1301 (CF_3Br).

aqueous concentrations matched equivalent atmospheric concentrations. Halon-1301 and CFC-13 concentrations in water were calculated under two hypotheses: that the signal with retention time of 2.9 min was Halon-1301, or CFC-13. The hypothetical calibration curves for Halon-1301 and CFC-13, illustrated in Fig. 4-6²⁵, were established using 10 ml of the calibrated air standard (composition as stated in Tab. 4-1) at different pressures and the analytical setup developed by Busenberg and Plummer (2008). The Halon-1301/CFC-13 signals obtained during analysis of 1 L tap and river water samples were interpreted into equivalent amounts in fmol, summarized in Tab. 4-4. This was carried out by using the established hypothetical calibration curves given in Fig. 4-6 and solubility relationship given in Eqn. 4-1 using the solubility estimated by Deeds (2008) for Halon-1301 and Scharlin and Battino (1995) and Deeds (2008) for CFC-13. Chromatograms of 10 ml modern air (calibrated air standard) and 1 L modern (tap) water samples are shown in Fig. 4-7.

Figure 4-5: Signal response to amount of SF_6 and SF_5CF_3 in 10 and 100 ml custom made standard gas (NOAA) at ambient temperature up to 20 bar

The results summarized in Tab. 4-4 show that the equivalent atmospheric concentration in modern water (equilibrated with atmospheric air at time of sampling) was around 3 pptv for Halon-1301 and 11 pptv for CFC-13. For comparison the atmospheric concentration at time of recharge (i.e. 2013) was 3.2 pptv for Halon-1301 and 5.3 pptv for CFC-13. These findings showed that the signal at 2.9 minutes was commiserate with the expected signal from Halon-1301 at atmospheric 2013 levels, while if it was CFC-13, atmospheric concentrations would have been more than twice the 2013 value. These results further support that the compound previously identified as CFC-13 is Halon-1301.

²⁵ Please note that the hypothetical standard curves did not cover the signal range obtained for modern water samples. Analysis of modern air at pressures ranging from 1 to 3.5 bar and analysis of water samples of 3 to 15 L (in Appendix B4) confirmed the nearly linear response of the ECD towards concentrations of Halon-1301/ CFC-13 at higher concentrations. Only for very high amounts (signals of approximately one order of magnitude higher than obtained in modern water) did the quadratic regression fit slightly better than the linear regression. A linear relationship between signal and amount was used to estimate concentrations of Halon-1301 and CFC-13 in modern water. Since the identification of Halon-1301/CFC-13 was the main aim of this section, uncertainties were not determined for the inferred aqueous concentrations and atmospheric concentrations. The reader is referred to the subsequent section for details on uncertainty estimates.

Figure 4-6: Typical standard curve data for Halon-1301/CFC-13 and equivalent concentration in 10 ml standard gas using the gas law relationship ($p \cdot V = n \cdot R \cdot T$)

Figure 4-7: Chromatogram of 10 ml calibrated air standard and 1 L tap water sample extracted using the vacuum sparge system [Busenberg and Plummer, 2000] and the analytical GC/ECD setup based on Busenberg and Plummer (2008)

Table 4-4: Signals and equivalent amount in fmol of Halon-1301 and CFC-13 obtained in tap and river water using standard curve slopes (amount/signal) of 3149.18 and 1942.98 $\mu\text{V}/\text{min}/\text{fmol}$ for Halon-1301 and CFC-13, respectively and Henry coefficients at 12.5°C and 10 m elevation obtained from various reported data; *^using solubility data reported by *Deeds, (2008) and ^Scharlin and Battino (1995)

Sample volume [L]	Signal peak area [uV/min]	Aqueous conc. of Halon-1301 [fmol]	Aqueous conc. of CFC-13 [fmol]	Atmospheric conc. of Halon-1301 [pptv]	Atmospheric concentration of CFC-13 [pptv]	
Tapwater						
0.92	24841	8.57	13.90	2.60*	11.01 [^]	11.94*
2.76	80837	9.30	15.07	2.82*	11.95 [^]	12.95*
4.6	120625	8.33	13.50	2.53*	10.70 [^]	11.59*
9.2	230874	7.97	12.92	2.42*	10.24 [^]	11.09*
River water						
0.92	27275	9.41	15.26	2.86*	12.09 [^]	13.11*
0.92	26414	9.12	14.78	2.77*	11.71 [^]	12.69*

The identification of the compound with retention time of 2.9 min as Halon-1301 using different gas standards and calibrated air was also in agreement with the conclusions of Rosiek et al. (2013), who had followed the general setup suggested by Busenberg and Plummer (2008), but with a longer (8 m instead of 3 m) column for separation of CFC-13 and Halon-1301. They had also improved the sensitivity of the analysis towards CFC-13, Halon-1301 and SF_5CF_3 with a custom made detector setup

[Rosiek et al., 2013]. They had analysed a calibrated air standard and additionally a custom gas containing CFC-13 only. The latter had allowed them to definitively identify the CFC-13 peak, which in the calibrated air standard had approximately been an order of magnitude lower than another compound at a very similar retention time (see Fig. 5 in Rosiek et al. (2013)), which they had concluded was Halon-1301 based on molecular structure. The results presented in this study, which included both a custom gas containing Halon-1301 and excluding CFC-13, and vice versa, and analysis of modern water samples provided more compelling evidence to confirm Rosiek et al.'s conclusion.

This study and Rosiek et al. (2013) suggested CFC-13 was at or below the LOD using the analytical setup developed by Busenberg and Plummer (2008) and either tracer extraction methods (headspace equilibrium or vacuum sparge technique) for normal groundwater applications considering achievable sample volumes and normal concentrations in water and air. Rosiek et al. (2013) reports an LOD for CFC-13 equivalent to 7 fmol (18.6 pptv at 10 ml ambient air), which is significantly lower than the LOD of around 800 fmol approximated in this study. This difference may have been caused by overload of the pre-concentration traps, discussed earlier, or by a difference in ECD performance (dependent e.g. on type of electron source or signal). However, this study's approximated LOD is somewhat in line with Sousa and Bialkowski (2001), who report a detection limit of 90 pg for HCFC-22 (CHF_2Cl)²⁶ that is ~ 1,000 fmol. For comparison, the CFC-13 concentration in 1 L water equilibrated with atmospheric air in 2013 (containing 5.3 pptv CFC-13, at 12.5°C and 10 m elevation, using solubility data from Deeds (2008)) is equivalent to 6.17 fmol CFC-13, which is just at the LOD reported by Rosiek et al. (2013) and far below the LOD estimated in this study.

Overall it was shown that the signal previously reported to have been caused by CFC-13 by Busenberg and Plummer (2008) is almost entirely caused by Halon-1301. This was demonstrated by agreement of Halon-1301 mole specific signals in calibrated air (containing various other compounds, such as HCFCs) and a standard only containing Halon-1301 and SF_6 , where a linear calibration curve was established using both standards. It was also shown that interfering signals of co-eluting compounds with the Halon-1301, such as CFC-13, were not a major problem when analysing 1 L modern water samples. Rosiek et al. (2013) also provided strong evidence for the absence of interfering signals in air caused by compounds with similar retention time as Halon-1301 and CFC-13 (see Fig. 5 in Rosiek et al. (2013)). However, further study is needed to confirm this exclusively, e.g. by assessing the retention time of potential co-eluting compounds on the GC column used in this study and assessment of the concentration range of potential co-eluting compounds in groundwater at normal/elevated atmospheric concentrations.

²⁶ CHF_2Cl is expected to result in a similar ECD signal intensity due to its similar structure (same amount of ECD sensitive atoms: 2 F and 1 Cl and similar size).

4.5 Results and discussion on the assessment of Halon-1301 for the use as an age tracer

As shown in the previous section, Halon-1301 can be adequately determined on the GC/ECD setup developed by Busenberg and Plummer (2008), which is an important requirement for its use as a groundwater age tracer. In the following section further evidence is presented that supports the applicability of Halon-1301 as a groundwater age tracer based on its performance as an age tracer in various groundwater samples (of different age and groundwater environment). As mentioned previously, the analytical setup allowed for the simultaneous determination of Halon-1301, SF₆ and potentially CFC-12 (if appropriate standard gases are used for calibration). This three way simultaneous determination of three independent tracers can aid more robust groundwater dating, due to the ability to identify problems related to the limited application range of the individual tracers. These are contact with air during sampling (indicated by an increased concentration of all three gas tracers), degradation/contamination of one or more of the gas tracers (indicated by a reduced/increased concentration, respectively) or unsaturated zone processes, such as diffusion or retardation (indicated by a reduced concentration of one or more of the gas tracers in comparison to a non-gaseous tracer such as tritium).

4.5.1.1 Calibration curve

Figure 4-8 illustrates the calibration curve established with the calibrated air standard (Scripps) and highly concentrated Halon-1301 standard (NZIG) with a nearly linear response of the ECD towards Halon-1301 concentration in the concentration range obtained for groundwater samples (signal up to 30 mV/min for modern water). Given this evidence of a linear signal response up to concentrations obtained in modern water, also confirming the findings presented earlier in Fig. 4-6, the calibration curve of Halon-1301 obtained with the calibrated air standard was linearly up-scaled to estimate concentrations of Halon-1301 in all groundwater samples. Using this approach introduced additional uncertainty, which was taken into account during discussion of the inferred MRTs (for further detail, see section 4.5.1.4 and Appendix B5).

Figure 4-8: Calibration curve (LEFT) and residual plot (RIGHT) for Halon-1301 using 10 ml calibrated air standard (category 1) and 0.5 ml highly concentrated Halon-1301 standard (NZIG) (category 2)

4.5.1.2 Uncertainty

Uncertainty assessment showed that the analysis allowed for an average repeatability of 3.6 % for Halon-1301 (and 2.8 % for SF₆) and an average standard deviation of the calibration curve of 9.8 % for Halon-1301 (and 6.9 % for SF₆). The overall analytical uncertainty in an average New Zealand groundwater sample²⁷ was 4.7 % for Halon-1301 (and 9.0 % for SF₆²⁸). Due to its characteristic S-shaped atmospheric history, this led to a larger uncertainty in inferred piston flow age for waters recharged before 1975 and after about 2000 when using Halon-1301 as illustrated in Fig. 4-9. The limit of detection (LOD) and limit of quantification (LOQ) of the analytical setup was 0.32 fmol/L and 0.98 fmol/L, respectively, for Halon-1301 (and 0.23 fmol/L and 0.69 fmol/L, respectively, for SF₆). For comparison, the LOQ was equivalent to a recharge year of 1975 for Halon-1301, at average recharge temperature (12.1°C), 10 m elevation and absence of excess air and headspace.

Figure 4-9: Effect of relative analytical uncertainty on inferred piston flow recharge year for SF₆ and Halon-1301

Sensitivity analysis showed that the most significant contributors to the overall uncertainty in the determination of Halon-1301 and SF₆ were uncertainties related to the calibration curve, repeatability, excess air and headspace correction. The main uncertainty for the determination of Halon-1301 was related to uncertainty of the calibration curve and repeatability. Without considering headspace and excess air, the total uncertainty became only marginally smaller for Halon-1301 (4.4 % instead of 4.6 %), but significantly smaller for SF₆ (3.2 % instead of 9.0 %). Detailed uncertainties in the inferred MRT for each groundwater sample are presented in section 4.5.1.4.

²⁷ A detailed study in New Zealand [van der Raaij and Beyer, 2015] showed groundwater samples have an average recharge temperature of 12.1±1.8°C; 2.9±1 ml (STP)/kg excess air and 0.5±0.05 ml headspace volume.

²⁸ Please note if SF₆ alone is analysed using a different GC column, it can be more accurately resolved with 4.5 % overall uncertainty [van der Raaij and Beyer, 2015]. The aim of this study was to simultaneously determine the two gaseous tracers SF₆ and Halon-1301 with a particular focus on resolving the Halon-1301 signal accurately. The higher uncertainty in SF₆ determination when using the presented approach may be resolved by adjustment of the GC column, ECD conditions or sampling technique, or processing of the ECD signal to enhance the signal recovery of SF₆. Appendix B6 shows promising findings when applying processing/filtering to the ECD signal with regard to the signal recovery of SF₆ and Halon-1301 and proposes sampling techniques which may potentially further improve their determination in groundwater.

4.5.1.3 Solubility

Figure 4-10 shows the solubility ($\ln K_H$) of SF_6 and Halon-1301 estimated using modern groundwater and equilibrated tap and river water in comparison to the solubility estimated by Deeds (2008) and determined by Bullister et al. (2002) for Halon-1301 and SF_6 , respectively. Table 4-3 contains the solubility parameters that were derived from the found relationship in Fig. 4-10 along with previously reported solubility parameters. As can be seen, the estimated solubility of SF_6 agreed well with its reported solubility, which indicated that the approach in this study should give relatively robust Halon-1301 solubility estimates. The solubility of Halon-1301 inferred in this study was significantly lower than the Deeds (2008) estimated solubility. When using the Deeds (2008) estimated solubility parameters, Halon-1301 concentrations were obtained which resulted in significantly older inferred Halon-1301 ages compared to tritium and SF_6 ages with an average discrepancy of +12 years in equilibrated tap and river water (note also the differences in inferred atmospheric concentrations to actual atmospheric concentrations when analysing modern (equilibrated) water to support the identification of Halon-1301 in Tab. 4-4). This offset was removed when using Halon-1301's solubility parameters estimated in this study. This further supports that the solubility of Halon-1301 estimated in this study better reflects its actual solubility than the solubility previously estimated according to its structure.

Figure 4-10: Estimated solubility ($\ln K_H$) of Halon-1301 and SF_6 determined in equilibrated tap water, river water, and oxic young groundwater in comparison to reported solubility data using solubility data from Deeds (2008) for Halon-1301 and Bullister et al. (2002) for SF_6

Due to absence of robust solubility data of Halon-1301, the solubility parameters estimated in this study (Tab. 4-3) were used to infer equivalent atmospheric Halon-1301 concentrations and with that derive Halon-1301 ages. The estimated solubility had a relatively large uncertainty of 9.8 % (estimated using regression analysis in Fig. 4-10), due to scatter in the data which may have been caused by e.g.

uncertainty in recharge temperature, unaccounted heterogeneity or mixing of water. Uncertainty in solubility added to the analytical uncertainty determined in the previous section, so that the overall uncertainty increased from 4.7 to 9.7 %. This increased uncertainty in turn affected uncertainty in inferred Halon-1301 age as discussed in the following section. Accurate measurement of the solubility of Halon-1301 was beyond the scope of this study. Due to the extremely low solubility of Halon-1301, specialised equipment is required. Further study is needed to more accurately determine the solubility of Halon-1301 to ultimately reduce the uncertainty in Halon-1301-inferred age distributions (as demonstrated in Chapter 5).

4.5.1.4 Assessment of inferred Halon-1301 ages

In the following, the consistency of inferred Halon-1301 MRTs with MRTs derived from tritium and SF₆ and the conservativeness of Halon-1301 in groundwater is assessed. Inferred MRTs were considered as agreeing, i.e. insignificantly different, when their 1 SD uncertainty bounds overlapped (except for 1 site where 1.1 SD was accepted). Elevated concentrations of Halon-1301, SF₆ or the CFCs (>10%) were considered as ‘potentially contaminated’ and highly elevated concentrations (>25%) were considered as ‘highly contaminated’. For signals at or below the LOD only a lower limit of the mean age could be assigned (e.g. recharged before 1970). Details on individual piston and exponential piston flow model MRTs and their uncertainty²⁹ inferred from Halon-1301 and SF₆ measurements determined in this study are listed in Tab. 4-5. In the following, all comparisons are made in relation to a total of 18 samples: 17 groundwater samples + 1 modern water sample (= average of various modern water samples). For comparison, Tab. 4-5 also contains MRTs that had been estimated from tritium, CFC and SF₆ in previous studies for these 18 samples.

Figure 4-11: Piston flow and exponential piston flow ages (MRTs) inferred from Halon-1301 and SF₆ concentrations, including error bars (1 SD uncertainty as overall uncertainty including uncertainty in solubility)

²⁹ Uncertainty was estimated using an error propagation approach, see section 4.3.3 for detail.

When using the piston flow model (PM) to conceptualize groundwater mixing, the estimated Halon-1301 MRTs were on average 5.4 years higher than the estimated SF₆ MRTs (over the entire age range) as illustrated in Fig. 4-11. However, as discussed previously, piston flow ages are unrealistic as they neglect mixing of water, also indicated by previously determined EPM ages inferred from tritium and SF₆ at the studied sites [e.g. Morgenstern and Taylor, 2009]. In the following the exponential piston flow model was used to conceptualize groundwater mixing. It was found that the choice of LPM significantly affected the age estimation with Halon-1301. This was attributed to its non-linear, S-shaped atmospheric input that was skewed during mixing (depending on the LPM choice). For SF₆, this was less of a problem, due to its nearly linear atmospheric input since the late 1980s. This finding highlighted the importance of considering mixing processes for estimation of groundwater age from Halon-1301. The sensitivity of Halon-1301 concentrations towards mixing of groundwater of different age also implied that groundwater dating with Halon-1301 may allow better constraining of the mixing parameters compared to SF₆. However, time series measurements of Halon-1301 are necessary to confirm this supposition. A first attempt in assessing the value of time series Halon-1301 data is carried out in Chapter 5.

Consistency of inferred Halon-1301 ages with inferred tritium and SF₆ ages using the EPM

Comparison of inferred Halon-1301 and SF₆ MRTs when using the EPM to previously derived tritium MRTs in Fig. 4-12 allowed the assessment of whether differences in inferred MRTs have been caused by processes affecting both gaseous tracers (such as lag-time in the unsaturated zone) or only Halon-1301 (such as potential degradation or sorption which does not occur for SF₆). Where present, samples exhibiting probable CFC degradation/contamination are highlighted in Fig. 4-12. Comparison to inferred CFC ages could not be made, because all samples (with available CFC data) were either degraded and/or contaminated in one or both CFC-11 and -12.

At one of 18 sites both gases and tritium were close to the LOD, but evidence of slight contamination with modern air during sampling was found, indicated by elevated concentrations of both SF₆ and Halon-1301 which were incompatible with their low tritium concentrations. Evaluation of the performance of Halon-1301 as an age tracer in comparison to SF₆ and tritium was not possible for this sample, which was therefore excluded for the overall comparison. For the majority of the remaining 17 samples, inferred SF₆ ages agreed well with previously determined tritium ages, which indicated that unsaturated zone processes were not significant in this study.

Halon-1301-inferred MRTs of 12 of 17 samples were in agreement with tritium- and SF₆-inferred MRTs (within an uncertainty of ~1 SD). This included four older groundwater samples, which showed concentrations at or close to the LOD of tritium, and were also free of Halon-1301 (Fig. 4-12 and Tab. 4-5). For the remaining waters (all > 1 year old and anoxic), inferred Halon-1301 ages were significantly

higher compared to tritium/SF₆ ages. The reasons for this offset are discussed in the following subsection along with the assessment of Halon-1301's conservativeness.

Table 4-5 showed that the relatively large uncertainty in its estimated solubility led to additional uncertainty in Halon-1301-inferred MRTs compared to estimates assuming only 1 % uncertainty in solubility, for demonstration purposes. An up to 170 % or 7 years higher uncertainty in Halon-1301-inferred MRTs was found when accounting for uncertainty in the estimated solubility. This implied that Halon-1301-inferred MRTs can potentially be better constrained with a more accurate solubility estimate. This also implied that the full potential of Halon-1301 as an age tracer could not be realised due to absence of accurate /robust solubility data.

Figure 4-12: Summary of MRTs including error bars (± 1 SD analytical uncertainty including uncertainty in solubility) inferred from Halon-1301, SF₆ vs mean residence times inferred from tritium using the exponential piston flow model, data points are highlighted according to CFC-12/CFC-11 contamination/degradation (see legend); Halon-1301 and SF₆ were determined in this study, tritium and the CFCs had been determined in previous study(s); the abbreviations 'c' and 'd' in the legend refer to: contaminated and degraded in one or both CFCs, respectively; c/d refer to contamination and degradation was observed for either CFC-12 or CFC-11; 'n/a' refers to no available CFC data.

Table 4-5: Summary of obtained exponential piston flow ages (MRT) inferred from Halon-1301 and SF₆ (determined in this study), tritium, CFC-12/ CFC-11 (determined in previous studies); contaminated samples (>10%) are displayed 'C', highly contaminated samples (>25%) are displayed as 'HC'; 'D' refers to potentially degraded; signals below or at LOD are illustrated 'LOD'

^a sampling date: 02/12/2013; ^b sampling date: 10/12/2013; ^c uncertainty (± 1 SD) including/excluding uncertainty in solubility, ^d E/PM= mixing ratio of exponential to total flow as defined in Eqn. 2-2 in Chapter 2, which had previously been inferred from tritium (time series) data

	equivalent atmospheric concentration					inferred MRT when using EPM								previously det. age information		
	Halon-1301			SF ₆		Halon-1301					SF ₆			tritium		CFC-12/ CFC-11
Well #	pptv	$\pm^c$ (incl. solub.)	$\pm^c$ (excl. solub.)	pptv	$\pm$	MRT [years]	$+^c$ (incl. solub.)	$-^c$ (incl. solub.)	$+^c$ (excl. solub.)	$-^c$ (excl. solub.)	MRT [years]	+	-	E/PM ^d	MRT [years]	MRT [years]
15	3.72	0.65	0.56	7.14	0.56	0	HC	4	C	2	1.5	2	1.4	var.	0	n/a
6 ^a	3.60	0.46	0.19	10.02	1.74	0	C	2	C	0	HC	HC	0.1	var.	1.0	C/n/a
21 ^b	3.77	0.59	0.28	10.63	1.34	C	HC	0	C	0	HC	HC	0.1	var.	1.0	C/HC
24 ^b	3.47	0.52	0.18	9.14	1.14	0	C	7	0	0	C	C	0.5	var.	1.5	C/12
25 ^a	2.95	0.78	0.67	8.21	1.09	7	C	11	7	9	0.1	1.9	C	var.	2.0	HC/24
19 ^b	2.22	0.35	0.16	6.04	0.85	18	5	5	2.5	2	7	4	3.5	0.8	2.5	19/D
11 ^a	2.66	0.26	0.11	5.23	0.34	11	4	4	1	2	10	2	1	var.	9.0	27/C
22 ^b	2.06	0.22	0.09	4.43	0.34	20	4	4	1.5	2	15	2.5	2	0.9	13	C/D
3 ^a	0.25	0.12	0.11	3.65	0.50	135	25	45	23	38	21	5	3.5	0.8	16	C/C
1 ^a	0.57	0.05	0.02	2.77	0.23	53	2	2	1	1	26	2	2	0.7	18	21/D
4 ^a	0.05	0.12	0.11	2.03	0.26	55	8	>14	8	>14	27	2	2	0.4	40	85
20 ^b	0.05	0.00	0.00	1.65	0.10	234	5	4	2	4	52	3	3	0.9	25	D/D
23 ^b	1.22	0.13	0.05	3.19	0.12	41	4	5	2	2	25.5	2	1.5	0.9	>21	39/D
18 ^b	0.62	0.09	0.04	1.30	0.12	62	6	5	3	2	51.5	4.5	3.5	0.8	75	-
26 ^a	LOD	-	-	LOD	-	-	-	-	-	-	-	-	-	0.1	100	95
17 ^b	0.05	0.01	0.00	0.12	0.01	234	6	6	6	6	215	10	5	0.9	140	n/a
27 ^a	LOD	-	-	LOD	-	-	-	-	-	-	-	-	-	var.	150	LOD/ LOD
16 ^b	LOD	-	-	1.57	0.71	-	-	-	-	-	52	28	17	var.	LOD	LOD/ LOD

Conservativeness of Halon-1301

No significantly elevated Halon-1301 concentrations were found, although the sites covered situations of land use and well construction that resulted in CFC contamination (Fig. 4-12 and Tab. 4-5). A significantly elevated Halon-1301 concentration was only found for one site in concert with an elevated SF₆ concentration, suggesting that the sample was contaminated with air during sampling rather than contaminated from (anthropogenic) sources of Halon-1301. This indicated absence of contamination for Halon-1301 from local sources at the studied sites. This has to be evaluated further, e.g. in groundwater recharged close to airports, where Halon-1301 is still in use as a fire suppressant during fuelling of planes. The absence of elevated Halon-1301 concentrations in this study may have also indicated that interference of the Halon-1301 signal with signals caused by CFC-13 or other co-eluting compounds was not an issue in the studied groundwater samples. However, this needs to be assessed further in groundwater with elevated concentrations of CFC-13 and/or other potentially co-eluting compounds.

Significantly reduced concentrations of Halon-1301 relative to SF₆ and tritium, i.e. higher Halon-1301 MRTs to tritium and SF₆ MRTs over an age range from 2.5 to 40 years MRT, were found in five of 17 groundwater samples, where direct age comparison could be made. These samples also showed evidence of more significant degradation of one or both CFC-11 and CFC-12 (if the sample was not contaminated with the CFCs). There are several possibilities for reduced Halon-1301 concentrations, which are assessed in detail in Appendix B5. A summary is presented in the following.

The assessment of reduced Halon-1301 concentrations showed degassing into headspace created by denitrification, production of methane or when groundwater is brought to the ground surface could be excluded, since this would have affected all determined gas tracers to the highest extent the least water soluble SF₆. Reduced concentrations of both Halon-1301 and SF₆ were not found in any of the analysed samples. Lag-time in the unsaturated zone was also excluded, because this would have affected all gas tracers, dependent on their diffusion coefficient [Goody et al., 2006] and reduced concentrations of Halon-1301, SF₆ and the CFCs were not found in any of the samples. Assuming that Halon-1301 behaved similarly to the CFCs with regard to sorption to specific materials, the risk of sorption to well casing and sampling material was considered minimal as robust sampling procedures established for the CFCs and SF₆ were followed. The remaining possibilities for reduced Halon-1301 concentrations were:

- l) Increased Halon-1301-inferred MRTs in younger water samples with a tritium- and SF₆-inferred MRT ≤ 15 years (applicable for one of five affected samples) were likely caused by uncertainties related to the recent levelling out atmospheric concentrations of Halon-1301 [AGAGE, 2014], which made it more difficult to constrain the MRT of these younger waters.

II) Increased Halon-1301-inferred MRTs in the remaining, particularly older samples with a tritium- and SF₆-inferred MRT > 15 years were likely caused by a) degradation³⁰, which is likely to occur under anoxic conditions (all affected samples were anoxic); b) sorption to organic material in the aquifer (could not be excluded for any of the sites).

Potential degradation of Halon-1301 during storage was assessed by analysis of groundwater samples from six different sites (covering an age range from modern (< 1 year) to over 100 years, and oxic to anoxic waters) stored for seven weeks at 14°C. Figure 4-13 illustrates concentrations determined before and after storage for seven weeks were within analytical uncertainty. The concentration of Halon-1301 in river water stored for over 1.2 years was also not significantly reduced in Halon-1301 compared to SF₆. These findings provided evidence for the stability of Halon-1301 in oxic and anoxic water stored up to seven weeks (potentially up to 1.2 years) at 14°C. These findings could not, however, provide evidence for the stability of Halon-1301 in oxic and anoxic groundwater residing in the subsurface. Further study is needed to confirm whether Halon-1301 is degradable or reduced concentrations are a result of sorption/retardation in the aquifer. This can be studied by determination of Halon-1301 in e.g. relatively old (with a MRT > 5 years) oxic groundwater and/or relatively young (with a MRT < 2 years) anoxic groundwater. Reduced concentrations of Halon-1301 in relatively old oxic water could confirm sorption/retardation, since degradation is likely only occurring in anoxic water. Similarly, analysis of relatively young anoxic groundwater, where sorption/degradation has not likely affected the concentration of Halon-1301, due to a relatively short travel time in the aquifer and the currently levelled out atmospheric trend, could confirm degradation of Halon-1301.

Figure 4-13: Comparison of Halon-1301 concentration in 1 L water samples analysed directly after sampling ('initial' = 2 of 3 samples) and after 7 weeks storage (1.2 years for Hutt River water), for Well 6 Halon-1301 was not detectable; * indicates anoxic water

³⁰ Assuming Halon-1301 behaves similarly to structurally similar CFCs in groundwater, microbial degradation (Lesage et al., 1992; Lovley and Woodward, 1992; Sonier et al., 1994) and hydrolysis (e.g. Butler et al., 1991; Sturges et al., 1991; Kanta Rao et al., 2003) are possible degradation mechanisms of Halon-1301.

4.4 Chapter summary and conclusion

Analysis of modern air and water samples and three different standard gases strongly suggested that the compound previously identified as CFC-13 by Busenberg and Plummer (2008) is instead Halon-1301 (with potentially a small interference with CFC-13). This study's findings complemented a separate study by Rosiek et al. (2013), who had suggested Halon-1301 was the dominant compound near the retention time of CFC-13 in a calibrated air standard. This study provided more definitive proof of this, through use of custom made gases including and excluding both compounds as appropriate.³¹

New analytical methods will need to be developed for the use of CFC-13 as a groundwater age tracer. This study showed that CFC-13 was difficult to determine with a simple GC/ECD setup. Higher sensitivity towards CFC-13 can be achieved by a custom made ECD setup [Rosiek et al., 2013]. However their method requires alteration of the commercially available ECD, with significant additional cost, and even with this detection of CFC-13 remained low. Another possible approach to determine CFC-13 concentrations in water may be the establishment of a GC/mass spectrometry system, as currently used for determination of atmospheric CFC-13 concentrations. However, such systems are not currently employed for groundwater analysis, so may be difficult to establish.³²

This study was the first to give attention to the application of Halon-1301 as a groundwater tracer. The following was found:

- It was demonstrated that Halon-1301 has strong potential as a groundwater age tracer.
- The capability of the analytical setup for robust simultaneous determination of Halon-1301 and SF₆ (and CFC-12) in the same 1 L water sample was shown. The analytical setup provides a cost-effective age estimation of relatively young groundwater (recharged <100 years) with three independent gaseous tracers.
- Actual solubility measurements of Halon-1301 were not available (only an estimate existed) and the solubility of Halon-1301 determined in this study did not match its initial estimate. To convert measured Halon-1301 concentrations in water into atmospheric concentrations, its solubility was estimated from a range of equilibrated water samples and recently recharged, oxic groundwater samples. Uncertainties arising from the estimation of Halon-1301's solubility led to significantly higher uncertainties in Halon-1301-inferred MRTs than observed when not taking account of uncertainty in the estimated solubility. More accurate determination of Halon-1301's solubility is required for better utilization of it as an age tracer.

³¹ Busenberg, E. agrees with these findings.

³² Promising separation of Halon-1301 and CFC-13 on a GC for determination in water and air was indicated in Rosiek et al. (2013); Miller et al. (2008); Culbertson et al. (2000) and Engen et al. (1998).

- To infer age from Halon-1301 (and SF₆) concentrations in groundwater, piston and exponential piston flow modelling were used. Significantly different age estimations were found with both modelling approaches. It was shown that Halon-1301 is particularly sensitive to the choice of mixing model due to its S-shaped atmospheric history, which is considerably skewed during mixing processes, in contrast to SF₆ with a nearly linear atmospheric history since the later 1980s. This indicated that the use of time series Halon-1301 data may allow better constraint of the mixing model than when using time series SF₆ data. However, further study is needed to support this.
- Previously inferred CFC-11, CFC-12, SF₆ and tritium MRTs at the studied groundwater sites allowed for comparison of the performance of Halon-1301 to other groundwater age tracers. For 12 of 17 groundwater samples, where direct comparison of inferred ages could be made, matching Halon-1301, SF₆ and/or tritium MRTs (within ~1 SD) were found. This compares favourably with the CFCs.
- The remaining 5, anoxic sites showed reduced concentrations of Halon-1301 along with significantly even further reduced concentrations of CFC-12 and CFC-11. Analysis of stored groundwater samples indicated that Halon-1301 was stable in oxic to anoxic water stored up to seven weeks at 14°C. It was unclear if reduced concentrations found in groundwater had been caused by degradation or retardation of Halon-1301 in the aquifer.
- Although the sites included different land use environments and well construction that resulted in CFC contamination, no significantly increased Halon-1301 concentrations in any of the analysed groundwater samples were found. This indicated no apparent sources of contamination of Halon-1301 in this study. To confirm the absence of local sources, Halon-1301's performance needs to be assessed at sites with higher risk of local sources e.g. close to airports or data centres.

Despite the not fully understood reduced Halon-1301 concentrations, this study's findings indicated that Halon-1301 has strong potential as a new complementary groundwater age tracer. Even if Halon-1301 was affected by degradation/sorption and/or contamination is occurring in specific areas, Halon-1301 is likely to be a more reliable groundwater age tracer than CFCs, as demonstrated in this study³³. CFCs face issues regarding their reliability to infer groundwater age due to (anthropogenic) contamination and degradation (in anoxic waters). Atmospheric CFC concentrations are also fading out, which will make the CFCs even less reliable in the future. Halon-1301 is also projected to start declining and eventually fade out, but not before 2020.

If used in combination with other established tracers, Halon-1301 is likely to aid in reducing the ambiguity in groundwater age estimations obtained through tritium, SF₆ and fading out CFC concentrations, and improve constraining of mixing models. Since Halon-1301 is a gaseous tracer, it

³³ All samples with available CFC data in our study were either degraded and/or contaminated in one or both CFC-11 and -12.

has additional potential to be used for assessment of unsaturated as well as saturated zone processes, especially with respect to the simultaneous determination of CFC-12 and SF₆ on the proposed analytical setup. Due to its S-shaped, fading out atmospheric input and analytical detection limits, the appropriate application range for inferring groundwater age from Halon-1301 is suggested to be for waters recharged between 1980 and 2005/2008. Higher uncertainty will be present in age estimates for waters of earlier (after 1970) or more modern recharge. Uncertainty in inferred Halon-1301 age can be further reduced by more accurate determination of its solubility (which requires special lab equipment due to its extremely low solubility in water).

To conclude, this study's findings suggest that Halon-1301 (as any other tracer) should be used complementarily together with other tracers to compensate for individual tracer limitations. It is not suggested that Halon-1301 is used as a stand-alone tracer (although in our study area it was significantly more reliable than CFCs, which are often used alone in the literature). Specifically, the simultaneous determination of Halon-1301 with SF₆ and CFC-12, using the cost-effective method presented in this study it is recommended. This allows for the determination of three complementary age tracers in the same water sample, which may enable more precise determination of groundwater age (and mixing), assessment of unsaturated zone processes, and increased robustness as the three tracers together allow for identification and exclusion of problem samples (e.g. where contact with air during sampling or degradation of one of the age tracers had occurred). To further improve the age estimation with Halon-1301, the complementary use of Halon-1301, SF₆ and CFC-12 together with tritium, which is possibly the most reliable groundwater age tracer (particularly in the southern hemisphere³⁴), is recommended. All four age tracers have different properties and input histories to groundwater enabling a more robust determination of groundwater age with a reduced ambiguity and uncertainty in inferred age. Their combined determination in the same water sample also reduces their individual determination costs. It also reduces the costs for determination of time series tritium and/or SF₆ data that would be necessary for an equally robust groundwater age estimate (particularly in the northern hemisphere where ambiguity in inferred tritium ages is still an issue). Other multi-tracer analysis approaches and applications have been demonstrated in recent years, e.g. the simultaneous determination of dissolved He, Ne, Ar, Kr, Xe, SF₆, N₂, and O₂ in Brennwald et al., 2013 and Bauer et al. 2001. It is hoped that multi-tracer analysis and application will become common practice, due to their significant advantages over single tracer analysis and application.

³⁴ Ambiguous age interpretations are often inferred from tritium in the northern hemisphere. This is less of a problem in the southern hemisphere due to the differing atmospheric tritium record in the northern and southern hemisphere.

5. A probabilistic age (LPM) modelling framework

5.1 Introduction

As highlighted in Chapter 2 (section 2.2), a more comprehensive quantification of uncertainty in age modelling is not standard and only emerged in age modelling studies published from 2010 onwards (with a single exception: the paper by Cirpka et al. (2007)). Although several recent studies attempted a more comprehensive uncertainty quantification in groundwater age modelling (listed in Tab. 2-1), there are still issues that need to be addressed. These are i) the demonstration of parametric LPMs in a probabilistic approach and the use of multiple models, ii) a more 'objective' choice of the objective function, and iii) consideration of all relevant uncertainties, in particular the uncertainty in the tracers' recharge to groundwater.

This study set out to fill these gaps. The aim was to demonstrate a relatively simple, easily applicable and widely transferable groundwater age modelling framework that 1) is applicable for the many situations with limited tracer data, and 2) allows for consideration of all sources of uncertainty and identification of relevant model components. Age modelling was placed into a relatively simple probabilistic framework using an uncertainty estimation method similar to GLUE (generalized likelihood uncertainty estimation) [Beven and Binley, 1992]. 'Classic' Monte Carlo Simulation [Hammersley and Handscomb, 1964] was used for random sampling. Simplified 'parametric' LPMs were used to conceptualize groundwater mixing and an objective function was used for model calibration. The framework allowed for application of multiple LPMs (to account for model structural errors) and can be applied to any tracer dataset in any aquifer, for which a 'parametric' LPM approach can be reasonably applied. The framework also allowed for identification of most appropriate LPM(s), objective function and recharge estimate, and the most relevant model input uncertainties. Combination of multiple tracers and the assessment of the (potential) contribution of each individual tracer towards a reduced uncertainty in inferred age were also carried out.

The framework was demonstrated on tritium, Halon-1301 and SF₆ data in a New Zealand aquifer and the most appropriate framework components (for this case study) were identified. In particular, the performance of Halon-1301, the new groundwater age tracer presented in Chapter 4, was further assessed when used alone in relation to SF₆ and tritium, and when used in combination with tritium and/or SF₆. To demonstrate the relatively simple application of the framework, the main parts (i.e. the framework components that had been found most appropriate/relevant in this study) were coded up and a GUI (graphical user interface) was created. Both can be found on the accompanying CD including a user manual and example datasets. The GUI can be run in Matlab (versions R2014a or later). The code can be modified to include other framework components that may be more relevant for other tracers and study areas.

To minimize confusion of the term ‘uncertainty or probability distribution in the age distribution’, the age distribution is in the following also referred to as ‘age estimation’ or ‘age estimate’.

5.2 General framework overview

5.2.1 Sources of uncertainty

There are various sources of uncertainty in age (LPM) modelling, which can be differentiated into model input uncertainties, uncertainty in tracer observations and model structural uncertainty³⁵.

- 1) Uncertainty in the model structure arises since the governing parametric LPM is a simplified model and may not adequately describe actual groundwater mixing. Although it has not been discussed in detail in age (LPM) modelling studies, ‘equifinality’ may occur, i.e. multiple conceptually different ‘parametric’ LPMs can result in similarly well represented tracer observations as often found in other areas of hydrological modelling [e.g. Beven and Binley, 1992].
- 2) Observational uncertainty, i.e. uncertainty in the tracer measurements (or observations), results from analytical uncertainty and inadequate sampling or sample storage. Additional uncertainty arises when the tracer cannot be directly measured, but is determined from other measurables. Uncertainty in time series tracer data induced by non-steady state conditions can also occur.
- 3) There are a range of model input uncertainties. The following were considered in this study (not all of these uncertainties are relevant for each study and need to be assessed based on the tracer(s) used and characteristics of the study area):
 - Uncertainty in decay (chemical, biological, radioactive) and retardation of the tracer in groundwater results from uncertainties in the tracer’s decay constant and retardation factor.
 - Various uncertainties related to the tracer’s historic recharge/input to groundwater were considered. These were:
 - a. The input of an atmospheric tracer to groundwater can be estimated from its atmospheric concentration, which is prone to uncertainties as a result of analytical and sampling uncertainty, but also spatial and temporal variability of the tracer’s atmospheric concentration. Whether uncertainty in atmospheric tracer records is biased or random (see example Fig. 5-1) and what effect this has on the age distribution has yet to be determined.

³⁵ It is acknowledged that numerical uncertainty (from numerical errors and approximations) may add to these uncertainties, but can be minimized by appropriate modelling procedures and approximation techniques. The procedures/methods used to minimize numerical uncertainty in this study are summarized in Appendix C2. A full assessment of numerical uncertainty was outside the scope of this study and was not further discussed. Please refer to existing discussions on this [e.g. Hammersley and Handscomb, 1964; Smyth, 2014].

Figure 5-1: Example of biased and random uncertainty in the tracer's input to groundwater, assuming the input concentration of the tracer to groundwater is 1 from time 1 to 5 with an uncertainty of ± 0.75 (1 SD). Biased uncertainty results in a shifted input function, random uncertainty results in additional variability of the tracer's input function.

- b. For a tracer with a seasonally variable atmospheric trend, additional uncertainty in the tracer's input may be introduced due to averaging of finely spaced records to coarsely spaced data (e.g. averaging of hourly recorded data to yearly data).
- c. Aside from the tracer's atmospheric concentration, tracer input is also dependent on the amount and timing of recharging water. This is often accounted for by weighting the tracer's atmospheric record with recharge estimates [e.g. Knott and Olimpio, 2001; Engesgaard et al., 1996; Allison and Hughes, 1978]. This introduces additional uncertainty in the tracer's input.
- d. Spatially variable rainfall may affect the tracer's recharge to groundwater leading to additional uncertainty in the estimation of the tracer's input [Schuurmans and Bierkens, 2007 and references therein].
- e. Local tracer sources can also interfere with the tracer's atmospheric concentration and/or its concentrations in groundwater [e.g. Cook et al., 2006].

5.2.2 General framework

To quantify uncertainty in the age distribution as a result of the uncertainties listed in the previous section, age modelling was placed into a probabilistic framework illustrated in Fig. 5-1. The framework included the generation of tracer concentrations by random sampling of the model inputs from within their uncertainty and identification of behavioural (adequately fitting/representative) simulations with the aid of an objective function. The general framework was similar to the frameworks that had been used in the existing probabilistic age modelling studies (listed in Tab. 2-1 in Chapter 2), but differed in its components. Generally, each framework component (model input, mixing model and objective function) has numerous choices associated with it. It is important to identify the most adequate model components to reduce uncertainty in model findings and predictions as highlighted in other areas of hydrological modelling. The following outlines which choices are generally associated with each model component in age (LPM) modelling, which ones were assessed in this study and how the most

appropriate ones were identified when demonstrating the framework on tritium and SF₆ data in a New Zealand aquifer.

Figure 5-2: Schema of the modelling approach with framework components: model input, mixing model & objective function

After identification of the most appropriate model components and most relevant uncertainties for the specific tracers and groundwater system in this study, these were used to infer the population of behavioural mixing model (LPM) parameters. Uncertainty in the age distribution was then estimated from the joint uncertainty in the LPM parameters. Each tracer's performance was assessed with regard to their ability to reduce uncertainty and/or ambiguity in inferred age in comparison to other tracers when used alone and in combination with other tracers. To assess the magnitude and shape of uncertainty in the age distribution and to discuss implications for groundwater management, uncertainty in the inferred age distribution was illustrated using different methods.

5.2.3 Specific framework components used in this study

5.2.3.1 The Mixing Model

A variety of approaches exist for conceptualization of groundwater mixing as detailed in Chapter 2. To allow for application of the framework to the many situations with limited available data (in regard to tracer and aquifer information), 'parametric' LPMs are used to conceptualize groundwater mixing in this study. The framework can be extended to allow for the use of more complex models.

Identifying the most appropriate parametric LPM(s) can be difficult as demonstrated in e.g. Massoudieh et al. (2014b), Green et al. (2014) and McCallum et al. (2014). No standard approach exists currently. Often certain LPM type(s) are prioritized or rejected based on the geometry of the studied aquifer and well construction. This ensures that mixing as conceptualized by the LPM is physically sensible. In the absence of aquifer and well construction information (or inconclusive information on these), the performance of various (preselected) LPM types is often assessed by evaluating the quality of the fit of simulated and observed tracer concentrations, such as the root mean square error (RMSE), a likelihood measure (Bayes factor), and/or by evaluating the identifiability of the LPM parameters [Massoudieh et al., 2014b; Green et al., 2014; McCallum et al., 2014]. The use of quantitative measures also allows for a more objective LPM choice. To address structural uncertainty, a multi-model approach can be used as suggested in other areas of hydrological modelling [e.g. Hoeting et al., 1999; Singh et al., 2010]. As an alternative approach to minimize or overcome structural uncertainty, 'shape-free'

LPMs can be used, although they are only applicable if an adequately large number of tracer data is available (not considered in this study).

In this particular case, multiple parametric LPM types were pre-selected based on the complexity of the groundwater system (i.e. physical realisticness) - a commonly used approach (see section 5.3 for detail on pre-selection of LPM types in this study). The performance of each pre-selected LPM type was then evaluated based on multiple quantitative and qualitative criteria. A large number of criteria were chosen to increase robustness of the approach. Widely applied performance measures, namely the bias, the root mean square error (RMSE) and the coefficient of variation (CV), were used. These had been previously applied in other probabilistic hydrological modelling studies but not in this combination, see e.g. references given in Efstratiadis and Koutsoyiannis (2010).³⁶ Specifically, the following criteria were used in this study³⁷:

1. On average (for all sites) the lowest bias of behavioural simulations and observations. This criterion penalized LPM types that resulted in biased fits.
2. On average (for all sites) the lowest RMSE of behavioural simulations and observations. This criterion penalized LPM types that led to poor fits.
3. On average (for all sites) the lowest CV of the behavioural LPM parameters. This criterion penalized poorly constrained LPM parameters and indirectly evaluated how much information was provided by the LPM type to reproduce tracer observations. Generally, the LPM parameters are likely to be poorly identifiable when the model/LPM is too complex leading to 'over-fitting'.³⁸
4. On average (for all sites) the highest number of behavioural models, which is a measure of the likelihood that the particular LPM type is appropriate (in combination with a low CV).
5. The lowest bias and RMSE of distinct/'important' tracer observations and behavioural simulation. This criterion ensured that all major features of the tracers input history were well represented.

³⁶ When information on aquifer complexity is unavailable or the pre-selected LPM types lead to poorly represented tracer observations, it is recommended that a wide range of LPM types is assessed.³⁶ The CV has been applied as performance measure in Massoudieh et al. (2012) - one of the identified age modelling studies listed in Tab. 2-1. For other types of performance criteria that have been applied in the age modelling literature see Massoudieh et al. (2013), Massoudieh et al. (2014b), Green et al. (2014) and McCallum et al. (2014).

³⁷ If the pre-selected LPM types are of different complexity (i.e. have a different number of independent variables) an additional criterion may be necessary to penalize more complex model structures. This counteracts over-fitting, despite equally well represented tracer observations. For example, Spiegelhalter et al. (2002) suggested the use of the deviance information criterion (DIC).

³⁸ The author notes that well constrained model parameters may not necessarily lead to the lowest model structural uncertainty, because structural uncertainty and parameter uncertainty interact. Ideally both structural and parameter uncertainty should be minimized.

Each LPM type was scored according to its performance for these criteria³⁹. All criteria were weighted equally. The LPM type with best overall score was considered most representative. If multiple trialled LPM types performed equally well, a multi-model approach was used to take account of equifinality, as applied in other areas of hydrological modelling [e.g. Hoeting et al., 1999; Singh et al., 2010]. The (weighted) average of all ‘behavioural’ model solutions was used to infer the population of behavioural age distributions when using each of these equally well performing LPMs.

In addition to these quantitative criteria the following qualitative criteria were used (if aquifer geometry and well construction were well studied) to ensure that mixing as conceptualized by the LPM type was physically sensible⁴⁰. These were:

6. Agreement of the LPM type with general aquifer geometry.
7. Agreement of inferred MRTs with well location with regard to recharge area or other dated wells.

5.2.3.2 The Model Inputs

As outlined in section 5.2.1, a range of model inputs and model input uncertainties exist, e.g. various tracer recharge estimates. Although often not explicitly stated in age modelling studies, commonly the assumed most relevant model inputs and uncertainties are subjectively pre-selected. To the authors knowledge a more comprehensive assessment of the relevance of individual model inputs and their (combined) effect on the age distribution has not been addressed in detail. This study attempts to firstly identify all relevant model inputs and uncertainties based on the tracer(s) used and study area. Tracer recharge was estimated using a) atmospheric tracer records with biased or random uncertainty and b) recharge weighted atmospheric concentrations, where the tracer recharge was weighted according to Eqn. 5-1. The most appropriate model inputs were then identified by assessing their individual performance using the quantitative performance criteria described in the section 5.2.3.1.

$$\text{Recharge weighted tracer input: } c_{in,y,w} = \frac{\sum(c_{in,m} * \text{recharge}(\text{monthly}))}{\sum \text{recharge}(\text{monthly})}, \quad \text{Eqn. 5-1}$$

where $c_{in,y,w}$ refers to the tracer’s recharge weighted concentration yearly (e.g. Jan-Dec); $c_{in,m}$ refers to the tracer’s monthly atmospheric concentration which is multiplied by the monthly recharged and divided by the total annual recharge.

³⁹ The performance of each LPM type was evaluated when using the most appropriate objective function and tracer recharge equivalent to average monthly atmospheric concentrations without consideration of uncertainties in tracer recharge and decay. It was acknowledged that the performance of each LPM type may depend on the objective function, model inputs and uncertainties used. It was outside the scope of this study to evaluate the performance of each LPM type when using combinations of different model inputs, uncertainties and objective functions. The same applied for the assessment of the most appropriate objective function and model inputs, which may depend on the LPM type and model inputs or objective function used, respectively.

⁴⁰ These measures are commonly studies in age modelling studies. A purely objective approach was not feasible, because information on physical realism could not be entirely quantitatively evaluated.

To keep the framework as simple as possible 'Classic' Monte Carlo Simulation was used to sample the model inputs from within their uncertainty. As detailed in Appendix C2, the LPM parameters were sampled from a uniform distribution. The MRT boundaries were set to 0 and 100 years. The mixing parameter boundaries were set to 0 and 1 (both are further detailed in Appendix C2). Setting the upper MRT limit to 100 years assumes that the water did not contain significant fractions of older (tracer free water). This may underestimate uncertainty in the inferred MRT. As can be seen in section 5.4.2.1, at only one site⁴¹ did the maximum limit of the behavioural MRT population reach the maximum MRT model boundary. For this particular site it could not be excluded that uncertainty in the MRT exceeded the MRT model boundary.

5.2.3.3 The Objective Function

As detailed in Chapter 2, other areas of hydrological modelling, where probabilistic approaches are more commonly used, highlighted the need for careful identification of objective functions [e.g. Krause et al., 2005; Gelman, 2008; Beven, 2006; Stedinger, 2008 and references therein; Beven and Binley, 2014]. Since only a few studies have demonstrated probabilistic age modelling approaches, assessment of the appropriateness of objective functions has not been carried out in age modelling. Generally, the performance of an objective function is dependent on the type and properties of the data, e.g. how much variation is in the data and how much data is available. To identify the most appropriate objective function, their performance is often assessed visually from the fit and/or bias and RMSE of modelled and observed data.

In this study, the Kling-Gupta [Gupta et al., 2009], the Nash-Sutcliffe efficiency [Nash and Sutcliffe, 1970], least square error, root mean square error and the Chi² statistic [e.g. Helsel and Hirsch, 2002; Guest, 2012] were used. Their performance is assessed using the quantitative criteria presented in section 5.2.3.1. To infer uncertainty in the age distribution from the population of behavioural LPM parameters, it was assumed that all behavioural models performed equally well, which is a commonly used approach, although debated [Beven and Binley, 2014]. If multiple tracers were available, the combination of each tracer's individual age estimation was expected to compensate individual tracer limitations, such as an ambiguous age estimate as often obtained with e.g. tritium. There are various methods to combine the age estimations inferred from multiple tracers [e.g. Massoudieh et al., 2014b]. Since there are only a few probabilistic age modelling studies, little work has been done to combine age estimates from multiple tracers when using other objective functions than a likelihood function. To obtain a combined age distribution from up to three tracers in this study, the following

⁴¹ when using tritium or SF₆. At three additional sites the upper uncertainty limit in the MRT could not be constrained when using Halon-1301. However, these sites were degraded in Halon-1301 which restricted robust determination of groundwater age at these sites.

methods were used. These involve modification of the selected, most appropriate objective function (e.g. Kling-Gupta, χ^2). The methods were⁴²:

- Method 1: the LPM parameter populations inferred from each individual tracer were averaged.
- Method 2: the LPM parameters were considered as behavioural if the objective function for all tracers was met⁴³.
- Method 3: LPM parameters were considered as behavioural if on average all individual tracers' objective function was met⁴³ (with equal weight for all tracers' objective function).
- Method 4: LPM parameters were considered as behavioural if on average all tracers' weighted objective function was met⁴³ (weighted according to the number of available data for each individual tracer divided by the sum of all available tracer data).

5.3 Study area specific framework components

The framework was demonstrated on SF₆, Halon-1301 and tritium data in the Lower Hutt Groundwater Zone (LHGWZ) described in detail in Chapter 3, with a particular focus on further assessing the performance of Halon-1301 as an age tracer. Table 5-1 contains the number and sampling times of the utilized SF₆, Halon-1301 and tritium data. More information on the studied wells can be found in Tab. 3-1 in Chapter 3 and in Appendix A.

Table 5-1: Site number, name, depth, tritium, Halon-1301 and SF₆ observations (amount and time range), *monthly spaced observations; Well number 15 = the Hutt River; sampling time in italics indicate artificial Halon-1301 data

Well #	Tritium data		SF ₆ data		Halon-1301	
	#	Sampling time	#	Sampling time	#	Sampling time
1	2	2010, 2013	3	2010, 2013, 2014	1	2014
2	2	2005, 2009	1	2007	-	
3	3	2002, 2007, 2011	2	2002, 2014	1	2014
4	9	1996-2010	3	2002, 2007, 2014	1	2014
5	9	1972-2013	3	2002, 2007, 2014	-	
6	4	1998-2010	2	2007, 2014	1	2014
7	2	2007, 2013	-	-	-	
8	3	2007, 2x 2013	2	2x 2013	-	
9	1	2013	-	-	-	
10	1	2013	-	-	-	
11	1	2013	4	2002, 2x2013, 2014	1	2014
12	1	2013	-	-	-	
13	1	2013	-	-	-	
14	11	2002-2003*	-	-	-	
15	1	2013	1	2014	1	2014

⁴² In this study, equal trusts in all tracers' capability as an age tracer (beyond analytical uncertainties on individual observations which were considered) were assumed. However, this could be generalized to account for differing levels of confidence.

⁴³ 'meeting the objective function' refers to meeting a specified threshold above or below which (depending on the objective function used) the model is considered behavioural. The approach is further detailed in Appendix C4.4.

Only single measurements of Halon-1301 were available (at six sites). These did not allow for a more comprehensive assessment of uncertainty in the inferred age distribution when using Halon-1301. In particular the potential of time series Halon-1301 data for identification of the mixing model and mixing parameter could not be carried out with single measurements of Halon-1301. To allow for a more comprehensive (and theoretical) assessment of uncertainty in Halon-1301-estimated age distributions when using Halon-1301 alone or in combination with tritium and/or SF₆, additional Halon-1301 measurements were generated in this study. Data generated for Well 6 and 11 are highlighted in italics in Tab. 5-1⁴⁴. Since the generated concentrations could not replace actual independent measurements of Halon-1301, artificial Halon-1301 data were only used to assess the potential value of time series Halon-1301 observations in this study as opposed to identifying the most relevant framework components.

Based on the structure of the LHGWZ (i.e. relatively homogenous aquifer layers with one recharge area) and well construction, the exponential piston flow model (EPM), the dispersion model (DM) and the partial exponential model (PEM) were pre-selected⁴⁵. Equations of these LPMs can be found in Appendix C2. The following model input uncertainties were considered relevant for tritium, Halon-1301 and SF₆ in this study. Uncertainties deemed insignificant or irrelevant for the applied tracers and given (aquifer) conditions are presented in Appendix C2 along with details on the reasoning behind their exclusion. The excluded uncertainties may be relevant in other studies and can be implemented in the presented framework if required. The considered model input uncertainties were:

1. Uncertainty in tracer recharge estimate:

SF₆ and Halon-1301 recharge were estimated using atmospheric SF₆ and Halon-1301 trends from Cape Grim (Australia) the closest monitoring station for these compounds [Bullister, 2014 and Newland et al., 2013], and either biased or random uncertainty in atmospheric trends was assumed. Tritium recharge was estimated using monthly and yearly (Dec-Nov and Jul-Jun average) atmospheric records from Kaitoke (New Zealand), the closest tritium monitoring station located 50 km north of the LHGWZ [Taylor, 1966, Morgenstern and Taylor, 2009], and either biased or random uncertainty in atmospheric trends was assumed. In addition to monthly and yearly atmospheric records, recharge weighted yearly (Dec-Nov) atmospheric records were used. All model input datasets are detailed in Appendix C2.2. To

⁴⁴ Halon-1301 data were only generated for Well 6 and 11, since these were not reduced in Halon-1301 concentrations. The remaining sites with reduced concentrations of Halon-1301 and the Hutt River sample were excluded. Reasons for their exclusion and details on the generation of artificial Halon-1301 data are given in Appendix C2. The objective function used in this study is presented in the subsequent section (5.3).

⁴⁵ More complex models (e.g. conceptualizing mixing of portions of considerably older and younger water as occurring in dual porosity aquifers) were not considered as they did not appear physically sensible for the given study area (for the given aquifer geometry and well construction further described in section 3.1). For a more thorough assessment, it is recommended to assess a large variety of mixing models.

weight the atmospheric tritium records according to Eqn. 5-1 the following recharge estimates were used:

- Recharge estimate 1: Groundwater recharge that had been estimated by Butcher (1993) given in Tab. 3-3 in Chapter 3 using the Thornthwaite-Mather method [Thornthwaite and Mather, 1955], was used.
- Recharge estimate 2: Groundwater recharge was estimated from the average monthly difference in precipitation and potential evapo-transpiration from selected monitoring sites in the catchment. Details on the locations and available data can be found in Appendix C2.
- Recharge estimate 3: Groundwater recharge was estimated similarly to Recharge estimate 2, but using monthly precipitation and potential evapo-transpiration data (not average). Details can also be found in Appendix C2.

To identify the most appropriate recharge estimate(s) for tritium and SF₆ in this study and the most representative LPM type(s), the criteria presented in section 5.2.3.1 were used. For criterion 5 (adequate representation of distinct/‘important’ tracer observations) tritium observations before and after arrival of the ‘bomb peak’⁴⁶ in Well 5 were used, i.e. observation 1 (1973) and 2 (1997) (Fig. 5-2). For SF₆ and Halon-1301, with a steadily increasing atmospheric trend, criterion 5 was omitted.

Figure 5-3: Tritium observations at site well 5 (points), an EPM (MRT of 20 years, E/PM of 0.1) was fit to the data points; the error was 2-4 %, except for the observation in 1971, which had an uncertainty of 7%

2. Uncertainty in half-life:

Tritium half-life has been determined with great precision (12.32 ± 0.02 years [Lucas and Unterweger, 2000]). This may indicate an insignificantly small effect of uncertainty in tritium half-life on the age distribution even for relatively old water. In this study, it was indeed found that uncertainty in tritium half-life did not significantly affect the population of behavioural LPM parameters for any site (details can be found in Appendix C3). The effect of uncertainty in tritium decay was therefore not further discussed in this study.

Decay and/or retardation were identified as possible causes of reduced Halon-1301 concentrations in Chapter 4. However, since this was the first study to assess the use of Halon-1301 as an age tracer,

⁴⁶ The peaking in tritium concentration in the 1950s/60s due to H bomb testing is referred to as ‘bomb peak’.

further study is needed to confirm these and estimate decay/retardation rates of Halon-1301. To make a first attempt in estimating uncertainty in Halon-1301-inferred age distributions in this study, Halon-1301 decay and retardation were assumed to be negligible. Further study is needed to more comprehensively assess uncertainty in Halon-1301 age estimates using derived Halon-1301 decay/retardation rate(s).

3. Uncertainty in tracer observations:

Uncertainties for SF₆ (data before 2014) and tritium data, provided by GNS Science, are detailed in Appendix C2. Uncertainties in SF₆ (2014 data) and Halon-1301 data were determined in Chapter 4, where uncertainties in Halon-1301 data were reported as including and excluding uncertainty in solubility. Both uncertainty measures were considered in this chapter to assess the effect of different magnitudes of measurement uncertainty on uncertainty in Halon-1301-inferred age distributions.

5.4 Results

In the following, the objective function, the LPM type(s) and tracer recharge estimate(s) that were found most appropriate and representative in this study are presented. Thereafter the LPM parameters and uncertainties inferred from Halon-1301, tritium and SF₆ individually and in combination (using the most appropriate framework components) are presented and discussed. Finally, the resulting age distribution and its uncertainty are illustrated and implications discussed. Since the performance of Halon-1301 was of particular interest to this study, results obtained when using Halon-1301 are discussed in more detail than these obtained when using SF₆ and tritium.

5.4.1 Most appropriate model components

5.4.1.1 *Objective function*

Although the Chi² statistic performed best in this study, it can only be applied on a relatively large dataset (which allows at least one degree of freedom e.g. a minimum of three tracer observations are necessary when using the EPM)⁴⁷. To allow for consistent comparison of tracer simulations and observations at all sites in this study a 'custom' objective function (Eqn. 5-2) at a threshold of 0.5 was used⁴⁸. Details on the custom objective function and its selection can be found in Appendix C3.

⁴⁷ The Chi² objective function also requires that the uncertainty in the tracer measurements can be transferred into a normal distribution. The analytical uncertainty in the tracer measurements was assumed to be normally distributed based on the analytical methods used for their determination. However, normality of the uncertainty caused by inhomogeneities in the subsurface or variability of groundwater flow could not be confirmed, although assessment of monthly sampled hydrochemistry data indicated normally distributed uncertainty as detailed in Appendix D1.

⁴⁸ The 'custom' objective function was found to have a similar performance as the Chi² statistic, i.e. it resulted in consistent behavioural models as the Chi² approach at 99 % confidence and uncertainty of 2 SDs at sites with more than three time series tracer data as detailed in Appendix C3.

$$obj. fct. = \frac{(x_1*1)+(x_2*0.5)+(x_3*0.25)+(x_4*-0.25)+(x_5*-0.5)+(x_6*-1)}{o}, \quad \text{Eqn. 5-2}$$

where o is the total number of tracer observations, x_1 as the number of simulations within 1 SD of tracer observation(s), x_2 is the number of simulations within 1-2 SDs of observation(s), x_3 is the number of simulations within 2-3 SDs of observation(s), ... and x_6 is the number of simulations greater than 5 SDs of the tracer observation(s). LPMs that resulted in a custom objective function above or equal to 0.5 were considered behavioural (i.e. adequately fitting). This implied that LPMs which generate tracer concentrations on average outside 2 SDs of observations were considered as non-behavioural and were disregarded.

5.4.1.2 LPM type

Despite relatively well constrained and identifiable behavioural LPM parameter populations inferred from tritium, Halon-1301 and SF₆ data for all assessed LPM types (see example illustrated in Fig. 5-3), the EPM appeared most representative for groundwater flow and mixing in the LHGWZ as indicated by the highest performance in evaluated criteria summarized in Tab. 5-2. The EPM resulted in the lowest CV, lowest bias, RMSE and highest number of accepted behavioural models. This was particularly prominent for sites with more than two tritium data. For the majority of sites with less than three tritium data all LPM types performed similarly well. Only small differences in CV, RMSE and bias were observed. The identification of the LPM type using the selected criteria with SF₆ data appeared difficult. On average the PEM was performing best, but large differences in performance were observed at each site (Tab. 5-3). This was likely a result of SF₆'s nearly linear input over the last few decades, which did not contain enough information to sufficiently constrain the LPM type as predicted in Chapter 4. When using Halon-1301 (with a different, S-shaped input), the EPM performed significantly better than the DM and the PEM for all sites, although only one Halon-1301 observation was available at each site in contrast to SF₆ time series data that were available at most sites. A similar picture (albeit with a slightly weaker indication towards the EPM) was observed when using generated Halon-1301 data in addition to the measured data (details can be found in Appendix C4). These findings indicated that the mixing model could be better constrained using Halon-1301 data than using SF₆ data, as a result of both tracers' historic input to groundwater.

Overall the EPM performed best (with regard to the set performance criteria) when using tritium and Halon-1301 data and also agreed well with the general aquifer geometry (partly unconfined) and well screen configuration (sampling of the entire aquifer layer). All other considered LPMs performed considerably less well, therefore the EPM was used in the following and a formal multi-model approach was not carried out, i.e. structural uncertainty is not formally assessed for this particular case study⁴⁹.

⁴⁹ Although the presented framework allows for implementation of a multi-model approach, it was most sensible to not use of a formal multi-model approach in this study. Firstly, this would require the use of a large number of LPM types or more complex models, although there is no objective method to pre-select sensible ones. Secondly, the use of a multi-model approach adds more complexity to the illustration of uncertainty in the inferred LPM parameters. One cannot simply combine the inferred MRTs or mixing parameter populations as

Figure 5-4: The figure illustrates behavioural LPM parameters that comply with the objective function (Eqn. 5.2) for assessment of the most representative LPM type for Well 4 using 9 tritium observations (LEFT), 6 SF₆ observations (MIDDLE) and 1 Halon-1301 observation (RIGHT), the mixing parameter refers to the ratio of exponential to total flow (E/PM) for the EPM; the dispersion parameter for the DM and the ratio of sampled volume to total volume for the PEM.

Table 5-2: Criteria to assess the most representative LPM type: median RMSE (root mean square error) and median bias of behavioural simulations and observation; median coefficient of variation (CV) of behavioural MRT and E/PM range; median number of behavioural models; median= median at all sites, sum points refers to the sum of points assigned for criteria - colour code: dark grey = 2 points (best fulfilled criterion); medium grey =1 point (medium performance for criterion); light grey = 0 points(worst performance for criterion); *data given as median (25/75 percentile), ^ median bias and median RMSE for observation number 9 (in 1972) before the arrival of the bomb peak and observation number 8 (in 1997) after arrival of the bomb peak at Well 5;

tracer	criterion	LPM type		
		EPM	DM	PEM
tritium	RMSE *	0.67 (0.60/0.93)	0.86 (0.70/1.13)	0.68 (0.53/0.89)
	Bias*	-0.006 (-0.004/ -0.020)	-0.007 (-0.002/ -0.024)	-0.006 (-0.003/ -0.022)
	CV (MRT/ mix.p.)	0.53/0.57	0.39/0.76	1.14/0.61
	# behav. mod.	886	258	463
	RMSE; bias important obs.^	1.49; 0.009	0.94; -0.009	1.64; 0.015
	Sum points	9	3	4
SF ₆	RMSE*	1.15 (0.49/2.1)	1.11 (0.48/1.99)	1.14 (0.49/2.6)
	Bias*	1.05 (0.42/ 1.78)	1.01 (0.49/1.76)	1.03 (0.42/ 1.76)
	CV (MRT/ mix.p.)	0.39/0.42	0.42/0.55	0.39/0.43
	# behav. mod.	7458	4790	7762
	Sum points	3	2	5
Halon-1301	RMSE* and Bias*	0.319 (0.06/0.63)	0.320 (0.08/0.63)	0.320 (0.06/0.63)
	CV (MRT/ mix.p.)	0.41/0.53	0.42/0.62	0.40/0.54
	# behav. mod.	19621	22748	19341
	Sum points	6	2	4
Overall	Sum points	18	7	13

5.4.1.3 Uncertainty in tracer recharge

Recharge estimate (applicable for tritium only)

For some sites the use of different tritium recharge estimates had a significant effect on the inferred EPM parameter populations. An example is illustrated in Fig. 5-4. For most locations, however, the

this can lead to misleading interpretation, because these parameters are linked to a specific type/shape of age distribution (depending on the LPM type). Further study is needed to demonstrate the implementation of a formal multi-model approach in age (LPM) modelling. As an alternative approach to minimize or overcome structural uncertainty, 'shape-free' non-parametric LPMs can be used, although their application requires a large number of tracer data (of the order of thousands of data points).

effect on the behavioural EPM parameter populations was relatively small (within ± 1 year of the MRT and within ± 0.1 of the mixing parameter in the following referred to as E/PM⁵⁰). Assessment of the selected performance criteria indicated that overall monthly average atmospheric concentrations performed best, closely followed by yearly (Dec-Nov and Jul-Jun) average atmospheric concentrations. For example, the CV and RMSE were highest and bias was the lowest when using the Jul-Jun average atmospheric concentrations. All observations (pre- and post- ‘bomb peak’) could be adequately well represented when using yearly/monthly average atmospheric concentrations, but could not be as well represented when recharge weighted atmospheric records were used. Details can be found in Appendix C3.

Figure 5-5: Effect of tritium input estimate on behavioural MRT and E/PM population; number of behavioural models as a function of MRT and E/PM using three different recharge weighted estimates for Well 4 (using 9 tritium observations)

These findings indicated that the tritium recharge could be best estimated with monthly average atmospheric concentrations in this study. It was also found that the effect of recharge weighted atmospheric records became only significant when absolute (time variable) recharge estimates were used. Where available the use of absolute recharge estimates and the assessment of the most appropriate tracer recharge estimate for the considered tracers are suggested.

Shape of uncertainty in tracer input

The shape of uncertainty in atmospheric tracer records had a significant effect on the behavioural LPM parameter populations for most sites when using tritium and SF₆ (see example illustrated in Fig. 5-5). Generally, random uncertainty in atmospheric tracer trends resulted in a significantly smaller uncertainty in the EPM parameters compared to the ones obtained when using biased uncertainty. For tritium, yearly average atmospheric concentrations with random uncertainty and monthly average concentrations with biased uncertainty resulted in similar behavioural EPM parameter populations.

⁵⁰ The E/PM is defined as the ratio of exponential to piston flow in Eqn.2-2 (Chapter 2).

This indicated that when tritium was used, seasonality in its recharge played a role and was important for constraining the EPM parameters in this study (seasonality was contained in monthly average atmospheric concentrations with biased uncertainty and induced by random uncertainty of the yearly average atmospheric record).

Evaluation of the performance criteria indicated that uncertainty in the atmospheric SF₆ record was more likely to be biased than random because of its better performance compared to random uncertainty. For tritium, this was less prominent. An overall slightly better performance of monthly and yearly average atmospheric records with biased uncertainty was observed compared to monthly atmospheric records and random uncertainty. The poorest performance was observed for the yearly atmospheric trend with random uncertainty. Tritium observations before and after the bomb peak could only be reproduced when considering biased uncertainty in the tritium record. Further detail can be found in Appendix C3.

Figure 5-6: Number of behavioural models as a function of MRT and E/PM when using yearly/monthly average tritium data and random (rnd)/biased uncertainty for Well 4 with 9 tritium observations (LEFT) and 6 SF₆ observations (RIGHT). The SF₆-inferred LPM parameter populations appear to be bimodal which may be a result of erroneous data (e.g. caused by contact with air) which did not get picked up by the objective function. To resolve this issue, reliability and potential in-appropriateness of individual tracer data need to be assessed either prior to uncertainty modelling (followed by removal of the erroneous data need to be removed), or accounted for in an appropriate objective function. The issues caused by erroneous tracer data is further discussed subsequently for reduced Halon-1301 concentrations.

In combination with the preceding findings demonstrating that the tritium input was more likely to follow the monthly atmospheric record, it was concluded that the tritium input could be best represented by the monthly average atmospheric record with biased uncertainty in this study.

When using purely measured Halon-1301 data and random and biased uncertainty in the Halon-1301 input, insignificantly different EPM parameters were inferred and both biased and random uncertainty performed similarly (details can be found in Appendix C3). This indicated that single Halon-1301 observations did not contain enough information to constrain the shape of uncertainty in the Halon-

1301 input, as anticipated. Similarly, when using single SF₆ observations, random and biased uncertainty in the SF₆ input also performed equally well confirming that time series data were necessary to provide information on the shape of uncertainty in the tracer's input. These findings were further strengthened when using generated Halon-1301 data in addition to measured Halon-1301 data, which resulted in significantly different EPM parameter populations. However, since artificial data cannot replace actual measurements, the shape of uncertainty in the Halon-1301 trend could not be confirmed in this study⁵¹. Since biased uncertainty in the SF₆ input had been found most appropriate in this study and biased uncertainty in the atmospheric Halon-1301 trend appeared also most reasonable when assessing atmospheric Halon-1301 records [e.g. Fraser et al., 1999], uncertainty in the Halon-1301 and SF₆ input was assumed to be biased for further analysis in this study⁵².

5.4.2 Quantifying uncertainty in inferred age when using the most appropriate framework components and most relevant model uncertainties

In the previous sections it was shown that the EPM was the most representative LPM type and that a custom objective function could be used for LPM calibration in this study. In addition, the tritium input was found to be best represented with monthly average atmospheric tritium concentrations and the shape of uncertainty in atmospheric tritium and SF₆ (and Halon-1301) trends was most likely biased (than random). On the basis of these findings, the custom objective function, the EPM and monthly atmospheric tracer records with biased uncertainty were used to infer age distributions and estimate their uncertainty from Halon-1301, SF₆ and tritium data in this study. Results are presented in the following.

5.4.2.1 Uncertainty in inferred LPM parameters using individual tracers

In this section, the LPM parameter populations inferred using individual tracers are presented. Firstly, the LPM parameters populations derived from each tracer are compared and each tracer's performance as an age tracer with regard to uncertainty and ambiguity in the estimated LPM parameter populations is assessed. Secondly, consistency of the inferred LPM parameters populations at each site and reasons for inconsistencies are discussed. Thirdly, the inferred LPM parameters are compared to the LPM parameters estimated using other techniques to assess the performance of the probabilistic framework.

⁵¹ The use of observed and generated Halon-1301 data indicated that biased uncertainty performed significantly better than random uncertainty in the input, although it was noted that artificial data had been generated assuming biased uncertainty in the Halon-1301 input. The findings therefore only suggested that if time series Halon-1301 data were available, the shape of the uncertainty in the Halon-1301 input could be potentially better constrained than with single Halon-1301 observations, as opposed to confirming the shape of the uncertainty in the Halon-1301 input.

⁵² The shape of uncertainty in Halon-1301 input (if biased or random) was not expected to show an effect on the inferred LPM parameters when using single Halon-1301 data, since the shape of uncertainty in the Halon-1301 input did not significantly affect the behavioural EPM parameters when using single Halon-1301 data.

The site specific uncertainty bounds of the inferred EPM parameters and most likely EPM parameters are summarized in Tab. 5-3. Note that uncertainty of the estimated EPM parameters is presented as total range (i.e. 100% coverage and confidence). For comparison uncertainty bounds at 90 and 95% confidence are given in Appendix C4. The probability should be consulted for interpretation of estimated age distributions as discussed in section 5.4.2.3. Fig. 5-6 and 5-7 illustrate two examples of EPM parameter probability distributions inferred from tritium, Halon-1301 and SF₆⁵³.

*Table 5-3: Range and most likely behavioural EPM parameters (MRT & E/PM) using tritium and SF₆; ^m.l. refers to the most likely LPM parameter with highest probability; +nearly uniformly distributed or ambiguous results where the m.l. = average; *visually best fitting MRT inferred from tritium when using a common spreadsheet approach*

Well #	tritium		SF ₆		Halon-1301 (incl./excl. uncertainty in solubility)		visual best fit*
	MRT (m.l.^) [years]	E/PM (m.l.^)	MRT (m.l.^) [years]	E/PM (m.l.^)	MRT (m.l.^) [years]	E/PM (m.l.^)	MRT [years] {E/PM}
1	7-64 (17)	0-1 (0.4)	0-38 (20)	0-1 (0.3)	29.4->100 (91.2)/ 29.9->100 (91.2)	0-1 (0.73)/ 0-1 (0.73)	18 {0.73}
2	0.8-50 (5)	0-1 (0.3)	0.2-5.5 (3 ⁺)	0-1 (0.9)	-	-	1 {0.30}
3	3-58 (12)	0-1 (0.8)	10-26 (13)	0-1 (0.9)	31.4->100 (70.8)/ 31.7->100 (70.8)	0-0.93 (0.30)/ 0-0.92 (0.30)	17 {0.88}
4	19-52 (41)	0.4-0.8 (0.5)	18-47 (31)	0.3-1 (0.9)	33.9->100 (62.0)/ 34.0->100 (62.0)	0-0.84 (0.69)/ 0-0.83 (0.69)	20.5 {0.40}
5	19.9-27 (21)	0.1-0.4 (0.2)	25->100 (30)	0-0.8 (0.8)	-	-	19 {0.17}
6	1.0-3.3 (1.9 ⁺)	0.0-0.9 (0.7 ⁺)	0-5 (1)	0-1 (0.3)	0-16.6 (9.7)/ 0-8.2 (3.6)	0-1 (0.82)/ 0-1 (0.18)	0.5 {0.25}
6	with one additional (artificial) Halon-1301 observation				0-5.0 (1.2)	0-1 (0.34)	
7	8-41 (28)	0.1-0.4 (0.3)	-	-	-	-	32 {0.22}
8	7-56 (14)	0-1 (0.9)	3-9 (6)	0-1 (0.9)	-	-	15 {0.60}
9	56->100 (79)	0-0.5 (0.4)	-	-	-	-	65 {0.22}
10	0.1-52 (2)	0-1 (0.1)	-	-	-	-	2.5 {0.80}
11	0.9-59 (4)	0-1 (0.2)	5-14 (13)	0-1 (0.9)	0.7-21.6 (16.7)/ 6.6-20.0 (16.7)	0-1 (0.91)/ 0-1 (0.91)	7 {0.40}
11	with one additional (artificial) Halon-1301 observation				7.2-17.6 (12.7)	0-1 (0.91)	
12	7-66 (17)	0-1 (0.3)	-	-	-	-	16 {0.60}
13	0.1-52 (2)	0-1 (0.1)	-	-	-	-	3.5 {0.70}
14	0-51 (42)	0-1 (0.4)	-	-	-	-	1 {0.30}
15	0.2-50 (1)	0-1 (0.1)	4-35 (12.7)	0-1 (0.9)	0-19.3 (12.7)/ 0-17.9 (17.8)	0-1 (0.91)/ 0-1 (0.68)	<0.5 {variable}

EPM parameter populations inferred from each tracer:

For some sites relatively flat EPM parameter distributions (highlighted with “+” in Tab. 5-3 and illustrated in Fig. 5-7) did not allow for identification of the most likely EPM parameters. For the remaining locations, the EPM parameter distributions appeared to be similar to a normal or log-normal distribution if not multi-modal. Strong correlation of the EPM parameters were found at most sites (e.g. in Fig. 5-6 and 5-7), which may have led to large uncertainties in the inferred EPM parameters. The strong correlation (and relatively large uncertainty) was most likely a result of too few or too

⁵³ The probability plots were established by binning the behavioural populations into 20 bins and normalization by the number of behavioural models. The effect of bin size on the distribution is discussed in Appendix D4.

closely spaced tracer measurements, which did not contain enough information to constrain the EPM parameters further. This may be resolved by additional tracer measurements.

Figure 5-7: Probability plots of LPM parameters inferred from 9 tritium observations (UPPER), 3 SF₆ (MIDDLE) and 1 Halon-1301 observation (without consideration of uncertainty in solubility) (LOWER) for Well 4; the inferred MRT population for Halon-1301 suggested uncertainty in the inferred MRT is larger than 100 years and would need to be evaluated further with larger MRT bounds.

Generally, how well LPM parameters can be constrained with each tracer is dependent on various factors, such as the tracer's input, number and time of tracer data in groundwater in relation to the input and/or radioactive day, which is further discussed in Appendix C4. In this study, generally less ambiguous MRTs were inferred from SF₆ and Halon-1301 than when inferred from tritium. The examples illustrated in Fig. 5-7 show two distinct MRT populations inferred from tritium and only one MRT population inferred from SF₆ and Halon-1301. This was attributed to the tracer's historic input to groundwater (i.e. a pulse function for tritium vs. SF₆ and continuously increasing Halon-1301) and the behaviour of the tracers in groundwater (i.e. radioactive decay of tritium vs. stability of SF₆ and Halon-1301). For all locations where ambiguous (i.e. bimodal) MRT populations were obtained with tritium, only one of the MRT populations overlapped with the MRT population inferred from SF₆ and/or Halon-1301. These findings indicated that ambiguity may be resolved and the LPM parameters may be better constrained when inferred from a combination of all three tracers.

Figure 5-8: Probability plots of LPM parameters inferred from tritium (UPPER), SF_6 (MIDDLE) and Halon-1301 (without consideration of uncertainty in solubility) (LOWER) for Well 11

The E/PM was generally best constrained (i.e. had a smaller uncertainty) when inferred from tritium, followed by Halon-1301 and SF_6 . This was attributed to the tracer's characteristic historic input and behaviour in groundwater as discussed previously. Significantly larger uncertainties in the inferred MRTs were obtained with Halon-1301 compared to the ones inferred from SF_6 and tritium (if not bimodal)⁵⁴. This may have been a consequence of the congregation of the following factors: 1) the relatively large analytical uncertainty in the determination of Halon-1301 in groundwater (determined in Chapter 4); 2) a relatively flat input of Halon-1301 to groundwater over the last few decades particularly since 2000 (e.g. an increase of 1.3 % in atmospheric Halon-1301 vs. 8.2 % in SF_6 from 2010 to 2012, as illustrated in Fig. 4-1 in Chapter 4); and 3) only one available Halon-1301 measurement at each site compared to time series SF_6 and tritium data at the majority of sites (a relatively large uncertainty in inferred EPM parameters was also observed when using single SF_6 measurements). The

⁵⁴ With inclusion of uncertainties in retardation/decay of Halon-1301 the uncertainty in inferred Halon-1301 age may actually exceed the uncertainty estimated in this study.

author notes that this comparison of Halon-1301's performance as an age tracer to tritium and SF₆ may underestimate Halon-1301's potential, because only 1 Halon-1301 measurement was available at each site compared to time series tritium and SF₆ data, and as some sites were known to be degraded in Halon-1301. For a more comprehensive analysis and comparison of the performance of Halon-1301 as an age tracer, one needs to assess a richer dataset with additional Halon-1301 data, and treat data with known issues with more caution.

When using generated Halon-1301 data in addition to measured data, a smaller uncertainty in the MRT, but an insignificantly different uncertainty in the E/PM was obtained (see Tab. 5-4). Inclusion of generated Halon-1301 data did therefore not allow for confirmation of the supposition that the mixing parameter can be better constrained with the aid of time series Halon-1301 data than with single Halon-1301 data. This needs to be assessed further with independent time series data of Halon-1301. Aside from the use of artificial Halon-1301 data that cannot replace actual measurements, the assessed groundwater samples were relatively young⁵⁵, i.e. contained a large fraction of water recharged during recent years with a flattening out atmospheric Halon-1301 concentration, which may have prevented further constraining of the E/PM in this study.

To assess if a lower analytical uncertainty in Halon-1301 measurements would result in a significantly reduced uncertainty in the inferred EPM parameters, the analytical uncertainty not taking uncertainty in the estimated solubility (as determined in Chapter 4) into account was used. As anticipated, a lower bias, lower RMSE and lower number of behavioural models were obtained with the lower uncertainty compared to the ones obtained when considering the more comprehensive analytical uncertainty (i.e. including uncertainty in solubility). However, only for the younger water samples (that were not reduced in Halon-1301) did the lower analytical uncertainty result in a significantly (up to 59%) smaller uncertainty in the inferred MRT (see Tab. 5-1 and Appendix C3 for details).

These findings highlighted the need for a reduced uncertainty in the determination of Halon-1301 (i.e. its solubility and/or analysis) and the use of time series Halon-1301 data to decrease uncertainty in the Halon-1301-inferred LPM parameters and ultimately expand Halon-1301's application range and reliability as a groundwater age. This was also noted in Chapter 4.

Consistency of EPM parameters inferred from each tracer:

For all locations where data for tritium and SF₆ were available, the behavioural EPM parameter populations derived from SF₆ and tritium overlapped, which indicated partially consistent age estimates inferred from either tracer. Estimated Halon-1301 MRTs only agreed with estimated SF₆ and

⁵⁵ Assessment of the effect of additional Halon-1301 data in the older wells was not possible, since these were all degraded in Halon-1301.

tritium MRTs for Well 6, 11 and 15. For the remaining sites Halon-1301-inferred MRTs were significantly lower than the MRTs inferred from tritium and SF₆, confirming the findings presented in Chapter 4 which showed reduced Halon-1301 concentrations at these sites. For some of the wells with a reduced concentration of Halon-1301, Halon-1301-inferred MRTs (and E/PMs) overlapped with MRTs derived from SF₆ and/or tritium (and E/PMs), due to the relatively large uncertainty in the MRT (and the E/PM) estimated from Halon-1301 data. This highlighted the need for considering uncertainty in tracer observations and/or the reliability of the tracer to reduce uncertainty in the inferred LPM parameters when using a combination of multiple tracers. For three of the wells with a reduced concentration of Halon-1301, uncertainty in the estimated MRT could not be sufficiently characterized, as it exceeded the maximum MRT boundary of 100 years used in this study (Tab. 5-3).

Although the MRTs derived from SF₆ and tritium overlapped for the majority of sites, the most likely MRT inferred from each tracer differed significantly (with a difference of 6-30 years) for five of eight sites (Tab. 5-3). Because the most likely MRTs estimated from tritium was not consistently higher than the ones estimated from SF₆ (and Halon-1301), the difference in the most likely MRT was unlikely to have been caused by travel through the unsaturated zone or on the surface (i.e. travel in the Hutt River). Instead, it was more likely that these differences were a result of e.g. analytical (or sampling) errors in the tracer measurements, air exposure in the well or due to a relatively flat MRT distribution with no clear probability maximum.

Comparison of LPM parameters inferred using the probabilistic approach to the ones inferred using other methods:

Table 5-3 also summarizes the (visually) best fitting EPM parameters derived from tritium when using TracerLPM, a commonly used spreadsheet approach to fit LPMs to tracer data using a deterministic single 'best fit' approach [Jurgens et al., 2012]. Although the best fitting EPM parameters inferred from TracerLPM were generally contained in the EPM parameter populations estimated using tritium in this study, there were significant discrepancies (differences of up to 41 years) between the most likely MRT inferred in this study and the (visually) best fitting MRT and mixing parameter estimated using TracerLPM for seven of 15 sites. These discrepancies highlighted that the commonly determined best fitting LPM parameters may not be the most likely ones.

Uncertainty in the MRTs inferred from SF₆ and Halon-1301 in this chapter greatly exceeded the ones estimated using an uncertainty perturbation approach presented in Chapter 4 (Tab. 4-5). In other words, the use of the probabilistic framework led to a more conservative uncertainty estimate in the MRT than inferred when using an uncertainty perturbation technique. These findings highlighted that uncertainty in the estimated LPM parameters may be significantly different when derived from

probabilistic and non-probabilistic approaches. For a more robust age estimation and quantification of uncertainty, the use of probabilistic approaches is recommended.

5.4.2.2 Uncertainty in inferred LPM parameters a combination of up to three tracers

In this section, the combined age estimates inferred using up to three tracers are presented. At the majority of sites any tracer combination method enabled reduction of uncertainty in the EPM parameters derived from SF₆ or Halon-1301 and reduction of ambiguity in the EPM parameters derived from tritium. For some sites, however, ambiguity still remained. With each tracer combination method significantly different uncertainty distributions in the inferred EPM parameters were obtained. Examples are illustrated in Fig. 5-8 and further detailed in Appendix C4. Note that the combination methods were increasingly more sophisticated with increasing method number (see section 5.2.3.3 for detail on the individual methods employed). Unsurprisingly, uncertainty in the LPM parameters became increasingly more constrained with increasing method number. The most constrained EPM parameters were obtained with method 4 (where the LPM parameters were considered as behavioural when the weighted average of all tracers' objective function was met).

The author notes that inclusion of reduced Halon-1301 concentrations when inferring a combined age interpretation tends to select the older MRT populations inferred with tritium and/or SF₆. The resulting age distributions appear to have narrowed while they may actually have been biased through inclusion of reduced Halon-1301 data. This finding demonstrates the potential danger in including potentially erroneous age tracer data. To resolve this issue, reliability and potential inappropriateness of individual tracer data need to be assessed either prior to uncertainty modelling (followed by removal of the erroneous data), or accounted for in an appropriate objective function.

Figure 5-9: Probability plots for Well 11 (LEFT) and Well 6 (RIGHT) showing the probability as a function of the MRT inferred from tritium, Halon-1301 and SF₆ using each tracer alone and in combination – combined with method 2 to 4 (method 1 simply combines the behavioural EPM parameters inferred from each tracer and is not illustrated as a separate graph here)

To assess whether uncertainty in the EPM parameters could be reduced with addition of Halon-1301 to tritium and/or SF₆, the change in uncertainty in the inferred EPM parameters when using Halon-1301 in addition to tritium and/or SF₆ was determined according to Eqn. 5-3.⁵⁶ Results are summarized in Tab. 5-4.

$$\Delta\epsilon\%(age)_H = \frac{\epsilon(age)_{S/T} - \epsilon(age)_{H+S/T}}{\epsilon(age)_{H+S/T}} * 100, \quad \text{Eqn. 5-3}$$

where $\epsilon(age)$ denotes uncertainty in inferred LPM parameters as determined from the full range (i.e. the 0th and 100th %centile) of the derived LPM parameters, e.g. uncertainty in estimated MRT $\epsilon(MRT)$ is equal to $MRT_{max} - MRT_{min}$. $\epsilon(age)_{S/T}$ refers to the age inferred from tritium and/or SF₆; $\epsilon(age)_{H+S/T}$ refers to the age derived from Halon-1301 and tritium and/or SF₆. $\Delta\epsilon\%(age)_H$ denotes the relative change in estimated LPM parameters when using Halon-1301 in combination with SF₆ and/or tritium compared to using SF₆ and/or tritium alone. For example a $\Delta\epsilon\%(MRT)_H < 0\%$ implied that uncertainty in the MRT inferred from tritium and/or SF₆ could be reduced with addition of Halon-1301.

Table 5-4: Average relative change in uncertainty in the MRT and E/PM when including Halon-1301 for all sites; statistically insignificant changes ($p > 0.05$) are highlighted in *italics*

Comb. method #	$\Delta\epsilon\%(MRT)_H$ [%] when using:			$\Delta\epsilon\%(E/PM)_H$ [%] when using:		
	All 3 compared to tritium and SF ₆	Halon-1301 and SF ₆ compared to SF ₆ alone	Halon-1301 and tritium compared to tritium alone	All 3 compared to tritium and SF ₆	Halon-1301 and SF ₆ compared to SF ₆ alone	Halon-1301 and tritium compared to SF ₆ alone
<i>When considering all sites</i>						
1	51.6	50.2	46.5	6.4	6.4	6.4
2	0	2437	456.0	0	727.5	401.5
3	51.2	10.1	31.3	-7.0	-0.4	-15.2
4	17.1	94.2	176.1	-18.6	1.5	-11.2
<i>When considering all sites plus artificial Halon-1301 data for Well 6 and 11</i>						
1	51.6	49.0	46.5	6.4	6.4	6.4
2	-8.6	2430	445.3	-16.5	727.5	391.6
3	53.1	55.3	17.8	-7.0	-0.4	-18.0
4	20.9	204.3	168.5	-18.1	1.5	16.9

It was found that the direction, magnitude and significance of the change in uncertainty in the EPM parameters with addition of Halon-1301 were dependent on the site and combination method. When using method 1, changes in uncertainty in the estimated MRT and E/PM were statistically significant, although uncertainty in the inferred MRT significantly increased (on average) with addition of Halon-1301 to tritium and/or SF₆. This increase in uncertainty with addition of Halon-1301 can be attributed to the large uncertainty in Halon-1301 data, but may also highlight the potential inappropriateness of method 1, as further discussed in Appendix C3. When using method 3, changes in uncertainty in the MRT and E/PM were also statistically significant. A significant reduction in uncertainty in the inferred E/PM was achieved when including Halon-1301 to tritium and/or SF₆, particularly when combining the two gaseous tracers Halon-1301 and SF₆. This appeared even more significant (higher reduction in

⁵⁶ A one tailed student t-test assuming independent populations with different variance was used to assess if the difference was significant. Significantly different populations were characterized by $p < 0.05$.

uncertainty of the inferred E/PM) when using artificially generated Halon-1301 data in addition to measured Halon-1301 data as shown in Tab. 5-4 and detailed in Appendix C4. This indicated that with the aid of time series Halon-1301 data uncertainty in the E/PM may be better constrained than when using single Halon-1301 observations. However, further study is needed to confirm this exclusively with additional independent measurements of Halon-1301.

5.4.2.3 Uncertainty in the age distribution

In this section, uncertainty and ambiguity in the estimated age distribution is illustrated. In addition, the compliance/non-compliance with the New Zealand drinking water standard (NZDWS), which requires < 0.005 % of the groundwater to be <1 year old [Ministry of Health, 2008], is assessed. The probability distribution of the age distribution was inferred from the joint probability of the EPM parameters derived from SF₆ and tritium using tracer combination method 1.⁵⁷ The illustration of the uncertainty in the age distribution is a multidimensional problem and little study has been carried out to assess appropriate illustration methods that can be consulted for assessment of compliance/ non-compliance with standards such as the NZDWS. In this study, two illustration methods were used.

Figure 5-9 illustrates the likelihood of water containing fractions of <1 year old water for Well 6 and for <1 year old water and 1-100 year old water for Well 4. Most of the water in Well 4 was most likely between one and 100 years old. Since there was a 95% probability that less than 0.005% of the water in Well 4 was <1 year old, water in Well 4 did comply with the NZDWS. For Well 6 <1 year old water may have made up 0 to 100% of the water, with the highest probability that the fraction of <1 year old water was close to 40%. This suggested water from Well 6 did not comply with the NZDWS.

Figure 5-10: Probability plots of the proportion of <1 year old water for Well 6 (LEFT), < 1 year old water for Well 4 (MIDDLE) and 1-100 year old water for Well 4 (RIGHT).

⁵⁷ Method 1 simply averaged the behavioural EPM parameters inferred from either tracer. Halon-1301 was not considered here since it was not available at all sites and some wells were degraded in Halon-1301 which prevented a robust age interpretation with Halon-1301 in these wells. The actual method and tracers used in this section was irrelevant as this section only served as a demonstration of illustration methods and communication of the uncertainty in the inferred age interpretation.

Figure 5-10 illustrates the most likely, median (at 50% probability) and the 10th and 90th percentile cumulative age distributions for water in Well 4 and 6. Figure 5-10 allowed for similar conclusions to the ones made with Fig. 5-9. For example most of the water in Well 6 was below 10 years old and according to the most likely and 10th percentile age distribution the water did not comply with the NZDWS. However, the median and 90th percentile age distributions indicated that the water at Well 6 did comply with the NZDWS. According to Fig. 5-10, a larger proportion of water in Well 4 was likely above 100 years old. The most likely, median and 10th percentile age distribution indicated that water at Well 4 did comply with the NZDWS. However, the 90th percentile age distribution indicated that water at Well 4 did not comply with the NZDWS.

Figure 5-11: Cumulative probability plots of age distribution inferred for Well 6 (UPPER) and Well 4 (LOWER)

These findings indicated, with either illustration method, a discussion on appropriate thresholds and their implication needs to take place (e.g. whether the 10th and 90th percentile are appropriate). This is particularly relevant when highly ambiguous age estimation is obtained. It is likely that this threshold will vary between counties and authorities (similar to drinking water contamination thresholds) and will depend on the application, e.g. assessment of contamination risks vs. sustainable use. In addition to the use of uncertainty thresholds, qualitative measures, such as the general understanding of the groundwater flow processes in the aquifer, may be used to interpret ambiguous age estimates. A

discussion on how such qualitative measures may be implemented in interpreting ambiguous age estimates and ultimately decision making (e.g. threshold setting, such as the NZDWS) is needed in further study.

5.5 Chapter summary and conclusion

An extensive literature review, carried out in this study, suggests that 1) very few groundwater age modelling studies have used a probabilistic approach to assess uncertainty; 2) although various model (input) uncertainties have been considered in the identified probabilistic age modelling studies, uncertainty in the tracer's recharge estimate has not been taken into account; and 3) there has been negligible effort in defining meaningful objective functions in age (LPM) modelling. Progress in other areas of hydrological modelling has shown the need for careful identification of such metrics and consideration of all relevant model input uncertainties. For a more comprehensive uncertainty assessment in groundwater age modelling, it is important to consider all sources of uncertainty and identify the most relevant model components.

In this study, age modelling was placed into a relatively simple probabilistic framework. The framework built on the work presented in the few identified probabilistic age modelling studies (listed in Tab. 2-1 in Chapter 2), but was aimed at the many studies where little tracer data is available. Parametric LPMs were used to conceptualize groundwater mixing. The use of more complex models, such as non-parametric LPMs, is also possible. The framework was demonstrated on tritium, Halon-1301 and SF₆ data in a New Zealand aquifer, but can be applied on any tracer dataset. Each individual uncertainty in model input and its relevance towards uncertainty in the age distribution was assessed in detail. Guidance was provided on how to identify the most suitable LPM type(s), most appropriate objective function and most appropriate and relevant model inputs and uncertainties by assessing their performance with quantitative criteria. It was suggested how to implement a multi-model approach to address structural uncertainty. The author notes, it is relatively simple to adapt the framework to include a range of LPMs and/or other structures, such as distributed models. The use of non-parametric LPMs is an alternative approach to minimize or overcome structural uncertainty, although a considerable amount of tracer data is required to overcome the large degrees of freedom introduced by this shape-free approach. Different combination techniques for age information gained from multiple tracers were also demonstrated. The main findings of this chapter and recommendations for further work are summarized in the following:

Framework specific findings and recommendations:

- The objective function that best fulfilled the chosen requirements in this study was the Chi² statistic. However, to allow for inferring of an age distribution from any number of time series tracer data,

the use of the custom objective function (Eqn. 5-2) was suggested which, as shown in this chapter, had a similar performance as the χ^2 statistic. The use of the χ^2 statistic is recommended, when an adequately large number of time series tracer data is available (e.g. three observations when using a 'parametric' LPM with two parameters) and the shape of uncertainty in tracer observations can be transformed into a Gaussian distribution. To confirm the wide transferability of both objective functions on any age tracer data set, their performance needs to be assessed in other environments (e.g. in the northern hemisphere where atmospheric tracer records are different) and/or when using other tracers than used in this study. Further work in this area is needed to identify meaningful objective functions.

- Information on aquifer complexity was used to pre-select the most relevant LPM types. The performance of the pre-selected LPMs was assessed using quantitative criteria, which were beneficial to infer the most representative LPM type. The transferability of the chosen criteria needs to be assessed on other tracer datasets. Particularly the (subjective) pre-selection of the most suitable LPM types based on aquifer complexity needs further assessment and may be best replaced by a quantitative assessment. To ensure that the most suitable LPM type is among the pre-selected LPM types, it is recommended to assess a large number of LPM types.
- A formal multi-model approach was not carried out. It is suggested future extensions of this work should use a multi-model approach, which allows for assessment of model structural errors. The implementation of a multi-model approach needs to be assessed further e.g. if the (weighted) average of the inferred LPM parameter populations is appropriate.
- This study made a first attempt to also assess the effect of uncertainty in the tracer's recharge to groundwater on the age distribution. Quantitative criteria were used to identify most likely tracer recharge estimates. It is suggested that future work should assess which uncertainties and tracer recharge estimate are most representative at the given study area and for the tracer used. Better (time and space variable) tracer recharge estimates may be taken account of by combining the approach with models that infer recharge more accurately.
- The framework also allowed for assessment of the performance of individual tracers with regard to uncertainty and ambiguity in estimated age. Of particular interest was the performance of Halon-1301, the new groundwater age tracer presented in Chapter 4. In the following case study specific findings and future recommendations are summarized.

Case study specific findings and recommendations:

- It was shown that the age distribution was sensitive towards a variety of data and model uncertainties. Uncertainty in the tritium decay rate did not significantly affect uncertainty in the age distribution in this study. However, for other tracers with a larger uncertainty in decay rate

and/or slower decay this may significantly affect the age estimate, particularly for older groundwater. It is suggested to assess the effect of all possible uncertainties on the uncertainty in the age distribution to ensure a robust uncertainty assessment in age modelling.

- The following was found with regards to the performance of Halon-1301 compared to SF₆ and tritium:
 - a) Identification of the most appropriate mixing model was more conclusive when using Halon-1301 than when using SF₆. In addition, uncertainty in the Halon-1301-inferred mixing parameter was smaller than the one inferred from SF₆. These findings confirmed the results from Chapter 4 indicating that Halon-1301 may aid constraining of mixing models due to its non-linear (S-shaped) historic input.
 - b) Halon-1301-estimated MRTs were prone to larger uncertainties than the ones inferred from tritium or SF₆ which can be related to the relatively large uncertainty in Halon-1301 measurements in groundwater, its relatively flat atmospheric trend particularly since 2000 and only one available Halon-1301 measurement at each studied site.
 - c) The relatively large uncertainty in the MRT was reduced when using multiple Halon-1301 data and/or when not considering uncertainty in the solubility of Halon-1301. This highlighted the need for further study to better estimate the solubility of Halon-1301 and/or to further reduce the analytical uncertainty in the determination of Halon-1301 (some suggestions have been provided in Appendix B6) to extend Halon-1301's application range as an age tracer. Further study is needed to determine independent time series Halon-1301 data and confirm the cause(s) of reduced concentrations of Halon-1301 and estimate rates of decay/retardation to more comprehensively assess the uncertainty in Halon-1301-inferred age estimates and its performance as an age tracer.
- Direct comparison and combination of age estimations from SF₆, Halon-1301 and tritium allowed for reduction of individual tracer limitations, such as ambiguity related to the use of tritium, and uncertainty in the LPM parameters related to the use of SF₆ and Halon-1301. These findings indicated that, although large uncertainties in the MRT may be inferred from Halon-1301 data, the value added through complementary use of Halon-1301 e.g. to constrain the mixing parameter and help resolve ambiguous MRTs, can outweigh this shortcoming. It is recommended to assess the age estimation inferred from each tracer individually before assessing different combination methods for robust groundwater dating.
- It was noted that, although the consideration of Halon-1301 data in combination with tritium and/or SF₆ narrowed the resulting LPM parameter populations inferred with each individual tracer, the age interpretation may have actually been biased towards higher ages due to the inclusion of data that is thought to have had degraded (reduced concentrations) of Halon-1301. This

demonstrates the potential danger in using (multiple) age tracer data while not accounting for the tracer's reliability, e.g. potential degradation. Further study is needed to find methods that allow for consideration of the tracer's reliability in age modelling. Potential methods include identification of erroneous tracer data prior to uncertainty modelling (followed by removal of the erroneous data need to be removed), and the use of an appropriate objective function that accounts for the tracer's reliability, e.g. by weighting tracer data based on their reliability.

Key messages:

- A key message arising from this work is that the commonly derived single (visually) best fitting LPM parameters do not generally comply with the most likely LPM parameters found when using the probabilistic framework.
- Aside from ambiguous age estimates, a significant uncertainty in the MRT ranging from 20 to over 3000% of the most likely MRT was found. The estimated uncertainties were significantly higher than uncertainties estimated using a simple sensitivity perturbation technique for Halon-1301 presented in Chapter 4. These findings highlighted the need for consideration of uncertainty in model inputs and the use of a probabilistic age modelling approach for robust groundwater dating. Use of a single parameter set is dangerous and should be avoided.
- It is recommended that further studies trial the presented framework and its components for assessment of uncertainty in age estimations inferred from other tracers than those utilised in this study. The performance of all common tracers should also be interrogated across a range of different hydrologic and geologic settings. It needs to be assessed whether similar conclusions about the shape and uncertainty in tracer input and contribution of model input uncertainties towards uncertainty in the age distribution can be made. Further work is also needed to assess the transferability of individual framework components, in particular the evaluation criteria and tracer combination methods, and identification of meaningful objective functions. The author hopes that further study will take the presented analysis further and implement a multi-model approach to quantify structural uncertainty related to the use of simplified models for groundwater dating such as parametric LPMs.
- Most importantly it is hoped that it will become common practice to quantify and take account of uncertainties in groundwater age modelling to ultimately robustly manage groundwater resources.
- It was highlighted that communicating uncertainty in the age distribution is a difficult task, since the age distribution is already a distribution (conceptualizing the fractions of different aged waters in a water sample). Discussion of appropriate illustration methods and probability thresholds (e.g. the use of the 10th and 90th percentile) is needed. This is particularly relevant when obtaining ambiguous age estimates.

6. Assessment of commonly measured hydrochemistry as a groundwater age tracer

6.1 Introduction

Despite their high value for groundwater characterization and management, age tracer measurements are only available for a limited number of groundwater sites, because their determination is relatively expensive and requires special lab equipment and expertise. In addition, the applicability and reliability of each age tracer can also be limited in specific groundwater environments and each tracer's time/age application range is restricted, as already detailed in Chapter 2. This study is not only concerned with finding new groundwater age tracers to complement the existing age tracers, but also finding cost-effective, easily determinable tracers to increase the number of available robust groundwater age estimates.

As detailed in Chapter 2, commonly measured hydrochemistry parameters⁵⁸ appear ideal candidates for the use as age tracers. The reasons for this include their cheap and routine determination and spatial and temporal wide availability. Commonly measured hydrochemistry has only been used to infer the age distribution of groundwater with a mean age ranging from weeks to months relying on a well monitored seasonally variable input of hydrochemistry to groundwater. Over a wider age range, where the seasonally variable input has been dampened, commonly measured hydrochemistry has only been used as an age proxy. To estimate age of groundwater recharged weeks to hundreds of years ago using commonly measured hydrochemistry, age estimates determined with other techniques (e.g. age tracers) are needed to establish hydrochemistry-age relationships. However, these relationships do not normally take account of groundwater mixing and have only been used to estimate mean or apparent age.

This chapter assesses the potential use of commonly measured hydrochemistry parameters as complementary age tracers further. Specifically, in a New Zealand groundwater system it is assessed:

- 1) whether and to what extent hydrochemistry can be used to reduce uncertainty and ambiguity in age estimates inferred with established age tracers (here tritium), and
- 2) whether and to what extent commonly measured hydrochemistry can be used to extrapolate age inferred with established age tracers for sites of otherwise unknown age.
- 3) For either and both of the above, it is also assessed which hydrochemistry parameter(s) work best and under what conditions.

⁵⁸ In this thesis, the term commonly measured hydrochemistry includes the concentration of major and trace ions, but does not include the concentrations of isotopic compounds, such as tritium and carbon, or other compounds, such as SF₆, that have been applied as groundwater age tracers through employment of their known input to groundwater and/or well-studied decay.

The independent use of hydrochemistry is expected to result in relative rather than absolute age estimates, because hydrochemistry of recharge is either assumed to be constant (meaning it carries no time information) or it is unknown [person. communication Daniel Sinclair, 25/11/2015]. For comparison, when using established age tracers, age can be constrained with the aid of a time-dependent parameter (such as its time dependent input to groundwater and/or a tracer-decay term) fed into the Convolution Integral (Eqn. 2-1), turning the concentration into a time-varying function. Nevertheless, for completeness and in the hope that physical constraints might somewhat constrain age, this thesis considers whether and to what extent age information can be inferred when using commonly measured hydrochemistry independently. In particular, it considers whether the deviation of observed hydrochemistry from hydrochemistry-piston flow time (PT) relationships contains information on groundwater mixing.

In this study, the outcome of these assessments will be somewhat specific to the studied dataset and/or study area, but may highlight the potential of hydrochemistry elsewhere. In addition, this study's finding may provide information for further study to seek generalizable results e.g. by region/geoclimatic regime. Aside from assessing the performance of commonly measured hydrochemistry as an age tracer, it was also assessed whether weathering rates and hydrochemistry of recharge could be inferred with the aid of groundwater chemistry. Estimates of weathering (or other reaction) rates have been shown to indirectly aid groundwater dating, e.g. by correction of C14 activities to infer C14 ages [Fontes and Garnier, 1979], and assessment of anthropogenic effects, e.g. the effect of acid rain [e.g. Pacheco and van der Weijden, 1996] or carbon sequestration [e.g. Cressey, 2014] on the groundwater's chemistry. Estimates of hydrochemistry of recharge have been shown to aid identification of recharge source(s) and temporal changes of recharge chemistry which are important for groundwater management [e.g. MacDonald et al., 2003; Böhlke and Denver, 1995; Lindsey et al., 2003; Freeze and Cherry, 1979].

6.2 Methods

6.2.1 General method overview

To assess whether commonly measured hydrochemistry parameters can be used as a stand-alone or complementary groundwater age tracer, the methodology illustrated in Fig. 6-1 and further described below was used. Firstly, commonly measured hydrochemistry data were collected from sites for which hydrochemistry-PT relationships are likely to exist (e.g. from sites located in one aquifer).⁵⁹ The data

⁵⁹ The transfer of lab-determined hydrochemistry-PT relationships to infer age from groundwater chemistry may be limited. Large differences (in kinetics) have been observed for hydrochemistry-PT relationships found in lab and field environments which can be attributed to the different conditions prevailing in controlled lab environments and more complex field environments [e.g. White and Brantley, 2003]. It was expected that hydrochemistry-PT relationships need to be determined specifically for each groundwater system rather than

were then assessed for apparent internal consistency with regard to potential drivers and controlling factors and to identify (potential) sub-datasets within the dataset (referred to as the data analysis step in Fig. 6-1). This is necessary because there are various processes and conditions that may affect the chemical composition of groundwater, aside from residence time and groundwater mixing. This may hinder establishment of strong hydrochemistry-PT relationships and inference of age information from commonly measured hydrochemistry, even if the sites were all located in one aquifer. The following methods were used to identify differences/similarities in hydrochemistry and potential drivers and controlling factors in this study⁶⁰:

1. Nearest neighbour hierarchical cluster analysis (HCA) [e.g. Gueler et al., 2002] in Statgraphics® Centurion XVI [StatPoint Technologies Inc., 2009] was used on standardized median major hydrochemistry data to identify differences in hydrochemistry of the studied samples. Difference may indicate contamination and/or differences in recharge of the respective sample(s).
2. The Mann-Kendall test [Mann 1945, Kendall 1975] and Sen's slope estimator [Sen, 1968; Helsel and Hirsch 1992] using the GNS Science Spreadsheet for automatic processing of water quality data [Daughney, 2010] were used on historical hydrochemistry records to identify apparent trends in major hydrochemistry. Trends may indicate anthropogenic effects or non-steady state conditions at the affected groundwater sites. Trends with $p < 0.05$ and an increase/year of $> 10\%$ were considered as significant based on Daughney and Reeves (2006), who considered relative hydrochemistry trends in New Zealand of $< 10\%$ as too slow to be attributed to anthropogenic effects (or non-steady state), but may be attributed to natural processes.
3. The Kruskal-Wallis test [Kruskal and Wallis, 1952; Helsel and Hirsch 1992] using the GNS Science Spreadsheet for automatic processing of water quality data [Daughney, 2010] was used on historical hydrochemistry records to identify significant seasonality in major hydrochemistry, which may indicate a change in recharge (e.g. season dependent rain/river recharge) or non-steady state conditions at the affected groundwater sites. Significant seasonality (assuming two or four seasons⁶¹) was characterized by $p < 0.05$ and a seasonal difference $> 10\%$.
4. Principal Component Analysis (PCA) [e.g. Gueler et al., 2002] in Statgraphics® Centurion XVI [StatPoint Technologies Inc., 2009] was used on standardized median hydrochemistry data to identify correlating hydrochemistry parameters, which may indicate the same potential

using generalizable relationships, due to differing conditions such as climate, geology or microbial populations that influence groundwater chemistry. Further study is needed to assess if generalizable relationships exist.

⁶⁰ The applicability of each tool may depend on the dataset and may need to be assessed for each study individually. Some commonly used statistical and graphical tools that can be used for assessment of the consistency of hydrochemistry within a dataset are summarized in Appendix D1. The approach presented in this study, can be adjusted to implement other tools.

⁶¹ The number of seasons was chosen based on the climate in the study area. See Chapter 3 for details on the seasonal precipitation and temperature pattern in the study area.

processes/reactions. The dominant processes that were identified with PCA were further assessed in an inverse mass balance model to identify dominant reactions and confirm their consistency at all sites. Because PCA indicated mineral weathering was one of the major processes that had altered major hydrochemistry in this study, a mineral weathering inverse mass balance model was established in PHREEQC [Parkhurst and Appelo, 1999].

5. To assess if the assumptions made and outputs of the inverse mass balance model and PCA were consistent with actual weathering processes, the aquifer material composition was determined. Aquifer material analysis was carried out on carbon coated thin sections on a microprobe using electron backscatter imaging, EDS and WDS (electron dispersive spectroscopy and wavelength dispersive spectroscopy, respectively).

After identification of potential sub-datasets, hydrochemistry-PT relationships and age information were inferred for each sub-dataset. For that a probabilistic approach similar to that presented in Chapter 5 was used. The relationship in Eqn. 2-1 in Chapter 2 (i.e. the convolution integral) was adjusted for the use of hydrochemistry as an age tracer in Eqn. 6-1.

$$c_{obs}(t) = \int_0^{\infty} g(t') * c_{in}(t - t') * c_{alt}(t') dt', \quad \text{Eqn. 6-1}$$

where $c_{obs}(t')$ is the observed hydrochemistry in groundwater; $c_{in}(t' - t)$ refers to the hydrochemistry of recharge; t is the observation time; t' is the residence time; the decay term in Eqn. 2-1 was replaced with $c_{alt}(t')$ with refers to the time dependent alteration of hydrochemistry in groundwater, i.e. the hydrochemistry-PT relationship.

Figure 6-1: Schema of 2-stepped modelling approach

The approach involved the generation of hydrochemistry (e.g. Si concentrations) by modelling of groundwater mixing processes and random sampling of the model inputs from within their uncertainty using 'Classic' Monte Carlo sampling [Hammersley and Handscomb, 1964]. The model inputs were: a) the mixing model parameters for each site in the selected dataset, b) hydrochemistry of recharge and c) the time dependent hydrochemistry altering process, i.e. hydrochemistry-PT relationship. Simulated and observed hydrochemistry data were then compared by means of an objective function to identify

model inputs (i.e. hydrochemistry-PT relationships and mixing model parameters) that led to 'behavioural' (i.e. adequately fitting, representative) hydrochemistry data. Details on the model components used in this study are given in the following.⁶²

Power law relationships between hydrochemistry and PT were assumed (Eqn. 6-2), because such relationships between hydrochemistry and groundwater age (or age equivalent) have been commonly found in both lab [e.g. Luce et al., 1972; Paces, 1973; Taylor and Blum, 1995] and field studies [e.g. Downes, 1985; Katz et al., 1995; Rademacher et al., 2001 and 2005; Morgenstern et al., 2009 and 2010].

Hydrochemistry-PT relationship: $c_{alt}(t') = a * t'^b + c$, Eqn. 6-2

where c_{alt} is the time dependent hydrochemistry concentration; and the parameters a , b and c , which are in the following referred to as process parameters.

Groundwater mixing was conceptualized by simplified LPMs from which the age distribution was determined. The following three scenarios with regard to prior information on the LPM parameters were used (also summarized in Tab. 6-1):

- A) To assess whether the often ambiguous tracer-inferred LPM parameters can be further constrained with the aid of commonly measured hydrochemistry, tracer-inferred LPM parameters were used to establish hydrochemistry-PT relationships. It was assumed that hydrochemistry and age tracers underwent the same flow and mixing processes.⁶³
- B) To assess the performance of hydrochemistry as an age proxy when used independently, the LPM parameters at each site were not constrained *a priori*. To assess whether hydrochemistry could be used to confirm the mixing model, a selection of LPM types was used. To identify the most appropriate LPM type, the performance criteria suggested in Chapter 5 were used⁶⁴. To assess whether a robustly pre-determined age distribution at one site would allow for inferring of the age distribution at the remaining sites purely based on commonly measured hydrochemistry, the LPM parameters were not constrained *a priori* at all but one site for which tracer-derived age

⁶² As extensively discussed in Chapter 5, numerous choices for each component of the probabilistic modelling approach exist and their applicability may depend on the dataset and may need to be assessed for each study individually. The presented method can be adjusted to implement other modelling components if required.

⁶³ This implied that the same mixing model could be applied to describe mixing of tracers and hydrochemistry with groundwater. It was also assumed that the assessed hydrochemistry parameters and age tracers were behaving conservatively in groundwater (i.e. retardation is negligible). Retardation has been shown to be negligible for the tracers used in this study (see Chapter 2 for detail) and only hydrochemistry parameters with negligible retardation were assessed in this study (see section 6.2.2 for detail).

⁶⁴ The performance criteria for identification of the most appropriate LPM type presented in Chapter 5 were: 1) the lowest CV of the behavioural LPM parameters. 2) the lowest bias of behavioural simulated and observed hydrochemistry. 3) the lowest RMSE (of simulated and observed hydrochemistry. 4) the highest number of behavioural models. 5) agreement of the LPM with general aquifer geometry. 6) agreement of inferred MRTs with well location with regard to recharge area or other dated wells.

information were used. To assess what type of data (poorly constrained vs well constrained, relatively old vs young) would lead to the most constrained groundwater age distributions, a correlation matrix was established which included the change in 1) the uncertainty in the hydrochemistry-inferred LPM parameters, 2) the most likely tracer-derived LPM parameters, and 3) the uncertainty in the tracer-inferred LPM parameters. To confirm if the results inferred in C) were meaningful, the value of the tracer-derived LPM parameters for each data point was assessed by using tracer-inferred LPM parameters at all but one site for which unconstrained LPM parameters were used.

Table 6-1: Use or prior information on groundwater age to assess the potential of hydrochemistry as an age tracer/proxy

Site #	Scenario A	Scenario B	Scenario C			
			C I	C II	C ...	C N
1	Unconstrained LPM parameters	Tracer-inferred LPM parameters	Tracer-inferred LPM parameters	Unconstrained LPM parameters	Unconstrained LPM parameters	Unconstrained LPM parameters
2			Unconstrained LPM parameters	Tracer-inferred LPM parameters		
...				Unconstrained LPM parameters	Tracer-inferred LPM parameters	Tracer-inferred LPM parameters
n					Unconstrained LPM parameters	

To calibrate the LPM and hydrochemistry-PT relationships, the ‘goodness of fit’ or χ^2 statistic was used (see Eqn. 6-3 after Helsel and Hirsch (2002) and Appendix D3 for further detail). The χ^2 statistic presumes a normally distributed uncertainty in the observations which were confirmed for each assessed hydrochemistry parameter at each site detailed in Appendix D3. The χ^2 statistic allowed for reporting of a specific confidence (e.g. 99% confidence) that observations and simulations agree within a certain uncertainty threshold (e.g. three standard deviations).

$$\chi^2 \text{ objective function: } \text{normalized } \chi^2(\text{observed}) = \sum \frac{(\text{obs}-\text{sim})^2}{\varepsilon^2} / df, \quad \text{Eqn. 6-3}$$

where *obs* refers to the observed hydrochemistry (the median of historical data was used if no trends in hydrochemistry records have been identified); *sim* is the simulated hydrochemistry; *df* refers to the degrees of freedom, which are defined as the difference between the # of observations and the # of relations between observations (which is dependent on the independent variables of the model, e.g. *df* = 3 for the EPM); ε represents uncertainty in hydrochemistry observations which reflects the analytical uncertainty, repeatability and the variability of the historical hydrochemistry data. ε was estimated from the standard deviation (SD) of the historical hydrochemistry data or the measurement uncertainty whichever was larger. $\varepsilon > 5$ SD was considered as too large to allow adequate constraining of hydrochemistry-PT relationships and age information.

It was found that the ability to establish hydrochemistry-PT relationships and infer age information differed for each assessed hydrochemistry parameter. The performance appeared dependent on the

considered uncertainty threshold (ϵ in Eqn. 6-3, i.e. the number of considered SDs⁶⁵) as illustrated in Fig. 6-2. Based on this finding, a flexible uncertainty threshold was used in this study. The most appropriate uncertainty threshold was identified for each hydrochemistry parameter using performance criteria detailed in Appendix D3. The χ^2 objective function has never been applied in this way, i.e. with a flexible uncertainty threshold. The closest equivalent to the objective function used in this study is an objective function with a specified threshold such as demonstrated in Timbe et al. (2014), who used the Nash-Sutcliffe efficiency with a specified 'cut-off' above which models were considered as behavioural.

Figure 6-2: Examples of hydrochemistry-PT relationships established using the χ^2 objective function with an uncertainty threshold (ϵ in Eqn. 6-3) of 3-4 SD. Relationships could not be established when considering an uncertainty threshold <2 SD. In this study, linear, asymptotic and exponentially decreasing hydrochemistry -PT relationships are assumed (Eqn. 6-2).

Weathering rates were estimated from the slope of the inferred hydrochemistry-PT relationships and by linking the hydrochemistry parameters to specific mineral weathering reactions. This was carried out based on the general understanding of mineral weathering reactions and the findings obtained during inverse mass balance modelling. The estimated weathering rates were then compared to weathering rates deduced in other field studies. Hydrochemistry of recharge was estimated from the intercept of the inferred hydrochemistry-PT relationships (i.e. process parameter c in Eqn. 6-2) and compared to observed hydrochemical composition of recharge in the study area.

6.2.2 Case study

The Lower Hutt Groundwater Zone (LHGWZ), described in Chapter 3, appeared to be a suitable case study to assess whether information on the age distribution can be inferred with the aid of groundwater chemistry. Firstly, the LHGWZ was believed to have a relatively simple/homogenous aquifer structure which was thought to indicate relatively consistent, homogenous hydrochemistry-altering processes throughout the aquifer. Secondly, commonly measured hydrochemistry and age tracer data were available in 15 locations across the LHGWZ, illustrated in Fig. 3-2 and summarized in Tab. 3-1 in Chapter 3, with mean residence times (MRTs) ranging from days to approximately 75 years.

⁶⁵ The uncertainty in observed hydrochemistry is commonly reported as 1 or 2 SD and is site and hydrochemistry parameter specific and reflects the analytical uncertainty, repeatability and the variation of hydrochemistry over time.

This rich dataset allowed for comparison of hydrochemistry-inferred and tracer-inferred age information and assessment of the complementary use of hydrochemistry and established age tracers for groundwater dating. Thirdly, the groundwater was not too saline, i.e. it was under-saturated for most minerals, as shown in section 6.3. Saturation may prohibit identification of hydrochemistry-PT relationships due to an insignificant increase of dissolved species with residence time when reaching saturation.

Median ion concentrations, median pH and median conductivity were determined from historical major hydrochemistry data (a summary of available data is given in Tab. 3-1 in Chapter 3) using the GNS Science Spreadsheet for automatic processing of water quality data [Daughney, 2010]. Further detail on the data used can be found in Appendix D1, which also describes how outliers and missing or below detection limit data of the historical hydrochemistry data were treated in this study. To confirm the composition of the water bearing material and identify weathering processes, two gravel pebbles were analysed. One was sampled from the Hutt River the other was sampled from the lower aquifer layer (68m below surface).⁶⁶ The location of the gravel samples in regard to the locations of groundwater wells is illustrated in Fig. 3-1 in Chapter 3. Further information on the aquifer material analysis and the inverse mass balance model can be found in Appendix D2.

Promising correlations of the hydrochemistry parameters Na, Si, TDS, Fe, F, Cl, Mg, K and Ca with tritium-inferred mean residence time (MRT) have been found in the LHGWZ as presented in Appendix D1. Because these parameters have also been shown to correlate well with mean or apparent age in other studies [e.g. Downes, 1985; Taylor et al., 1992; Katz et al., 1995; Rademacher et al., 2001 and 2005; Morgenstern et al., 2009 and 2010], the focus of this study was to assess these parameters for the use as groundwater age tracers/proxies.⁶⁷ Additionally, PCA was used as a data reduction tool and the identified Principal Components were assessed for the use as age proxies/tracers. To simulate hydrochemistry data (i.e. the concentration of Na, Si, Fe, F, Cl, Mg, K and Ca, TDS and the PCs) in the

⁶⁶ Although, this approach involved analysis of 2 aquifer gravel pebbles only, the mineral analysis outcome of these two samples agreed well with the general greywacke composition reported by Rowe (1980) and weathering processes derived from inverse mass balance modelling shown in section 6.3.1. On the basis of these findings, it was assumed that the relative composition and relative weathering processes inferred from these 2 samples were relatively representative for the studied aquifer. For a more thorough assessment of weathering reactions, the author recommends the analysis of sand size particles as they are likely dominating water chemistry due to their relatively large surface areas, although the determination of bulk (unweathered) aquifer material chemistry is more difficult when using sand size particles than when using pebble sized material.

⁶⁷ Ratios and combinations of one or more of these parameters were also assessed for the use as age tracers/proxies (e.g. the sum/ratio of their concentrations was used or the objective function was adjusted for multiple parameters as presented in Chapter 5). However, since no behavioural relationships with PT (with $\varepsilon < 5$ SD) could be established, these were not further discussed in this study. Although not successful in this study, it is strongly believed that the combination of hydrochemistry parameters can aid more robust and certain groundwater dating in (other) groundwater environments. Further study is needed to look into this.

LHGWZ the process parameters a , b and c (Eqn. 6-2) were randomly sampled from a uniform distribution⁶⁸.

To assess whether groundwater age distributions can be inferred purely using hydrochemistry, unconstrained/floating age information were used. The mixing parameter was sampled from a uniform distribution from 0 to 1 (its natural boundaries, see example of the EPM in Eqn. 2-2, Chapter 2) and the MRT was drawn from a uniform distribution in the open interval⁶⁹. To conceptualize groundwater mixing, the exponential piston flow model (EPM), partial exponential model (PEM) and the dispersion model (DM) were used, which have been found most suitable for the LHGWZ based on the complexity of the groundwater system (see Appendix D4 for equations of these LPMs and Chapter 5 for a discussion on the pre-selection of LPM types). Monte Carlo (MC) simulation was carried out using 1 million runs. One million runs have been found appropriate, because no significant differences in model output were found when using more than 500,000 MC runs. Further detail on the MC simulation and selected model components can be found in Appendix D.

To examine the effect of using hydrochemistry on previously inferred age information, the tracer-inferred EPM parameter populations (i.e. the MRT and E/PM pairs, see Eqn. 2-2 in Chapter 2) obtained in Chapter 5, were randomly sampled. To assess whether and to what extent the tracer-inferred or unconstrained groundwater age information were (further) constrained with the aid of hydrochemistry, the relative change in uncertainty in the EPM parameters with the aid of hydrochemistry was determined using Eqn. 6-4.

$$\Delta\epsilon\%(age)_{hc} = \frac{\epsilon(age)_{hc} - \epsilon(age)_t}{\epsilon(age)_t} * 100, \quad \text{Eqn. 6-4}$$

where $\epsilon(age)$ denotes uncertainty in inferred LPM parameters determined as the absolute (the 0th and 100th percentile or full range) uncertainty which is equal to the difference between max and min of the inferred LPM parameters, e.g. $\epsilon(MRT)$ refers to uncertainty in the estimated MRT determined as $MRT_{max} - MRT_{min}$; $\epsilon(age)_t$ = uncertainty in the tracer-derived/unconstrained LPM parameters; $\epsilon(age)_{hc}$ refers to uncertainty in the hydrochemistry-inferred LPM parameters; $\Delta\epsilon\%$ denotes a

⁶⁸ To simulate TDS in this study, the process parameters a , b , c (Eqn. 6-2) were randomly sampled from a uniform distribution with the following boundaries: $a = -10$ to 100 , $b = 0$ to 2 , $c = 0$ - 100 . For simulation for the remaining hydrochemistry parameters (Na, Si, Fe, F, Cl, Mg, K and Ca) and PCs, the process parameters a , b and c (Eqn. 6-2) were randomly sampled from a uniform distribution with the following boundaries: $a = -10$ to 30 , $b = 0$ to 2 , $c = 0$ - 40 . These boundaries have been chosen based on the range of behavioural process parameters obtained during a pre-run with wider process parameter boundaries. These boundaries also respected natural boundaries. Parameter c was not further constrained, e.g. to hydrochemistry of recharge, to allow for one additional degree of freedom and inference of hydrochemistry of recharge with this approach.

⁶⁹ As a starting point the MRT was sampled from a uniform distribution from 0 to 100 years (based on the range of previously inferred MRTs using age tracers and the general application range of the tracers. However, insignificantly different (relative) results were obtained when drawing the MRT from a uniform distribution from 0 to 500 or 0 to 1000 years indicating that the MRT could only be constrained relatively when estimated purely based on hydrochemistry as presented in the section 6.3.2.

relative change in uncertainty e.g. a $\Delta\epsilon\%(MRT)_{hc}$ of 0 % or <0 % implies no change or a reduction of uncertainty in the tracer-derived/unconstrained MRT with the aid of hydrochemistry, respectively.

6.3 Results

6.3.1 Identification of similarities/differences in major hydrochemistry and sub-datasets

In the following the outcome of the data analysis are summarized and the identified sub-datasets are presented. Further detail can be found in Appendix D1.

No statistically significant trends in historical hydrochemistry data were found for any site. This may have indicated insignificant anthropogenic influence (on the assessed hydrochemistry) and/or may have confirmed steady state flow conditions at the studied sites. Significant seasonality in the assessed hydrochemistry parameters was only found for two shallow groundwater wells located in the unconfined part of the aquifer (Well 2 and 6). For > 70% of the assessed hydrochemistry parameters⁷⁰ insignificant seasonality was confirmed. These included the parameters that were assessed for the use as age tracers in this study. To meet the objectives of this study, it was concluded that on the basis of the trend and seasonality analysis it was acceptable to use the hydrochemistry data in the chosen study area. Based on the lack of seasonality and trends in the composition of the Hutt River (the main recharge source of the LHGWZ), it was assumed that the variability of hydrochemistry in recharge was insignificant compared to changes induced by mixing and/or residence in the subsurface⁷¹. With this assumption the convolution integral (Eqn. 6-1) became⁷²:

$$c_{obs}(t) = \int_0^{\infty} g(t') * c_{alt}(t') dt' \quad \text{Eqn. 6-5}$$

HCA carried out on a range of hydrochemistry parameters⁷³ indicated that hydrochemistry at two groundwater sites (Well 5 and 9) was significantly different from the hydrochemistry at any other site. Further assessment of their individual chemical composition indicated that water from Well 5 was reduced in SO₄ and water from Well 9 was significantly affected by ion exchange. Well 9 was the only well that tapped into the lower aquifer layer. The aquifer material in the lower (and older) aquifer layer was expected to be more weathered and to contain a larger amount of clay minerals than the aquifer material in the upper aquifer layer. This supports the inference of significant ion exchange in Well 9.

⁷⁰ The hydrochemistry parameters used for trend and seasonality analysis can be found in Tab. 3-2, Chapter 3.

⁷¹ For trend and seasonality analysis hydrochemistry records from 1992 to 2014 were used. To confirm a lack of trends and seasonality over the entire groundwater age range exclusively further study is needed. See Appendix D1 for a more detailed discussion on this.

⁷² If the variation of hydrochemistry of recharge (or the recharge itself) was significant, a representative recharge function that accounts for time variable hydrochemistry recharge may be used. Identification of a representative recharge function would require sufficient time series data of hydrochemistry of recharge for the time range covering the ages of the studied groundwater.

⁷³ using Total Alkalinity, NH₄-N, Br, Ca, Cl, Conductivity (field), DO, Fe, Mg, NO₃-N, K, SiO₂, Na, SO₄, pH (field) because these parameters were available and above the Limit of Detection (LOD) at all sites.

PCA carried out on a range of hydrochemistry parameters⁷³ indicated that the main processes that altered hydrochemistry in the LHGWZ were mineral weathering and to a smaller extent microbial process. The outcome of the inverse mass balance model confirmed the same minerals weathered at all sites. Mineral identification carried out by EDS point and area analysis confirmed the presence of mainly quartz, K-feldspar and albite, and smaller amounts of chlorite/biotite, anorthite, gibbsite/kaolinite and possibly some higher-order silicates, such as muscovite, which had been identified in greywacke rock in the aquifer region by Rowe (1980) (detailed in Appendix D2). EDS and WDS analysis also revealed that both gravel samples were depleted in the elements Ca, Na, K and Fe close to the rim, which indicated weathering. Ratios of EDS signals confirmed the rim was enriched in Si in relation to Al, Na and K and depleted in Al in relation to Si, Na and K, which might be linked to K-feldspar, anorthite and albite weathering, and quartz and kaolinite precipitation, as indicated during inverse mass balance modelling. These findings also supported that the aquifer material was fairly weathered, as indicated by inverse mass balance modelling, and agreed with reaction path modelling of silicate weathering in the general sense [e.g. Langmuir, 1997; White and Buss, 2013].

These findings provided valuable information on the difference/similarities in hydrochemistry that aided selection of datasets for inferring hydrochemistry-PT relationships. In summary, the data analysis showed that major processes that have altered the groundwater's chemistry in the LHGWZ were relatively consistent across the entire aquifer and effects of anthropogenic and/or non-steady state conditions on the assessed hydrochemistry parameters were insignificant. It was shown that hydrochemistry and its controlling factors may have been differentiated between individual aquifer layers and that hydrochemistry was significantly influenced by mineral weathering and microbial processes. Microbial processes generally differ in oxic and anoxic environments and may affect mineral weathering kinetics as indicated in e.g. Welch et al. (1999). Based on these findings the potential of groundwater chemistry for the use as an age tracer/proxy and for inference of hydrochemistry of recharge and weathering rates was assessed on the following dataset:

- a) Data from the entire aquifer (at all sites) were used.
- b) Data in anoxic and oxic waters were assessed separately⁷⁴.
- c) Data in different aquifer layers were assessed separately⁷⁵.

⁷⁴ Water that contained > 0.5 mg/L DO was considered as oxic (≤ 0.5 mg/L was considered as anoxic). The threshold of 0.5 mg/L was chosen based on recommendation of McMahon and Chapelle (2008) and Jurgens et al. (2009) and because the variation in ion concentrations ≤ 0.5 mg/L DO was significantly larger than > 0.5 mg/L (Appendix D1). This threshold split the dataset into half (Well 14 was left out due to unavailable DO data).

⁷⁵ Layer specific analysis separated Well 9 from the remaining sites, because Well 9 was the only well that tapped into the lower aquifer layer (the remaining wells tapped into the upper aquifer layer, see Chapter 3 for details on individual wells).

6.3.2 Inferring age information from hydrochemistry

In the following the derived hydrochemistry-PT relationships and inferred age information⁷⁶, weathering rates and hydrochemistry of recharge are presented for each sub-dataset. Detailed results can be found in Appendix D3 and D4 on inferred hydrochemistry-PT relationships, and estimated groundwater age, hydrochemistry of recharge and weathering rates, respectively.

6.3.2.1 Inferred hydrochemistry-RT relationships

Table 6-2 lists uncertainty thresholds that were considered in the Chi² objective function (Eqn.6-3) to establish hydrochemistry-PT relationships (fulfilling the criteria detailed in Appendix D3.4) for the studied hydrochemistry parameter and sub-dataset. The left and right hand side of Tab. 6-2 summarize results obtained with age information derived from tritium and unconstrained/floating age information, respectively. No significant difference in the model outcome with regard to the required uncertainty threshold and behavioural models was found when using the DM, EPM or the PEM. Results are therefore presented as average inferred when using all three LPM types in the following. Detailed LPM specific results can be found in Appendix D3.

Table 6-2: Required uncertainty threshold (i.e. number of SDs, Eqn. 6-3) to establish hydrochemistry-PT relationships (illustrated in Fig. 6-2) for each individual hydrochemistry parameter in the different groundwater environments using age information entirely gained from tritium (LEFT) and entirely unconstrained age information (RIGHT); * layer specific analysis (i.e. excluding Well 9 from the dataset); ** average when using DM, PEM and EPM

Uncertainty threshold (i.e. number of SDs) required to establish hydrochemistry-PT relationships										
	When using tritium-inferred age information					When using unconstrained age information**				
Parameter	Oxic sites	Anoxic sites	Anoxic sites layer*	All sites	All sites layer*	Oxic sites	Anoxic sites	Anoxic sites layer*	All sites	All sites layer*
Si	2	4.4	4.4	> 5	> 5	2.7	4	3.2	5	4.8
Na	2.5	3.8	3	4.3	3.9	2.2	4.2	3.4	4.6	4.1
Ca	3.1	2	1.7	3.2	2.9	3	3.6	2.4	4.4	3.1
K	3.7	> 5	> 5	> 5	> 5	3.5	> 5	> 5	> 5	> 5
Fe, Mg, F, PCs	> 5	> 5	> 5	> 5	> 5	> 5	> 5	> 5	> 5	> 5
Cl	> 5	2.5	2.7	> 5	> 5	> 5	2.6	2.8	> 5	> 5
TDS	5	2.6	2.7	4.5	4.7	4.2	2.1	2.0	4.2	4.2

As can be seen, behavioural models were only found for Na, Si, Ca, K and TDS (at an uncertainty threshold < 5 SD), which are ions whose relationship to PT should have been affected by mineral weathering as opposed to microbial processes. Relationships between PT and Na, Si and TDS were found for oxic and anoxic sites, but not when considering all sites or layer specific sites. This indicated potentially different prevailing reactions in oxic and anoxic waters. For K, which is involved in ion exchange processes of clay minerals, hydrochemistry-PT relationships were only found for oxic sites. Relationships between Cl and PT were only found for anoxic sites. No relationships were found for Fe,

⁷⁶ The term 'age information' or 'age estimate' referred to an age distribution as conceptualized by the LPM which is a function of the MRT and one or several mixing parameter.

Mg, F or the two Principal Components (PCs) inferred from PCA. Fe is redox sensitive and therefore also extremely sensitive to contact with air (e.g. the sampling procedure) and tends to form colloids with organic matter [Koenings and Hooper, 1976] which may have prevented strong relationships with PT. Mg is closely related to Ca and the HCO_3 cycle and therefore also sensitive to redox conditions and contact with air, F was at or close to the detection limit for eight out of 15 sites and the PCs are lumped parameters, which may have prevented the determination of relationships with PT.

The findings summarized in Tab. 6-2 also indicated that when oxic or anoxic sites were considered separately, a significantly lower uncertainty threshold was required to establish hydrochemistry-PT relationships for either case than when all (oxic and anoxic) sites were considered. Similarly, when only the sites that tap into the upper aquifer layer were assessed (i.e. excl. Well 9), a lower uncertainty threshold was needed to establish hydrochemistry-PT relationships than when Well 9 was included, except for Cl and TDS. Generally increasing concentrations of Si and Na and decreasing concentrations of Ca and Cl with increasing PT were obtained.⁷⁷ However, the inferred hydrochemistry-PT relationships differed in magnitude and sign for the various sub-datasets. These findings indicated that hydrochemistry-PT relationships and the ability to constrain age information may be significantly different for certain time dependent reactions in the lower and upper aquifer layer and oxic and anoxic waters. This was further assessed in section 6.3.2.2.

It was also found that the derived hydrochemistry-RT relationships were generally more ambiguous and more uncertain when using unconstrained age information than when using age information inferred from tritium (detailed in Appendix D3). This confirmed the initial prediction, that hydrochemistry-PT relationships (and consequently age information) can be better constrained when using constrained (age tracer-inferred) age formation than when not constraining the age information *a priori*. Similarly, on average similar results were obtained with any LPM type, which indicated that the hydrochemistry-PT relationships were not significantly affected by the choice of mixing model (at least the ones that were used in this study).

6.3.2.2 Hydrochemistry-inferred age information

In the following hydrochemistry-inferred age information are presented for the three scenarios: 1) using entirely tracer-derived LPM parameters, 2) using unconstrained/floating LPM parameters and 3) using tracer-inferred LPM parameters for one site and unconstrained LPM parameters for the

⁷⁷ A decreasing Cl concentration with residence time was somewhat opposed to the general understanding/belief that Cl concentrations increase with residence time due to the release of Cl during mineral weathering reactions. The decrease in Cl found in this study may have been a result of Cl complexation (primarily with heavy metals), but actual reasons were unknown.

remaining sites. The relative change in the LPM parameters with the aid of hydrochemistry is abbreviated as $\Delta\epsilon\%(age)_{hc}$ or as $\Delta\epsilon\%(MRT)_{hc}$ and $\Delta\epsilon\%(E/PM)_{hc}$ (defined in Eqn. 6-4).

When using tracer-inferred LPM parameters in combination with hydrochemistry

When using tracer-derived age information at all sites to assess whether hydrochemistry can support age information estimated from other techniques, it was found that uncertainty in the tracer-inferred LPM parameters was significantly reduced with the aid of hydrochemistry at the majority of sites (see Fig. 6-3). At four of eight affected sites (Well 3, 10, 11 and 13) ambiguous MRTs that had been previously inferred from tritium were resolved with the aid of hydrochemistry (examples are illustrated in Fig. 6-4). Overall, relationships between Na, Si, Ca and PT led to the highest reduction of uncertainty in the MRT. Uncertainties in the tracer-derived E/PMs could not be as significantly reduced as uncertainties in the tracer-inferred MRTs with the aid of hydrochemistry (illustrated in Fig. 6-3). The magnitude of the reduction in uncertainty in the tracer-derived EPM parameters appeared site, hydrochemistry parameter and groundwater environment dependent without any clear pattern and may have been a result of parameter and site specific hydrochemistry-PT relationships shown previously.

Figure 6-3: Average change in age information (uncertainty in MRT and E/PM) inferred from hydrochemistry compared to the age information derived from tritium, at each site and groundwater environment and as a function of uncertainty threshold (# of SDs); error bars indicate the max and min change in age information; * ambiguous MRTs were inferred from tritium; ^aquifer layer specific analysis excluded Well 9 from the dataset

With decreasing uncertainty threshold (i.e. stronger hydrochemistry-PT relationships) uncertainties in the tracer-inferred MRTs appeared increasingly reduced through the use of hydrochemistry. The most significantly reduced uncertainty in the tracer-derived MRT was found at or below an uncertainty threshold of 2 SD (Fig. 6-3). This negative trend, although not statistically significant, implied where hydrochemistry data was less prone to outliers, here uncertainty in hydrochemistry-PT relationships and ultimately the age distributions could be potentially better constrained. Identification and removal of outliers is complicated, since outliers may not necessarily indicate problems during analysis and/or sampling, but may indicate heterogeneities in the aquifer or different recharge of the prospective

wells. Poor or weak hydrochemistry-PT relationships may also arise from unaccounted interaction between hydrochemistry parameters, which may be resolved by coupling the LPM approach with detailed geochemical process models or the use of known relationships among the parameters. Further study is needed to assess ways to best identify outliers and assess if the removal of outliers and use of known relationships/coupling with geochemical models can lead to reduced uncertainties in the inferred age information.

Figure 6-4: MRT and E/PM inferred from hydrochemistry and tritium; to obtain these probability plots, the population of behavioural LPM parameters were binned into 10 bins. The effect of bin size on the distribution is discussed in Appendix D3.

When using hydrochemistry independently

When using unconstrained age information (i.e. floating LPM parameters) at all sites to assess whether age distributions can be inferred purely based on hydrochemistry, it was found that on average the LPM parameters could be significantly constrained with the aid of hydrochemistry as illustrated in Fig. 6-5. However, insignificantly different results were obtained when drawing the MRT from different uniform distribution (e.g. from 0 to 100 or 0 to 500 years) indicating that the MRT could only be constrained relatively when derived purely based on hydrochemistry. This confirmed the initial prediction that when used independently, hydrochemistry could only be used as an age proxy to distinguish relatively old from relatively young water. Although the mixing parameter could be significantly (absolutely) constrained with the aid of hydrochemistry for some sites (Fig. 6-6), no significant difference in performance of any of the three assessed LPM types (using the performance criteria presented in section 6.2.2) was found as detailed in Appendix D4. These findings indicated that

the type of LPM could not be confirmed purely based on hydrochemistry in this study. It is expected that it may be possible to identify the most suitable LPM type with the aid of hydrochemistry, if groundwater mixing was more complex than in this study, e.g. mixing of significantly different aged water occurred that had a more significant effect on the deviation of the observed hydrochemistry from hydrochemistry-PT relationships than observed in this study. However, further study is needed to confirm this.

Figure 6-5: Average change in uncertainty in the MRT and the mixing parameter (here E/PM when using the EPM) inferred from hydrochemistry compared to their input uncertainties (=100%), at each site and groundwater environment and as a function of uncertainty threshold (# of SDs); error bars indicate the max and min change in estimated age information; *aquifer layer specific analysis excluded Well 9 from the dataset

Similar to the preceding findings, it was found that the MRT could be better constrained than the mixing parameter and the magnitude of change was site, environment and hydrochemistry parameter dependent without any clear pattern as illustrated in Fig. 6-5. Relationships between PT and TDS worked best in constraining the LPM parameters. The ability to constrain the LPM parameters did not appear to be dependent on the MRT of the groundwater (sites are sorted with increasing tracer-inferred most likely MRT in Fig. 6-5). Generally the MRT could be increasingly more constrained at a lower uncertainty threshold (although the trend was again not significant) and the most constrained MRT was found at 2 SDs, as also found when using hydrochemistry to constrain tracer-inferred age information.

Relatively poor constraining of the MRT at some sites purely based on hydrochemistry may have been caused by highly uncertain or ambiguous hydrochemistry-PT relationships as presented and discussed previously. It was assessed if the consideration of exclusively increasing concentrations with increasing PT (i.e. positive process parameter 'a' in Eqn. 6-2 and unambiguous hydrochemistry-PT relationships) would constrain uncertainty in hydrochemistry-inferred age information more significantly. To limit the risk of over-constraining the hydrochemistry-PT relationships and ultimately age information, only the hydrochemistry parameters Si, Na and TDS were used for which positive relationships with PT

appeared reasonable⁷⁸. As illustrated in Fig. 6-6, uncertainty in the hydrochemistry-inferred MRT could be significantly more constrained than when using all behavioural (ambiguous) hydrochemistry-PT relationships. These findings highlighted that constraining hydrochemistry-PT relationships to positive (or negative) relationships can (potentially) further constrain age information estimated purely using hydrochemistry data.

Figure 6-6: Average constraining in the MRT and the E/PM inferred from hydrochemistry when only considering positive hydrochemistry-PT relationships at each site and groundwater environment; error bars indicate the max and min change in estimated age information, * aquifer layer specific analysis excluded Well 9 from the dataset

Figure 6-7: Probability plots of the hydrochemistry-inferred MRT when using positive hydrochemistry-PT relationships and the EPM (light grey) compared to the unconstrained MRT input (black), the x-axis is showing a floating MRT with x being any positive value; to obtain these probability plots, the population of behavioural LPM parameters was binned into 10 bins, the effect of bin size on the distribution is assessed in Appendix D4.

At all sites all considered hydrochemistry parameters gave indications towards relatively old/young groundwater which complied with the tritium-inferred MRTs (in a relative sense). One exception was

⁷⁸ As indicated during mass balance modelling and confirmed by aquifer material analysis, Si and Na have been released during weathering of the aquifer material which is likely contributing to an increase in TDS.

Well 7 for which non-conforming results were obtained: Si indicated the water was relatively old and TDS indicated that the water was relatively young as illustrated in Fig. 6-7. These findings highlighted the need for use of multiple hydrochemistry parameters (and/or tracers) to robustly infer groundwater age as opposed to using a single hydrochemistry parameter.

These promising findings using only commonly measured hydrochemistry to estimate groundwater age distribution relatively raised the question of whether and to what extent the MRT could be constrained absolutely if one of the sites had available age tracer data, i.e. a reference age was available. This is assessed in the following.

When using tracer-inferred LPM parameters at one site and unstrained LPM parameters at the remaining sites

Tracer-derived LPM parameters at one site and unconstrained/floating LPM parameters at the remaining sites were used to assess whether tracer-inferred age information could allow the use of hydrochemistry as an age tracer (as opposed to the use of hydrochemistry as an age proxy) at the remaining sites. This was carried out for oxic and anoxic sites and the parameters Na, Si, Ca, K, Cl and TDS.⁷⁹ It was found that with addition of age information at one site, the hydrochemistry-inferred LPM parameters could be significantly further constrained (up to several thousand %) as illustrated in Fig. 6-8. This suggested absolute constraining of hydrochemistry-derived MRTs is possible with the aid of pre-determined age information at one site, i.e. a reference age. However, it is noted that the system is essentially under-constrained (i.e. fitting of three parameters (a, b and c, Eqn. 6-2) with only one MRT and E/PM data, and boundaries on a, b and c detailed in section 6.2.1). It is likely that three to four age estimates is optimal to more fully constrain Equation 6-2. Similar to the preceding findings, the magnitude of change in uncertainty in the EPM parameters was site, environment and hydrochemistry parameter dependent without any clear pattern. To assess what type of age data led to the most significant change in purely hydrochemistry-inferred EPM parameters at the remaining sites, a correlation matrix was established in Tab. 6-3.

A positive and strong although statistically insignificant correlation (with an average R of 0.44) was observed between uncertainty in tracer-inferred MRT and the relative constraining of the MRT with the aid of hydrochemistry ($\Delta\epsilon\%(MRT)_{hc}$). The correlation between uncertainty in tracer-derived E/PM and $\Delta\epsilon\%(E/PM)_{hc}$ was also positive, and also statistically significant (R of 0.63). These findings

⁷⁹ Oxic and anoxic dataset were chosen for this analysis, since the strongest hydrochemistry-PT relationships and most constrained age information were found at oxic and anoxic sites (compared to the other groundwater environments) in this study. The parameters Na, Si, Ca, K, Cl and TDS (for which hydrochemistry-PT relationships could be established at oxic and/or anoxic sites) were used. The floating MRT range was set to 0-1000 years, much greater than the range of 0 to 100 years that had been inferred with the aid of tracers to ensure that the changes in uncertainty in the MRT could be identified.

indicated that the tracer-inferred age information (i.e. reference age) would need to be relatively well constrained to allow for (most constrained) absolute hydrochemistry-inferred age distributions at the remaining sites.

Figure 6-8: Average change in age information (uncertainty in MRT and E/PM) inferred from hydrochemistry when using unconstrained age information at all sites except one site, at which age derived from tritium was used; only considering oxic and anoxic sites; error bars indicate the max and min change in estimated age information

Table 6-3: Correlation matrix of tracer-inferred LPM parameters (i.e. uncertainty* in MRT and E/PM and most likely MRT and E/PM) and the constraining of the MRT and E/PM ($\epsilon\%(E/PM)$ and $\epsilon\%(MRT)$) with the aid of hydrochemistry when replacing unconstrained age data at one site with tritium-derived age data; data are given as average obtained for all hydrochemistry parameters and at oxic and anoxic sites; a correlation coefficient of $R > 0.55$ was considered as statistically significant at 80% confidence and with seven samples = sites for anoxic/oxic waters); *uncertainty in LPM parameters = the full range of the inferred LPM parameters (max-min)

Hydrochemistry-inferred	Tracer-inferred				Hydrochemistry-inferred	
	Uncertainty* in the MRT	Most likely MRT	Uncertainty* in the E/PM	Most likely E/PM	$\Delta\epsilon\%(MRT)_{hc}$	$\Delta\epsilon\%(E/PM)_{hc}$
$\Delta\epsilon\%(MRT)_{hc}$	0.44	0.03	0.22	-0.57	1	
$\Delta\epsilon\%(E/PM)_{hc}$	0.26	-0.60	0.63	0.29	-0.01	1

A negative, statistically significant correlation (average R of -0.60) between the most likely tracer-inferred MRT and $\Delta\epsilon\%(E/PM)_{hc}$ was found indicating that the older the tracer-derived age estimate, the better the E/PM could be constrained purely using hydrochemistry at the remaining sites. In addition, a significant correlation (R of -0.57) between $\Delta\epsilon\%(MRT)_{hc}$ and the most likely inferred E/PM) was found indicating the higher the E/PM (i.e. the closer groundwater mixing is to pure exponential flow or the furthest away it is from pure piston flow) of the tracer-inferred age estimate, the better the MRT could be constrained purely using hydrochemistry at the remaining sites. These trends were also supported by the findings obtained when using unconstrained age data at one site and tracer-inferred age information at the remaining sites (see Appendix D4 for details). Please note that statistical significance was very difficult to establish for some relationships, because only a relatively low number of samples were available for this analysis (i.e. seven data point when using the anoxic and oxic dataset). Further study is needed to assess whether similar correlations can be found on other (larger) datasets.

6.3.2.3 Inferred weathering rates and hydrochemistry of recharge

In the following it is demonstrated that the derived hydrochemistry-PT relationships can also provide information on weathering rates and hydrochemistry of recharge. Figure 6-9 illustrates the range of (max, min and most likely) hydrochemistry-PT relationships inferred for Si and Na at anoxic and oxic

sites when using tritium-inferred age information. To make the results comparable to reaction rates deduced in other (field) studies, the hydrochemistry observations were plotted as a function of piston flow time equivalent (the definition of this term is detailed in Appendix D3). The kinetics for Si/Na release which are linked to mineral weathering appeared to be steeper (faster) at anoxic sites than at oxic sites in this study. These findings contrasted the findings of Ullman et al. (1997) who had found that micro-organisms can accelerate silicate weathering in oxic water. Slower weathering rates at oxic sites compared to anoxic sites in this study may have been caused by a thicker biofilm on the aquifer material surface in oxic waters which may have hindered diffusion of solutes to and from the mineral surfaces in oxic waters more significantly than in anoxic waters. Due to the apparent difference in kinetics at anoxic and oxic waters in this study, weathering rates were inferred in oxic and anoxic waters separately as presented in the following.

Figure 6-9: Inferred range of hydrochemistry-PT relationships (max, min most probable (best)) for Si (LEFT) and Na (RIGHT) at anoxic sites (UPPER) and oxic sites (LOWER). Hydrochemistry observations are plotted as function of piston flow time equivalent (Appendix D3) obtained from best (most probable) MRT and E/PM. The y-error bars on the observations are the uncertainties displayed in two levels of 1 and 2 SD. The x-error bars on the observations illustrate uncertainty of piston flow time equivalent (max/min) as a result of uncertainty in age information inferred from environmental tracers

Since hydrochemistry-PT relationship (< 5 SDs) were only found for Si, Na, Ca, K, Cl and TDS and of these only Na and K could be linked to weathering of a single mineral⁸⁰, weathering rates for albite and

⁸⁰ TDS is a lumped parameter and could not be directly linked to one specific weathering reaction; Si could be related to weathering of several minerals such as albite, anorthite, K-feldspar and quartz weathering in this study; Ca could be linked to calcite weathering, but is also related to the HCO_3 cycle and sensitive to contact with air during sampling; Cl could not be directly linked to weathering of a specific mineral.

K-feldspar were inferred from Na-PT and K-PT relationships, respectively. To allow for comparison of the derived rates to rates published in Rademacher et al. (2001), Kim (2002), Burns et al. (2003) and Peters et al. (2013), who had studied the dissolution kinetics of fairly weathered rocks and consequently report linear weathering kinetics, weathering rates were inferred from the slope of the nearly linear part of the hydrochemistry-PT relationships (from ~20 years to ~100 years, Fig. 6-9).

Figure 6-9 shows an increase of 1 mg/L to 15 mg/L (derived from the min and max line, respectively) of Na in oxic water from 20 to 100 years, which equated to 0.5 to 8.2 $\mu\text{mol/L/year}$. Assuming that all Na had been produced by albite weathering as indicated by inverse mass balance modelling and aquifer material analysis, the rate of Na release was equivalent to 0.5 to 8.2 $\mu\text{mol/L/year}$ albite weathering. The upper value was close to the weathering rate of 6.3-7.2 $\mu\text{mol/L/year}$ obtained in Burns et al. (2003) for total Plagioclase weathering in a mostly oxic riparian Panola Granite Aquifer in Atlanta, Georgia, US. The lower value was close to weathering found for A-plagioclase by Rademacher et al. (2001) of 0.0116 $\mu\text{mol/L/year}$ established with CFC-11 ages in an oxic glacial till (andesite and granodiorite) aquifer. In anoxic waters, an albite weathering rate between 1.6 and 16.3 $\mu\text{mol/L/a}$ was inferred from the found Na-PT relationships. The lower rate compared well to Plagioclase weathering rates ranging from 1.4 to 2.3 $\mu\text{mol/L/year}$ in anoxic water of a sandy silicate aquifer in Wisconsin, US [Kim, 2002]. For K an increase of up to 0.14 $\mu\text{mol/L/year}$ (and decrease of 0.2 nmol/L) in oxic water was found which was equivalent to 0.14 $\mu\text{mol/L/year}$ K-feldspar weathering (no behavioural relationships were found in anoxic water). This estimated weathering rate was comparable to the K-feldspar weathering rates of 0.20-0.42 $\mu\text{mol/L/year}$ estimated in Burns et al. (2003) in a mostly oxic riparian Panola Granite Aquifer in Atlanta, Georgia, US.

Table 6-4 summarizes the estimated hydrochemistry of recharge⁸¹ (i.e. process parameter c in Eqn. 6-2) when using tritium-inferred or unconstrained/floating age information in the identified sub-datasets. Table 6-4 also contains data on recharge chemistry observed in Wellington rain and the Hutt River for comparison. On average, uncertainty in the inferred chemistry of recharge was relatively high, which may have indicated relatively poorly constrained hydrochemistry-PT relationships and/or poorly constrained intercepts of these relationships. Generally, uncertainty in hydrochemistry of recharge estimated purely using groundwater chemistry was smaller than the one estimated using tracer-inferred age information and groundwater chemistry. This may have indicated that hydrochemistry-PT relationships (in particular the intercept) were over-constrained with tracer-inferred age information. This suggested hydrochemistry of recharge may be better inferred purely using

⁸¹ assuming hydrochemistry of recharge has been constant over time. Absence of trends and seasonality in the Hutt River chemistry were found when assessing hydrochemistry records from 1993 to 2015. To confirm hydrochemistry of recharge was constant for the entire groundwater age range exclusively, further study is needed (e.g. through reconstruction of anthropogenic inputs to the aquifer).

groundwater chemistry. Both hydrochemistry of recharge estimates using A) purely groundwater chemistry and B) groundwater chemistry and age tracer data overlapped i.e. agreed partly for the majority of hydrochemistry parameters and sub-datasets. Generally, the hydrochemistry observed in rain was close to the lower end of the inferred recharge chemistry. The hydrochemistry observed in the Hutt River was close to the median of the derived recharge chemistry. One exception of this was the estimated Ca concentration inferred from tracer-derived age information and groundwater chemistry which did not agree with the observed median Ca concentration of recharge when considering anoxic sites and all sites (both including and excluding Well 9). This may have been caused by contact with air during sampling of anoxic groundwater as Ca concentrations are sensitive to this. Overall, these findings highlighted that hydrochemistry of recharge could be estimated using groundwater chemistry even if (tracer-inferred) age information was unavailable.

Table 6-4: Groundwater chemistry-inferred hydrochemistry of recharge (max, min of behavioural process parameter c) and observed chemistry of the Hutt River and Wellington rain [Harvey et al., 1988] (TDS was approximated from conductivity data reported by Harvey et al. (1988) and conductivity -TDS relationship found in the Hutt river (see Appendix D2 for details). Significant differences in inferred and observed hydrochemistry are highlighted in italics; * layer specific analysis excludes data from Well 9. ^ Ca corrected refers to the Ca concentration inferred using the inferred concentrations of Si, Na, Ca, K and/or TDS and relationships amongst them as further detailed subsequently.

Hydrochemistry parameter	Max, min of inferred hydrochemistry at recharge when using tritium-derived age information (UPPER value) and floating age information, positive relationships and the EPM (LOWER value) [mg/L]										Observed recharge chemistry [mg/L]		
	All sites		All sites layer*		Oxic sites		Anoxic sites		Anoxic sites layer*		Rain [Harvey et al., 1988]		Hutt River
	max	min	max	min	max	min	max	min	max	min	summer	winter	median (SD)
Si	- -	- -	5.4 16.5	1.3 0.10	15.0 15.63	0.01 0.06	18.5 18.71	0.29 0.32	40.0 17.92	0.47 0.00	n/a	n/a	9.1 (4.3)
Na	14.3 11.25	0.05 0.11	22.3 11.3	0.05 0.11	22.2 10.02	0.04 0.11	12.2 12.72	0.02 0.06	37.8 12.72	0.02 0.16	2.0	5.6	7.6 (1.5)
K	- -	- -	- -	- -	11.0 1.27	0.02 0.03	- -	- -	- -	- -	0.01	0.39	0.7 (0.1)
Cl	- -	- -	- -	- -	- -	- -	33.4 13.7	0.04 0.33	33.4 14.2	0.04 0.02	3.9	10.3	12.6 (1.1)
TDS	99.8 74.9	1.2 0.9	99.8 74.9	1.2 0.9	99.8 75.5	1.3 0.64	100.0 73.7	0.07 0.43	100.0 73.70	0.07 0.43	35.9	68.4	66.0 (5.0)
Ca	17.2 4.1	5.5 0.01	17.7 5.9	5.3 0.0	17.5 6.44	0.01 0.0	25.8 3.13	7.9 0.0	28.2 5.52	7.9 0.0	0.2	0.2	4.7 (4.7)
Ca corrected^	10.2 7.2	0 0	4.7 6.9	0 0	0 7.7	0 0	30.6 5.7	0 0	18.6 6.3	0 0			

To demonstrate the potential value of further (physical) constraints on groundwater dating with the aid of hydrochemistry, multiple regression analysis was carried out on median concentrations of K, Na, Si, Cl and/or TDS to explain Ca for each sub-dataset. The found relationships and the derived (max and min) concentrations of K, Na, Si, Cl and/or TDS were then used to infer 'corrected' (max and min) Ca concentrations. Further detail on the approach, including the found relationships is given in Appendix D4. The 'corrected' Ca concentrations are detailed in Tab. 6-4 showing that the previously non-

conforming Ca concentrations at all sites and anoxic sites now agreed with the Ca concentration found in Wellington rain and the Hutt River. With the aid of the established relationships among the hydrochemistry parameters, the lower limit of the estimated Ca concentrations was 'corrected' to not detectable (or 0 mg/L) and the upper limit of the estimated Ca concentration was significantly reduced (when using tracer-inferred age information with a reduction of 41, 73 and 34 % for all sites, all layer specific sites and anoxic layer specific sites, respectively). These findings indicated that the use of known relationships among the hydrochemistry parameters may aid to inferring of other hydrochemistry parameters for which hydrochemistry-PT relationships could not be established and may aid further constraining of hydrochemistry-PT relationships and ultimately age information. Further study is needed to explore this more comprehensively.

6.4 Chapter summary and conclusion

Commonly measured hydrochemistry data⁸² are spatially and temporally widely available and their determination is relatively easy and cost-effective. The use of commonly measured hydrochemistry parameters as age tracers may be particularly useful when the use of established groundwater dating techniques is limited or not possible. The potential of commonly measured hydrochemistry for groundwater characterization has been discussed for decades. For example, commonly measured hydrochemistry parameters have been applied as age proxies to distinguish relatively old from relatively young groundwater and to support age information inferred from established age tracers. The independent use of commonly measured hydrochemistry parameters has only been demonstrated for an age ranging from weeks to months relying on seasonal hydrochemistry of recharge. Over a wider age range, the seasonal hydrochemistry input is dampened and recharge is either assumed to be relatively constant over time or unknown, hence no time carrying model input is available. To estimate the mean age of groundwater recharged weeks to hundreds of years ago using commonly measured hydrochemistry, age estimates determined with other techniques (e.g. age tracers) are needed to establish hydrochemistry-age relationships.

This chapter further investigated whether and to what extent commonly measured hydrochemistry can be used to 1) reduce uncertainty and ambiguity in age estimates inferred with established age tracers, and 2) extrapolate age inferred with established age tracers in a New Zealand groundwater system. For completeness the independent use of commonly used hydrochemistry was also assessed, although it was expected that the independent use of hydrochemistry could not allow for inferring of absolute age estimates. In particular, it was assessed whether the deviation of observed

⁸² In this thesis, the term commonly measured hydrochemistry includes the concentration of major and trace ions, but does not include the concentrations of isotopic compounds, such as tritium and carbon, or compounds, such as SF₆, that have been applied as groundwater age tracers through employment of their known input to groundwater and/or well-studied decay.

hydrochemistry from hydrochemistry-piston flow time (PT) relationships contained information on groundwater mixing.

The main findings of this chapter include:

- The hydrochemistry parameters Si, Na, Ca and TDS were successfully used as a complementary age tracer to reduce uncertainty in age information (i.e. LPM parameters) inferred from established age tracers and to resolve ambiguous tracer-derived MRTs (at 50% of the affected sites).
- When established age tracer data was unavailable, the parameters Si, Na, Ca and TDS could act as groundwater age proxies to estimate the relative age of groundwater and to distinguish older from younger water. This finding is in line with previous studies, which have also demonstrated the use of hydrochemistry as an age proxy.
- As expected, inferring information on the age distribution purely based on hydrochemistry was difficult. The mixing parameter could not be significantly constrained only using hydrochemistry. No clear preference for any LPM type (the assessed ones were the EPM, DM and PEM) was found indicating that the mixing model could not be identified purely based on hydrochemistry in this study. It was speculated that it may be possible to identify the mixing model if groundwater underwent more complex mixing that had a more significant effect on hydrochemistry than found in this study, although further study is needed to confirm this supposition.
- The use of a reference age (i.e. tracer-inferred age information at one site) aided the use of commonly measured hydrochemistry as an 'independent' age tracer at the remaining sites⁸³. It was shown that the tracer-derived reference age needed to be relatively well constrained, robust in the older age range and highly mixed (i.e. furthest away from piston flow) to allow for significant constraining of purely hydrochemistry-inferred age information at the remaining sites. This finding highlighted the significant potential of using hydrochemistry to supplement age information inferred from established techniques. The complementary use of hydrochemistry and other groundwater dating techniques appears to be a much more cost-effective way to gain multiple age estimates than the sole use of expensive age dating techniques.
- For the majority of sites the hydrochemistry-inferred MRTs agreed well when derived from Si, Na, Ca and TDS. For a few sites significantly different age information were inferred using one of the parameter that using other parameters. This indicated that multiple hydrochemistry parameters may need to be applied complementarily to confirm age estimates. This is also often faced when using established, currently used age tracers for groundwater dating.

⁸³ It is noted that the system is essentially under-constrained (i.e. fitting of three parameters (a, b and c, Eqn. 6-2) with only one MRT and E/PM data, and boundaries on a, b and c detailed in section 6.2.1). Further study is needed to more comprehensively assess how many and what type of age information is needed to use hydrochemistry as an age tracer at the remaining sites.

- With the aid of groundwater chemistry, hydrochemistry of recharge and weathering rates could be inferred. These can indirectly aid groundwater dating and characterization.

It is hypothesized that other commonly measured hydrochemistry parameters that were not detected (or assessed) in this study may also show strong relationships with residence time and may contain (more) information on the groundwater age distribution, hydrochemistry of recharge and weathering rates. For example, trace metals, which were not determined in this study, have been shown useful as groundwater and surface water tracers [e.g. Johannesson et al., 1997; Gruau et al., 2004; Åström, 2001; Davranche et al., 2011]. Further study is needed to assess whether strong correlations between hydrochemistry and groundwater age can be found in other groundwater environments (e.g. of different lithology, organic content, oxidation state) and whether these can be used to infer groundwater age. Overall, it needs to be further assessed whether commonly measured hydrochemistry can be used as a (complementary) groundwater age tracer and under what conditions. It is hoped that the method presented in this study can serve as a basis or inspiration for this further work and that the following recommendations resulting from this study's findings may be of help:

- Since it was helpful to consider different groundwater environments separately in this study, it is recommended to assess the performance of hydrochemistry as an age proxy/tracer groundwater environment, site and hydrochemistry parameter specific⁸⁴.
- Although the χ^2 objective function worked well in this study, further study is needed to find and/or define meaningful objective functions. If one intended to use the χ^2 objective function on other datasets, it is recommended to assess the performance of each hydrochemistry parameter at a range of uncertainty levels (e.g. 1 to 5 SD) to identify the most optimal uncertainty threshold. If one wanted to use a fixed uncertainty threshold, an uncertainty between 2 and 3 SDs is recommended as this appeared most promising for constraining the age distribution and hydrochemistry-PT relationships in this study.

Overall, this chapter's findings suggest that commonly measured hydrochemistry parameters may be useful complementary age tracers. When used in combination with robust age estimates, commonly measured hydrochemistry parameters can be used to infer age at sites with otherwise unavailable age information. If used independently, commonly measured hydrochemistry can also be used as an age proxy to differentiate relatively old from relatively young groundwater which may already provide sufficient information for groundwater management in a relatively cost effective, fast, easy and widely

⁸⁴ This approach, however, reduces the dataset and may prevent successful inferring of hydrochemistry-PT relationship and age information and the use of the χ^2 objective function (or other objective function) in studies with fewer available data. Further study is needed to find objective functions that can be used on smaller datasets and to identify the most appropriate/maximum/minimum size of a dataset for successful use of hydrochemistry for groundwater dating.

applicable manner. Overall, this study's findings confirm the general perception that hydrochemistry is useful for a variety of purposes. It can be used e.g. for estimation of groundwater age, information on aquifer homogeneity or stratification, recharge area and source, and deserves further study.

7. Main findings, conclusions and future research recommendations

The focus of this study was on the characterization of groundwater resources with the aid of groundwater dating. Of specific interest was the dating of relatively young groundwater recharged months to about 100 years ago. This age range is particularly important to understand, because relatively shallow and young groundwater is often abstracted due to its easier accessibility than deeper/older groundwater but is most vulnerable to contamination. Since mixing of groundwater generally occurs during discharge or sampling, water samples often contain fractions of different aged water. Often the mean age is estimated, but this can be misleading in many contexts. The importance of determining and considering the groundwater's age distribution for robust groundwater management is increasingly recognized. The most widely applied technique to infer the groundwater's age distribution makes use of environmental tracers that have a well monitored input to groundwater and/or undergo well studied processes such as radioactive decay. In the many situations with only a limited number of available age tracer data, simplified lumped parameter models (LPMs) are used to conceptualize groundwater mixing. There are a number of limitations related to the use of age (LPM) modelling and groundwater age tracers. The aim of this study was to contribute to some of the most pressing needs arising from these limitations. These were:

- 1) The currently used age tracers face limitations regarding their application range and reliability. For example, some tracers are degradable in certain groundwater environments and/or have local sources that can lead to contamination. Both contamination and degradation can result in misleading age estimates. Other tracers have historic inputs to groundwater that can result in ambiguous age estimates. To overcome individual tracer limitations, multiple tracers are often applied complementarily. However, even with multiple tracers age estimates can remain highly uncertain and ambiguous. In addition, some tracers are fading out in the environment and will become of limited use in the future. To reduce uncertainty and ambiguity in age estimates and replace those tracers that are disappearing in the environment, new complementary groundwater age tracers are needed. Since the established age tracers are very costly, cheaper and easily determinable complementary age tracers are preferred.
- 2) Consideration of model uncertainties and quantification of uncertainty in the age estimates is currently not standard in age (LPM) modelling in contrast to other areas of hydrological modelling. As shown in an extensive literature review in this study, only very few studies have implemented probabilistic approaches to quantify uncertainty in age modelling. The majority of these studies used relatively complex approaches that are inapplicable for the many cases with limited available tracer data and have not considered uncertainty in the tracer's recharge estimate. Because only a few studies have demonstrated probabilistic age modelling approaches, the identification of most appropriate model components, such as the objective function, have not been assessed. Studies in

other areas of hydrological modelling, where probabilistic approaches are more commonly used, have shown the need for careful identification of such metrics. To allow for a more comprehensive quantification of uncertainty in age modelling including all sources of uncertainty with a limited number of available tracer data, appropriate age (LPM) modelling frameworks are needed.

To address these needs, this thesis set out to:

- 1) identify new age tracers applicable for dating of groundwater recharged months to ~ 100 years ago to complement the tracers currently used for this purpose, with widely available, easily and cheaply determinable tracers preferred
- 2) demonstrate and assess their performance as groundwater age tracers individually in relation to established age tracers, but also in combination with established tracers in a range of groundwater environments.
- 3) demonstrate an easily applicable and widely transferable age (LPM) modelling framework that allows for identification of relevant model components and uncertainties for quantification of uncertainty in age estimates.

Progress to address these objectives was made in this thesis as detailed in the preceding chapters. In the following, the main findings and conclusions of the preceding chapters are summarized and future research recommendations are drawn.

7.1 Halon-1301, a new complementary groundwater age tracer

A new groundwater age tracer, Halon-1301, was identified and demonstrated in Chapter 4. Strong and conclusive evidence was provided that Halon-1301's signal had been misidentified as caused by CFC-13 (a supposed groundwater age tracer). Both compounds have an extremely close retention time on the analytical setup that had been developed to determine CFC-13 in groundwater [Busenberg and Plummer, 2008]. This study's findings complemented a separate study by Rosiek et al. (2013), who had suggested Halon-1301 was the dominant compound near the retention time of CFC-13 in a calibrated air standard. This study provided more definitive proof of this, through use of custom made gases including and excluding both compounds as appropriate.

The behaviour of Halon-1301 in water and its performance as an age tracer had not been previously evaluated. As shown in Chapter 4, its properties, such as long lifetime in the atmosphere and monitored, steadily increasing atmospheric concentration over the last few decades, make it a promising new age tracer candidate. However, little was known regarding its behaviour in groundwater. To further assess its suitability as an age tracer, Halon-1301 was determined in various groundwater samples and ages were inferred from its concentration. Comparison of inferred Halon-1301 ages with ages previously derived from tritium, SF₆ and CFC-11 and CFC-12 (the most commonly

used age tracers for dating of relatively young groundwater) and simultaneous analysis for Halon-1301 and SF₆ in the same water samples allowed for detailed assessment of the potential of Halon-1301 as a groundwater age tracer. The main findings and recommendations for future research were:

- For 71% of the samples, inferred Halon-1301 ages agreed with ages derived from SF₆ and tritium (within ~1 SD). The remaining anoxic waters showed reduced concentrations of Halon-1301. The cause(s) of reduced Halon-1301 concentrations need to be evaluated further, but are likely due to degradation and/or retardation of Halon-1301 in the aquifer.
- No evidence for Halon-1301 contamination was found, which suggests absence of sources of Halon-1301 contamination in the study area. Further study is needed to assess if contamination of Halon-1301 is an issue in areas where Halon-1301 is still in use, e.g. at airports or in data centres.
- The previously estimated solubility of Halon-1301 did not comply with the solubility estimated in this study. Since solubility is a key requirement for the determination of groundwater age from its concentration, Halon-1301's solubility needs to be accurately and robustly determined to confirm the full potential of Halon-1301 as an age tracer⁸⁵.
- The presented analytical approach can be used to determine Halon-1301 together with SF₆ and potentially CFC-12 (if an appropriate standard gas is used) with negligible additional costs to the sole determination of SF₆. The determination of SF₆ and Halon-1301 in the same water sample allowed for identification of problems such as contact with air during sampling and degradation/contamination of one of the tracers.

Although this study provided compelling evidence that Halon-1301 is a useful new groundwater age tracer particularly when used in combination with other tracers, its performance and reliability as an age tracer need to be assessed in other groundwater environments. As a consequence of its characteristic atmospheric trend, Halon-1301 seems particularly useful for dating of groundwater recharged between 1980 and 2005. Before and after this time period a higher uncertainty in inferred age is obtained due to its relatively flat increase in the atmosphere before 1980 and after 2005, although this may be resolved with an improved determination of Halon-1301 in groundwater and/or the use of time series data of Halon-1301. Halon-1301 will become of limited use as an age tracer in the future, due to its soon decreasing and eventually declining atmospheric concentration (it is predicted to start decreasing between 2020 and 2030 and fade out after 2060/2070). However, until then, Halon-1301 can replace the CFCs, which are prone to degradation, contamination and have already decreasing atmospheric concentrations (since about 2000).

⁸⁵ Since the solubility of Halon-1301 is very low, robust determination of solubility requires special laboratory equipment.

It is recommended to use Halon-1301 together with other tracers to compensate individual tracer limitations (although in our study area it was significantly more reliable than CFC-12 and CFC-11, which are commonly used alone in the literature). Specifically, the simultaneous determination of Halon-1301 with SF₆ and CFC-12 using the cost-effective method presented in this study is recommended. This may allow for the determination of three complementary age tracers in the same water sample, which may enable more precise determination of groundwater age (and mixing), assessment of unsaturated zone processes, and increase robustness as the three tracers together allow identification and exclusion of problem samples (e.g. where contact with air during sampling or degradation of one or more of the age tracers has occurred). To further improve the age estimation with Halon-1301, the complementary use of Halon-1301, SF₆ and CFC-12 together with tritium, which is possibly the most reliable groundwater age tracer in the southern hemisphere⁸⁶, is recommended. All four age tracers have different properties and a different input history to groundwater. This allows for relatively robust determination of groundwater age (with a reduced ambiguity and uncertainty in inferred age) in a reasonably cost-effective manner.

7.2 Achievements in LPM age modelling

Progress to address the need for a more comprehensive probabilistic age modelling approach that is applicable for the many situations with limited data availability was made in Chapter 5. Age (LPM) modelling was placed into a relatively simple, transferable probabilistic framework. The framework was demonstrated on tritium, Halon-1301 and SF₆ data in New Zealand groundwater samples. Each individual uncertainty in model input and its relevance towards uncertainty in the age distribution was assessed in detail. Guidance was provided on how to identify the most suitable LPM type(s), most appropriate objective function and most appropriate and relevant model inputs and uncertainties by assessing their performance with quantitative criteria. Different combination techniques for age information gained from multiple tracers were also demonstrated. Application of the framework to Halon-1301 data allowed for further assessment of the performance of Halon-1301 with regard to uncertainty in age estimates compared to tritium and SF₆. In the following the key findings and future recommendations are summarized. These were:

- Although a custom objective function (with a similar performance as the Chi² statistic) best fulfilled the chosen criteria in this study, further study is needed to assess whether it is widely transferable to other tracer dataset and to identify other meaningful objective functions.

⁸⁶ Ambiguous age interpretations are often inferred from tritium in the northern hemisphere. This is less of a problem in the southern hemisphere due to the differing atmospheric tritium record in the northern and southern hemisphere.

- The age distribution was sensitive towards a variety of uncertainties (e.g. in the tracer's recharge estimate). It was shown that uncertainty in the inferred mean residence time (MRT) can be significant (of order of decades) and significantly larger than uncertainty estimated with an uncertainty perturbation technique. Probabilistic approaches are known to be more robust, but (simpler) perturbation techniques are generally used. It is suggested to assess the relevance and effect of all possible model uncertainties on uncertainty in the age distribution using probabilistic approaches and to consider uncertainty in the age distribution for robust groundwater dating.
- It was shown that the mixing model and mixing parameter could be better constrained with Halon-1301 than with SF₆ as a result of their characteristic atmospheric concentration over the last few decades⁸⁷ (confirming Chapter 4's prediction). Relatively large uncertainties in the Halon-1301-inferred MRTs were observed compared to the ones inferred from SF₆ or tritium. The relatively large uncertainty in the MRT inferred from a single Halon-1301 measurement was significantly reduced with the aid of (generated⁸⁸) time series Halon-1301 data, and also when not considering uncertainty in the solubility of Halon-1301 in groundwater. Based on these findings, it is recommended to robustly determine the solubility of Halon-1301⁸⁹ and/or use time series Halon-1301 data to reduce uncertainty in Halon-1301 age estimates. Further study is also needed to confirm the full potential of time series Halon-1301 data for groundwater dating using independent measurements of Halon-1301.
- Combination of age information inferred from multiple tracers (in this study SF₆, Halon-1301 and tritium) allowed for reduction of uncertainty and ambiguity in the estimated age distribution. In particular the use of Halon-1301 in combination with tritium and/or SF₆ significantly reduced uncertainty in the age distribution derived from tritium and/or SF₆. This suggests that Halon-1301 is a useful complementary age tracer to SF₆ and tritium. Their complementary use can reduce the tracers' individual limitations and can ultimately result in more robust age estimations, although it was also highlighted that the use of erroneous tracer data, e.g. reduced Halon-1301 concentrations, may reduce uncertainty in LPM parameters while actually biasing the model outcome
- When illustrating the uncertainty in the inferred age distribution to assess implications for groundwater management, it was found that there is a need to discuss appropriate thresholds, e.g. whether the use of the 10th/90th percentile age distribution is adequate.

Further study is needed to trial the presented framework and its components for quantification of uncertainty in age estimates using (other) tracers in different hydrologic and geologic settings and

⁸⁷ SF₆ has a nearly linear input and Halon-1301 has an S-shaped input over the last few decades.

⁸⁸ since only one actual Halon-1301 measurement was available at each site, generated data were used to assess the potential of time series data

⁸⁹ Other methods to reduce uncertainty in the determination of Halon-1301 were also presented in Appendix B.

assess if similar conclusions can be made. Assessment of the appropriateness of the employed objective function is needed, since studies in other areas of hydrological modelling have shown the need for careful identification of such metrics and only a few studies have used a probabilistic approach in groundwater age modelling. Employment of a multi-model approach would also be valuable to address structural uncertainty. It is relatively simple to adapt the framework to include a range of LPMs and it is also possible to include other structures such as distributed models. Other approaches that can be used to reduce structural uncertainty (apart from the use of a multi-model approach) includes the use of non-parametric LPMs, although a rich dataset is needed to implement this more complex approach. Further study is needed to confirm the cause(s) of reduced concentrations of Halon-1301 and estimate rates of decay/retardation to more comprehensively assess the uncertainty in Halon-1301-inferred age estimates. Most importantly, it is hoped that it will become common practice to quantify uncertainties in groundwater age modelling for robust groundwater dating.

7.3 Hydrochemistry, a (new) groundwater age proxy and complementary ‘age tracer’

In Chapter 6, the performance of commonly measured hydrochemistry⁹⁰ as a complementary age tracer (and as an age proxy and indicator for recharge sources and weathering processes) was demonstrated. The use of commonly measured hydrochemistry has significant advantages to the use of established age tracers. Reasons include their easy and cost-effective determination and spatially and temporally widely available data with major regional and national groundwater monitoring programmes. The potential of commonly measured hydrochemistry for characterization of groundwater has been known for decades, but its performance as an independent and complementary age tracer is not well established. The groundwater’s age distribution has only been successfully inferred purely based on commonly measured hydrochemistry for relatively young groundwater (with a mean age ranging from weeks to several months). Other studies have demonstrated the use of hydrochemistry as an age proxy or have established relationships between hydrochemistry and mean age derived with other techniques to estimate age at sites with unavailable age information. This study set out to further assess the potential use of commonly measured hydrochemistry as (complementary) age tracer. Of particular interest was to assess whether the deviation of hydrochemistry from relationships between hydrochemistry and piston flow time may contain information on groundwater mixing. The following key findings and future recommendations were drawn:

- Commonly measured hydrochemistry was useful as a complementary age tracer. It helped reduce uncertainty and ambiguity in the age distributions inferred from established age tracers.

⁹⁰ In this thesis, the term commonly measured hydrochemistry refers to relatively easily determinable and widely available parameters, e.g. the concentration of major ions, pH and conductivity. It does not include the concentration of isotopic compounds or other compounds that have been applied as groundwater age tracers.

- When used independently, commonly measured hydrochemistry could be used as an age proxy to distinguish relatively old from relatively young groundwater. This can help interpret ambiguous age estimates inferred with established age tracers.
- With the aid of a single reference age (derived from established age tracers), commonly measured hydrochemistry parameters could be used as 'independent' age tracers at sites with otherwise unavailable age information.
- Aside from directly inferring age information from hydrochemistry, it was also found that hydrochemistry of recharge and weathering rates could be estimated purely using groundwater chemistry. These can (indirectly) aid groundwater dating and characterization.

In summary, this study provided evidence that certain commonly measured hydrochemistry parameters can aid groundwater dating as a complementary age tracer, age proxy and as an indicator for recharge sources and weathering processes. This study's findings may be specific to the study area. It is therefore recommended to assess the potential of (other) hydrochemistry parameters in other groundwater environments for use as age proxies/tracers. Further study is also needed to assess whether it is possible that hydrochemistry can aid characterization of groundwater over a wider age range than possible with established age tracer, such as tritium, SF₆ and Halon-1301 and may be used to date surface water in addition to groundwater (as also achievable with tritium).

Combining the findings from the above, the following recommendations are drawn with regard to the use of the new groundwater age tracer Halon-1301 and age proxy hydrochemistry:

- If the resources and groundwater environment allow for it and robust age estimates are needed, it is recommended to simultaneously determine Halon-1301, SF₆ and CFC-12 in the same groundwater sample. In addition, tritium may be used to support the age information estimated with these tracers and to allow for study of unsaturated zone processes. If hydrochemistry data is also available, these may aid further reduction in ambiguity and uncertainties in the age estimates or (prospect of further study) hydrochemistry may be used as a standalone age tracer.
- If resources are limited and/or the determination of relative groundwater age is sufficient for the purpose of the study, it is recommended to use hydrochemistry as an age proxy.
- If resources are limited and robust age estimates are needed, it is recommended to infer age with a well-established technique at a small fraction of the studied sites and extrapolate age information purely based on commonly measured hydrochemistry at the remaining sites. This 'complementary' use of commonly measured hydrochemistry in combination with other groundwater dating techniques bears significant advantages, such as cost-effectiveness and availability, compared to the sole use of expensive groundwater dating techniques.

- Further study is needed to more comprehensively assess the potential of Halon-1301 and commonly measured hydrochemistry for the use as groundwater age tracers/proxies in other groundwater environments.

7.4 Final summary

This study's achievements allow for more robust⁹¹ determination of groundwater age and groundwater mixing and ultimately better management and protection of groundwater resources, particularly for groundwater recharged < 100 years ago. In summary the following was achieved:

- 1) A new groundwater age tracer, namely Halon-1301, was identified and its performance was demonstrated against established age tracers. Halon-1301 can be determined simultaneously with SF₆ (and CFC-12) in the same water sample at little additional cost to the sole determination of SF₆. This determination of three independent tracers can reduce limitations and ultimately result in more robust age estimates than can be achieved with a single age tracer.
- 2) Age (LPM) modelling was placed into a relatively simple, transferable probabilistic framework that allowed for a more comprehensive assessment of uncertainty in estimated age. Only few probabilistic age modelling studies have been demonstrated. This study was the first to demonstrate the identification of relevant model components, such as the objective function and tracer recharge estimate, and assessment of all relevant model uncertainties which are important for robust uncertainty assessment in age modelling.
- 3) It was demonstrated that commonly measured hydrochemistry can be used as a complementary age tracer (and as an age proxy and indicator for recharge sources and weathering processes). This has not been demonstrated to this extent. The use of commonly measured hydrochemistry as an age tracer may allow for cheaper and easier determination of robust groundwater age information and may be particularly useful in areas where the established age tracers/dating techniques are of limited use.

This study's findings and recommendations reinforce the growing recognition in recent groundwater age modelling studies, namely the use of multiple tracers and consideration of uncertainty for robust groundwater dating. In summary, it is hoped that the findings of this thesis encourage the groundwater dating community to:

- include quantification of uncertainty as a standard procedure for groundwater age modelling. This is expected to become even more important in the future, due to predicted increasing water demands which may require the utilization and characterization of more complex groundwater systems. For a more comprehensive determination of uncertainty, probabilistic approaches should be used as opposed to uncertainty perturbation approaches;

⁹¹ more reliable, more accurate, more informative in regard to ambiguity and uncertainty in the age distribution

- consider the use of multiple tracers to reduce the limitations faced with individual tracers. In particular, consider the use of Halon-1301 as an additional complementary groundwater age tracer and take advantage of its simultaneous determination together with SF₆ and CFC-12 for robust and cost-effective groundwater dating; and
- consider the use of commonly measured hydrochemistry as 1) a complementary 'age tracer' to reduce uncertainty in age inferred from established age tracers, and/or 2) a age proxy to distinguish relatively old from relatively young groundwater.

Further study is needed to further assess the performance of Halon-1301 and commonly measured hydrochemistry as age tracers/proxies in other groundwater environments and further improve the probabilistic age modelling approach. The author notes that other approaches can be used to (potentially better) quantify age information and its associated uncertainty. These include the use of non-parametric LPMs (these overcome structural uncertainty) and physics based groundwater models, although a rich dataset is generally needed to successfully implement these more complex approaches. This study made a first attempt in more comprehensively determining the uncertainty in age modelling using parametric LPMs.

Although this study identified and demonstrated new groundwater age tracers, all groundwater dating techniques including the new age tracers face limitations regarding their application range and reliability. Additional, complementary groundwater age tracers or dating techniques need to be identified to reduce these limitations and to replace the tracers that will become of limited use in the future. In view of a growing population and increasing pressure on groundwater resources, groundwater characterization methods, such as groundwater dating techniques, are predicted to remain important tools for groundwater management and protection and deserve further study.

References

- AGAGE (Advanced Global Atmospheric Gases Experiment) (2014) Atmospheric SF₆ data available online: http://agage.eas.gatech.edu/data_archive/agage/gc-ms-medusa/monthly/CGO-medusa.mon (last accessed 14/02/2014).
- AGAGE (Advanced Global Atmospheric Gases Experiment) (2014) Atmospheric SF₆ data available online: http://agage.eas.gatech.edu/data_archive/agage/gc-ms-medusa/monthly/CGO-medusa.mon (last accessed 14/02/2014).
- Ajami, N. K., Q. Duan, and S. Sorooshian (2007) An integrated hydrologic Bayesian multimodel combination framework: Confronting input, parameter, and model structural uncertainty in hydrologic prediction, *Water Resour. Res.* 43, W01403, doi:10.1029/2005WR004745.
- Ajami, N. K., Q. Duan, and S. Sorooshian (2007) An integrated hydrologic Bayesian multimodel combination framework: Confronting input, parameter, and model structural uncertainty in hydrologic prediction, *Water Resour. Res.* 43, W01403, doi:10.1029/2005WR004745.
- Allison, G.B.; Hughes, M.W. (1978) The use of environmental chloride and tritium to estimate total recharge to an unconfined aquifer, *Australian J. Soil Research* 16, 181–195.
- Allison, G.B.; Hughes, M.W. (1978) The use of environmental chloride and tritium to estimate total recharge to an unconfined aquifer, *Australian Journal of Soil Research* 16, 181–195.
- Amin, I.E. and M.E. Campana (1996) A general lumped parameter model for the interpretation of tracer data and transit time calculation in hydrologic systems. *J. Hydrol.* 179(1-4), 1-21.
- Amin, I.E. and M.E. Campana (1996) A general lumped parameter model for the interpretation of tracer data and transit time calculation in hydrologic systems. *Journal of Hydrology* 179(1-4), 1-21.
- Anderson, M.P. (2005) Heat as a ground water tracer. *Ground Water* 43, 951–968.
- Anderson, M.P. (2005) Heat as a ground water tracer. *Ground Water* 43, 951–968.
- Åström, M. (2001) Abundance and fractionation patterns of rare earth elements in streams affected by acid sulphate soils, *Chem. Geol.* 175, 249–258
- Åström, M. (2001) Abundance and fractionation patterns of rare earth elements in streams affected by acid sulphate soils, *Chem. Geol.* 175, 249–258
- Barletta, B., P. Nissenon, S. Meinardi, D. Dabdub, F. Sherwood Rowland, R. A. VanCuren, J. Pederson, G. S. Diskin, and D. R. Blake (2011) HFC-152a and HFC-134a emission estimates and characterization of CFCs, CFC replacements, and other halogenated solvents measured during the 2008 ARCTAS campaign (CARB phase) over the South Coast Air Basin of California, *Atmos. Chem. Phys.* 11(6), 2655-2669.
- Barletta, B., P. Nissenon, S. Meinardi, D. Dabdub, F. Sherwood Rowland, R. A. VanCuren, J. Pederson, G. S. Diskin, and D. R. Blake (2011) HFC-152a and HFC-134a emission estimates and characterization of CFCs, CFC

replacements, and other halogenated solvents measured during the 2008 ARCTAS campaign (CARB phase) over the South Coast Air Basin of California, *Atmos. Chem. Phys.* 11(6), 2655-2669.

Bartyzel, J. (2015) Wykorzystanie środowiskowych znaczników gazowych (SF₆, SF₅CF₃, CCl₂F₂, CBrF₃) do datowania wód podziemnych – zagadnienia metodyczne i zastosowania. PhD thesis. Wydziału Geologii, Geofizyki i Ochrony Środowiska AGH (University of Science and Technology in Kraków).

Bartyzel, J. (2015) Wykorzystanie środowiskowych znaczników gazowych (SF₆, SF₅CF₃, CCl₂F₂, CBrF₃) do datowania wód podziemnych – zagadnienia metodyczne i zastosowania. PhD thesis. Wydziału Geologii, Geofizyki i Ochrony Środowiska AGH (University of Science and Technology in Kraków).

Basu, N. B., P. Jindal, K. E. Schilling, C. F. Wolter, and E. S. Takle (2012), Evaluation of analytical and numerical approaches for the estimation of groundwater travel time distribution, *J. Hydrol.* 47(5), 65–73, doi:10.1016/j.jhydrol.2012.08.052.

Basu, N. B., P. Jindal, K. E. Schilling, C. F. Wolter, and E. S. Takle (2012), Evaluation of analytical and numerical approaches for the estimation of groundwater travel time distribution, *J. Hydrol.*, 475, 65–73, doi:10.1016/j.jhydrol.2012.08.052.

Bauer, S.; Fulda, C.; Schaefer, W. (2001) A multi-tracer study in a shallow aquifer using age dating tracers ³H, ⁸⁵Kr, CFC-113 and SF₆ - Indication for retarded transport of CFC-113, *Journal of Hydrology* 248, 14-34

Begg, J.; Brown, L.; Gyopari, M. and A. Jones (2005) A review of Wairarapa geology – with a groundwater bias. Institute of Geological and Nuclear Sciences Client Report 2005/159.

Begg, J.; Brown, L.; Gyopari, M. and A. Jones (2005) A review of Wairarapa geology – with a groundwater bias. Institute of Geological and Nuclear Sciences Client Report 2005/159.

Begg, J.G. and M.R. Johnston (compilers) (2000) Geology of the Wellington area. Institute of Geological and Nuclear Sciences 1:250000 geological map 10. I sheet + 64p. Lower Hutt, New Zealand: Institute of Geological and Nuclear Sciences Limited.

Begg, J.G. and M.R. Johnston (compilers) (2000) Geology of the Wellington area. Institute of Geological and Nuclear Sciences 1:250000 geological map 10. I sheet + 64p. Lower Hutt, New Zealand: Institute of Geological and Nuclear Sciences Limited.

Beven, K, and A. Binley (1992) The future of distributed models: Model calibration and uncertainty prediction. *Hydrological Processes* 6 (3), 279–298.

Beven, K, and A. Binley (1992) The future of distributed models: Model calibration and uncertainty prediction. *Hydrological Processes* 6 (3), 279–298.

Beven, K. and A. Binley (2014) GLUE: 20 years on, *Hydrol. Process.* 28; 5897–5918, doi: 10.1002/hyp.10082.

Beven, K. and A. Binley (2014) GLUE: 20 years on, *Hydrol. Process.* 28; 5897–5918, doi: 10.1002/hyp.10082.

Beven, K.J. and Binley, A.M., (1992) The future of distributed models: model calibration and uncertainty prediction, *Hydrological Processes*, 6, p.279–298.

Beven, K.J. and Binley, A.M., (1992) The future of distributed models: model calibration and uncertainty prediction, *Hydrological Processes*, 6, p.279–298.

Beyer, M.; Morgenstern, U. and B. Jackson (2014) Review of dating techniques for young groundwater (<100 years) in New Zealand. *J. Hydrol. New Zealand* 53(2), 93-111.

Beyer, M.; Morgenstern, U. and B. Jackson (2014) Review of dating techniques for young groundwater (<100 years) in New Zealand. *Journal of Hydrology* *J. Hydrol. New Zealand* 53(2), 93-111.

Böhlke, J.-K. (2002) Groundwater recharge and agricultural contamination. *Hydrogeology J.* 10(1), pp.153-179.

Böhlke, J.-K. (2002) [Groundwater recharge and agricultural contamination](#). *Hydrogeology J.*, Vol.10(1), pp.153-179.

Brennwald, M. S.; Hofer, M. and R. Kipfer (2013) [Simultaneous Analysis of Noble Gases, Sulfur Hexafluoride, and Other Dissolved Gases in Water](#). *Env. Science and Techn.* 47(15), 8599–8608.

Bullister, J. (NOAA/PMEL) (2011) Atmospheric CFC-11, CFC-12, CFC-113, CCl4 and SF6 Histories (1910-2011), Ocean CO2, carbon dioxide information analysis centre, online resource http://cdiac.ornl.gov/oceans/new_atmCFC.html, accessed 1/10/2012.

Bullister, J. (NOAA/PMEL) (2011) Atmospheric CFC-11, CFC-12, CFC-113, CCl4 and SF6 Histories (1910-2011), Ocean CO2, carbon dioxide information analysis centre, online resource http://cdiac.ornl.gov/oceans/new_atmCFC.html, accessed 1/10/2012.

Bullister, J.L. (2014) Atmospheric CFC-11, CFC-12, CFC-113, CCl4 and SF6 Histories. http://cdiac.ornl.gov/ftp/oceans/CFC_ATM_Hist/CFC_ATM_Hist_2014. Carbon Dioxide Information Analysis Center, Oak Ridge National Laboratory, US Department of Energy, Oak Ridge, Tennessee. Doi: 10.3334/CDIAC/otg.CFC_ATM_Hist_2014

Bullister, J.L. (2014) Atmospheric CFC-11, CFC-12, CFC-113, CCl4 and SF6 Histories. http://cdiac.ornl.gov/ftp/oceans/CFC_ATM_Hist/CFC_ATM_Hist_2014. Carbon Dioxide Information Analysis Center, Oak Ridge National Laboratory, US Department of Energy, Oak Ridge, Tennessee. Doi: 10.3334/CDIAC/otg.CFC_ATM_Hist_2014

Bullister, J.L. and B.S. Lee (1995) Chlorofluorocarbon-11 removal in anoxic marine waters.

Bullister, J.L. and B.S. Lee (1995) Chlorofluorocarbon-11 removal in anoxic marine waters.

Bullister, J.L.; Wisegarver, D.P. and F.A. Menzia (2002) The solubility of sulfur hexafluoride in water and seawater. *Deep-Sea Res. I* 49, 175-188.

Bullister, J.L.; Wisegarver, D.P. and F.A. Menzia (2002) The solubility of sulfur hexafluoride in water and sewerage. *Deep-Sea Res.* 49, 175-188.

Burkholder, J.B.; Wilson, R.R.; Gierczak, T.; Talukdar, R.; McKeen, S.A.; Orlando, J.L.; Vaghijianiand, G.L. and A.R. Ravishankara (1991) Atmospheric fate of CBrF₃, CBr₂F₂, and CBrF₂CBrF₂, *J. Geophys. Res.* 96, 5025–5043, doi:10.1029/90JD02735.

Burkholder, J.B.; Wilson, R.R.; Gierczak, T.; Talukdar, R.; McKeen, S.A.; Orlando, J.L.; Vaghijianiand, G.L. and A.R. Ravishankara (1991) Atmospheric fate of CBrF₃, CBr₂F₂, and CBrF₂CBrF₂, *J. Geophys. Res.* 96, 5025–5043, doi:10.1029/90JD02735.

Burns, D. A.; Plummer, L. N.; McDonnell, J. J.; Busenberg, E.; Casile, G. C.; Kendall, C.; Hooper, R. P.; Freer, J. E.; Peters, N. E.; Beven, K. P. and Schlosser (2003) The Geochemical Evolution of Riparian Ground Water in a Forested Piedmont Catchment. *Groundwater*, 41, 913–925. Doi: 10.1111/j.1745-6584.2003.tb02434.x

Burns, D. A.; Plummer, L. N.; McDonnell, J. J.; Busenberg, E.; Casile, G. C.; Kendall, C.; Hooper, R. P.; Freer, J. E.; Peters, N. E.; Beven, K. P. and Schlosser (2003) The Geochemical Evolution of Riparian Ground Water in a Forested Piedmont Catchment. *Groundwater*, 41, 913–925. Doi: 10.1111/j.1745-6584.2003.tb02434.x

Busenberg, E. and L.N. Plummer (2000) Dating young groundwater with sulphur hexafluoride: natural and anthropogenic sources of sulfur hexafluoride. *Water Resources Research* 36, 3011–3030.

Busenberg, E. and L.N. Plummer (2000) Dating young groundwater with sulphur hexafluoride: natural and anthropogenic sources of sulfur hexafluoride. *Water Resources Research* 36, 3011–3030.

Busenberg, E. and L.N. Plummer (2010) A rapid method for the measurement of sulfur hexafluoride (SF₆), trifluoromethyl sulfur pentafluoride (SF₅CF₃), and Halon 1211 (CF₂ClBr) in hydrologic tracer studies, *Geochem. Geophysics Geosystems* 11.

Busenberg, E. and L.N. Plummer (2010) A rapid method for the measurement of sulfur hexafluoride (SF₆), trifluoromethyl sulfur pentafluoride (SF₅CF₃), and Halon 1211 (CF₂ClBr) in hydrologic tracer studies, *Geochem. Geophysics Geosystems* 11.

Busenberg, E. and N. Plummer (2008) Dating groundwater with trifluoromethyl sulfurpentafluoride (SF₅CF₃), sulfurhexafluoride (SF₆), CF₃Cl (CFC-13) & CF₂Cl₂ (CFC-12), *Water Resources Research* 44.

Busenberg, E. and N. Plummer (2008) Dating groundwater with trifluoromethyl sulfurpentafluoride (SF₅CF₃), sulfurhexafluoride (SF₆), CF₃Cl (CFC-13) & CF₂Cl₂ (CFC-12), *Water Resources Research* 44.

Busenberg, E.; Weeks, E.P.; Plummer, L.N. and R.C. Bartholomay (1993) Age dating groundwater by use of chlorofluorocarbons (CCl₃F and CCl₂F₂) and distribution of chlorofluorocarbons in the unsaturated zone, Snake River aquifer, Idaho National Engineering Laboratory, Idaho. U.S. Geological Survey Water Resour. Invest. Rep. 93-4054, 896 1-47.

Busenberg, E.; Weeks, E.P.; Plummer, L.N. and R.C. Bartholomay (1993) Age dating groundwater by use of chlorofluorocarbons (CCl₃F and CCl₂F₂) and distribution of chlorofluorocarbons in the unsaturated zone, Snake

River aquifer, Idaho National Engineering Laboratory, Idaho. U.S. Geological Survey Water Resour. Invest. Rep. 93-4054, 896 1-47.

Butcher, G.M. (1993) Estimate of potential rainfall recharge to the Hutt Aquifer System. Wellington Regional Council, Technical Report WRC/CI-T-93/52.

Butcher, G.M. (1993) Estimate of potential rainfall recharge to the Hutt Aquifer System. Wellington Regional Council, Technical Report WRC/CI-T-93/52.

Butler, J. H.; Montzka, S. A.; Clarke, A. D.; Lobert, J. M. and J. W. Elkins (1998) Growth and distribution of halons in the atmosphere, *J. Geophys. Res.* 103(D1), 1503–1511, doi:10.1029/97JD02853.

Butler, J. H.; Montzka, S. A.; Clarke, A. D.; Lobert, J. M. and J. W. Elkins (1998) Growth and distribution of halons in the atmosphere, *J. Geophys. Res.* 103(D1), 1503–1511, doi:10.1029/97JD02853.

Butler, J.; Elkins, J.; Thompson, T.; Hall, B.; Swanson T. and V. Koropalov (1991) Oceanic consumption of CH₃CCl₃; implications for tropospheric OH, *J. Geophys. Res.* 96, 22347-22355.

Butler, J.; Elkins, J.; Thompson, T.; Hall, B.; Swanson T. and V. Koropalov (1991) Oceanic consumption of CH₃CCl₃; implications for tropospheric OH, *J. Geophys. Res.* 96, 22347-22355.

Butler, J.H.; Battle, M.; Bender, M.L.; Montzka, S.A.; Clarke, A.D.; Saltzman, E.S.; Sucher, C.M.; Severinghausand, J.P. and J.W. Elkins (1999) A record of atmospheric halocarbons during the twentieth century from polar firn air, *Nature* 399(6738), 749-755.

Butler, J.H.; Battle, M.; Bender, M.L.; Montzka, S.A.; Clarke, A.D.; Saltzman, E.S.; Sucher, C.M.; Severinghausand, J.P. and J.W. Elkins (1999) A record of atmospheric halocarbons during the twentieth century from polar firn air, *Nature* 399(6738), 749-755.

Castro, M.C. and P. Goblet (2005) Calculation of ground water ages – A comparative analysis. *Ground Water* 43(3), 368-380.

Castro, M.C. and P. Goblet (2005) Calculation of ground water ages – A comparative analysis. *Ground Water* 43(3), 368-380.

Caulcutt, R. and Boddy, R. (1983) *Statistics for Analytical Chemist*. Chapman and Hall, London.

Caulcutt, R. and Boddy, R. (1983) *Statistics for Analytical Chemist*. Chapman and Hall, London.

Chang, W. and C.S. Criddle (1995) BiotransformationofHCFC-22, HCFC-142b, HCFC-123, and HFC-134a by methanotrophic mixed culture MM1. *Biodegradation* 6, 1–9.

Chang, W. and C.S. Criddle (1995) BiotransformationofHCFC-22, HCFC-142b, HCFC-123, and HFC-134a by methanotrophic mixed culture MM1. *Biodegradation* 6, 1–9.

Cirpka, O. A.; Fienen, M. N.; Hofer, M.; Hoehn, E.; Tessarini, A.; Kipfer, R. and P. K. Kitanidis (2007) Analyzing Bank Filtration by Deconvoluting Time Series of Electric Conductivity. *Groundwater* 45, 318–328, doi: 10.1111/j.1745-6584.2006.00293.x.

- Cirpka, O. A.; Fienen, M. N.; Hofer, M.; Hoehn, E.; Tessarini, A.; Kipfer, R. and P. K. Kitanidis (2007) Analyzing Bank Filtration by Deconvoluting Time Series of Electric Conductivity. *Groundwater* 45, 318–328, doi: 10.1111/j.1745-6584.2006.00293.x.
- Clark, I.D., and P. Fritz (1997) *Environmental isotopes in hydrogeology*: New York, Lewis Publishers, 328 p.
- Clark, I.D., and P. Fritz (1997) *Environmental isotopes in hydrogeology*: New York, Lewis Publishers, 328 p.
- Cook, P. and A. Herczeg (2000) *Environmental Tracers in Subsurface Hydrology*, Kluwer Academic Press, Boston, USA, 479–510.
- Cook, P. and A. Herczeg (2000) *Environmental Tracers in Subsurface Hydrology*, Kluwer Academic Press, Boston, USA, 479–510.
- Cook, P. G.; Jolly, I. D.; Leaney, F. W.; Walker, G. R.; Allan, G. L.; Fifield, L. K. and G. B. Allison (1994) Unsaturated zone tritium and chlorine 36 profiles from southern Australia: Their use as tracers of soil water movement, *Water Resour. Res.* 30(6), 1709–1719, doi:10.1029/94WR00161.
- Cook, P. G.; Jolly, I. D.; Leaney, F. W.; Walker, G. R.; Allan, G. L.; Fifield, L. K. and G. B. Allison (1994) Unsaturated zone tritium and chlorine 36 profiles from southern Australia: Their use as tracers of soil water movement, *Water Resour. Res.* 30(6), 1709–1719, doi:10.1029/94WR00161.
- Cook, P.G. and D.K. Solomon (1995) Transport of atmospheric trace gases to the water table: Implications for groundwater with chlorofluorocarbons and dating krypton 85. *Water Resources Research* 31, doi:10.1029/94WR02232. issn: 0043-1397.
- Cook, P.G. and D.K. Solomon (1995) Transport of atmospheric trace gases to the water table: Implications for groundwater with chlorofluorocarbons and dating krypton 85. *Water Resources Research* 31, doi:10.1029/94WR02232. issn: 0043-1397.
- Cook, P.G.; Plummer, N.L.; Solomon, D.K.; Busenberg, E. and L.F. Han (2006) Effects and processes that can modify apparent CFC age. In: *Use of chlorofluorocarbons in hydrology*. IAEA, Vienna, 31-58.
- Cook, P.G.; Plummer, N.L.; Solomon, D.K.; Busenberg, E. and L.F. Han (2006) Effects and processes that can modify apparent CFC age. In: *Use of chlorofluorocarbons in hydrology*. IAEA, Vienna, 31-58.
- Cornaton, F. J. (2012) Transient water age distributions in environmental flow systems: The time-marching Laplace transform solution technique, *Water Resour. Res.* 48, W03524, doi:10.1029/2011WR010606.
- Cornaton, F. J. (2012) Transient water age distributions in environmental flow systems: The time-marching Laplace transform solution technique, *Water Resour. Res.* 48, W03524, doi:10.1029/2011WR010606.
- Cox, M.; Su, G. and J. Constantz (2007) Heat, chloride, and specific conductance as ground water tracers near streams, *Groundwater* 45, 187–195.
- Cox, M.; Su, G. and J. Constantz (2007) Heat, chloride, and specific conductance as ground water tracers near streams, *Groundwater* 45, 187–195.

Cressey, D. (2014) Rock's power to mop up carbon revisited - Experts push for more research into olivine weathering. *Nature* 505, 464, doi:10.1038/505464a

Cressey, D. (2014) Rock's power to mop up carbon revisited - Experts push for more research into olivine weathering. *Nature* 505, 464, doi:10.1038/505464a

Culbertson, J. A.; Prins, J. M.; Grimsrud, E. P.; Rasmussen, R. A.; Khalil, M. A. K. and M. J. Shearer (2004) Observed trends for CF₃-containing compounds in background air at Cape Meares, Oregon, Point Barrow, Alaska, and Palmer Station, Antarctica, *Chemosphere* 55, 1109– 1119.

Culbertson, J. A.; Prins, J. M.; Grimsrud, E. P.; Rasmussen, R. A.; Khalil, M. A. K. and M. J. Shearer (2004) Observed trends for CF₃-containing compounds in background air at Cape Meares, Oregon, Point Barrow, Alaska, and Palmer Station, Antarctica, *Chemosphere* 55, 1109– 1119.

Daughney, C. J. and R. R. Reeves (2005) Definition of hydrochemical facies in the New Zealand National Groundwater Monitoring Programme. *J. Hydrol. (New Zealand)* 44, 105-130.

Daughney, C. J. and R. R. Reeves (2005) Definition of hydrochemical facies in the New Zealand National Groundwater Monitoring Programme. *Journal of HydrologyJ. Hydrol. (New Zealand)* 44, 105-130.

Daughney, C.; Jones, J.; Baker, T.; Hanson, C.; Davidson, P.; Zemansky, G.; Reeves, R. and M. Thompson (2006) A National Protocol for State of the Environment Groundwater Sampling in New Zealand. ME report 781. Ministry for the Environment Wellington, New Zealand.

Daughney, C.; Jones, J.; Baker, T.; Hanson, C.; Davidson, P.; Zemansky, G.; Reeves, R. and M. Thompson (2006) A National Protocol for State of the Environment Groundwater Sampling in New Zealand. ME report 781. Ministry for the Environment Wellington, New Zealand.

Daughney, C.J. (2010) Spread sheet for automatic processing of water quality data: 2010 update, calculation of percentiles and tests for seasonality. Lower Hutt: GNS Science. GNS Science report 2010/42, 16 p.

Daughney, C.J. (2010) Spread sheet for automatic processing of water quality data: 2010 update, calculation of percentiles and tests for seasonality. Lower Hutt: GNS Science. GNS Science report 2010/42, 16 p.

Daughney, C.J. and R.R. Reeves (2006) Analysis of temporal trends in New Zealand's groundwater quality based on data from the National Groundwater Monitoring Programme, *J. Hydrol. (NZ)* 45 (1), 41-62.

Daughney, C.J. and R.R. Reeves (2006) Analysis of temporal trends in New Zealand's groundwater quality based on data from the National Groundwater Monitoring Programme, *Journal of HydrologyJ. Hydrol. (NZ)* 45 (1), 41-62.

Daughney, C.J.; Morgenstern, U.; van der Raaij, R. and R.R. Reeves (2010) Discriminant analysis for estimation of groundwater age from hydrochemistry and well construction: application to New Zealand aquifers, *Hydrogeol. J.* 18(2), 417-428.

Daughney, C.J.; Morgenstern, U.; van der Raaij, R. and R.R. Reeves (2010) Discriminant analysis for estimation of groundwater age from hydrochemistry and well construction: application to New Zealand aquifers, *Hydrogeology Journal* J. 18(2), 417-428.

Davranche, M.; Grybos, M.; Gruau, G.; Pédrot, M.; Dia, A. and R. Marsac (2011) Rare earth element patterns: a tool for identifying trace metal sources during wetland soil reduction. *Chem. Geol.* 284, 127–137.

Davranche, M.; Grybos, M.; Gruau, G.; Pédrot, M.; Dia, A. and R. Marsac (2011) Rare earth element patterns: a tool for identifying trace metal sources during wetland soil reduction. *Chem. Geol.* 284, 127–137.

Deeds, D.A. (2008) The Natural Geochemistry of Tetrafluoromethane and Sulfur Hexafluoride: Studies of Ancient Mojave Desert Groundwaters, North Pacific Seawaters and the Summit Emissions of Kilauea Volcano, Ph.D. Dissertation, University of California, San Diego, 2008; available as Scripps Institution of Oceanography Technical Report, UC, San Diego; Permalink: <http://www.escholarship.org/uc/item/1hp1f3bd>.

Deeds, D.A. (2008) The Natural Geochemistry of Tetrafluoromethane and Sulfur Hexafluoride: Studies of Ancient Mojave Desert Groundwaters, North Pacific Seawaters and the Summit Emissions of Kilauea Volcano, Ph.D. Dissertation, University of California, San Diego, 2008; available as Scripps Institution of Oceanography Technical Report, UC, San Diego; Permalink: <http://www.escholarship.org/uc/item/1hp1f3bd>.

Downes, C.J. (1985) Redox reactions, mineral equilibria, and ground water quality in New Zealand aquifers. In: *Ground Water Quality*. Ward, C.H.; Giger, W.; McCarty, P.L. (eds). Wiley & Sons: NY.

Downes, C.J. (1985) Redox reactions, mineral equilibria, and ground water quality in New Zealand aquifers. In: *Ground Water Quality*. Ward, C.H.; Giger, W.; McCarty, P.L. (eds). Wiley & Sons: NY.

Drever, J. I. (1988) *The Geochemistry of Natural Waters*, 388, Prentice-Hall, Englewood Cliffs, N.J..

Drever, J. I. (1988) *The Geochemistry of Natural Waters*, 388, Prentice-Hall, Englewood Cliffs, N.J..

Eberts, S. M., J. K. Böhlke, L. J. Kauffman, and B. C. Jurgens (2012), Comparison of particle-tracking and lumped-parameter age-distribution models for evaluating vulnerability of production wells to contamination, *Hydrogeol. J.*, 20, 263–282

Eberts, S. M., J. K. Böhlke, L. J. Kauffman, and B. C. Jurgens (2012), Comparison of particle-tracking and lumped-parameter age-distribution models for evaluating vulnerability of production wells to contamination, *Hydrogeol. J.*, 20, 263–282

Eberts, S.M.; Böhlke, J.K.; Kauffman, L.J. and B.C. Jurgens (2012) Comparison of particle-tracking and lumped-parameter age-distribution models for evaluating vulnerability of production wells to contamination. *Hydrogeol. J.* 20 (2) 263-282.

Eberts, S.M.; Böhlke, J.K.; Kauffman, L.J. and B.C. Jurgens (2012) Comparison of particle-tracking and lumped-parameter age-distribution models for evaluating vulnerability of production wells to contamination. *Hydrogeology Journal* J. 20 (2) 263-282.

Edmunds, W. M. and P. L. Smedley (2000), Residence time indicators in groundwater: The East Midlands Triassic sandstone aquifer, *Appl. Geochem.* 15, 737–752.

Edmunds, W. M. and P. L. Smedley (2000), Residence time indicators in groundwater: The East Midlands Triassic sandstone aquifer, *Appl. Geochem.* 15, 737–752.

Edmunds, W.M. and N.R.G. Walton (1980) A geochemical and isotopic approach to recharge evaluation in semi-arid zones, past and present, *Arid Zone Hydrology, Investigations with Isotope Techniques*, IAEA, Vienna, 47–68.

Edmunds, W.M. and N.R.G. Walton (1980) A geochemical and isotopic approach to recharge evaluation in semi-arid zones, past and present, *Arid Zone Hydrology, Investigations with Isotope Techniques*, IAEA, Vienna, 47–68.

Edmunds, W.M.; Shand, P.; Hart, P. and R.S. Ward (2003) The natural (baseline) quality of groundwater: a UK pilot study, *Science of The Total Environment* 310(1–3), 25-35.

Edmunds, W.M.; Shand, P.; Hart, P. and R.S. Ward (2003) The natural (baseline) quality of groundwater: a UK pilot study, *Science of The Total Environment* 310(1–3), 25-35.

Efstratiadis, A. and D. Koutsoyiannis (2010) One decade of multi-objective calibration approaches in hydrological modelling: a review, *Hydrological Sciences J.*, 55:1, 58-78.

Efstratiadis, A. and D. Koutsoyiannis (2010) One decade of multi-objective calibration approaches in hydrological modelling: a review, *Hydrological Sciences Journal*, 55:1, 58-78.

Ellison, S.L.R. and A. Williams (eds.) (2012) EURACHEM/CITAC Guide CG4. Quantifying Uncertainty in Analytical Measurement, 3rd Edition.

Ellison, S.L.R. and A. Williams (eds.) (2012) EURACHEM/CITAC Guide CG4. Quantifying Uncertainty in Analytical Measurement, 3rd Edition.

Emerson, S. and J. Hedges (2008) *Chemical Oceanography and the Marine Carbon Cycle*, Chapter 3 Thermodynamics background, Cambridge University Press, ISBN 978-0-521-83313-4.

Emerson, S. and J. Hedges (2008) *Chemical Oceanography and the Marine Carbon Cycle*, Chapter 3 Thermodynamics background, Cambridge University Press, ISBN 978-0-521-83313-4.

Engen, M. A.; Wagner, V. A.; Sears, L. J. and E. P. Grimsrud (1998) Detection of CF₃-containing compounds in background air by gas chromatography/high-resolution mass spectrometry, *J. Geophysical Research: Atmospheres*, 103(D19), 25287-25297.

Engen, M. A.; Wagner, V. A.; Sears, L. J. and E. P. Grimsrud (1998) Detection of CF₃-containing compounds in background air by gas chromatography/high-resolution mass spectrometry, *Journal J. of Geophysical Research: Atmospheres*, 103(D19), 25287-25297.

Engesgaard, P.; Jensen, K. H.; Molson, J.; Frind, E. O. and H. Olsen (1996) Large-Scale Dispersion in a Sandy Aquifer: Simulation of Subsurface Transport of Environmental Tritium, *Water Resour. Res.*, 32(11), 3253–3266, DOI: 10.1029/96WR02398.

- Engesgaard, P.; Jensen, K. H.; Molson, J.; Frind, E. O. and H. Olsen (1996) Large-Scale Dispersion in a Sandy Aquifer: Simulation of Subsurface Transport of Environmental Tritium, *Water Resour. Res.*, 32(11), 3253–3266, DOI: 10.1029/96WR02398.
- Fienen, M.N.; Luo, J. and P.K. Kitanidis (2006) A Bayesian geostatistical transfer function approach to tracer test analysis, *Water Resources Research* 42, W07426.
- Fienen, M.N.; Luo, J. and P.K. Kitanidis (2006) A Bayesian geostatistical transfer function approach to tracer test analysis, *Water Resources Research* 42, W07426.
- Fontes, J.C. and J.M. Garnier (1979) Determination of the Initial ^{14}C Activity of the Total Dissolved Carbon: A Review of the Existing Models and a New Approach. *Water Resources Research* 15(2), 399-410.
- Fontes, J.C. and J.M. Garnier (1979) Determination of the Initial ^{14}C Activity of the Total Dissolved Carbon: A Review of the Existing Models and a New Approach. *Water Resources Research* 15(2), 399-410.
- Fortuin, N.P.M. and A. Willemsen (2005) Exsolution of nitrogen and argon by methanogenesis in Dutch groundwater. *J. Hydrol.* 301. 1–13.
- Fortuin, N.P.M. and A. Willemsen (2005) Exsolution of nitrogen and argon by methanogenesis in Dutch groundwater. *Journal of Hydrology* *J. Hydrol.* 301. 1–13.
- Fraser, P. J.; Langenfelds, R.; Derek, N. and L. Porter (1991) Studies in air archiving techniques, 1, Long term stability of atmospheric trace gases in dry, natural air stored in high pressure, surface treated aluminium cylinders, Baseline, , 89S. Wilson, J. Gras, 16–29, *Bur. Meteorol. and CSIRO Atmos. Res.*, Melbourne, Victoria, Australia.
- Fraser, P. J.; Langenfelds, R.; Derek, N. and L. Porter (1991) Studies in air archiving techniques, 1, Long term stability of atmospheric trace gases in dry, natural air stored in high pressure, surface treated aluminium cylinders, Baseline, , 89S. Wilson, J. Gras, 16–29, *Bur. Meteorol. and CSIRO Atmos. Res.*, Melbourne, Victoria, Australia.
- Fraser, P.J.; Oram, D. E.; Reeves, C. E.; Penkett, S. A. and A. McCulloch (1999) Southern Hemispheric halon trends (1978-1998) and global halon emissions. *J. Geophysical Research* 104 (D13), 15.
- Fraser, P.J.; Oram, D. E.; Reeves, C. E.; Penkett, S. A. and A. McCulloch (1999) Southern Hemispheric halon trends (1978-1998) and global halon emissions. *Journal J. Of of Geophysical Research*, Vol. 104, No. D13, 15.
- Freeze R.A. and J.A. Cherry (1979) *Groundwater*. Prentice-Hall: New Jersey
- Freeze R.A. and J.A. Cherry (1979) *Groundwater*. Prentice-Hall: New Jersey
- Gelman, A. (2008) Objections to Bayesian statistics *Bayesian Analysis* 3 (3), 445-450.
- Gelman, A. (2008) Objections to Bayesian statistics *Bayesian Analysis* 3 (3), 445-450.
- Ginn, T. R.; Haeri, H.; Foglia, L. and A. Massoudieh (2009) Notes on groundwater age in forward and inverse modeling, *Transport in Porous Media* 79, 117-134.

- Ginn, T. R.; Haeri, H.; Foglia, L. and A. Massoudieh (2009) Notes on groundwater age in forward and inverse modeling, *Transport in Porous Media* 79, 117–134.
- Goody, D.; Darling, G.; Abesser, C.; Lapworth, D.J. (2006) Using chlorofluorocarbons (CFCs) and sulphur hexafluoride (SF₆) to characterise groundwater movement and residence time in a lowland Chalk catchment. *J. Hydrol.*, 330 (1-2). 44-52. 10.1016/j.jhydrol.2006.04.011
- Goody, D.; Darling, G.; Abesser, C.; Lapworth, D.J. (2006) Using chlorofluorocarbons (CFCs) and sulphur hexafluoride (SF₆) to characterise groundwater movement and residence time in a lowland Chalk catchment. *Journal of Hydrology*. *J. Hydrol.*, 330 (1-2). 44-52. 10.1016/j.jhydrol.2006.04.011
- Goode, D. J. (1996) Direct Simulation of Groundwater Age, *Water Resour. Res.* 32(2), 289–296, doi:10.1029/95WR03401.
- Goode, D. J. (1996) Direct Simulation of Groundwater Age, *Water Resour. Res.* 32(2), 289–296, doi:10.1029/95WR03401.
- Grant-Taylor, T.L. (1967) Groundwater in New Zealand. NZGS report 24, presented at “Water of Peace” conference, 1967, Washington.
- Grant-Taylor, T.L. (1967) Groundwater in New Zealand. NZGS report 24, presented at “Water of Peace” conference, 1967, Washington.
- Green, C. T.; Zhang, Y.; Jurgens, B. C.; Starn, J. J. and M. K. Landon (2014) Accuracy of travel time distribution (TTD) models as affected by TTD complexity, observation errors, and model and tracer selection, *Water Resour. Res.* 50, 6191–6213, doi:10.1002/2014WR015625.
- Green, C. T.; Zhang, Y.; Jurgens, B. C.; Starn, J. J. and M. K. Landon (2014) Accuracy of travel time distribution (TTD) models as affected by TTD complexity, observation errors, and model and tracer selection, *Water Resour. Res.* 50, 6191–6213, doi:10.1002/2014WR015625.
- Gruau, G.; Dia, A.; Olivié-Lauquet, G.; Davranche, M. and G. Pinay (2004) Controls on the distribution of rare earth elements in shallow groundwaters. *Water Res.* 38 (2004), 3576–3586.
- Gruau, G.; Dia, A.; Olivié-Lauquet, G.; Davranche, M. and G. Pinay (2004) Controls on the distribution of rare earth elements in shallow groundwaters. *Water Res.* 38 (2004), 3576–3586.
- Gueler, C., Thyne, G. D., and McCray, J. E. (2002) Evaluation of graphical and multivariate statistical methods for classification of water chemistry data, *Hydrogeol. J.* 10, 455–474.
- Gueler, C., Thyne, G. D., and McCray, J. E. (2002) Evaluation of graphical and multivariate statistical methods for classification of water chemistry data, *Hydrogeol. J.* 10, 455–474.
- Guest, P.G. (2012) *Numerical Methods of Curve Fitting*, Cambridge University Press, ISBN-13: 978-1107646957.
- Guest, P.G. (2012) *Numerical Methods of Curve Fitting*, Cambridge University Press, ISBN-13: 978-1107646957.

Gupta, H.V.; Kling, H.; Yilmaz, K.K. and G.F. Martinez (2009) Decomposition of the mean squared error and NSE performance criteria: Implications for improving hydrological modelling, *J. Hydrol.* 377(1-2), 80-91.

Gupta, H.V.; Kling, H.; Yilmaz, K.K. and G.F. Martinez (2009) Decomposition of the mean squared error and NSE performance criteria: Implications for improving hydrological modelling, *Journal of Hydrology**J. Hydrol.* 377(1-2), 80-91.

GWRC - Greater Wellington Regional Council (2014) Air, land and water in the Wellington region – state and trends. Regional Council Information Brochure - GW/EMI-G-12/152 June 2012.

GWRC - Greater Wellington Regional Council (2014) Air, land and water in the Wellington region – state and trends. Regional Council Information Brochure - GW/EMI-G-12/152 June 2012.

Gyopari, M. (2014) Lower Hutt Aquifer Model Revision (Ham3): Sustainable Management Of The Waiwhetu Aquifer, Earth in Mind Ltd. a Report Prepared For Greater Wellington Regional Council, June 2014.

Gyopari, M. (2014) Lower Hutt Aquifer Model Revision (Ham3): Sustainable Management Of The Waiwhetu Aquifer , Earth in Mind Ltd. a Report Prepared For Greater Wellington Regional Council, June 2014.

Hammersley, J. M. and D. C. Handscomb (1964) Monte Carlo Methods. Methuen & Co., London, And John Wiley & Sons, New York.

Hammersley, J. M. and D. C. Handscomb (1964) Monte Carlo Methods. Methuen & Co., London, And John Wiley & Sons, New York.

Harvey M.J. and T.S. Clarkson (1988) The Chemical Composition of Rain at an Inland and a Coastal New Zealand Site, *Clean Air* 22, 58-63.

Harvey M.J. and T.S. Clarkson (1988) The Chemical Composition of Rain at an Inland and a Coastal New Zealand Site, *Clean Air* 22, 58-63.

Heaton, T.H.E. and J.C. Vogel (1981) “Excess air” in groundwater. *J. Hydrol.* 50, 201-216.

Heaton, T.H.E. and J.C. Vogel (1981) “Excess air” in groundwater. *Journal of Hydrology**J. Hydrol.* 50, 201-216.

Helsel, D.R. and R.M. Hirsch (1992) *Statistical Methods in Water Resources*, Elsevier, 522 p.

Helsel, D.R. and R.M. Hirsch (1992) *Statistical Methods in Water Resources*, Elsevier, 522 p.

Helsel, D.R. and R.M. Hirsch (2002) *Statistical Methods in Water Resources Techniques of Water Resources Investigations*, Book 4, chapter A3. U.S. Geological Survey. 522 p.

Helsel, D.R. and R.M. Hirsch (2002) *Statistical Methods in Water Resources Techniques of Water Resources Investigations*, Book 4, chapter A3. U.S. Geological Survey. 522 p.

Hill, M.C. and C.R. Tiedeman (2007) *Effective groundwater model calibration: with analysis of data, sensitivities, predictions, and uncertainty*, 455 pp. Wiley-Interscience, Hoboken, NJ.

- Hill, M.C. and C.R. Tiedeman (2007) Effective groundwater model calibration: with analysis of data, sensitivities, predictions, and uncertainty, 455 pp. Wiley-Interscience, Hoboken, NJ.
- Hoeting, J.A.; Madigan, D.; Raftery, A.E. and C.T. Volinsky (1999) Bayesian model averaging: A tutorial. *Statistical Science* 14(4), 382–401.
- Hoeting, J.A.; Madigan, D.; Raftery, A.E. and C.T. Volinsky (1999) Bayesian model averaging: A tutorial. *Statistical Science* 14(4), 382–401.
- Hofmann, T.; Darsow, A.; Gröning, M.; Aggarwal, P. and A. Suckow (2010) Direct-push profiling of isotopic and hydrochemical vertical gradients. *J. Hydrol.* 385 (1-4), 84-94.
- Hofmann, T.; Darsow, A.; Gröning, M.; Aggarwal, P. and A. Suckow (2010) Direct-push profiling of isotopic and hydrochemical vertical gradients. *Journal of Hydrology*. *J. Hydrol.* 385 (1-4), 84-94.
- HTOC (2012) Halon Technical Options Committee: Progress Report following the Assessment Report of the Halon Technical Options Committee 2011, Ozone Secretariat, UNEP (United Nations Environment Program), Manchester, UK.
- HTOC (2012) Halon Technical Options Committee: Progress Report following the Assessment Report of the Halon Technical Options Committee 2011, Ozone Secretariat, UNEP (United Nations Environment Program), Manchester, UK.
- IAEA (2013) Isotope Methods for Dating Old Groundwater, International Atomic Energy Agency, Vienna, April, 2013. STI/PUB/1587, ISBN 978-92-0-137210-9, 357 p., available online: <http://www-pub.iaea.org/books/IAEABooks/8880/Isotope-Methods-for-Dating-Old-Groundwater>.
- IAEA (2013) Isotope Methods for Dating Old Groundwater, International Atomic Energy Agency, Vienna, April, 2013. STI/PUB/1587, ISBN 978-92-0-137210-9, 357 p., available online: <http://www-pub.iaea.org/books/IAEABooks/8880/Isotope-Methods-for-Dating-Old-Groundwater>.
- Johannesson, K.H.; Stetzenbach, K.J. and V.F. Hodge (1997) Rare earth elements as geochemical tracers of regional groundwater mixing *Geochim. Cosmochim. Acta* 61, 3605–3618
- Johannesson, K.H.; Stetzenbach, K.J. and V.F. Hodge (1997) Rare earth elements as geochemical tracers of regional groundwater mixing *Geochim. Cosmochim. Acta* 61, 3605–3618
- Jones, A. and M. Gyopari (2006) Regional conceptual and numerical modelling of the Wairarapa groundwater basin. Technical Report GW/EMI-T-06/293, Greater Wellington Regional Council.
- Jones, A. and M. Gyopari (2006) Regional conceptual and numerical modelling of the Wairarapa groundwater basin. Technical Report GW/EMI-T-06/293, Greater Wellington Regional Council.
- Jones, A. and T. Barker (2005) Groundwater monitoring technical report. Greater Wellington Regional Council, Publication No. GW/RINV-T-05/86, Wellington.

Jones, A. and T. Barker (2005) Groundwater monitoring technical report. Greater Wellington Regional Council, Publication No. GW/RINV-T-05/86, Wellington.

Jurgens, B.C.; Böhlke, J.K. and S.M. Eberts (2012) TracerLPM (Version 1): An Excel® workbook for interpreting groundwater age distributions from environmental tracer data: U.S. Geological Survey Techniques and Methods Report 4-F3, 60 p.

Jurgens, B.C.; Böhlke, J.K. and S.M. Eberts (2012) TracerLPM (Version 1): An Excel® workbook for interpreting groundwater age distributions from environmental tracer data: U.S. Geological Survey Techniques and Methods Report 4-F3, 60 p.

Jurgens, B.C.; McMahon, P.B.; Chapelle, F.H. and S.M. Eberts (2009) An Excel workbook for identifying redox processes in ground water: U.S. Geological Survey Open-File Report 2009–1004 8 p. Available at <http://pubs.usgs.gov/of/2009/1004>

Jurgens, B.C.; McMahon, P.B.; Chapelle, F.H. and S.M. Eberts (2009) An Excel workbook for identifying redox processes in ground water: U.S. Geological Survey Open-File Report 2009–1004 8 p. Available at <http://pubs.usgs.gov/of/2009/1004>

Kanta Rao, P.; K. S. Rama Rao and A. Hari Padmasri (2003) Transformation of chlorofluorocarbons through catalytic hydrodehalogenation. CATTECH 7(6), 218-225.

Kanta Rao, P.; K. S. Rama Rao and A. Hari Padmasri (2003) Transformation of chlorofluorocarbons through catalytic hydrodehalogenation. CATTECH 7(6), 218-225.

Katz, B. G.; Plummer, L. N.; Busenberg, E.; Revesz, K. M.; Jones, B. F. and T. M. Lee (1995) Chemical Evolution of Groundwater Near a Sinkhole Lake, Northern Florida: 2. Chemical Patterns, Mass Transfer Modeling, and Rates of Mass Transfer Reactions, Water Resour. Res. 31(6), 1565–1584, doi:10.1029/95WR00220.

Katz, B. G.; Plummer, L. N.; Busenberg, E.; Revesz, K. M.; Jones, B. F. and T. M. Lee (1995) Chemical Evolution of Groundwater Near a Sinkhole Lake, Northern Florida: 2. Chemical Patterns, Mass Transfer Modeling, and Rates of Mass Transfer Reactions, Water Resour. Res. 31(6), 1565–1584, doi:10.1029/95WR00220.

Kavetski, D.; Kuczera, G. and S. W. Franks (2006) Bayesian analysis of input uncertainty in hydrological modeling: 2. Application, Water Resour. Res. 42, W03408, doi:10.1029/2005WR004376.

Kavetski, D.; Kuczera, G. and S. W. Franks (2006) Bayesian analysis of input uncertainty in hydrological modeling: 2. Application, Water Resour. Res. 42, W03408, doi:10.1029/2005WR004376.

Kazemi, G.A.; Lehr, J.H. and P. Perrochet (2006) Groundwater Age. Hoboken, NJ: John Wiley & Sons. ,325 pp.

Kazemi, G.A.; Lehr, J.H. and P. Perrochet (2006) Groundwater Age. Hoboken, NJ: John Wiley & Sons. ,325 pp.

Keenan, L.; Thompson, M. and D. Mzila (2012) Freshwater allocation and availability in the Wellington region: State and trends. Greater Wellington Regional Council, Publication No. GW/EMI-T-12/141, Wellington.

- Keenan, L.; Thompson, M. and D. Mzila (2012) Freshwater allocation and availability in the Wellington region: State and trends. Greater Wellington Regional Council, Publication No. GW/EMI-T-12/141, Wellington.
- Kendall, C. and J. J. McDonnell (1998) Isotope tracers in catchment hydrology. Elsevier.
- Kendall, C. and J. J. McDonnell (1998) Isotope tracers in catchment hydrology. Elsevier.
- Kendall, M.G. (1975) Rank Correlation Methods, 4th edition, Charles Griffin, London.
- Kendall, M.G. (1975) Rank Correlation Methods, 4th edition, Charles Griffin, London.
- Kenoyer, G. J., and C. J. Bowser (1992) Groundwater chemical evolution in a sandy silicate aquifer in northern Wisconsin: 1. Patterns and rates of change, *Water Resour. Res.* 28(2), 579–589, doi:10.1029/91WR02302.
- Kenoyer, G. J., and C. J. Bowser (1992) Groundwater chemical evolution in a sandy silicate aquifer in northern Wisconsin: 1. Patterns and rates of change, *Water Resour. Res.* 28(2), 579–589, doi:10.1029/91WR02302.
- Kilchmann, S.; Waber, H.N.; Parriaux, A. and M. Bensimon (2004) Natural tracers in recent groundwaters from different Alpine aquifers, *Hydrogeol. J.* 12(6), 643 – 661.
- Kilchmann, S.; Waber, H.N.; Parriaux, A. and M. Bensimon (2004) Natural tracers in recent groundwaters from different Alpine aquifers, *Hydrogeology Journal J.* 12(6), 643 – 661.
- Kim, K. (2002) Plagioclase weathering in the groundwater system of a sandy, silicate aquifer. *Hydrol. Process.* 16, 1793–1806, doi: 10.1002/hyp.1081.
- Kim, K. (2002) Plagioclase weathering in the groundwater system of a sandy, silicate aquifer. *Hydrol. Process.* 16, 1793–1806, doi: 10.1002/hyp.1081.
- Knee, K. L.; Garcia-Solsona, E.; Garcia-Orellana, J.; Boehm, A. B. and A. Paytan (2011) Using radium isotopes to characterize water ages and coastal mixing rates: A sensitivity analysis *Limnol. Oceanogr. Methods* 9.
- Knee, K. L.; Garcia-Solsona, E.; Garcia-Orellana, J.; Boehm, A. B. and A. Paytan (2011) Using radium isotopes to characterize water ages and coastal mixing rates: A sensitivity analysis *Limnol. Oceanogr. Methods* 9.
- Knott, J. F. and J. C. Olimpio (2001) Estimation of Recharge Rates to the Sand and Gravel Aquifer Using Environmental Tritium, Nantucket Island, Massachusetts, U.S. Geological Survey, Water-Supply Paper 2297.
- Knott, J. F. and J. C. Olimpio (2001) Estimation of Recharge Rates to the Sand and Gravel Aquifer Using Environmental Tritium, Nantucket Island, Massachusetts, U.S. Geological Survey, Water-Supply Paper 2297.
- Koenings, J. P. and F. F. Hooper (1976) The influence of colloidal organic matter on iron and iron-phosphorus cycling in an acid bog lake, *Limnology and Oceanography*, 5, doi: 10.4319/lo.1976.21.5.0684.
- Koenings, J. P. and F. F. Hooper (1976) The influence of colloidal organic matter on iron and iron-phosphorus cycling in an acid bog lake, *Limnology and Oceanography*, 5, doi: 10.4319/lo.1976.21.5.0684.
- Koh, D.C.; Plummer, L.N.; Busenberg, E. and Y. Kim (2007) Evidence for terrigenous SF₆ in groundwater from basaltic aquifers, Jeju Island, Korea: Implications for groundwater dating. *J. Hydrol.* 339(1-2), 93-104.

- Koh, D.C.; Plummer, L.N.; Busenberg, E. and Y. Kim (2007) Evidence for terrigenous SF₆ in groundwater from basaltic aquifers, Jeju Island, Korea: Implications for groundwater dating. *J. of Hydrology* 339(1-2), 93-104.
- Kragten, J. (1994) Calculating standard deviations and confidence intervals with a universally applicable spreadsheet technique, *Analyst* 119, 2161-2166.
- Kragten, J. (1994) Calculating standard deviations and confidence intervals with a universally applicable spreadsheet technique, *Analyst* 119, 2161-2166.
- Krause, P.; Boyle, D. P. and F. Bäse (2005) Comparison of different efficiency criteria for hydrological model Assessment, *Advances in Geosciences* 5, 89–97.
- Krause, P.; Boyle, D. P. and F. Bäse (2005) Comparison of different efficiency criteria for hydrological model Assessment, *Advances in Geosciences* 5, 89–97.
- Kruskal W. and W.A. Wallis (1952) Use of ranks in one-criterion variance analysis. *J. Am. Stat. Ass.* 47 (260), 583–621, doi:10.1080/01621459.1952.10483441.
- Kruskal W. and W.A. Wallis (1952) Use of ranks in one-criterion variance analysis. *Journal J. of the American Am. Statistical Stat. Association* 47 (260), 583–621, doi:10.1080/01621459.1952.10483441.
- Lalbat, F.; Blavoux, B. and O. Banton (2007) Description of a simple hydrochemical indicator to estimate groundwater residence time in carbonate aquifers, *Geophys. Res. Lett.* 34, L19403, doi:10.1029/2007GL031390.
- Lalbat, F.; Blavoux, B. and O. Banton (2007) Description of a simple hydrochemical indicator to estimate groundwater residence time in carbonate aquifers, *Geophys. Res. Lett.* 34, L19403, doi:10.1029/2007GL031390.
- Landowne, R.A. and S.R. Lipsky (1962) Electron Capture Spectrometry, an Adjunct to Gas Chromatography Quantitative Study of Operating Parameters and the Qualitative and Quantitative Distinction between Compounds Containing the Same Heteroatom. *Anal. Chem.* 34, 726.
- Landowne, R.A. and S.R. Lipsky (1962) Electron Capture Spectrometry, an Adjunct to Gas Chromatography Quantitative Study of Operating Parameters and the Qualitative and Quantitative Distinction between Compounds Containing the Same Heteroatom. *Anal. Chem.* 34, 726.
- Langmuir, D. (1997) *Aqueous Environmental Geochemistry*. Prentice-Hall: New Jersey.
- Langmuir, D. (1997) *Aqueous Environmental Geochemistry*. Prentice-Hall: New Jersey.
- Lesage, S., Brown, S., Hosler, K.R., 1992. Degradation of chlorofluorocarbon-113 under anaerobic conditions. *Chemosphere* 24 (9), 1225–1243.
- Lesage, S., Brown, S., Hosler, K.R., 1992. Degradation of chlorofluorocarbon-113 under anaerobic conditions. *Chemosphere* 24 (9), 1225–1243.
- Lesage, S.; Jackson, R.E.; Priddle, M.W. and P.G. Riemann (1990) Occurrence and fate of organic solvent residues in anoxic groundwater at the Gloucester landfill, Canada. *Environmental Science and Technology* 24, 559-566.

- Lesage, S.; Jackson, R.E.; Priddle, M.W. and P.G. Riemann (1990) Occurrence and fate of organic solvent residues in anoxic groundwater at the Gloucester landfill, Canada. *Environmental Science and Technology* 24, 559-566.
- Liao, Z. and O. A. Cirpka (2011) Shape-free inference of hyporheic traveltime distributions from synthetic conservative and “smart” tracer tests in streams, *Water Resour. Res.* 47, W07510, doi:10.1029/2010WR009927
- Liao, Z. and O. A. Cirpka (2011) Shape-free inference of hyporheic traveltime distributions from synthetic conservative and “smart” tracer tests in streams, *Water Resour. Res.* 47, W07510, doi:10.1029/2010WR009927
- Liu, Y. and H. V. Gupta (2007) Uncertainty in hydrologic modeling: Toward an integrated data assimilation framework, *Water Resources Research* 43, W07401, doi:10.1029/2006WR005756.
- Liu, Y. and H. V. Gupta (2007) Uncertainty in hydrologic modeling: Toward an integrated data assimilation framework, *Water Resources Research* 43, W07401, doi:10.1029/2006WR005756.
- Lindsey, B.D., Phillips, S.W., Donnelly, C.A., Speiran, G.K., Plummer, L.N., Böhlke, J.K., Focazio, M.J., and Burton, W.C., 2003, Residence time and nitrate transport in ground water discharging to streams in the Chesapeake Bay Watershed: U.S. Geological Survey Water-Resources Investigations Report 03-4035, 202 p
- Lovley, D.R., Woodward, J.C., (1992) Consumption of freons CFC-11 and CFC-12 by anaerobic sediments and soils. *Environmental Science & Technology* 26 (5), 925–929.
- Lovley, D.R., Woodward, J.C., (1992) Consumption of freons CFC-11 and CFC-12 by anaerobic sediments and soils. *Environmental Science & Technology* 26 (5), 925–929.
- Luce, R.W.; Bartlett, R.W. and G.A. Parks (1972) Dissolution kinetics of magnesium silicates. *Geochim. Cosmochim. Acta* 36 (1972), 35–50
- Luce, R.W.; Bartlett, R.W. and G.A. Parks (1972) Dissolution kinetics of magnesium silicates. *Geochim. Cosmochim. Acta* 36 (1972), 35–50
- MacDonald, A. ; Darling, W. ; Ball, D. ; Oster, H. (2003) Identifying trends in groundwater quality using residence time indicators: an example from the Permian aquifer of Dumfries, Scotland. *Hydrogeol. J.* 11(4), pp.504-517
- MacDonald, A. ; Darling, W. ; Ball, D. ; Oster, H. (2003) [Identifying trends in groundwater quality using residence time indicators: an example from the Permian aquifer of Dumfries, Scotland](#). *Hydrogeology Journal*, Vol.11(4), pp.504-517
- Maiss, M. and C.A.M. Brenninkmeijer (1998) Atmospheric SF₆: Trends, sources and prospects. *Environmental Science & Technology*. 32, 3077-3086.
- Maiss, M. and C.A.M. Brenninkmeijer (1998) Atmospheric SF₆: Trends, sources and prospects. *Environmental Science & Technology*. 32, 3077-3086.
- Małoszewski, P. and A. Zuber (1982) Determining the turnover time of groundwater systems with the aid of environmental tracers. *J. Hydrol.* 5, 207–231.

- Małoszewski, P. and A. Zuber (1982) Determining the turnover time of groundwater systems with the aid of environmental tracers. *Journal of Hydrology* J. Hydrol. 5, 207–231.
- Maloszewski, P. and A. Zuber (1996) Lumped parameter models for the interpretation of environmental tracer data, chap. 2 in International Atomic Energy Agency, ed., *Manual on mathematical models in isotope hydrogeology*, TECDOC-910: Vienna, Austria, International Atomic Energy Agency Publishing Section, p. 9–58.
- Maloszewski, P. and A. Zuber (1996) Lumped parameter models for the interpretation of environmental tracer data, chap. 2 in International Atomic Energy Agency, ed., *Manual on mathematical models in isotope hydrogeology*, TECDOC-910: Vienna, Austria, International Atomic Energy Agency Publishing Section, p. 9–58.
- Mann, H.B. (1945) Non-parametric tests against trend, *Econometrica* 13, 163-171.
- Mann, H.B. (1945) Non-parametric tests against trend, *Econometrica* 13, 163-171.
- Massoudieh, A. (2013) Inference of long-term groundwater flow transience using environmental tracers: A theoretical approach, *Water Resour. Res.* 49, 8039–8052, doi:10.1002/2013WR014548.
- Massoudieh, A. (2013) Inference of long-term groundwater flow transience using environmental tracers: A theoretical approach, *Water Resour. Res.* 49, 8039–8052, doi:10.1002/2013WR014548.
- Massoudieh, A.; Leray, S. and J.-R. de Dreuzy (2014b) Assessment of the value of groundwater age time-series for characterizing complex steady-state flow systems using a Bayesian approach, *Applied Geochemistry* 50, 240–251, doi:10.1016/j.apgeochem.2013.10.006
- Massoudieh, A.; Leray, S. and J.-R. de Dreuzy (2014b) Assessment of the value of groundwater age time-series for characterizing complex steady-state flow systems using a Bayesian approach, *Applied Geochemistry* 50, 240–251, doi:10.1016/j.apgeochem.2013.10.006
- Massoudieh, A.; Sharifi, S. and D. K. Solomon (2012) Bayesian evaluation of groundwater age distribution using radioactive tracers and anthropogenic chemicals, *Water. Resour. Res.* 48, W09529, doi:10.1029/2012WR011815.
- Massoudieh, A.; Sharifi, S. and D. K. Solomon (2012) Bayesian evaluation of groundwater age distribution using radioactive tracers and anthropogenic chemicals, *Water. Resour. Res.* 48, W09529, doi:10.1029/2012WR011815.
- Massoudieh, A.; Visser, A.; Sharifi, S. and H.P. Broers (2014a) A Bayesian modeling approach for estimation of a shape-free groundwater age distribution using multiple tracers, *Applied Geochemistry* 50, 252-264.
- Massoudieh, A.; Visser, A.; Sharifi, S. and H.P. Broers (2014a) A Bayesian modeling approach for estimation of a shape-free groundwater age distribution using multiple tracers, *Applied Geochemistry* 50, 252-264.
- Mazor, E. (1996) *Chemical and Isotopic Groundwater Hydrology: The Applied Approach*. Marcel Dekker Inc.
- Mazor, E. (1996) *Chemical and Isotopic Groundwater Hydrology: The Applied Approach*. Marcel Dekker Inc.
- McCallum, J. L., N. B. Engdahl, T. R. Ginn, and P. G. Cook (2014) Nonparametric estimation of groundwater residence time distributions: What can environmental tracer data tell us about groundwater residence time? *Water Resour. Res.* 50, 2022–2038, doi:10.1002/2013WR014974.

- McCallum, J. L., N. B. Engdahl, T. R. Ginn, and P. G. Cook (2014) Nonparametric estimation of groundwater residence time distributions: What can environmental tracer data tell us about groundwater residence time? *Water Resour. Res.* 50, 2022–2038, doi:10.1002/2013WR014974.
- McConchie, J.; Webby, G.; Morrow, F.; Maas, F. and J. Cox (2011) Quantification and validation of a sediment budget for the lower Hutt River, Wellington, New Zealand, *J. Hydrol. NZ* 50, 241-256.
- McConchie, J.; Webby, G.; Morrow, F.; Maas, F. and J. Cox (2011) Quantification and validation of a sediment budget for the lower Hutt River, Wellington, New Zealand, *Journal of Hydrology*. *J. Hydrol. NZ* 50, 241-256.
- McDonnell, J.J.; Rowe, L.K. and M.K. Stewart (1999) A combined tracer-hydrometric approach to assess the effect of catchment scale on water flow path, source, and age. *Integrated methods in Catchment Hydrology – Tracer, Remote Sensing and New Hydrometric Techniques. Proceedings of IUGG 99 Symposium HS4, Birmingham, July. IAHS Publication No. 258.*
- McDonnell, J.J.; Rowe, L.K. and M.K. Stewart (1999) A combined tracer-hydrometric approach to assess the effect of catchment scale on water flow path, source, and age. *Integrated methods in Catchment Hydrology – Tracer, Remote Sensing and New Hydrometric Techniques. Proceedings of IUGG 99 Symposium HS4, Birmingham, July. IAHS Publication No. 258.*
- McGuire K.J. and J.J. McDonnell (2006) A review and evaluation of catchment transit time modeling. *J. Hydrol.* 330, 543–563.
- McGuire K.J. and J.J. McDonnell (2006) A review and evaluation of catchment transit time modeling. *Journal of Hydrology*. *J. Hydrol.* 330, 543–563.
- McMahon, P.B. and F.H. Chapelle (2008) Redox processes and water quality of selected principal aquifer systems: *Ground Water* 46(2), 259–271.
- McMahon, P.B. and F.H. Chapelle (2008) Redox processes and water quality of selected principal aquifer systems: *Ground Water* 46(2), 259–271.
- Meylan, W. M. and P. H. Howard (1991) Bond contribution method for estimating henry's law constants. *Environmental Toxicology and Chemistry* 10, 1283–1293, doi: 10.1002/etc.5620101007.
- Meylan, W. M. and P. H. Howard (1991) Bond contribution method for estimating henry's law constants. *Environmental Toxicology and Chemistry* 10, 1283–1293, doi: 10.1002/etc.5620101007.
- Meylan, W. M.; Howard, P. H. and R. S. Boethling (1996) Improved method for estimating water solubility from octanol/water partition coefficient. *Environmental Toxicology and Chemistry* 15, 100–106. doi: 10.1002/etc.5620150205.
- Meylan, W. M.; Howard, P. H. and R. S. Boethling (1996) Improved method for estimating water solubility from octanol/water partition coefficient. *Environmental Toxicology and Chemistry* 15, 100–106. doi: 10.1002/etc.5620150205.

Miller, B. R., R. F. Weiss, P. K. Salameh, T. Tanhua, B. R. Greally, J. Muhle, and P. G. Simmonds (2008) Medusa: A Sample Preconcentration and GC/MS Detector System for in Situ Measurements of Atmospheric Trace Halocarbons, Hydrocarbons, and Sulfur Compounds, *Anal. Chem.* 80(5), 1536-1545.

Miller, B. R., R. F. Weiss, P. K. Salameh, T. Tanhua, B. R. Greally, J. Muhle, and P. G. Simmonds (2008) Medusa: A Sample Preconcentration and GC/MS Detector System for in Situ Measurements of Atmospheric Trace Halocarbons, Hydrocarbons, and Sulfur Compounds, *Anal. Chem.* 80(5), 1536-1545.

Ministry of Health (2008) Drinking-water Standards for New Zealand 2005 (Revised 2008). Ministry of Health, Wellington, New Zealand. 163 p. http://www.health.govt.nz/system/files/documents/publications/drinking-water-standards-2008_0.pdf (accessed July 2013).

Ministry of Health (2008) Drinking-water Standards for New Zealand 2005 (Revised 2008). Ministry of Health, Wellington, New Zealand. 163 p. http://www.health.govt.nz/system/files/documents/publications/drinking-water-standards-2008_0.pdf (accessed July 2013).

Montzka, S. A. and P. J. Fraser (2003) Controlled substances and other gases, in scientific Assessment of Ozone Depletion 2002, 1-87, World Meteorol. Org., Geneva.

Montzka, S. A. and P. J. Fraser (2003) Controlled substances and other gases, in scientific Assessment of Ozone Depletion 2002, 1-87, World Meteorol. Org., Geneva.

Montzka, S. A., Reimann, S. (coordinating lead authors), Engel, A., Krüger, K., O'Doherty, S., Sturges, W., Blake, D., Dorf, M., Fraser, P., Froidevaux, L., Jucks, K., Kreher, K., Kurylo, M., Mellouki, A., Miller, J., Nielsen, O.-J., Orkin, V., Prinn, R., Rhew, R., Santee, M., Stohl, A., and D. Verdonik (2011) Scientific Assessment of Ozone Depletion: 2010, Global Ozone Research and Monitoring Project, Report No. 52, 516 pp., Chapter 1, Ozone-Depleting Substances (ODSs) and Related Chemicals, World Meteorological Organization, Geneva, Switzerland, 2011.

Montzka, S. A., Reimann, S. (coordinating lead authors), Engel, A., Krüger, K., O'Doherty, S., Sturges, W., Blake, D., Dorf, M., Fraser, P., Froidevaux, L., Jucks, K., Kreher, K., Kurylo, M., Mellouki, A., Miller, J., Nielsen, O.-J., Orkin, V., Prinn, R., Rhew, R., Santee, M., Stohl, A., and D. Verdonik (2011) Scientific Assessment of Ozone Depletion: 2010, Global Ozone Research and Monitoring Project, Report No. 52, 516 pp., Chapter 1, Ozone-Depleting Substances (ODSs) and Related Chemicals, World Meteorological Organization, Geneva, Switzerland, 2011.

Mook W. and Y. Yurtsever (eds.); Zuber, A.; Małoszewski, P.; Campana, M.E.; Harrington, G.A.; Tezcan, L. and L.F. Konikow (2001) Environmental Isotopes in the Hydrological Cycle: Principles and Applications. V. VI: Modelling, UNESCO Publishing, Paris.

Mook W. and Y. Yurtsever (eds.); Zuber, A.; Małoszewski, P.; Campana, M.E.; Harrington, G.A.; Tezcan, L. and L.F. Konikow (2001) Environmental Isotopes in the Hydrological Cycle: Principles and Applications. V. VI: Modelling, UNESCO Publishing, Paris.

Morgenstern, U. and C. B. Taylor (2009) Ultra Low-level tritium measurement using electrolytic enrichment and LSC, *Isotopes in Environmental and Health Studies* 45, 96–117.

Morgenstern, U. and C. B. Taylor (2009) Ultra Low-level tritium measurement using electrolytic enrichment and LSC, *Isotopes in Environmental and Health Studies* 45, 96–117.

Morgenstern, U. and C.J. Daughney (2012) Groundwater age for identification of baseline groundwater quality and impacts of land-use intensification: The National Groundwater Monitoring Programme of New Zealand. *J. Hydrol.* 456/457, 79-93.

Morgenstern, U. and C.J. Daughney (2012) Groundwater age for identification of baseline groundwater quality and impacts of land-use intensification: The National Groundwater Monitoring Programme of New Zealand. *Journal of Hydrology*. *J. Hydrol.* 456/457, 79-93.

Morgenstern, U.; Brown, L.J.; Begg, J.; Daughney, C. and P. Davidson (2009) Linkwater catchment ground-water residence time, flow pattern, and hydrochemistry trends. Institute of Geological and Nuclear Sciences science report 2009/08, 47 p.

Morgenstern, U.; Brown, L.J.; Begg, J.; Daughney, C. and P. Davidson (2009) Linkwater catchment ground-water residence time, flow pattern, and hydrochemistry trends. Institute of Geological and Nuclear Sciences science report 2009/08, 47 p.

Morgenstern, U.; Stewart, M. K. and R. Stenger (2010) Dating of streamwater using tritium in a post nuclear bomb pulse world: continuous variation of mean transit time with streamflow, *Hydrol. Earth Syst. Sci.*, 14, 2289-2301, doi:10.5194/hess-14-2289-2010.

Morgenstern, U.; Stewart, M. K. and R. Stenger (2010) Dating of streamwater using tritium in a post nuclear bomb pulse world: continuous variation of mean transit time with streamflow, *Hydrol. Earth Syst. Sci.*, 14, 2289-2301, doi:10.5194/hess-14-2289-2010.

Nash, J.E. and J.V. Sutcliffe (1970) River flow forecasting through conceptual models. *J. Hydrol.* 10, 282-290.

Nash, J.E. and J.V. Sutcliffe (1970) River flow forecasting through conceptual models. *Journal of Hydrology*. *J. Hydrol.* 10, 282-290.

Newland, M.J.; Reeves, C. E.; Oram, D. E.; Laube, J. C.; Sturges, W. T.; Hogan, C.; Begley, P. and P. J. Fraser (2013) Southern hemispheric halon trends and global halon emissions, 1978–2011, *Atmos. Chem. Phys.* 13, 5551-5565, doi:10.5194/acp-13-5551-2013.

Newland, M.J.; Reeves, C. E.; Oram, D. E.; Laube, J. C.; Sturges, W. T.; Hogan, C.; Begley, P. and P. J. Fraser (2013) Southern hemispheric halon trends and global halon emissions, 1978–2011, *Atmos. Chem. Phys.* 13, 5551-5565, doi:10.5194/acp-13-5551-2013.

Nir, A. (1986) Role of tracer methods in hydrology as a source of physical information: basic concepts and definitions—time relationship in dynamic systems. In: *Mathematical models for interpretation of tracer data in groundwater hydrology*, IAEA, TECDOC-381. IAEA, Vienna, Austria, 7–44.

Nir, A. (1986) Role of tracer methods in hydrology as a source of physical information: basic concepts and definitions—time relationship in dynamic systems. In: Mathematical models for interpretation of tracer data in groundwater hydrology, IAEA, TECDOC-381. IAEA, Vienna, Austria, 7–44.

NIWA (2015) CliFlo: NIWA's National Climate Database on the Web, URL: <http://cliflo.niwa.co.nz/>, Retrieved 06/06/2015.

NIWA (2015) CliFlo: NIWA's National Climate Database on the Web, URL: <http://cliflo.niwa.co.nz/>, Retrieved 06/06/2015.

O'Brien, A.K.; Rice, K.C.; Bricker, O.P.; Kennedy, M.M. and R.T. Anderson (1997) Use of geochemical mass balance modelling to evaluate the role of weathering in determining stream chemistry in five mid-Atlantic watersheds on different lithologies, *Hydrol. Processes* 11, 719 – 744.

O'Brien, A.K.; Rice, K.C.; Bricker, O.P.; Kennedy, M.M. and R.T. Anderson (1997) Use of geochemical mass balance modelling to evaluate the role of weathering in determining stream chemistry in five mid-Atlantic watersheds on different lithologies, *Hydrological Processes* 11, 719 – 744.

Oster, H.; Sonntag, C. and K.O. Munnich (1996) Groundwater age dating with chlorofluorocarbons. *Water Resources Research* 32(10), 2989-3001.

Oster, H.; Sonntag, C. and K.O. Munnich (1996) Groundwater age dating with chlorofluorocarbons. *Water Resources Research* 32(10), 2989-3001.

Paces, T. (1973) Steady-state kinetics and equilibrium between ground water and granitic rock. *Geochim. Cosmochim. Acta*, 37 (1973), 2641–2663.

Paces, T. (1973) Steady-state kinetics and equilibrium between ground water and granitic rock. *Geochim. Cosmochim. Acta*, 37 (1973), 2641–2663.

Pacheco, F. and C. H. van der Weijden (1996) Contributions of Water-Rock Interactions to the Composition of Groundwater in Areas with a Sizeable Anthropogenic Input: A Case Study of the Waters of the Fundão Area, Central Portugal, *Water Resour. Res.* 32(12), 3553–3570, doi:10.1029/96WR01683.

Pacheco, F. and C. H. van der Weijden (1996) Contributions of Water-Rock Interactions to the Composition of Groundwater in Areas with a Sizeable Anthropogenic Input: A Case Study of the Waters of the Fundão Area, Central Portugal, *Water Resour. Res.* 32(12), 3553–3570, doi:10.1029/96WR01683.

Pacheco, F.A.L. and C.H. van der Weijden (2012) Weathering of plagioclase across variable flow and solute transport regimes. *J. Hydrol.* 420–421, 46-58.

Pacheco, F.A.L. and C.H. van der Weijden (2012) Weathering of plagioclase across variable flow and solute transport regimes. *Journal of Hydrology*. *J. Hydrol.* 420–421, 46-58.

Peacock, R.D.; Cleary, T.G. and R.H., Jr. Harris (1994) Evaluation of Alternative In-Flight Fire Suppressants for full Scale Testing in Simulated Aircraft Engine Nacelles and Dry Bays, NIST Special Pub. 861, 643-668, U.S. Department of Commerce, Washington D.C.

Peacock, R.D.; Cleary, T.G. and R.H., Jr. Harris (1994) Evaluation of Alternative In-Flight Fire Suppressants for full Scale Testing in Simulated Aircraft Engine Nacelles and Dry Bays, NIST Special Pub. 861, 643-668, U.S. Department of Commerce, Washington D.C.

Peters, N. E.; Burns, D. A. and B.T. Aulenbach (2013) Evaluation of High-Frequency Mean Streamwater Transit-Time Estimates Using Groundwater Age and Dissolved Silica Concentrations in a Small Forested Watershed, *Aquatic Geochemistry* 20(2-3), 183-20.

Peters, N. E.; Burns, D. A. and B.T. Aulenbach (2013) Evaluation of High-Frequency Mean Streamwater Transit-Time Estimates Using Groundwater Age and Dissolved Silica Concentrations in a Small Forested Watershed, *Aquatic Geochemistry* 20(2-3), 183-20.

Petrides, B.; Cartwright, I. and T. R. Weaver (2006) The evolution of groundwater in the Tyrrell catchment, south-central Murray Basin, Victoria, Australia, *Hydrogeol. J.* 14, 1522–1543, doi:10.1007/s10040-006-0057-9.

Petrides, B.; Cartwright, I. and T. R. Weaver (2006) The evolution of groundwater in the Tyrrell catchment, south-central Murray Basin, Victoria, Australia, *Hydrogeol. J.* 14, 1522–1543, doi:10.1007/s10040-006-0057-9.

Phillips, F.M. and M.C. Castro (2003) Groundwater dating and residence-time measurements. In *Treatise on Geochemistry*, ed. HD Holland, KK Turekian Vol. 5: Surface and Ground Water, Weathering, and Soils, ed. JI Drever, 451–97. Oxford: Elsevier, 626 pp.

Phillips, F.M. and M.C. Castro (2003) Groundwater dating and residence-time measurements. In *Treatise on Geochemistry*, ed. HD Holland, KK Turekian, Vol. 5: Surface and Ground Water, Weathering, and Soils, ed. JI Drever, 451–97. Oxford: Elsevier, 626 pp.

Phreatos Groundwater Consulting (2003) Revision of the numerical model for the Lower Hutt groundwater zone. Report prepared for Wellington Regional Council. WRC publication number GW\RINV-T-03/07.

Phreatos Groundwater Consulting (2003) Revision of the numerical model for the Lower Hutt groundwater zone. Report prepared for Wellington Regional Council. WRC publication number GW\RINV-T-03/07.

Plummer, L. N. and C. L. Sprinkle (2001) Radiocarbon dating of dissolved inorganic carbon in groundwater from confined parts of the Upper Floridan aquifer, Florida, USA, *Hydrogeol. J.* 9, 127–150, doi:10.1007/s100400000121.

Plummer, L. N. and C. L. Sprinkle (2001) Radiocarbon dating of dissolved inorganic carbon in groundwater from confined parts of the Upper Floridan aquifer, Florida, USA, *Hydrogeol. J.* 9, 127–150, doi:10.1007/s100400000121.

Plummer, L.N. and E. Busenberg (1999) Chlorofluorocarbons, in Cook, P., and Herczeg, A., eds., *Environmental tracers in subsurface hydrology*: Boston, Mass., Kluwer Academic Publishers, 441-478.

- Plummer, L.N. and E. Busenberg (1999) Chlorofluorocarbons, in Cook, P., and Herczeg, A., eds., *Environmental tracers in subsurface hydrology*: Boston, Mass., Kluwer Academic Publishers, 441-478.
- Plummer, L.N.; Busby, J.F.; Lee, R.W. and B.B. Hanshaw (1990) Geochemical modelling of the Madison aquifer in parts of Montana, Wyoming, and South Dakota: *Water Resources Research* 26, 1981-2014.
- Plummer, L.N.; Busby, J.F.; Lee, R.W. and B.B. Hanshaw (1990) Geochemical modelling of the Madison aquifer in parts of Montana, Wyoming, and South Dakota: *Water Resources Research* 26, 1981-2014.
- Plummer, L.N.; Busenberg, E. and P.G. Cook (2006) Principles of Chlorofluorocarbon Dating, in IAEA (International Atomic Energy Agency) *Use of chlorofluorocarbons in Hydrology: A Guidebook*, 277 pp., IAEA, Vienna.
- Plummer, L.N.; Busenberg, E. and P.G. Cook (2006) Principles of Chlorofluorocarbon Dating, in IAEA (International Atomic Energy Agency) *Use of chlorofluorocarbons in Hydrology: A Guidebook*, 277 pp., IAEA, Vienna.
- Plummer, L.N.; Busenberg, E.; Eberts, S.M.; Bexfield, L.M.; Brown, C.J.; Fahlquist, L.S.; Katz, B.G. and M.K. Landon (2008) Low-Level Detections of Halogenated Volatile Organic Compounds in Groundwater: Use in Vulnerability Assessments. *J. Hydrol. Engineering Engin.* 13(11), 1049.
- Plummer, L.N.; Busenberg, E.; Eberts, S.M.; Bexfield, L.M.; Brown, C.J.; Fahlquist, L.S.; Katz, B.G. and M.K. Landon (2008) Low-Level Detections of Halogenated Volatile Organic Compounds in Groundwater: Use in Vulnerability Assessments. *Journal of Hydrologic Hydrol. Engineering Engin.* 13(11), 1049.
- Poole C.F. (2013) Derivatization reactions for the use with the electron-capture detector. *J. Chromatogr. A* 1296, 15-24.
- Poole C.F. (2013) Derivatization reactions for the use with the electron-capture detector. *Journal J.of Chromatography Chromatogr. A* 1296, 15-24.
- Rademacher, L.K.; Clark, J.F.; Clow, D.W. and G.B. Hudson (2005) Old groundwater influence on stream hydro-chemistry and catchment response times in a small Sierra Nevada catchment: Sagehen Creek, California, *Water Resource Research* 41, W02004.
- Rademacher, L.K.; Clark, J.F.; Clow, D.W. and G.B. Hudson (2005) Old groundwater influence on stream hydro-chemistry and catchment response times in a small Sierra Nevada catchment: Sagehen Creek, California, *Water Resource Research* 41, W02004.
- Rademacher, L.K.; Clark, J.F.; Hudson, G. B.; Erman, D.C. and N.A. Erman (2001) Chemical evolution of shallow groundwater as recorded by springs, Sagehen Basin, Nevada County, California, *Chemical Geology* 179, 37–51.
- Rademacher, L.K.; Clark, J.F.; Hudson, G. B.; Erman, D.C. and N.A. Erman (2001) Chemical evolution of shallow groundwater as recorded by springs, Sagehen Basin, Nevada County, California, *Chemical Geology* 179, 37–51.
- Reynolds, G.W.; Hoff, J.T. and R.W. Gillham (1990) Sampling bias caused by materials used to monitor halocarbons in groundwater, *Environ. Sci. Technol.* 24, 135-142.

- Reynolds, G.W.; Hoff, J.T. and R.W. Gillham (1990) Sampling bias caused by materials used to monitor halocarbons in groundwater, *Environ. Sci. Technol.* 24, 135-142.
- Robins, N.S. (1998) Groundwater pollution, aquifer recharge and vulnerability, Geological Society of London, London.
- Robins, N.S. (1998) Groundwater pollution, aquifer recharge and vulnerability, Geological Society of London, London.
- Rosen, M.R.; Bright, J.; Carran, P.; Stewart M.K. and R. Reeves (1999b) Estimating rainfall recharge and soil water residence time in Pukekohe, New Zealand, by combining geophysical, chemical and isotopic methods. *Groundwater* 37(6), 836-844.
- Rosen, M.R.; Bright, J.; Carran, P.; Stewart M.K. and R. Reeves (1999b) Estimating rainfall recharge and soil water residence time in Pukekohe, New Zealand, by combining geophysical, chemical and isotopic methods. *Groundwater* 37(6), 836-844.
- Rosen, M.R.; Cameron, S.G.; Taylor, C. B. and R.R. Reeves (1999a) New Zealand guidelines for the collection of groundwater samples for chemical and isotopic analysis. Institute of Geological and Nuclear Sciences Science Report 99/9: Wellington, New Zealand.
- Rosen, M.R.; Cameron, S.G.; Taylor, C. B. and R.R. Reeves (1999a) New Zealand guidelines for the collection of groundwater samples for chemical and isotopic analysis. Institute of Geological and Nuclear Sciences Science Report 99/9: Wellington, New Zealand.
- Rosiek, J.; Bartyzel, J.; Rozanski, K. and I. Sliwkab (2013) The use of a custom mode electron capture detector to determine mixing ratios of environmental tracers: Sulfur hexafluoride, chlorotrifluoromethane and bromotrifluoromethane. *J. Chromatogr. A* 1282, 194– 198.
- Rosiek, J.; Bartyzel, J.; Rozanski, K. and I. Sliwkab (2013) The use of a custom mode electron capture detector to determine mixing ratios of environmental tracers: Sulfur hexafluoride, chlorotrifluoromethane and bromotrifluoromethane. *Journal J.I of Chromatography Chromatogr. A* 1282, 194– 198.
- Rowe, G.H. (1980) Applied Geology of Wellington Rocks for Aggregate and Concrete, PhD, Victoria University of Wellington.
- Rowe, G.H. (1980) Applied Geology of Wellington Rocks for Aggregate and Concrete, PhD, Victoria University of Wellington.
- Rupert, M.G. and L.N. Plummer (2009) Groundwater quality, age, and probability of contamination, Eagle River watershed valley-fill aquifer, north-central Colorado, 2006-2007. U.S. Geological Survey Scientific Investigations Report 2009-5082, 59pp.
- Rupert, M.G. and L.N. Plummer (2009) Groundwater quality, age, and probability of contamination, Eagle River watershed valley-fill aquifer, north-central Colorado, 2006-2007. U.S. Geological Survey Scientific Investigations Report 2009-5082, 59pp.

- Santella, N.; Ho, D.T.; Schlosser, P. and M. Stute (2003) Distribution of atmospheric SF₆ near a large urban area as recorded in the vadose zone. *Environmental Science and Technology* 37(6), 1069-1074.
- Santella, N.; Ho, D.T.; Schlosser, P. and M. Stute (2003) Distribution of atmospheric SF₆ near a large urban area as recorded in the vadose zone. *Environmental Science and Technology* 37(6), 1069-1074.
- Santella, N.; Ho, D.T.; Schlosser, P. and M. Stute (2008) Widespread elevated atmospheric SF₆ mixing ratios in the Northeastern United States: Implications for groundwater dating. *J. Hydrol.* 349(1-2), 139-14.
- Scanlon, B. R., R. E. Mace, M. E. Barrett, and B. Smith (2003), Can we simulate regional groundwater flow in a karst system using equivalent porous media models? Case study, Barton Springs Edwards aquifer, USA, *J. Hydrol.*, 276, 137–158.
- Scharlin, P., and R. Battino (1995) Solubility of CCl₂F₂, CClF₃, CF₄, and CH₄ in water and seawater at 288.15– 303.15 K and 101.325 kPa, *J. Chem. Eng. Data* 40, 167–169.
- Schuermans, J.M., and M.F.P. Bierkens (2007) Effect of spatial distribution of daily rainfall on interior catchment response of a distributed hydrological model, *Hydrol. Earth Syst. Sci.* 11, 677–693.
- Sen, P.K. (1968) Estimates of the regression coefficient based on Kendall's tau. *J. Am. Stat. Ass.* 63:1379-1389.
- Shapiro, S.D.; Schlosser, P.; Smethie, W.M. and M. Stute (1997) The use of H-3 and tritiogenic He-3 to determine CFC degradation and vertical mixing rates in Framvaren Fjord, Norway. *Marine Chemistry* 59 (1–2), 141–157.
- Shrestha, D.L.; Kayastha, N. and D. P. Solomatine (2009) A novel approach to parameter uncertainty analysis of hydrological models using neural networks. *Hydrol. Earth System Sci.* 13, 1235–1248.
- Shrivastava, A. and V.B. Gupta (2011) Methods for the determination of limit of detection and limit of quantitation of the analytical methods, *Chronicles of Young Scientists* 2(1), 21.
- Singh, A.; Mishra, S. and G. Ruskauff (2010) Model averaging techniques for quantifying conceptual model uncertainty. *Ground Water* 48(5), 701–715.
- Smyth, G.K. (2014) Numerical Integration. Wiley StatsRef: Statistics Reference Online.
doi: 10.1002/9781118445112.stat05029.
- Sonier, D.N., Duran, N.L., Smith, G.B. (1994) Dechlorination of trichlorofluoromethane (CFC-11) by sulfate-reducing bacteria from an aquifer contaminated with halogenated aliphatic-compounds. *Applied and Environmental Microbiology* 60 (12), 4567–4572.
- Sousa, S.R. and S.E. Bialkowski (2001) Comparison of gas chromatography detection limits and relative responses of common alternative fluorocarbons using electron capture, atomic emission, and mass spectrometry detection", *ANALYT CHIM* 433(2), 181-186.
- Spiegelhalter, D.J.; Best, N.G.; Carlin, B.P.; van der Linde, A. (2002). Bayesian measures of model complexity and fit (with discussion). *J. Royal Statistical Society, Series B* 64 (4): 583–639. doi:10.1111/1467-9868.00353.

- Statistics NZ - Statistics New Zealand (2014) 2013 Census QuickStats about Wellington. http://www.stats.govt.nz/Census/2013-census/profile-and-summary-reports/quickstats-about-a-place.aspx?request_value=14322&tabname=, accessed 15/06/2015.
- StatPoint Technologies, Inc. (2009) STATGRAPHICS® Centurion XVI User Manual. available online (last accessed 25/05/2015): <http://www.statlets.com/main.pdf>
- Stedinger, J. R.; Vogel, R.M.; Lee, S.U. and R. Batchelder (2008) Appraisal of the generalized likelihood uncertainty estimation (GLUE) method, *Water Resour. Res.* 44, W00B06, doi:10.1029/2008WR006822.
- Stewart, A. (2014) Land use and water quality. Report prepared for the GWRC (Greater Wellington regional Council and the Ruamāhanga Whaitua Committee. Report number: #1368159, 36p.
- Stewart, M. and U. Morgenstern (2001) Age and Source of Groundwaters from Isotopic Tracers. In: *Groundwaters of New Zealand*. Rosen, M.R. and White P.A. (eds), 161-183.
- Stewart, M.K. and C.B. Taylor (1981) Environmental isotopes in New Zealand Hydrology; 1. Introduction. The role of oxygen-18, deuterium, and tritium in hydrology. *New Zealand J. Science* 24(3/4): 295-311.
- Sturges, W. (ed.), Baring, T.; Butler, J.; Elkins, J.; Hall, B.; Myers, R.; Montzka, S.; Swanson, T. and T. Thompson (1991) Nitrous Oxide and Halocarbons Group, Section 7 in: *Climate Monitoring and Diagnostics Laboratory, No. 19 Summary Report 1990*, E. Ferguson and R. Rosson (eds.), US Department of Commerce, NOAA-ERL, Boulder, Colorado, USA, 63-71.
- Suckow, A. (2014) The age of groundwater – Definitions, models and why we do not need this term. *Appl. Geochem.*, <http://dx.doi.org/10.1016/j.apgeochem.2014.04.016>
- Szabo, Z.; Rice, D.E.; Plummer, L.N.; Busenberg, E.; Drenkard, S. and P. Schlosser (1996) Age-dating of shallow groundwater with chlorofluorocarbons, tritium/helium 3, and flow path analysis, southern New Jersey coastal plain: *Water Resources Research* 32, 1023–1038.
- Tadros, C.V.; Hughes, C.E.; Crawford, J.; Hollins, S. E. and R. Chisari (2014) Tritium in Australian precipitation: A 50 year record. *J. Hydrol.* 513 (26), 262-273.
- Taylor, A. and J.D. Blum (1995) Relation between soil age and silicate weathering rates determined from the chemical evolution of a glacial chronosequence. *Geology* 23, 979-982.
- Taylor, C.B. (1966) Tritium in Southern Hemisphere precipitation 1953–1964. *Tellus*, 18, 105–131. doi: 10.1111/j.2153-3490.1966.tb01449.x
- Taylor, C.B., Trompetter, V. J. and Brown, L. J. (2001) The Manawatu Aquifers, North Island, New Zealand: Clarification of Hydrogeology Using a Multidisciplinary Environmental Tracer Approach. *Hydrological Processes* 15, 3269.

Taylor, C.B.; Brown, L.J.; Cunliffe, J.J. and P.W. Davidson (1992) Environmental tritium and ^{18}O applied in a hydrological study of the Wairau Plain and its contributing mountain catchments, Marlborough, New Zealand. *J. Hydrol.* 138, 269-319.

Thompson, T.M.; Butler, J.H.; Daube, B.C.; Dutton, G.S.; Elkins, J.W.; Hall, B.D.; Hurst, D.F.; King, D.B.; Kline, S.; Lafleur, B.G.; Lind, J.; Lovitz, S.; Ondeel, D. J.; Montzka, S.A.; Moore, F.L.; Nance, J.D.; Neu, J.L.; Romashkin, P.A.; Scheffer, A. and W.J. Snible (2004) Halocarbons and other atmospheric trace species, in Climate Monitoring and Diagnostics Laboratory Summary Report 2002–2003, Rep. 27, chap. 5, 174 pp., Natl. Oceanic and Atmos. Admin., Boulder, Colorado.

Thorntwaite, C. W. and J. W. Mather (1955) The Water Balance, Publ. Climatol. Lab. Climatol. Drexel Inst. Technol. 8(1), 1-104.

Tidswell, S.; Conwell, C. and J.R. Milne (2012) Groundwater quality in the Wellington Region: State and trends. Greater Wellington Regional Council, Publication No. GW/EMI-T-12//140, Wellington.

Timbe, E., Windhorst, D. Crespo, P., Frede, H.-G., Feyen, J. and L. Breuer (2014) Understanding mean transit times in Andean tropical montane cloud forest catchments: combining tracer data, lumped parameter models and uncertainty analysis. *Hydrol. Earth Syst. Sci. Discuss.* 10, 15871-15914.

Turnadge, C. and B.D. Smerdon (2014) A review of methods for modelling environmental tracers in groundwater: Advantages of tracer concentration simulation, *Journal of Hydrology*. *J. Hydrol.*, doi: <http://dx.doi.org/10.1016/j.jhydrol.2014.10.056>

Ullman W.J.; Welch, S.A. and P.C. Bennett (1997) Microbially mediated, proton-promoted feldspar dissolution by organic acids excretion under unbuffered and nutrient limited conditions in oxic aquifers. Seventh Annual V. M. Goldschmidt Conference, Tuscon AZ June 2–6 1997.

USGS - United States Geological Survey (1999) Tracing and Dating Young Ground Water, US Department of the Interior, Fact Sheet-134-99, available online: <http://pubs.usgs.gov/fs/FS-134-99/pdf/fs-134-99.pdf>.

van der Raaij, R. and M. Beyer (2015) Use of CFCs and SF_6 as groundwater age tracers in New Zealand, *J. Hydrol. New Zealand* 54(1), in press.

van der Raaij, R. W. (2003) Age-dating of New Zealand groundwaters using sulphur hexafluoride. Unpublished, MSc thesis, Victoria University, Wellington.

Visser, A. (2009) Trends in groundwater quality in relation to groundwater age, PhD thesis, Netherlands Geographical Studies 384, Faculty of Geosciences, Utrecht University, Netherlands.

Vogel, J.C. (1967) Investigation of groundwater flow with radiocarbon: Isotopes in Hydrology, International Atomic Energy Agency, Vienna, 355-368.

Warner, M.J. and R.F. Weiss (1985) Solubility of chlorofluorocarbons 11 and 12 in water and seawater. *Deep-Sea Res.* 32, 1485-97.

- Watson, A.J.; Ledwell, J.R. and S.C. Sutherland (1991) The Santa Monica Basin tracer experiment--Comparison of release methods and performance of perfluorodecalin and sulfur hexafluoride, *J. Geophys. Res.*, 96(C5), 8719-8725.
- Welch, S.A.; Barker W.W. and J.F. Banfield (1999) Microbial extracellular polysaccharides and plagioclase dissolution. *Geochim. Cosmochim. Acta* 63, 1405–1419.
- White, A.F. and H.L. Buss (2013) Natural Weathering Rates of Silicate Minerals. in JI Drever (ed.), *Treatise on Geochemistry: Surface and Ground Water, Weathering and Soils*. 2nd edn, Elsevier.
- White, A.F. and S.L. Brantley (2003) The effect of time on the weathering of silicate minerals: Why do weathering rates differ in the laboratory and field?, *Chem. Geol.*, 202, 479–506.
- White, P.A. and M.R. Rosen (2001) Chapter 1: Introduction. In Rosen, M.R. & White, P.A. (eds.), *Groundwaters of New Zealand*. New Zealand Hydrological Society Inc. Wellington. 1-3.
- Wilhelm, E.; Battino, R. and R.J. Wilcock (1977) Low pressure solubility of gases in liquid water. *Chem. Rev.* 77, 219-262.
- Wilson, R.D. and D.M. Mackay (1996) SF₆ as a conservative tracer in saturated media with high intra granular porosity of high organic carbon content, *Ground Water* 34(2), 241-249.
- WRC - Wellington Regional Council (1993) Wainuiomata Water Resource Statement. Wellington Regional Council publication WRC/PP-T-93/15.
- Zuber, A.; Róžański, K.; Kania, J. and R. Purtschert (2011) On some methodological problems in the use of environmental tracers to estimate hydrogeologic parameters and to calibrate flow and transport models, *Hydrogeol. J.* 19(1), 53-69.

Appendices

Table of content of Appendices

Appendix A – Available tracer data for studied groundwater sites	154
Appendix B – for Chapter 4	158
B1 Potentially co-eluting compounds	158
B2 Details on analytical procedure.....	160
B3 Correction for excess air and headspace	160
B4 Calibration curve established with larger amounts of Halon-1301 than contained in modern water	161
B5 Detailed assessment of elevated Halon-1301 ages	162
B5.1 Analytical issues	162
B5.2 Halon-1301 property related issues.....	163
B6 Proposed methods for an improved analytical determination of Halon-1301 (and SF ₆)	164
B6.1 Proposed signal processing method for the determination of Halon-1301 and SF ₆	164
B6.2 Proposed sampling techniques for determination of Halon-1301 and SF ₆ in groundwater.....	173
B6.3 Summary of Appendix B6.....	176
A7 References.....	177
Appendix C – for Chapter 5	182
C1 Details literature search	182
C2 Detailed model description	206
C2.1 MC Simulation details	206
C2.2 Input functions, input uncertainties and their convolution and integration.....	208
C2.3 Hydrochemistry trends for assessment of steady state flow.....	217
C3 Detailed model outcome.....	218
C3.1 Details on the objective function	218
C3.2 Detailed assessment of input uncertainties on the behavioural LPM parameter populations	222
C4 Detailed age estimation	228
C4.1 Probability plots	228
C4.2 Age estimation at 90 and 95% confidence.....	229
C4.3 Factors that influence uncertainty of the age estimation.....	231
C4.4 Tracer combination methods from a combined age estimation inferred from tritium, Halon-1301 and SF ₆	232
C5 References.....	236
Appendix D – for Chapter 6	237

D1 Detailed assessment of hydrochemistry in the LHGWZ.....	237
D1.1 Statistical and graphical tools for assessment of the consistency of hydrochemistry data.....	237
D1.2 Data Analysis.....	237
D1.3 Determination of median and standard deviation	239
D1.4 Trends and seasonality	239
D1.5 Hierarchical Cluster Analysis (HCA) and Principal Component Analysis (PCA)	243
D1.6 Inverse mass balance mineral weathering model	244
D1.6 Groundwater environments	245
D1.7 Assessment of normal distribution of data.....	246
D1.8 Relationships between hydrochemistry and the tritium-inferred MRT in the Lower Hutt Groundwater Zone	246
D2 Detailed assessment of aquifer material	247
D2.1 Details on aquifer composition of the LHGWZ by Rowe (1980)	247
D2.2 Location of the Gravel pebbles	247
D2.3 Details on WDS and EDs analysis	247
D2.4 Detailed results of aquifer material analysis	248
D2.5 Determination of differences and apparent trend in mineral abundance within the studied aquifer pebbles.....	251
D3 - Detailed results hydrochemistry-time modelling	252
D3.1 Equations of LPMs used	252
D3.2 Median of considered hydrochemistry parameters	253
D3.4 Chi ² objective function and the effect of uncertainty threshold on behavioural hydrochemistry-time relationships.....	254
D3.5 Effect of number of MC runs on behavioural hydrochemistry-time relationships.....	255
D3.6 Effect of binning on the probability distribution of behavioural hydrochemistry-PT relationships.....	257
D3.7 Determination of equivalent piston flow time	257
D4 Detailed results on constrained age information with hydrochemistry-time relationships	258
D4.1 Inferred hydrochemistry-time relationships.....	258
D4.2 Inferred age information	261
D4.3 Including/excluding tritium/hydrochemistry.....	263
D4.4 Constraining of inferred hydrochemistry of recharge with known relationships of hydrochemistry parameters.....	264
D5 References of Appendix	264

Appendix A – Available tracer data for studied groundwater sites

A summary of available tracer data (well number, well name, coordinates (NZ Map Grid coordinates), sampling date and concentration of tracer data) in the groundwater wells studied in this thesis is given in Tab. A1.

Table A1: Summary of available tracer data for wells studied in this thesis. Data in italics were considered as outliers

Well #	Well name	Easting /Northing	Tritium data		SF ₆ data		CFC-11 & CFC-12 data	
			date	Concentration [TU]	Date	Concentration [pptv]	date	Concentration [pptv]
Lower Hutt Groundwater Zone								
6	Avalon studios	2673100/6000400	3.2.98; 6.7.05; 29.2.08; 30.1.10	2.62 (±0.06); 1.75 (±0.04); 1.76 (±0.06); 1.80 (±0.05)	27.02.07; 2.12.13	5.84 (±n/a); 10.0 (±1.7)	27.2.07; 2.12.13	286 (±7); & 581 (±11); 272(±30); & 607 (± 58)
2	Mahoe St	2672219/5997514	6.07.05; 5.03.09	1.80; 1.69	27.02.07	4.75 (± 0.48)	-	-
13	Hutt GC	2673362/5999592	29.5.13	1.699 (±0.04)	-	-	-	-
14	Bloomfield	2671470/5997916	In 2002: 25.7.; 15.8.; 19.9.; 17.10.; 15.11.; 16.12.; In 2003: 16.1. 17.2.; 4.3.; 15.4.; 1.5.	(all ±0.04) 1.87; 1.97; 1.90; 1.82; 1.86; 2.03; 1.88; 1.90; 1.88; 1.91; 1.93	-	-	-	
5	Somes Island	2666233/5992581	6.9.72; 15.2.97; 16.11.99; 19.5.02; 22.8.04; 24.2.07; 11.10.08; 5.6.10; 5.3.13	0.97 (±0.08); 2.59 (±0.11); 1.78 (±0.06); 1.61 (±0.04); 1.26 (±0.04); 0.92 (±0.03); 0.96 (±0.04); 0.84 (±0.04); 0.77 (±0.02)	19.05.02; 24.02.07	0.31 (±n/a); 0.14 (±n/a);	-	-
1	Buick Street	5996330/2667750	30.11.10; 6.3.13	1.14 (±0.04); 0.98 (±0.03)	30.11.10; 6.11.13; 2.12.13	2.72 (±0.23) 2.90 (±0.19) 2.77 (±0.23)	30.11.10	20.5 (±3.5) & 379 (±27)
4	IBM No 2	2667000/5996210	27.12.96; 21.12.98; 11.1.00; 20.5.02; 18.6.03; 2.3.05; 19.3.07; 27.6.08; 18.9.10 6.3.13; 29.5.13	2.87 (±0.12); 2.23 (±0.06); 2.20 (±0.06); 1.79 (±0.04); 1.68 (±0.04); 1.49 (±0.05); 1.31 (± 0.04); 1.17 (±0.04); 1.07 (±0.03); 0.25(±0.02); 0.46(±0.02)	20.05.02; 19.03.07; 2.12.13	1.74 (±0.17); 1.98 (±0.20); 2.03 (±0.26)	20.05.02; 19.03.07; 29.05.13	2.5 (±n/a) & 60.1(±n/a); 193 (±n/a) & 1474(±n/a); 1.1 (±1.6) & 51.2 (+/16.2);
7	TS Tamatoa (sh)	2667033/5995965	24.5.07; 29.5.13	1.50(±0.05); 0.82 (±0.03)	-	-	-	-

Well #	Well name	Easting /Northing	Tritium data		SF ₆ data		CFC-11 & CFC-12 data	
			date	Concentration [TU]	date	Concentration [pptv]	date	Concentration [pptv]
3	Seaview Wools	2669950/ 5994230	16.5.02; 21.12.05 2.02.11	1.64 (± 0.07); 1.37 (± 0.04); 1.17(±0.03)	16.05.02; 2.12.13	2.74 (±0.27); 3.65 (±0.50)	-	-
9	TS Tamatoa (deep)	2667033/ 5995965	2.5.07; 29.5.13	0.15 (±0.04); 0.09 (±0.02)	-	-	-	-
10	Hutt Hospital	2673438/ 5998720	29.05.13	1.71 (±0.04)	-	-	-	-
8	McEwan Park	2669656/ 5995140	24.5.07; 29.5.13; 29.5.13	1.5 (±0.05); 1.15 (± 0.03); 1.16 (±0.07)	29.05.13; 29.05.13	4.99 (± 0.43); 5.03 (± 0.46)	-	-
12	NZTS	2668336/ 5995769	29.5.13	0.98 (±0.03)	-	-	-	-
11	Shandon GC	5995900/ 2668925	8.5.13	1.31 (±0.03)	16.05.02; 7.05.13; 8.05.13	3.37 (±n/a); 5.10 (±0.43); 5.23 (±0.34)	-	-
15	Hutt River	2672804/ 6000103	21.6.13	1.83 (±0.04)	2.12.13	7.14 (±0.56)	-	-
26	IBM 1	2667000/ 5996210	27.12.96; 21.12.98; 10.1.01; 19.3.07	0.17 (±0.02); 0.00 (±0.02); - 0.01(±0.02); 0.02(±0.02)	25.2.05; 19.3.07; 2.12.13	all < LOD (0.2): <0.02; 0; 0	25.2.05; 19.3.07	3 (±n/a) & 4.4 (±n/a); 0.3 (±n/a) & 79.7(±n/a)
27	UWA3	2669835/ 5994960	18.12.98 10.01.01 16.05.02	-0.01(±0.02); 0.00(±0.02); 0.01(±0.02)	16.5.02 2.12.13	all <LOD (0.2): 0.06; 0	16.5.02	0.9 (±n/a) & 2.7(±n/a)
Wairarapa groundwater zone								
16	Finlayson	2696313/ 5986755	5.05.05	-0.005 (±0.021)	3.5.05; 10.12.13	0.38 (± n/a); 1.57 (±0.71)	3.5.05	2.1 (±0.3) & 4.1 (±1.8)
17	Warren	2691376/ 5981438	12.04.83; 28.2.05	0.27 (±0.11); 0.28 (±0.02)	10.12.13	0.12 (±0.01)	-	-
18	Lake Ferry MC	2689300/ 5977370	20.4.83; 28.2.05;	1.22 (±0.14); 0.720 (±0.03);	10.12.13	1.3 (±0.12)	-	-
19	Johnston	2706525/ 6000655	13.7.05; 17.3.09; 3.2.11	1.69 (±0.07); 1.72 (±0.07); 1.68 (±0.07)	3.5.05; 10.12.13	3.85 (±n/a); 6.04 (±0.85)	26.03.07; 11.12.13	67.1 (± 0.7) & 410 (±3); 400 (±40) & 16.9 (±3.6)
20	George	2713369/ 5999061	4.05.05; 16.06.09	1.22 (±0.04); 1.02 (±0.04)	3.5.05; 10.12.13	1.24 (± n/a), 1.65 (±0.1)	3.5.05	0.42 (± 0.60) & 1.39 (±1.97)
21	Pawai Springs	2717500/ 6010730	2.6.83; 6.06.08	3.92 (±0.22); 1.88 (±0.05)	3.5.05; 10.12.13	6.37 (±n/a); 10.6 (±1.3)	3.5.05	1431 (±6) & 917.4 (±5.3)

Well #	Well name	Easting /Northing	Tritium data		SF ₆ data		CFC-11 & CFC-12 data	
			date	Concentration [TU]	date	Concentration [pptv]	date	Concentration [pptv]
22	CDC south	2720489/ 6015999	12.5.05; 5.6.08; 4.2.11	1.41 (±0.06); 1.28 (±0.04); 1.24 (±0.04)	3.5.05; 10.12.13	2.71 (±n/a); 4.43 (±0.34)	3.5.05	112.0 (±0.1) & 19963 (+/135)
23	Duffy deep	2737500/ 6023500	28.4.83; 3.5.05; 19.03.09	5.11 (±0.26); 1.08 (±0.03); 0.96 (±0.03)	3.5.05; 10.12.13	1.45 (±0.02); 3.19 (±0.12)	3.5.05	5.29 (±0.11) & 252.7 (+/4.4)
24	Trout Hatchery	2732160/ 6024730	-	-	3.5.05; 10.12.13	5.39 (±0.04); 9.12 (±1.14)	3.5.05	237.4 (±1.8) & 565.3 (+/1.4)
<i>Wainuiomata aquifer</i>								
25	Wainuiomata	2672300/ 5987500	7.7.05; 29.2.08	1.59 (±0.06); 1.62 (±0.06)	27.2.07; 10.12.13	6.14 (±n/a); 8.18 (±1.09)	27.2.07; 11.12.13	192.7 (±0.2) & 1455 (±27); 191.2 (±21.5) & 1055 (± 102)

Appendix B – for Chapter 4

This Appendix contains a summary of compounds that potentially co-elute with Halon-1301 (B1), details on the analytical procedure used in Chapter 4 (B2), detailed information on the correction of excess air and headspace (B3), calibration curve established with larger amounts of Halon-1301 than contained in modern water to assess the linearity of the calibration curve beyond concentrations obtained in water (B4), detailed assessment of reduced concentrations of Halon-1301 in anoxic water (B5) and proposed methods for an improved determination of Halon-1301 (and SF₆) to increase their application range as age tracers (B6).

B1 Potentially co-eluting compounds with Halon-1301

B2 Details on analytical procedure

B3 Correction for excess air and headspace

B4 Calibration curve established with larger amounts of Halon-1301 than contained in modern water

B5 Detailed assessment of elevated Halon-1301 ages

B6 Proposed methods for an improved determination of Halon-1301 (and SF₆)

B1 Potentially co-eluting compounds

Structurally similar compounds with similar boiling point and size compared to Halon-1301 are likely to co-elute with Halon-1301. Rosiek et al. (2013) concluded that CFC-13 had a similar retention time to Halon-1301. They used the same column type used in this study, but of longer length (Carbograph 1AC coated with 1% AT-1000, 8 m instead of 3 m). Their chromatogram also shows that there may be an additional potentially co-eluting non-specified compound (see signal peak at around 13 min in Fig. 5 in their publication), when the shorter (3 m) column is used. Other potentially co-eluting compounds can be found in Miller et al. (2008) and Sousa and Bialkowski (1997), who used different but comparable GC columns (CP-PoraBond Q and Poraplot Q, respectively). A summary of compounds which could potentially co-elute with Halon-1301 is given in Tab. B1. Table B1 also summarizes LODs and LODs in relation to CFC-12 obtained using an ECD (in pptv in 1 L gas at STP), current atmospheric concentration and amount of present day air needed to obtain concentrations greater than LOD. It should be noted that these reported LODs should only be considered in a relative sense, since their absolute values are dependent on the performance of the LOD such as electron source or signal type (analogue signals vs counter based signals), among other things. The ratio of reported LODs between compounds can be used to get a feeling about the relative range of LODs, although it should be noted that LODs reported for SF₆ in relation to CFC-12 vary greatly (the ECD is reported to be 4.8 to 700 times less sensitive to SF₆ than CFC-12).

Overall it can be seen that the ECD is significantly less sensitive towards the majority of potentially co-eluting compounds listed in Table B1. As a result of their relatively high LODs and low atmospheric concentration interference with the Halon-1301 signal is highly unlikely, when calibrated air or custom made standard gases are analysed in this study. Potentially interfering compounds are SO₂F₂ and HCFC-22 (CHClF₂) due to their relatively low LOD and high atmospheric concentration. Both compounds were present in the calibrated air standard, but lacking in the custom made NZIG and NOAA standard.

Potentially higher solubility in water of potentially co-eluting compounds compared to Halon-1301 may lead to higher concentrations in water and therefore a possibility of interference with the Halon-1301 signal. This is only an issue when the water is analysed using the vacuum sparge system used in this study, but not using the equilibrium spray-technique used in Busenberg and Plummer (2008). Absolute solubility data of all potentially co-eluting compounds are not available or sparse. Relative water solubilities were inferred from estimated water solubilities at saturation using the ALOGPS 2.1 software [Tetko et al., 2005]. It can be seen that HCFC-22 is significantly more soluble than Halon-1301 or CFC-13. However HCFC-22, similarly to other HCFCs and the CFCs, is prone to microbial degradation [Chang and Criddle, 1995; Balsiger et al., 2005 and references therein], which may reduce concentrations in water to below LOD.

*Table B1: Potentially co-eluting compounds with Halon-1301, their LOD using an ECD, atmospheric concentration and estimated solubility in water at saturation using ALOGPS 2.1 software [Tetko et al., 2005] (SF₆ is not potentially co-eluting with Halon-1301, but given for comparison of LOD), atmospheric concentration data: ~ http://cdiac.ornl.gov/ftp/ale_gage_Agase/AGAGE/gc-ms-medusa/complete/ in NH (Jungfraujoch) and SH (Cape Grim); LOD data from: * Sousa and Bialkowski (2001); + Plummer et al., (2008); # Vollrath et al. (1995); % Rosiek et al. (2013); x Qu et al. (2000) (sample V unknown, assumed to be 1 L); @Reuter et al. (2010); \$ Śliwka et al. (2010); & Darling et al. (2010); ! Labasque et al. (2014); ^van der Raaij and Beyer (2015).*

Compound	LOD in 1 L @ STP [pptv]	Atm. conc. NH/SH [pptv] (volume for LOD [L])	LOD relative to CFC-12	Estimated solubility in H ₂ O @ saturation [mmol/L]
carbonyl sulphide (COS)	Not sensitive	-	-	-
Sulfuryl fluoride (SO ₂ F ₂)	0.4 ^x	2.0/1.7~ (0.20/0.24)	n/a	n/a
PFC-218 (CF ₃ CF ₂ CF ₃)	n/a	0.59/0.56~ (n/a)	n/a	0.78
HFC-143a (CH ₃ CF ₃)	n/a	7.4 ⁺ /n/a (n/a)	n/a	302.00
HFC-125 (CF ₃ CHF ₂)	2,650*	13.0/10.8~ (204/245)	5,600*	67.61
CFC-115 (CClF ₂ CF ₃)	1,700 [#]	8.5/8.4~ (200/202)	37 [#]	3.02
HFC-152a (CH ₃ CHF ₂)	> 17,000*	9.1/4.3~ (1,900/4,000)	>20,000*	n/a
HFC-134a (CH ₂ FCF ₃)	10,000*	75/65~ (133/154)	18,000*	181.97
HCFC-22 (CHClF ₂)	23.6 *	233/212~ (0.10/0.11)	36*; 89 [@]	549.54
Sulfur hexa-fluoride (SF ₆)	0.06 [^]	7.8/7.5~ (0.008/0.008)	4.8 ⁺ ; 38 ^{\$} ; 100 ^{&} ; 700 [!]	n/a
Halon-1301 (CF ₃ Br)	0.011 [%]	3.3/3.3~ (0.003/0.003)	1.5 ^{@%}	131.83
CFC-13 (CF ₃ Cl)	0.186 [%]	5.3 (0.035)	25.4 [@] ; 17 [%] (relative to Halon-1301)	60.26

Overall the agreement of Halon-1301 signals per mole in calibrated air (containing various other compounds, such as HCFCs) and a standard only containing Halon-1301 and SF₆ (linear calibration curve established using both standards), as well as agreement of inferred atmospheric concentration from modern water samples and modern atmospheric concentration, demonstrated that co-elution is not likely to be a major problem.

B2 Details on analytical procedure

For the purpose of this study, the author is confident that the analytical setup used in this study is comparable to that of Busenberg and Plummer (2008). The details of this study's analytical setup are described in the following.

The analysis included the separation of the compounds on a 30 cm 0.32 mm OD stainless steel pre-column packed with mole sieve 5 (80-100 mesh) and a 3 m long 0.32 mm OD stainless steel column filled with 60/80 mesh Carbograph 1AC coated with 1% AT-1000. Subsequently the trace gases were trapped at -72 °C and released at 95 °C from two consecutive traps, a 90 cm long 3.2 mm OD stainless steel trap packed with Porapak Q (800-100mesh) and a 10 cm 3.2 mm-OD trap packed with 5 cm Porapak T and 5cm Poracil C. The carrier gas flow (N₂) was set to 20 ml/min at 75 °C and subsequent analysis was carried out on a Shimadzu GC2014 using a Shimadzu ECD-2014 set at 345 °C and 2 nA and amplification at 10⁰.

To ensure representativeness of results, many replicates were analysed under varying conditions (pressures and volumes) at ambient temperature. Hundreds of standard gas samples, including replicates, of 10 and ~200 ml volume at 0.1 to 1 bar and pressures ranging from 1 to 20 bar of a calibrated air standard (prepared by Scripps Institution of Oceanography) and a custom made standard gas (prepared by NOAA) were analysed, respectively. Tens of samples of a Halon/SF₆ standard gas (prepared by New Zealand Industrial Gases) were also analysed at volumes of 0.205 and 10 ml and pressures ranging from 0.1 to 1 bar. Additionally 1 L (river and tap) water samples were analysed in triplicates.

B3 Correction for excess air and headspace

Due to degassing of the water sample after sampling, a gas bubble/headspace can form in the sample bottle which are recorded and accounted for when analysing water samples in this study. Not taking account of headspace can lead to an underestimation of total amount of Halon-1301 (and SF₆) in the water sample during analysis since gas bubble can contain a significant amount of Halon-1301 (and SF₆) depending on its size (both Halon-1301 and SF₆ are highly volatile). The amount of Halon-1301 (and SF₆) 'lost' into the bubble (headspace) was determined using the solubility relationships as described earlier and the method described in Pankow (1986). The total amount of Halon-1301 (and

SF₆) contained in the sample was then determined as the sum of Halon-1301 (and SF₆) contained in the bubble/ headspace and (dissolved) in the water sample (determined via analysis).

Additionally the total amount of Halon-1301 (and SF₆) in the sample was corrected by excess air trapped in the sample during recharge following the method described in Pankow (1986). If not accounted for, trapped excess air can introduce additional amounts of Halon-1301 (and SF₆) into the sample which can lead to an overestimation of the total amount of Halon-1301 (and SF₆) in the water sample when the sample is analysed. Excess air data, which had been determined with the aid of dissolved Ar and N₂ concentrations (after Heaton and Vogel (1981)), were provided by GNS Science.

B4 Calibration curve established with larger amounts of Halon-1301 than contained in modern water

Figure B1 illustrates the calibration curve when using larger amounts of Halon-1301 than contained in modern water (using the highly concentrated NZIG standard gas) showing a fairly linear relationship between Halon-1301 concentration (here volume/pressure of the analysed standard gas and water sample).

Figure B1: Assessment of linearity of the ECD signal towards Halon-1301/CFC-13 (the peak with retention time of 2.9 min) using 10ml modern air at different pressures (LEFT) and water at different volumes (RIGHT) showing an almost linear signal to pressure/volume (UPPER) and acceptable residuals (LOWER), lines in upper graphs represent the best least square fit, fit with standard deviation of slope and 95% confidence interval

B5 Detailed assessment of elevated Halon-1301 ages

B5.1 Analytical issues

Calibration curve

The calibration curve was linearly up-scaled for concentrations that were not covered with the calibration curve established with calibrated air (at the time of analysis of groundwater samples in this study, only calibrated air was available). This may have introduced additional uncertainty, but was considered fairly minor (see fairly linear calibration curve for larger amounts of Halon-1301 than contained in 1 L modern water). The slight non-linearity of the 'true' calibration curve relationship would have mostly affected the modern water samples – only one of the five affected groundwater wells with an apparent reduced concentration of Halon-1301 (Well 19 and with 3 years tritium MRT). It was considered unlikely that uncertainties related to calibration would have caused the significant differences in concentrations/ inferred ages observed for the older groundwater age sites (e.g. Well 3 with ca. 16 years MRT obtained with tritium and SF_6), hence cannot explain the found reduced concentrations (higher inferred ages) of Halon-1301 in Well 20, 1, 22, 4 and Well 3.

High uncertainty in inferred age for water recharged before 1975 and after 2000

Results of uncertainty calculations showed an overall average relative uncertainty of 4.6 % for Halon-1301 determination. Due to its characteristic S-shaped input function (less difference in concentration from year to year before 1975 and after about 2000), a larger uncertainty in inferred piston flow age was faced for waters recharged before 1975 and after about 2000. In Well 19 and potentially Well 22 higher uncertainties due to a reduced growth rate may explain reduced Halon-1301 concentrations (compared to other gaseous tracers). However, significantly reduced Halon-1301 concentrations in the remaining affected groundwater of higher MRT were considered unlikely to have been caused by a reduced growth rate and/or seasonal fluctuations in atmospheric Halon-1301 concentrations, because these were recharged before 2000 and after 1975.

Interference of the Halon-1301 signal with co-eluting compounds

As shown in Chapter 4, the interference of the Halon-1301 signal with co-eluting compounds, such as CFC-13, did not appear to be a major problem when (calibrated) air was analysed, due to the lower sensitivity of the ECD towards CFC-13 and potential co-eluting compounds at concentrations present in air. The same applied for water samples. However interference of the Halon-1301 signal with signal from other compounds in groundwater could not be excluded in this study, because contamination of the water with potentially co-eluting compounds could not be excluded.

Since the interference with the CFC-13 signal could be excluded in (calibrated) air, it was considered unlikely that reduced concentrations of Halon-1301 (compared to other gaseous tracers) have been caused by an erroneous calibration curve that had been affected by interference of co-eluting compounds. Similarly, it was considered unlikely that reduced concentrations of Halon-1301 have been

caused by interference of the Halon-103 signal with co-eluting compounds in groundwater, because this would lead to increased inferred concentrations.

B5.2 Halon-1301 property related issues

Degradation

Similarly to the CFCs, degradation of Halon-1301 only appeared possible in anoxic conditions. The groundwater wells where reduced concentrations of Halon-1301 occurred were Well 1, 20, 3, 4 with a DO of 0.26, 0.02, 0.2, and 0.3 mg/L, respectively and methanogenic Well 23. In all wells anoxic conditions could have allowed for degradation of Halon-1301 which would have led to reduced Halon-1301 concentrations (in concert with reduced CFC concentrations as found in the majority of these wells). However, further study is needed to verify that reduced Halon-1301 concentration have been caused by degradation in these wells.

Lag-time in unsaturated zone

Differences in gas ages and tritium age can also occur, due to diffusive travelling of tracer gases through the unsaturated zone and associated lag-time [Cook and Solomon, 1995]. The time lag is a function of the tracer's diffusion coefficient, tracer solubility in water, and soil water content [Weeks et al., 1982; Cook and Solomon, 1995]. Goody et al. (2006) simulated lag-times for SF₆, CFC-11 and CFC-12 and showed lag-times in order SF₆ < CFC-12 < CFC-11 in the given environment, which only resulted in a significant age difference with unsaturated zone depth of more than 10 m. An existing lag-time would have affected all gas tracers (including SF₆). A decreased concentration of Halon-1301 and SF₆ (and the CFCs) was not observed for any of the sites.

Degassing

Degassing of gas tracers into gas bubbles/headspace created due to de-nitrification, production of methane or when groundwater is brought to the ground surface may have occurred [Blicher-Mathiesen et al., 1998; Fortuin and Willemsen, 2005; Visser et al., 2007]. However this should have also affected SF₆ concentrations, actually to a higher extent than Halon-1301, due to its lower solubility in water compared to Halon-1301. Reduced Halon-1301 concentrations were not observed along with even further reduced SF₆ concentrations at any affected site. Hence degassing could not explain reduced Halon-1301 concentrations in this study.

Adsorption in aquifer or material used

Another reason for the offset in determined Halon-1301 ages in regard to SF₆ and tritium ages is potential absorption to organic material and therefore retardation in the aquifer (as reported for the CFCs in e.g. Cook et al. (1995) and Brown (1980)). This could not be excluded for any site, because little is known regarding the sorption behaviour of Halon-1301. Reported estimated K_{oc} values for Halon-1301 vary highly ranging from moderately mobile to very mobile (organic carbon coefficient (K_{oc}) of 244.8 (e.g. Ansul Incorporated (2009) and other safety data sheets) or 49 (estimated, using a log K_{ow}

of 1.86 [Hansch et al., 1995] and a regression-derived equation [Lyman et al., 1990]) or 102 (estimated by Montgomery (2007) using the method by Chiou et al. (1979)).

Sorption to well casing or sampling equipment may also lead to reduced gas tracer concentrations of certain (halo-)carbons, particularly if of certain plastic material other than the recommended Nylon and glass ware [Glenn et al., 1990]. It is assumed that the effect of sorption to sampling equipment or well material in this study was of minor importance, since the time the water was in contact with the well or sampling material was very short in the order of seconds to minutes which could not allow a large difference in Halon-1301 concentration.

B6 Proposed methods for an improved analytical determination of Halon-1301 (and SF₆)

The application range of Halon-1301 (and other compounds) as groundwater age tracers is limited, due to their specific atmospheric trend and limitations of their determination in water (i.e. the LOD and uncertainty of the determination) as demonstrated in Chapter 4 (for Halon-1301) and Chapter 5 of this thesis (for Halon-1301, SF₆ and tritium). Generally, there are two principle ways to improve the analytical determination of any compounds in any medium 1) the analysis needs to be improved (i.e. the sensitivity of the analysis towards the compounds needs to be increased) and 2) the sampling needs to be improved to collect or up-concentrate larger amounts of the compounds for subsequent analysis. Both approaches are in the following applied on the determination of Halon-1301 and SF₆ in water using the sampling and analytical method presented in Chapter 4. Firstly the limitations (particularly in regard to the relatively poor uncertainty in determination and LOD) of the currently used analytical method for determination of Halon-1301 and SF₆ are highlighted. It is then shown that the LOD and uncertainty of the determination can be significantly improved by the use of signal processing. Secondly, the limitations of the currently used sampling methods are highlighted and alternative approaches which are currently used for sampling of (other) gaseous substances in water are presented and discussed.

Due to time constraints of this PhD the potential of these alternative sampling methods and signal processing could not be fully assessed, but these are presented here in hope that subsequent studies will (further) assess their potential to improve the determination of Halon-1301 (and SF₆ and other gaseous tracers) in water to extend their application range as groundwater age tracers.

B6.1 Proposed signal processing method for the determination of Halon-1301 and SF₆

B6.1.1 Introduction

The determination of Halon-1301 (and SF₆) with the current GC/ECD (gas chromatography with attached electron capture detector) setup presented in Chapter 4, which is similar to the one developed by Busenberg and Plummer (2008) is restrained due to poor repeatability and high

uncertainties related to the establishment of the calibration curve (as presented in Chapter 4 and 5). Poor repeatability and large uncertainties in the calibration curve may be a result of disturbance of both compounds' signals in the chromatogram, particularly at very low concentrations. In general, disturbances of GC signals can be caused by high frequency background noise induced by electrical disturbances (e.g. electromagnetic and electrostatic interference from cables and wiring) and/or low frequency background (drift) induced by methodological disturbances (e.g. temperature or pressure variation or contamination of the GC column in some instances leading to ghost peaks). Figure B2 illustrates a typical chromatogram obtained when analysing a 1 L water sample containing SF₆ and Halon-1301 with the analytical setup presented in Chapter 4. It can be seen that the signals of both analytes are sufficiently large for a young water sample (e.g. 1 year old in Fig. B2). However, when determining an older groundwater sample (e.g. 50 years in Fig. B2) with significantly lower concentration of SF₆ and Halon-1301, the effect of background variations and noise on their ECD signals increases significantly.

Figure B2: GC/ECD chromatogram of 1L modern (1 year) & older (50 years) water sample containing SF₆, CFC-13

In chromatography two approaches have been commonly used to improve the recovery of analyte signals (particularly of low concentration/low signal analytes) as illustrated in Fig. B3 (after Pierce et al. (2012)). These are: 1) signal enhancement and 2) noise reduction/removal. For best signal recovery both approaches should be applied complementarily. In the following both approaches are further detailed and their effect (and potential improvement) on the simultaneous determination of Halon-1301 and SF₆ is assessed.

Figure B3: Approaches to increase determination of low concentrations/ low signal compounds

Signal enhancement involving hardware adjustments

Adjusting the analytical setup (hardware), such as choosing an appropriate detector and adjusting GC and detector settings (such as temperature), to enhance the signal recovery of one or more analytes is a relatively simple standard procedure in chromatography [e.g. Scott, 2009]. However, this approach is often not satisfactory if one aims to improve the determination of multiple analytes in a chromatogram, as encountered in this study. When adjusting the GC and ECD temperature, GC flow and ECD current to enhance the signals of both SF_6 and Halon-1301 in this study, significant improvement of both compounds' determination could not be achieved simultaneously. Note that the pressure peak that is interfering with the SF_6 signal in Fig. B3 could not be resolved without reducing the Halon-1301 signal at the same time and vice versa.

Since the potential of Halon-1301 as a new groundwater age tracer (and its simultaneous determination with SF_6) had been first highlighted in this study (detailed Chapter 4), little study has been done to identify the most appropriate detector for the simultaneous determination of Halon-1301 and SF_6 in water that could potentially improve the determination of both compounds compared to their determination with the current analytical setup (presented in Chapter 4). One study by Rosiek et al. (2013) assessed different detector setups for the determination of SF_6 and Halon-1301 (although they did not provide full evidence that the signal believed to be caused by Halon-1301 was actually caused by Halon-1301). They suggested the use of two custom-made ECDs in resonance mode instead of a single ECD (as used in this study following the suggestion of Busenberg and Plummer (2008)) which significantly improved the signal recovery of Halon-1301 and most other compounds in the chromatogram (e.g. SF_5CF_3) but not SF_6 . Further study is needed to assess if other detector(s) and/or detector setups may be able to improve the determination of both SF_6 and Halon-1301 simultaneously.

Noise reduction/removal involving software adjustments

Although the advantages of signal processing for reduction and removal of disturbances (i.e. noise) and increase of signal recovery is known for decades, it is not commonly carried out in chromatography [e.g. Smit and Walg, 1975; Vilianti, 1980; Alciaturi et al., 1998; Stewart et al., 2011] and has also never

been applied to assess the potential improvement for the simultaneous determination of the Halon-1301 and SF₆. Signal processing is sparsely fully applied, because its components are specific for each analysis (depending on the nature of noise and signal) [Di Marco and Bombi, 2001 and references therein; Stewart et al., 2011]. For convenience often conventional GC software is used (e.g. Shimadzu's GCsolution®, Agilent's ChemStation® or Leco's ChromaTOF®) which is provided with the analytical system. However, conventional chromatography data processing software has limited data processing options (e.g. often only the sampling rate and filter/bunching rate can be adjusted) [e.g. Shimadzu, 2001; Angilent Technologies, 2009; Leco Corporation, 2011]. Data processing options are often chosen in a trial and error approach until the best analyte peak resolution is obtained, which can be very time consuming and inaccurate, and the resolution of one signal is often sacrificed for poorer resolution of others in the same chromatogram [e.g. Shimadzu, 2001; Agilent Technologies, 2009]. Peak integration with conventional chromatography data processing software (not well documented) often involves defining a signal threshold above which a peak is defined or setting a fixed start/end time of the peak based on the retention time of the analyte. In other cases, manual integration is necessary due to a variable background signal (e.g. background drift) or interference with 'ghost peaks'. Adequate resolution of overlapping signal peaks can often not be achieved with conventional data processing tools, because it does not allow for assessment of the shape and nature of the signal which is necessary for choosing an appropriate peak integration technique [Dyson, 1998; Di Marco and Bombi, 2001].

As an alternative to conventional GC software, software packages/codes have been developed to provide more (targeted) options for processing of chromatographic data (e.g. 'Chromeleon' [Dionex Corporation, 2001], 'PyMS' [O'Callaghan et al., 2012] and 'AMDIS' [Nair et al., 2013]), although research has shown that the larger amount of available processing options can often be misleading resulting in inadequately processed signals [e.g. Shoval, 2001; Fagan, 2011; de la Mata et al., 2012; Zhou, 2013; Giovanelli, 2014]. For more targeted data processing, custom made data processing has been developed that based on assessment of the nature of signal and noise [e.g. Shoval, 2001; Fagan, 2011; de la Mata et al., 2012; Zhou, 2013; Giovanelli, 2014]. These custom made tools make use of signal filtering to reduce the effect of background noise on the analyte signal. For removal of e.g. high frequency (white) noise, a low pass filter has been successfully applied. However, the removal of low frequency noise and/or noise with a similar frequency as the analyte signal has been proven difficult (without affecting the analyte signal itself) [Stewart et al., 2011 and references therein]. Aside from signal filtering, a variety of peak integration techniques have been used to eliminate or significantly reduce the effects of low frequency noise [Dyson, 1998; Di Marco and Bombi, 2001]. Signal averaging techniques (e.g. boxcar, median, Savitzki-Golay or weighting average filter) have also been used to reduce noise, but these do significantly affect the analyte signal(s) [Pierce et al., 2012]. Despite the advantage of custom made targeted data processing, these have been developed for processing of

specific data and are often not widely transferable. In this study a relatively simple and easily applicable (possibly widely transferable) custom-made data processing method is presented. It is demonstrated that the method can be used to significantly improve the signal recovery of both Halon-1301 and SF₆ simultaneously on the analytical setup presented in Chapter 4 (similar to the one developed by Busenberg and Plummer (2008)).

B6.1.2 Method

General method overview

The method used to significantly improve the signal recovery of both Halon-1301 and SF₆ (simultaneously) in this study is illustrated in Fig. B4. It involves the identification of the nature of the signal (in particular its shape for targeted customized signal peak integration) and noise (e.g. high/low frequency noise for targeted application of a customized low/high frequency pass filter, respectively), as detailed in the following.

Firstly Fourier transformation of the 'raw' (unfiltered) chromatogram (time domain) into the frequency domain is carried out, which enables identification of noise and data structure [e.g. Lam and Isenhour, 1981]. Secondly, assessment of the frequency spectrum is carried out to identify an approximate 'cut-off' frequency below/above which data are removed while still within the Fourier domain to reduce low/high frequency noise components, respectively. To allow for the most appropriate choice of the 'cut-off' frequency, the data are run through not only the selected 'cut-off' frequency but also six additional frequencies three above and three frequencies below (in 2Hz increments)⁹². The data are then back transferred into time domain (using inverse Fourier transformation) and the filtered chromatograms (and their derivatives) are inspected to select the most appropriate 'cut-off' frequency. Most appropriate noise removal is indicated by a near horizontal, smooth baseline of the chromatogram and improved analyte signals. An unsteady baseline after application of this approach to filtering frequencies may have indicated a too high 'cut-off' frequency (leading to 'under-filtering' and insufficiently removed noise) or a too low 'cut-off' frequency (leading to 'over-filtering' and additional induced noise). The type of filter (high or low frequency) is chosen based on the nature of the noise (as indicated in the chromatogram and/or frequency spectrum) and best removal of the noise (as indicated in the filtered chromatogram). After running the data through the selected filter (e.g. high/low pass filter) at the specified 'cut-off' frequency, the most appropriate peak integration technique (e.g. Gaussian peak integration) is selected based on the nature/shape of the signal (e.g. near Gaussian peak shape). The used 'filtering' method is very simple and easy to apply, but needs further assessment regarding artefacts and wide transferability for general application.

⁹² These can be adjusted if appropriate. Optionally a factor multiplication of the Fourier transformed data can be applied to resolve issues related to overlapping signal peaks [Engblom, 1990].

Figure B4: Simplified schema of methodology used to improve the signal recovery of both Halon-1301 and SF₆ (simultaneously) in this study

The data processing part of the method (i.e. application of the high/low pass frequency filter and selection of the ‘cut-off’ frequency) have been coded up in Matlab software R2012a. Since the removal of high frequency noise (with a low pass frequency filter) most significantly improved the signals of Halon-1301 and SF₆, a low pass frequency filter is implemented into the code, but this be easily adjusted for the use of a high (or both high and low) pass frequency filter. The script is provided with the accompanying CD including a user manual and an example data set. For peak integration and selection of the most appropriate peak integration method, the interactive peak fitter (developed by O’Haver (2012)) was used. The method (and Matlab code) is potentially widely transferable and easily applicable for processing of chromatography or related data for which high/low pass frequency filtering is appropriate. In the following the specific method components used for improvement of the determination of SF₆ and Halon-1301 in groundwater are detailed.

Specific method components for demonstration on SF₆ and Halon-1301

The GC/ECD system (described in Chapter 4 of this thesis similar to the one presented in Busenberg and Plummer (2008)) was used to determine the concentrations of Halon-1301 and SF₆ in groundwater. To allow for an improved signal recovery (determination) of both Halon-1301 and SF₆ (simultaneously), the customized data processing (described above) was applied on ‘raw’ ECD signals (recorded at the smallest sampling and filter rate (4ms) at the detector). For comparison, conventional GC software (GCsolution software from Shimadzu Ver.2 (Columbia, MD, USA)), was used in which the filtering and sampling rate was adjusted to achieve the best separation of the Halon-1301 and SF₆ signals and noise (following the instructions given in the user manual [GCsolution, 2001]). A filtering rate of 200 ms and sampling rate of 20 ms led to (visually) best recovery of the Halon-1301 and SF₆ signals. Signal peak integration was carried out by manual adjustment of the start and end time of the signal peaks (as supposed to an automatically set start and end time based on a signal threshold or set retention time), because an automatically set start and end time of the peak did not allow for adequate integration of the SF₆ peak (due to disturbance of the pressure peak with the SF₆ signal).

When using the custom data processing, it was found that a low pass frequency filter with a cut-off frequency of ca. 12 Hz (see Fig. B5) best removed the high frequency noise from the chromatogram.

Since the SF₆ and Halon-1301 signal peaks in the chromatogram appear to follow a normal distribution and it is generally believed that compounds exiting the GC or other chromatography follow a normal distribution [Scott, 2009], Gaussian peak integration was used. The start end time of the Gaussian peak integration was determined from the 1st derivative of the data.

Figure B5: Frequency spectrum

Both conventional and customized data processing and peak integration were applied to a total 87 chromatograms. For each analyte (SF₆ and Halon-1301) 30 calibration curves (least square fit, forced through 0/0)⁹³ were established by analysing 10ml (at ambient temperature and pressures up to 1 bar) of a custom made standard gas containing 29.3 ppt ± 0.2 Halon-1301 and 10.97 ppt ± 0.04 SF₆, supplied by National Oceanic and Atmospheric Administration (NOAA). Fifty % of the calibration curves were established with data processed with the conventional data processing and the remainder were established with data processed with customized data processing. To reduce effects of changes in the GC/ECD performance (e.g. reduced sensitivity due aging of column fill) or user induced changes (e.g. better performance with more practice), all calibration curves were determined within a short period of time (2 days) applying custom and conventional data processing in alternation.

To compare the performance of each data processing tool with regard to an improved determination of Halon-1301 and SF₆, relevant calibration curve statistics such as the coefficient of determination (R²), standard deviation (SD) of the slope of the calibration curve and the signal as well as the limit of detection (LOD) and limit of quantification (LOQ) were determined. The linear fit and statistics (R², SD, slope, etc.) were obtained using the Excel LINEST function. LOD and LOQ were estimated by taking into

⁹³ Blank samples (only containing N₂) were analysed which indicated 0 signal for SF₆ and Halon-1301. In addition the statistical difference between the intercept of the calibration curves for SF₆ and Halon-1301 (when not forced through 0/0) were not significant (at 99% confidence). The intercept of the calibration curve was therefore considered insignificantly different from 0, hence the calibration curve was forced through 0/0 to simplify the calibration procedure and to ensure 0 signal is interpreted as a concentration of 0 (fmol/L, e.g.). This procedure is following the suggestion of Helsel and Hirsch (2002) and Caulcutt and Boddy (1983).

account the slope and standard deviation (SD) of the data (Eqn. B1 and B2) [Shrivastava and Gupta, 2011]:

$$LOD = 3.3 SD/slope \quad \text{Eqn. B-1;}$$

$$LOQ=10 SD/slope \quad \text{Eqn.B-2}$$

B6.1.3 Results

Custom data processing visually effectively reduced the effect of the low frequency noise on the chromatogram in contrast to the chromatogram obtained after conventional data processing which still showed a significant effect of noise on the Halon-1301 and SF₆ signal (Fig. B6).

Figure B6: Example chromatograms obtained when using conventional data processing (left) and custom processing (right), not that the right chromatogram (obtained when analysing calibrated air) contains an oxygen peak, which is not contain in the left chromatogram (obtained when analysing water)

Table B2: Statistics summary of 10 linear regressions of SF₆ and Halon-1301 including average, best and poorest outcome of R², standard deviation of response (y) and standard error of slope, using conventional and developed post-analysis; improved data are highlighted in bold, note: all calibration curves are forced through zero (zero signal - zero compound)

Compound	Statistics parameter	Data processing method			
		Custom	Conventional	Custom	Conventional
		Average	Average	SD	SD
SF ₆	slope	4469.6	4653.1	236.1	189.8
	SD of slope	53.42	93.43	32.82	49.88
	R2	0.9993	0.9979	0.0007	0.0019
	SD of signal (y)	300.62	561.23	153.90	292.85
Halon-1301	slope	2448.3	2483.2	130.5	37.9
	SD of slope	24.88	27.35	14.03	15.66
	R2	0.9994	0.9993	0.0007	0.0011
	SD of signal (y)	387.78	443.48	218.29	264.87

Average statistics of the calibration curves established for Halon-1301 and SF₆ when applying conventional and custom data processing are summarized in Tab. B2 and illustrated in Fig. B6. As can be seen, the standard deviation and standard error of the calibration curve slope are on average significantly lower and the R² significantly higher when the data were processed with the custom data processing method compared to the ones obtained when using conventional data processing for both SF₆ and Halon-1301. The standard deviation of the response (signal), which is a measure for repeatability, improved 13% and 64% for Halon-1301 and SF₆, respectively and the standard deviation

of the calibration curve slope improved 9% and 43%, respectively, when using the custom data processing method (with respect to data obtained with conventional data processing).

As a result of the improvement in calibration curve statistics a significant improvement (i.e. decrease with respect to conventional GC software) of 43% and 14% for SF₆ and Halon-1301, respectively of the LOD/LOQ with the custom data processing method was achieved as summarized in Tab. B3.

Figure B7: Calibration curves of compound Halon-1301, raw data processed in developed post analysis tool (left) and conventional GC software (right). Diamond shaped points represent data points, solid line is linear least square regression, dashed lines represent 95% prediction interval with upper and lower limits

Table B3: Comparison of average LOD/LOQ of SF₆ and Halon-13012 obtained from calibration curves using conventional or developed post-analysis; improved data highlighted in bold

	LOD (SD) [fmol]		LOQ (SD) [fmol]		Improvement with custom data processing compared to conventional data processing
	Data processing				
Compound	custom	conventional	custom	conventional	
SF ₆	0.23 (0.12)	0.40 (0.20)	0.68 (0.38)	1.20 (0.60)	43 %
Halon-1301	0.52 (0.32)	0.61 (0.35)	1.58 (0.97)	1.84(1.07)	14 %

B6.1.3 Discussion

Please note that the data (e.g. the calibration curve statistics and the LOD/LOQ) presented here are not directly comparable to the data presented in Chapter 4, due to fluctuations in sensitivity of the ECD over time. Note the over 20 % reduced calibration curve slopes for both compounds compared to the data presented in Chapter 4. Relative comparison of the findings, however, can be made. If one assumed that the relative improvement of the calibration curve statistics was independent of the ECD

sensitivity (although this would need to be confirmed in further study), the relative improvement in the standard deviation of the calibration curve found in this study would imply an overall reduced uncertainty of the analytical system to 4.1 and 8.6% compared to uncertainties presented previously of 4.6 and 9.0% for an average modern water sample (average headspace, excess air and recharge temperature). This implies that uncertainty in inferred groundwater age also decreases when using the developed data processing⁹⁴. The improvement in LOD and LOQ implies that we could potentially use a (43 %) smaller water sample to determine SF₆ without compromising the performance of the determination. This also implies that the minimum determinable groundwater age (assuming piston flow) reduces from 1975 and 1979 to 1974 and 1975 for Halon-1301 and SF₆, respectively, when using the custom data processing. Further study is needed to confirm these numbers for the previously observed (higher) ECD sensitivity. However, even if the relative change in calibration curve statistics was dependent on the ECD sensitivity, these findings indicated that custom made (targeted) data processing can potentially significantly improve the determination of Halon-1301 and SF₆ (and potentially other analytes) and improve their application range as groundwater age tracers.

At this stage the proposed data processing is slightly more time consuming than conventional data processing, but it could be setup automatically once the most optimal parameters, such as the most appropriate cut-off frequency, have been determined. The wide transferability of the proposed method needs to be confirmed on other compounds and analytical systems.

B6.2 Proposed sampling techniques for determination of Halon-1301 and SF₆ in groundwater

A range of sampling techniques has been developed to determine highly volatile gases, such as Halon-1301 and SF₆ in water. These techniques often include purging and sampling of headspace (also referred to as 'purge and trap') allowing for sampling of larger volumes of water and/or pre-concentration of the volatile gases and therefore improved determination of volatile compounds in water [e.g. Biziuk et al., 1996; Marczak et al., 2004; Demeetrere, 2007]. In addition cryo-trapping (as often integrated in the analytical setup) is often used for further pre-concentration of the compounds in the gas phase, which is subsequently analysed [Kellner et al., 2004]. Four main sampling/purging approaches have been used for determination of gaseous tracers in groundwater as detailed in the following. Not all of these methods have been used but may be applicable for sampling of groundwater for determination of Halon-1301 and SF₆ and may improve their determination in regard to an improved signal recovery and calibration statistics as well as improved handling (e.g. a reduced sampling times and sampling volumes). These are:

⁹⁴ The actual reduction in uncertainty in the inferred age (distribution) for SF₆ and Halon-1301 is complicated since it depends on the average age and/or the proportion of ages recharged at a specific concentration of Halon-1301 and SF₆, particularly for Halon-1301 since its historic input over the last few decades is non-linear.

- A) The vacuum purge system (as illustrated in Fig. B8) originally developed by Bullister and Weiss (1988) and Smethie et al. (1988) is widely used for determination of SF₆ and the CFCs in groundwater [e.g. Busenberg and Plummer, 2000; this study; van der Raaij and Beyer, 2015]. It involves bubbling of nitrogen (or other inert gas) through a water sample in a chamber of confined volume until all targeted gases are fully removed into the gas phase (and trapped in a cryo-trap), which is subsequently analysed. The determination of the gaseous compounds with this method is limited due to a limited amount of purged water (usually 1 L).
- B) To allow for purging of larger volumes of water the spray equilibrium technique (illustrated in Fig. B9) had been developed by Busenberg and Plummer (2008) which involves continuous pumping and spraying of groundwater into a confined headspace volume until equilibrium between water and gas phase is reached. The apparatus is employed in the field and the headspace samples are stored and transported for analysis in the laboratory. The confined headspace volume limits the amount of gas and analytes that can be determined with this approach (depending on their equilibrium concentration) [Busenberg and Plummer 2008].
- C) Similar to the headspace equilibrium technique, the Venturi sampling technique can also handle larger (unlimited) groundwater sample volumes. The Venturi sampling technique had been developed by Morgenstern and Herbert (1991) for sampling of CO₂ in groundwater. It consists of a Venturi-nozzle (therefore the name Venturi sampler), which allows for improved phase transport and equilibrium between gas and liquid phase due to well mixed water and gas phase by finely dispersed gas bubbles (such as nitrogen or air) in a turbulent water stream (illustrated in Fig. B10). Similar to the headspace equilibrium technique, the Venturi sampler is run until equilibrium between gas and water phase is reached and the amount of gas and analyte that can be determined is limited due to a limited headspace/gas phase volume. Alternatively a trap (e.g. limewater for CO₂) is employed to increase the amount of analyte that can be trapped. This method (including or excluding the trap) has never been used for sampling of gaseous age tracers, such as Halon-1301 or SF₆ in groundwater, but may allow improved determination of these.
- D) To improve sample handling and storage compared to the techniques presented above, passive diffusion may be applicable, which has been demonstrated for the determination of noble gases in groundwater by Gardner and Solomon (2009). A passive diffusion sampler (such as the one employed by Gardner and Solomon (2009)) consists of a membrane permeable for gases, but impermeable for water, which forms a confined space either filled with an inert gas (such as nitrogen) or vacuum (simplified schema in Fig. B11). The sampler is put into groundwater (e.g. in a well) and gas tracers, among other volatile compounds, present in the groundwater diffuse into the sampler. When equilibrium is reached the sampler is withdrawn from the water, closed and transported to the lab for determination of the target gases. This method has the advantage of

simple sample handling in the field, but is limited in regard to sampling time (diffusion can be a slow process – depending on the properties of the gas), water volume and amount of gas phase and target gases that can be sampled.

- E) To improve equilibrium times and sampling of larger water volumes an active diffusion sampler can be used as demonstrated by Loose et al. (2009) and recently Matsumoto et al. (2012) for determination of SF_6 and SF_5CF_3 among other volatile compounds in water. This method takes advantage of a flow through diffusion sampler (or membrane contractor) which benefits from an increased surface area due to the use of membrane fibres (in which the gas phase is located, either pumped through or of a confined volume) and advective water flow around the fibres (illustrated in Fig. B12). The increased surface area decreases equilibrium times compared to the ‘passive’ diffusion sampler presented in D. However this method is not well established and needs further study [Matsumoto et al., 2012], e.g. as currently the analysis for SF_6 and SF_5CF_3 is carried out in the field with a portable analytical system, which may not be practicable for other gaseous substances, such as Halon-1301.

To improve the determination of Halon-1301 and SF_6 the active diffusion sampler and Venturi sampler offer potential alternatives to the currently (most widely) used vacuum sparge chamber and the equilibrium spray technique. To overcome the issues related to sample handling and storage that are faced by all above mentioned sampling methods, it is suggested to employ a trap to sorb the gaseous tracers, such as a solid sorbent trap, or a cryo-trap. A tracer trap can not only potentially simplify handling and storage of gas samples enriched in the target tracers (e.g. Halon-1301 and SF_6), but may potentially further shorten the sampling time due to an increased concentrations gradient. The material/specifics of the trap will be dependent on the tracer properties. For most tracers, such as Halon-1301 and SF_6 , activated carbon is expected to do well. The advantage of using activated carbon (over a cryo-trap) is that it can be applied at ambient temperatures. Subsequent desorption (at higher temperatures and/or increased pressure) would allow for analysis of larger amounts of gaseous substances than currently possible with the sampling methods mentioned above. However, first experiments with activated coal carried out in this study showed, that the method is very sensitive to desorption (and adsorption) temperatures, pressures and times. In addition the most appropriate injection method of the desorbed gases into the currently used GC system (presented in Chapter 4) needs to be found. Full development of this method may need relatively long development times as these are currently not well studied for the pre-concentration of gaseous age tracers.

B6.3 Summary of Appendix B6

The determination of Halon-1301 and SF₆ for the use as groundwater age tracers is limited, due to limitations of the current analytical setup and sampling procedure which affect uncertainty in the determination (i.e. calibration curve statistics), repeatability and the limit of detection and quantification (LOD/LOQ, respectively) of Halon-1301 and SF₆ in groundwater.

This study demonstrated significant improvement of the analytical determination of Halon-1301 and SF₆ (in terms of uncertainty in the calibration and LOD/LOQ) can be achieved with the aid of a relatively simple targeted (custom) data processing method (which included a low pass frequency filter and Gaussian peak integration). This implies that a lower uncertainty and lower LOD/LOQ in Halon-1301- and SF₆- inferred recharge year (or age) can be achieved. The finding also highlights the potential use of smaller groundwater samples without compromising the LOD/LOQ. Although further study is needed to confirm that the performance of the data processing is independent of the ECD sensitivity (only relative comparison of the performance of the developed data processing could be made in this

study due to a fluctuating sensitivity of the ECD (towards both compounds) over time and a decreased ECD sensitivity in this study compared to the ECD sensitivity presented earlier (Chapter 4)), the presented findings highlight the significant potential of an improved determination of both compounds, particularly for SF₆ with a relative simple custom data processing method. The applied processing method was very simple and easy to apply and needs further assessment regarding artefacts and wide transferability for general application.

Available sampling procedures have also been highlighted which may significantly further improve the determination of Halon-1301 and SF₆ in regard to the LOD/LOQ by allowing for sampling of larger volumes and/or increased pre-concentration of both compounds. It is expected that the complementary application of both the most appropriate sampling procedure and the customized data processing can significantly improve the determination of Halon-1301 and SF₆ in groundwater (compared to the currently used method) and extend their application range as groundwater age tracers, due to a reduced LOD/LOQ and lower uncertainties for both compounds. It is hoped that the potential of these sampling methods and data processing will be more fully assessed in the future.

B7 References of Appendix B

Agilent Technologies (2009) Agilent ChemStation manual - Understanding Your ChemStation, no G2070-91126, 07/09 ed., available online: http://www.chem.agilent.com/Library/usermanuals/Public/G2070-91126_Understanding.pdf (last accessed 28/05/2015).

Ansul Incorporated (2009) Halon-1301 safety datasheet, available online: <http://www.daytonafire.com/wp-content/uploads/2011/09/MSDS-Ansul-Halon1301CleanAgentMaterialSafetyDataSheet.pdf> (last accessed 28/05/2015).

Balsiger, C., Holliger, C. and P. Höhener (2005) Reductive dechlorination of chlorofluorocarbons and hydrochlorofluorocarbons in sewage sludge and aquifer sediment microcosms. *Chemosphere* 61, Issue 3.

Beyer, M., van der Raaij, R., Morgenstern, U. and B. Jackson (2015) Assessment of Halon-1301 as a groundwater age tracer, *Hydrol. Earth Syst. Sci.*, 19, 2775-2789, doi:10.5194/hess-19-2775-2015.

Blicher-Mathiesen, G.; McCarty, G.W. and L.P. Nielsen (1998) Denitrification and degassing in groundwater estimated from dissolved dinitrogen and argon. *J. Hydrol.*, 208 (1-2 /2), pp. 16-24.

Brown J.D.: Evolution of Fluorocarbon Compounds as Ground Water Tracers-Soil Column Studies. M.S. Thesis. Department of Hydrology Water Resources, University Arizona, Tuscon, 97pp., 1980.

Busenberg, E. and N. Plummer (2008) Dating groundwater with trifluoromethyl sulfurpentafluoride (SF₅CF₃), sulfurhexafluoride (SF₆), CF₃Cl (CFC-13) and CF₂Cl₂ (CFC-12), *Water Resources Research* 44,

Chiou, C.T.; Peters, L. J. and V. H. Freed (1979) A physical concept of soil-water equilibria for non-ionic compounds, *Science* 206 (4420), pp. 831-832.

Cook P.G., Solomon D.K., Plummer L.N., Busenberg E. and S.L. Schiff (1995) Chlorofluorocarbons as tracers of groundwater transport processes in a shallow, silty sand aquifer. *Water Resour. Res.* 31(3), 425-434.

Cook, P.G. and D.K. Solomon (1995) Transport of atmospheric trace gases to the water table: Implications for groundwater with chlorofluorocarbons and dating krypton 85. *Water Resources Research* 31: DOI: 10.1029/94WR02232. issn: 0043-1397.

Darling, W. G., D. C. Gooddy, B. L. Morris, and A. M. MacDonald (2010), Using CFCs and SF₆ for groundwater dating: A SWOT analysis, *Water-Rock Interaction XIII*, edited by P. Birkle and I. Torres-Alvarado, pp. 15–22, CRC Press. Studies13th International Conference on Water-Rock Interaction, WRI-13; Guanajuato; Mexico

- de la Mata, A. P.; Nizio, K. D. and J. J. Harynuk (2012) Integration parameters and their effects on quantitative results with two-step peak summation quantitation in comprehensive two-dimensional gas chromatography. *J. Chromatogr. A* 1255, 190– 195.
- Di Marco, V.B. and G.G. Bombi (2001) Review: Mathematical functions for the representation of chromatographic peaks, *J. Chromatography A*, 93, 11–30.
- Dionex Corporation (2001) CHROMELEON™ Chromatography Data Systems Tutorial and manual. Product Release Notes for CHROMELEON™ and PeakNet®6 Release 6.40, Sunnyvale, CA, US, available online: http://www.dionex.com/en-us/webdocs/4565-CM640_V18.pdf (last accessed 29/05/2015).
- Dyson, N. (1998) Chromatographic Integration Methods. Royal Society of Chemistry Chromatography Monographs, 2nd edn. Royal Society of Chemistry, Cambridge.
- Engblom, S.O. (1990) The Fourier transform of a voltammetric peak and its use in resolution enhancement. *J. Electroanal. Chem.* 296, 371-394.
- Fagan, C.C.; Everard, C.D. and K. McDonnell (2011) Prediction of moisture, calorific value, ash and carbon content of two dedicated bioenergy crops using near-infrared spectroscopy, *Bioresource Technology*.
- Fortuin, N. P. M. and A. Willemsen (2005) Exsolution of nitrogen and argon by methanogenesis in Dutch ground water. *J. Hydrol.* 301, 1-13.
- Giovanelli, G.; Sinelli, N.; Beghi, R.; Guidetti, R. and E. Casiraghi (2014) NIR spectroscopy for the optimization of postharvest apple management; *Postharvest Biology and Technology*.
- Goody, D.C.; Darling, W. G.; Abesser, C. and D. J. Lapworth (2006) Using chlorofluorocarbons (CFCs) and sulphur hexafluoride (SF6) to characterise groundwater movement and residence time in a lowland Chalk catchment, *J. Hydrol.* 330, 44– 52.
- Hansch, C., A. Leo, and D. Hoekman (1995) Exploring QSAR. Hydrophobic, Electronic and Steric Constants. American Chemical Society, Washington, DC.
- Heaton, T.H.E. and J.C. Vogel (1981) "Excess air" in groundwater. *J. Hydrol.* 50, 201-216.
- Labasque, T.; Aquilina, L.; Vergnaud, V. and F. Barbecot (contributors from participating laboratories) (2014) Inter-laboratory comparison of the analyses of sulphur hexafluoride (SF6) and three chlorofluorocarbons (CFC-11, -12 and -113) in groundwater and an air standard, *Applied Geochemistry*, 40, 119–125. doi: <http://dx.doi.org/10.1016/j.apgeochem.2014.03.009>.
- Leco Corporation (2011) ChromaTOF® Software Instruction Manual, St. Joseph, MI, Version 4.4x ed.
- Lyman, W.J. ; Reehl, W. F. and D. H. Rosenblatt (1990) Handbook of Chemical Property Estimation Methods. American Chemical Society, Washington, DC.
- Montgomery, J.H. (2007) Groundwater Chemicals Desk Reference, Fourth Edition, CRC Press.
- Nair, H.; Woo, F.; Hoofnagle, A.N. and G.S. Baird (2013) Clinical Validation of a Highly Sensitive GC-MS Platform for Routine Urine Drug Screening and Real-Time Reporting of up to 212 Drugs, *J. Toxicology* 2013, Article ID 329407, 7 pages, 2013. doi:10.1155/2013/329407.
- O'Callaghan, S.; Souza, D.P.; Isaac, A.; Wang, Q. Hodgkinson, L. Olshansky, M. Erwin, T. Appelbe, B. Tull, D.L. Roessner, U. Bacic, A. McConville, M.J. and V.A. Likić (2012) PyMS: a Python toolkit for processing of gas chromatography-mass spectrometry (GC-MS) data. Application and comparative study of selected tools, *BMC Bioinformatics*, 13, article 115.
- O'Haver, T. (2012) Interactive Peak Fitter (Version 8.61), available online: <http://www.mathworks.com/matlabcentral/fileexchange/23452-interactive-peak-fitter-version-8-61>, MATLAB Central File Exchange, retrieved 2/11/2012.
- Pankow, J.F. (1986) Magnitude of artefacts caused by bubbles and headspace in the determination of volatile compounds in water. *Analytical Chemistry*. 58, 1822-1826.
- Pierce, K.M.; Nadeau, J.S. and R.E. Synovec (2012) Data Analysis Methods Chapter 17 in: *Gas Chromatography*, p. 415–434, Available online 2 June 2012.

- Plummer, L. N., E. Busenberg, S. M. Eberts, L. M. Bexfield, C. J. Brown, L. S. Fahlquist, B. G. Katz and M. K. Landon (2008) Low-Level Detections of Halogenated Volatile Organic Compounds in Groundwater: Use in Vulnerability Assessments. *J. of Hydrologic Engineering* 13(11), 1049.
- Qu, J.; Xu, H. and Z. Zhang (2000) Determination of sulfonyl fluoride in air by GC, *Fenxi Yiqi* 2, 32–34.
- Reuter, N., E. Witte, I. Meer, L. Flipse (2010) Agilent – Inspirations Newsletter. February 2010, available at: http://www.chem.agilent.com/en-US/Newsletters_old/einspirations/2010/february/Pages/techtip.aspx (last accessed 03/08/2014).
- Reynolds, G.W.; Hoff, J. T. and R. W. Gillham (1990) Sampling bias caused by materials used to monitor halocarbons in groundwater, *Environmental Science and Technology* 24 (1), 135-142.
- Rosiek, J.; Lasas, J.; Sliwka, I. and K. Róžański (2007) Application of GC and modulated ECD for the determination of SF₅CF₃ mixing ratios in the atmosphere, *Chemia Analityczna (Chemical Analysis)* 52, 235–242.
- Scott, R.P.W. (2009) *Encyclopedia of Chromatography*, 3rd Edition (Print Version) CRC Press 2009, ISBN: 978-1-4200-8459-7, DOI:10.1201/NOE1420084597.ch358.
- Shimadzu (2001) GCsolution - Chromatography Data System Reference Manual Version 2.3, available online: http://www.labtoday.net/uploads/soft/110404/Gc_reference.pdf (last accessed 28/05/2015).
- Shoval, S.; Yariv, S.; Michaelian, K.H.; Boudeulle, M and G. Panczer (2001) Hydroxyl-stretching bands in curve-fitted micro-Raman, photoacoustic and transmission infrared spectra of dickite from St. Claire, Pennsylvania, *Clays and Clay Minerals* 49, 347–354.
- Shrivastava, A. and V.B. Gupta (2011) Methods for the determination of limit of detection and limit of quantitation of the analytical methods, *Chronicles of Young Scientists*, 2(1), 21.
- Śliwka, I.; Lasas, J.; Bielewski, J.; Grombik, I.; Limanówka, D. and J. Rosiek (2010) Long-Term Measurements of CFCs and SF₆ Concentrations in Air; *Polish J. of Environ. Stud.* Vol. 19, No. 4 (2010), 811-815.
- Smit, H. C. and H. L. Walg, (1975) Base-line noise and detection limits in signal-integrating analytical methods. Application to chromatography, *Chromatographia* 8(7), 311-323.
- Sousa, S.R. and S.E. Bialkowski (1997) Temperature-Dependent Electron-Capture Detector Response to Common Alternative Fluorocarbons", *Analytical chemistry*, 69(19), pp. 3871-3878.
- Sousa, S.R. and S.E. Bialkowski (2001) Comparison of gas chromatography detection limits and relative responses of common alternative fluorocarbons using electron capture, atomic emission, and mass spectrometry detection", *ANALYT CHIM*, 433(2), pp. 181-186.
- Stewart, M. and U. Morgenstern (2001) Age and Source of Groundwaters from Isotopic Tracers. In: *Groundwaters of New Zealand*. Rosen, M.R. and White P.A. (eds), 161-183.
- Stewart, R.; Gideoni, I. and Y. Zhu (2011). *Signal Processing Methods for Capillary Electrophoresis, Systems and Computational Biology - Bioinformatics and Computational Modeling*, Prof. Ning-Sun Yang (Ed.), ISBN: 978-953-307-875-5, InTech, DOI: 10.5772/23446. Available from: <http://www.intechopen.com/books/systems-and-computational-biology-bioinformatics-and-computational-modeling/signal-processing-methods-for-capillary-electrophoresis>.
- Tetko, I.V.; Gasteiger, J.; Todeschini, R.; Mauri, A.; Livingstone, D.; Ertl, P.; Palyulin, V.A.; Radchenko, E.V.; Zefirov, N.S.; Makarenko, A.S.; Tanchuk, V.Y. and V.V. Prokopenko (2005) Virtual computational chemistry laboratory - design and description, *J. Comput. Aid. Mol. Des.* 19, 453-63
- van der Raaij, R. and M. Beyer (2015) Use of CFCs and SF₆ as groundwater age tracers in New Zealand, *J. Hydrol. New Zealand* 54(1), in press.
- van der Raaij, R.W. (2003) Age-dating of New Zealand groundwaters using sulphur hexafluoride. MSc (Physical Geography) thesis, Victoria University of Wellington, New Zealand, 122 p.
- Villalanti, C. D. (1980) *Digital Signal Processing Techniques Applied To Chromatography*, PhD thesis, University of Arizona, available online: <http://hdl.handle.net/10150/281918> (last accessed 12/02/2015).
- Visser, A., Broers, H.P. and Bierkens, M.F.P. (2007) Dating degassed groundwater with 3H/3He. *Water Resources Research*, 43 (10), W10434.

Vollrath, A.; Hohl, C. and H.G. Seiler (1995) Trace analysis of chlorofluorocarbons/partially halogenated chlorofluorohydrocarbons (CFC/HCFC) in polymeric foams by headspace capillary gas chromatography with electron-capture detection or ion trap detection combined with preconcentration on a cold trap. *Fresenius J. Anal. Chem.* 351, 251.

Warner, M.J. and R.F. Weiss (1985) Solubility of chlorofluorocarbons 11 and 12 in water and seawater. *Deep-Sea Res.* 32, 1485-97.

Weeks, E.P.; Earp, D.E. and G.M. Thompson (1982) Use of atmospheric fluorocarbons F-11 and F-12 to determine the diffusion parameters of the unsaturated zone in the southern high plains of Texas. *Water Resour. Res.* 18, 1365–1378.

Zhou, Z.; Qin, W.; Chu, Y. and W. Fei (2013) Elucidation of the structures of tributyl phosphate/Li complexes in the presence of FeCl₃ via UV-visible, Raman and IR spectroscopy and the method of continuous variation, *Chemical Engineering Science*.

Appendix C – for Chapter 5

This appendix contains detailed information on the literature review (C1), the modelling approach (C2), and the model outcome with regard to inferred hydrochemistry-PT relationships (C3) and inferred age information (C4).

C1 Details on literature review

C2 Detailed model description

C3 Detailed model outcome

C4 Detailed age estimation

C5 References of Appendix C

C1 Details literature search

Table C1 summarizes 400 most relevant age modelling studies (sorted by relevance and ear published) identified in the Web of Science in January 2015.

Table C1: Summary of the 400 most relevant age modelling studies found in the Web of Science with the following keywords (here sorted by date of publication): 'water' or 'groundwater' and 'residence time' or 'age' or 'dating' and 'tracer' or 'lumped parameter'; A – 1= contains the following uncertainty key word or word parts in abstract or title 'uncertain', 'error', 'probability', 'Bayes' or 'reali(z/s)ations', 0- does not contain such keywords; B- 1= study uses probabilistic framework for more comprehensive uncertainty assessment in age modelling, 0 –study does not considers a more comprehensive uncertainty assessment; studies that use a 'fuller' uncertainty assessment are highlighted in bold

Authors	Title	Place of publication	Vol.	Year	A	B
Timbe et al.	Understanding Uncertainties When Inferring Mean Transit Times Of Water Trough Tracer-Based Lumped-Parameter Models In Andean Tropical Montane Cloud Forest Catchments	Hydrology And Earth System Sciences	18	2014	1	1
Zhang et al.	Impact Of Impoundment On Groundwater Seepage In The Three Gorges Dam In China Based On Cfcs And Stable Isotopes	Environmental Earth Sciences	72	2014	0	0
Tait et al.	The Influence Of Groundwater Inputs And Age On Nutrient Dynamics In A Coral Reef Lagoon	Marine Chemistry	166	2014	0	0
Kietavainen et al.	Noble Gas Residence Times Of Saline Waters Within Crystalline Bedrock, Outokumpu Deep Drill Hole, Finland	Geochimica Et Cosmochimica Acta	145	2014	0	0
Visser et al.	Intercomparison Of Tritium And Noble Gases Analyses, H-3/He-3 Ages And Derived Parameters Excess Air And Recharge Temperature	Applied Geochemistry	50	2014	1	0
Mahara et al.	Effects Of Terrigenic He Components On Tritium-Helium Dating: A Case Study Of Shallow Groundwater In The Saijo Basin	Applied Geochemistry	50	2014	0	0
Kralik et al.	Using O-18/H-2, H-3/He-3, Kr-85 And Cfcs To Determine Mean Residence Times And Water Origin In The Grazer And Leibnitzer Feld Groundwater Bodies (Austria)	Applied Geochemistry	50	2014	0	0
Delbart et al.	Investigation Of Young Water Inflow In Karst Aquifers Using SF6-CFC-H-3/He-Kr-85-Ar-39 And Stable Isotope Components	Applied Geochemistry	50	2014	0	0
Mayer et al.	A Multi-Tracer Study Of Groundwater Origin And Transit-Time In The Aquifers Of The Venice Region (Italy)	Applied Geochemistry	50	2014	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Petersen et al.	Quantifying Paleorecharge In The Continental Intercalaire (CI) Aquifer By A Monte-Carlo Inversion Approach Of CI-36/CI Data	Applied Geochemistry	50	2014	0	0
Suckow	The Age Of Groundwater - Definitions, Models And Why We Do Not Need This Term	Applied Geochemistry	50	2014	0	0
Akesson et al.	Modelling Pesticide Transport In A Shallow Groundwater Catchment Using Tritium And Helium-3 Data	Applied Geochemistry	50	2014	0	0
Massoudieh et al.	Assessment Of The Value Of Groundwater Age Time-Series For Characterizing Complex Steady-State Flow Systems Using A Bayesian Approach	Applied Geochemistry	50	2014	1	1
Massoudieh et al.	A Bayesian Modeling Approach For Estimation Of A Shape-Free Groundwater Age Distribution Using Multiple Tracers	Applied Geochemistry	50	2014	1	1
Earnest et al.	Investigating The Role Of Hydromechanical Coupling On Flow And Transport In Shallow Fractured-Rock Aquifers	Hydrogeology Journal	22	2014	0	0
Zhang et al.	A Study Of The Interrelation Between Surface Water And Groundwater Using Isotopes And Chlorofluorocarbons In Sanjiang Plain, Northeast China	Environmental Earth Sciences	72	2014	0	0
Ritterbusch et al.	Groundwater Dating With Atom Trap Trace Analysis Of Ar-39	Geophysical Research Letters	41	2014	0	0
Houben et al.	Freshwater Lenses As Archive Of Climate, Groundwater Recharge, And Hydrochemical Evolution: Insights From Depth-Specific Water Isotope Analysis And Age Determination On The Island Of Langeoog, Germany	Water Resources Research	50	2014	0	0
Marques et al.	Assessment Of Mixing Between Shallow And Thermal Waters Using Geochemical And Environmental Isotope Tracers (N Portugal): A Review And Reinterpretation	Environmental Earth Sciences	72	2014	0	0
Stoelzle et al.	Streamflow Sensitivity To Drought Scenarios In Catchments With Different Geology	Geophysical Research Letters	41	2014	0	0
Beyer et al.	Potential Groundwater Age Tracer Found: Halon-1301 (CF ₃ Br), As Previously Identified As CFC-13 (CF ₃ Cl)	Water Resources Research	50	2014	0	0
Jiménez-Martínez et al.	Temporal And Spatial Scaling Of Hydraulic Response To Recharge In Fractured Aquifers: Insights From A Frequency Domain Analysis	Water Resour. Res.	49	2013	0	0
Boehlke et al.	Educational Webtool Illustrating Groundwater Age Effects On Contaminant Trends In Wells	Ground Water	52	2014	0	0
Jurgens et al.	A Ternary Age-Mixing Model To Explain Contaminant Occurrence In A Deep Supply Well	Ground Water	52	2014	0	0
Starn, J. J et al.	Simulating Water-Quality Trends In Public-Supply Wells In Transient Flow Systems	Ground Water	52	2014	1	1
Musgrove et al.	Factors Affecting Public-Supply Well Vulnerability In Two Karst Aquifers	Ground Water	52	2014	0	0
Somarathne	Characteristics Of Point Recharge In Karst Aquifers	Water	6	2014	0	0
Somarathne et al.	Three Criteria Reliability Analyses For Groundwater Recharge Estimations	Environmental Earth Sciences	72	2014	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Kwicklis and Farnham	Testing The C-14 Ages And Conservative Behavior Of Dissolved C-14 In A Carbonate Aquifer In Yucca Flat, Nevada (USA), Using Cl-36 From Groundwater And Packrat Middens	Hydrogeology Journal	22	2014	0	0
Bekele et al.	Aquifer Residence Times For Recycled Water Estimated Using Chemical Tracers And The Propagation Of Temperature Signals At A Managed Aquifer Recharge Site In Australia	Hydrogeology Journal	22	2014	0	0
Yu Dun; Changyuan Tang; Yanjun Shen	Identifying Interactions Between River Water And Groundwater In The North China Plain Using Multiple Tracers	Environmental Earth Sciences	72	2014	0	0
Desbarats et al.	Groundwater Flow Dynamics And Arsenic Source Characterization In An Aquifer System Of West Bengal, India	Water Resources Research	50	2014	0	0
Su et al.	Sustainability Of Intensively Exploited Aquifer Systems In The North China Plain: Insights From Multiple Environmental Tracers	Journal Of Earth Science	25	2014	0	0
Mastrocicco et al.	Modelling Groundwater Residence Time In A Sub-Irrigated Buffer Zone	Ecohydrology	7	2014	0	0
Gardner et al.	A Multiple-Tracer Approach To Understanding Regional Groundwater Flow In The Snake Valley Area Of The Eastern Great Basin, USA	Applied Geochemistry	45	2014	0	0
Hopkins et al.	Evaluation Of The Importance Of Clay Confining Units On Groundwater Flow In Alluvial Basins Using Solute And Isotope Tracers: The Case Of Middle San Pedro Basin In Southeastern Arizona (USA)	Hydrogeology Journal	22	2014	0	0
Leray et al.	Temporal Evolution Of Age Data Under Transient Pumping Conditions	Journal of Hydrology	511	2014	0	0
Cowie et al.	Use Of Natural And Applied Tracers To Guide Targeted Remediation Efforts In An Acid Mine Drainage System, Colorado Rockies, USA	Water	6	2014	0	0
Diem et al.	Assessing The Effect Of Different River Water Level Interpolation Schemes On Modeled Groundwater Residence Times	Journal of Hydrology	510	2014	1	0
Jin-Yong Lee	Use Of Environmental And Applied Tracers For Groundwater Studies In Korea	Geosciences Journal	18	2014	0	0
McCallum et al.	Bias Of Apparent Tracer Ages In Heterogeneous Environments	Ground Water	52	2014	1	0
McCallum et al.	Nonparametric Estimation Of Groundwater Residence Time Distributions: What Can Environmental Tracer Data Tell Us About Groundwater Residence Time?	Water Resources Research	50	2014	1	1
Liu et al.	Using Chlorofluorocarbons (Cfcs) And Tritium (H-3) To Estimate Groundwater Age And Flow Velocity In Hohhot Basin, China	Hydrological Processes	28	2014	0	0
Wood et al.	Factors Affecting Carbon-14 Activity Of Unsaturated Zone CO 2 And Implications For Groundwater Dating.	Journal of Hydrology (Amsterdam)	519	2014	0	0
Kashiwaya et al.	Multiple Tracer Study In Horonobe, Northern Hokkaido, Japan: 1. Residence Time Estimation Based On Multiple Environmental Tracers And Lumped Parameter Models.	Journal of Hydrology (Amsterdam)	519	2014	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Tekleab et al.	Characterisation Of Stable Isotopes To Identify Residence Times And Runoff Components In Two Meso-Scale Catchments In The Abay/Upper Blue Nile Basin, Ethiopia	Hydrology And Earth System Sciences	18	2014	0	0
Cendon et al.	Groundwater Residence Time In A Dissected And Weathered Sandstone Plateau: Kulnura-Mangrove Mountain Aquifer, NSW, Australia	Australian Journal Of Earth Sciences	61	2014	0	0
Eller et al.	Radium Sampling Methods And Residence Times In St. Andrew Bay, Florida	Estuaries And Coasts	37	2014	0	0
Heilweil et al.	Innovative Environmental Tracer Techniques For Evaluating Sources Of Spring Discharge From A Carbonate Aquifer Bisected By A River	Ground Water	52	2014	0	0
Massoudieh	Inference Of Long-Term Groundwater Flow Transience Using Environmental Tracers: A Theoretical Approach	Water Resources Research	49	2013	1	1
Davila et al.	A Toolkit For Groundwater Mean Residence Time Interpretation With Gaseous Tracers	Computers & Geosciences	61	2013	1	0
Visser et al.	Groundwater Age Distributions at a Public Drinking Water Supply Well Field Derived From Multiple Age Tracers (Kr-85, H-3/He-3, and Ar-39)	Water Resources Research	49	2013	1	0
Foster et al.	The Aquifer Pollution Vulnerability Concept: Aid Or Impediment In Promoting Groundwater Protection?	Hydrogeology Journal	21	2013	0	0
Currell et al.	Analysis Of Environmental Isotopes In Groundwater To Understand The Response Of A Vulnerable Coastal Aquifer To Pumping: Western Port Basin, South-Eastern Australia	Hydrogeology Journal	21	2013	0	0
Tomasky-Holmes et al.	Determination Of Water Mass Ages Using Radium Isotopes As Tracers: Implications For Phytoplankton Dynamics In Estuaries	Marine Chemistry	156	2013	0	0
Ako et al.	Flow Dynamics And Age Of Groundwater Within A Humid Equatorial Active Volcano (Mount Cameroon) Deduced By Delta D, Delta O-18, H-3 And Chlorofluorocarbons (Cfcs)	Journal of Hydrology	502	2013	0	0
Frisbee et al.	Are We Missing The Tail (And The Tale) Of Residence Time Distributions In Watersheds?	Geophysical Research Letters	40	2013	0	0
Al-Charideh and Hasan	Use Of Isotopic Tracers To Characterize The Interaction Of Water Components And Nitrate Contamination In The Arid Rasafeh Area (Syria)	Environmental Earth Sciences	70	2013	0	0
Yager et al.	Comparison Of Age Distributions Estimated From Environmental Tracers By Using Binary-Dilution And Numerical Models Of Fractured And Folded Karst: Shenandoah Valley Of Virginia And West Virginia, USA	Hydrogeology Journal	21	2013	0	0
Kamdee et al.	Use Of Isotope Hydrology For Groundwater Resources Study In Upper Chi River Basin	Journal Of Radioanalytical And Nuclear Chemistry	297	2013	0	0
Han and Plummer	Revision Of Fontes & Garnier's Model For The Initial C-14 Content Of Dissolved Inorganic Carbon Used In Groundwater Dating	Chemical Geology	351	2013	1	0
Robertson et al.	Variability Of Groundwater Nitrate Concentrations Over Time In Arid Basin Aquifers: Sources, Mechanisms Of Transport, And Implications For Conceptual Models	Environmental Earth Sciences	69	2013	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Hiyama et al.	Estimation Of The Residence Time Of Permafrost Groundwater In The Middle Of The Lena River Basin, Eastern Siberia	Environmental Research Letters	8	2013	0	0
Meredith et al.	The Lithium, Boron And Strontium Isotopic Systematics Of Groundwaters From An Arid Aquifer System: Implications For Recharge And Weathering Processes	Geochimica Et Cosmochimica Acta	112	2013	0	0
Yuanzheng et al.	Characterizing The Groundwater Renewability And Evolution Of The Strongly Exploited Aquifers Of The North China Plain By Major Ions And Environmental Tracers	Journal Of Radioanalytical And Nuclear Chemistry	296	2013	0	0
Zhai et al.	Characterizing The Groundwater Renewability And Evolution Of The Strongly Exploited Aquifers Of The North China Plain By Major Ions And Environmental Tracers	Journal Of Radioanalytical And Nuclear Chemistry	296	2013	0	0
Briggs et al.	Relating Hyporheic Fluxes, Residence Times, And Redox-Sensitive Biogeochemical Processes Upstream Of Beaver Dams	Freshwater Science	32	2013	0	0
Friedrich et al.	Factors Controlling terrigenous SF ₆ in young groundwater of the Odenwald Region (Germ.)	Applied Geochemistry	33	2013	0	0
Nakata et al.	Groundwater Dating Using Radiocarbon in Fulvic Acid in Groundwater Containing Fluorescein	Journal of Hydrology	489	2013	0	0
Grundl et al.	Mechanisms Of Subglacial Groundwater Recharge As Derived From Noble Gas, C-14, And Stable Isotopic Data	Earth And Planetary Science Letters	369	2013	0	0
Selle et al.	Recharge And Discharge Controls On Groundwater Travel Times And Flow Paths To Production Wells For The Ammer Catchment In Southwestern Germany	Environmental Earth Sciences	69	2013	0	0
Lapworth et al.	Residence Times Of Shallow Groundwater In West Africa: Implications For Hydrogeology And Resilience To Future Changes In Climate	Hydrogeology Journal	21	2013	0	0
Samborska et al.	Estimation Of Groundwater Residence Time Using Environmental Radioisotopes (14C,T) In Carbonate Aquifers, Southern Poland	Isotopes In Environmental And Health Studies	49	2013	0	0
Molenat et al.	Use Of Gaseous Tracers (Cfcs And SF ₆) And Transit-Time Distribution Spectrum To Validate A Shallow Groundwater Transport Model	Journal of Hydrology	480	2013	1	0
Al-Charideh	Recharge and Mineralization of Groundwater of The Upper Cretaceous Aquifer In Orontes Basin, Syria	Hydrological Sciences Journal-Journal Des Sciences Hydrologiques	58	2013	0	0
Farid et al.	Hydrogeochemical Investigation Of Surface And Groundwater Composition In An Irrigated Land In Central Tunisia	Journal Of African Earth Sciences	78	2013	0	0
Alvarado et al.	Dating Groundwater In The Bohemian Cretaceous Basin: Understanding Tracer Variations In The Subsurface	Applied Geochemistry	29	2013	0	0
Marques et al.	Isotopic And Hydrochemical Data As Indicators Of Recharge Areas, Flow Paths And Water-Rock Interaction In The Caldas Da Rainha-Quinta Das Janelas Thermomineral Carbonate Rock Aquifer (Central Portugal)	Journal of Hydrology	476	2013	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Haiyan et al.	The Application Of Dating Shallow Groundwater with Sulfur Hexafluoride (SF ₆) in Groundwater Vulnerability Assessment In The Core Area Of Daqing Oilfield	Advanced Materials Research	726-731	2013	0	0
Zhang, et al	The Application Of Dating Shallow Groundwater With Sulfur Hexafluoride (SF ₆) In Groundwater Vulnerability Assessment In The Core Area Of Daqing Oilfield	Advances In Environmental Technologies, Pts 1-6	726-731	2013	0	0
Frey and Kulls	New Hydrological Age-Dating Techniques Using Cosmogenic Radionuclides Beryllium-7 And Sodium-22	Isotopes In Hydrology, Marine Ecosystems And Climate Change Studies - Proceedings Of The International Symposium		2013	0	0
Gastmans et al.	Groundwater Ages And Hydrochemical Evolution Along A Flow-Path In The Northeastern Sector Of The Guarani Aquifer System (GAS) Derived From Structural Geology, Isotopes And Hydrochemical Data			2013	1	0
Mayer et al.	Multiple Tracer (4He, 14C, 39Ar, 3hphe, 85kr) Depth Profile In An Extensively Exploited Multilevel Aquifer System In The Venetian Plain, Italy			2013	0	0
Ndembo et al.	The Use Of Multiple Environmental Tracers In Age estimation Of The Mount Amba Aquifer, Kinshasa, Democratic Republic Of Congo			2013	0	0
Takahashi et al.	Radiocarbon Dating Of Groundwater In Granite Fractures In Abukuma Province, Northeast Japan	Radiocarbon	55	2013	0	0
Baudron et al.	Assessing Groundwater Residence Time In A Highly Anthropized Unconfined Aquifer Using Bomb Peak C-14 And Reconstructed Irrigation Water H-3	Radiocarbon	55	2013	0	0
Matray and Dauzeres	Origin Of Cl- And High Delta Cl-37 Values In Radiocarbon Dated-Fracture Groundwaters At The Tournemire URL (France)	Proceedings Of The Fourteenth International Symposium On Water-Rock Interaction, Wri 14	7	2013	1	0
Carreira et al.	Isotopic And Geochemical Tracers In The Evaluation Of Groundwater Residence Time And Salinization Problems At Santiago Island, Cape Verde		7	2013	0	
Cao et al.	Residence Time As A Key For Comprehensive Assessment Of The Relationship Between Changing Land Use And Nitrates In Regional Groundwater Systems	Environmental Science-Processes & Impacts	15	2013	0	0
Gusyeve et al.	Calibration Of A Transient Transport Model To Tritium Data In Streams And Simulation Of Groundwater Ages In The Western Lake Taupo Catchment, New Zealand	Hydrology And Earth System Sciences	17	2013	0	0
Avrahamov et al.	Carbon Isotope Exchange During Calcite Interaction With Brine: Implications For C-14 Dating Of Hypersaline Groundwater	Radiocarbon	55	2013	0	0
Intissar et al.	Hydrogeochemical Investigation Of Surface And Groundwater Composition In An Irrigated Land In Central Tunisia.	Journal Of African Earth Sciences	78	2013	0	0
Xiao-Wei et al.	A Quantitative Study On Accumulation Of Age Mass Around Stagnation Points In Nested Flow Systems	Water Resources Research	48	2012	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Han et al.	Using Chlorofluorocarbons (Cfcs) And Tritium To Improve Conceptual Model Of Groundwater Flow In The South Coast Aquifers Of Laizhou Bay, China	Hydrological Processes	26	2012	0	0
Plummer et al.	Old Groundwater In Parts Of The Upper Patapsco Aquifer, Atlantic Coastal Plain, Maryland, USA: Evidence From Radiocarbon, Chlorine-36 And Helium-4	Hydrogeology Journal	20	2012	0	0
Bakari et al.	Groundwater Residence Time And Paleorecharge Conditions In The Deep Confined Aquifers Of The Coastal Watershed, South-East Tanzania	Journal of Hydrology	466	2012	0	0
Jaunat et al.	Hydrochemical Data And Groundwater Dating To Infer Differential Flowpaths Through Weathered Profiles Of A Fractured Aquifer	Applied Geochemistry	27	2012	0	0
Leray et al.	Contribution Of Age Data To The Characterization Of Complex Aquifers	Journal of Hydrology	464	2012	0	0
Massoudieh et al.	Bayesian Evaluation Of Groundwater Age Distribution Using Radioactive Tracers And Anthropogenic Chemicals	Water Resources Research	48	2012	1	1
Darling et al.	The Practicalities Of Using Cfcs And SF6 For Groundwater Dating And Tracing	Applied Geochemistry	27	2012	0	0
Manning et al.	Evolution Of Groundwater Age In A Mountain Watershed Over A Period Of Thirteen Years	Journal of Hydrology	460	2012	0	0
Morgenstern and Daughney	Groundwater Age For Identification Of Baseline Groundwater Quality And Impacts Of Land-Use Intensification - The National Groundwater Monitoring Programme Of New Zealand	Journal of Hydrology	456	2012	0	0
Hoque et al.	C-14 Dating Of Deep Groundwater In The Bengal Aquifer System, Bangladesh: Implications For Aquifer Anisotropy, Recharge Sources And Sustainability	Journal of Hydrology	444	2012	0	0
Qin et al.	Determination Of Groundwater Recharge Regime And Flowpath In The Lower Heihe River Basin In An Arid Area Of Northwest China By Using Environmental Tracers: Implications For Vegetation Degradation In The Ejina Oasis	Applied Geochemistry	27	2012	0	0
Flewelling et al.	Travel Time Controls The Magnitude Of Nitrate Discharge In Groundwater Bypassing The Riparian Zone To A Stream On Virginia's Coastal Plain	Hydrological Processes	26	2012	0	0
Koh et al.	Flow Paths And Mixing Properties Of Groundwater Using Hydrogeochemistry And Environmental Tracers In The Southwestern Area Of Jeju Volcanic Island	Journal of Hydrology	432	2012	0	0
Stewart	A 40-Year Record Of Carbon-14 and Tritium In The Christchurch Groundwater System, New Zealand: Dating of Young Samples with C14	Journal of Hydrology	430	2012	0	0
Blondel et al.	Punctual And Continuous Estimation Of Transit Time From Dissolved Organic Matter Fluorescence Properties In Karst Aquifers, Application To Groundwaters Of 'Fontaine De Vaucluse' Experimental Basin (SE France)	Environmental Earth Sciences	65	2012	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Liu et al.	Groundwater Recharge Environments And Hydrogeochemical Evolution In Beijing, China: Multi-Tracer Approach	Advances In Environmental Science And Engineering, Pts 1-6	518-523	2012	0	0
Jilai et al.	Groundwater Recharge Environments And Hydrogeochemical Evolution In Beijing, China: Multi-Tracer Approach	Advanced Materials Research	518-523	2012	0	0
Satrio et al.	Groundwater Dynamic And Its Interrelationship With River Water Of Bandung Basin Using Environmental Isotopes (18O, 2H, 14C).	Modern Applied Science	6	2012	0	0
Salle et al.	Groundwater Residence Time Downgradient Of Trench No. 22 At The Chernobyl Pilot Site: Constraints On Hydrogeological Aquifer Functioning.	Applied Geochemistry	27	2012	0	0
Mahara et al.	New Dating Method: Groundwater Residence Time Estimated From The He-4 Accumulation Rate Calibrated By Using Cosmogenic And Subsurface-Produced Cl-36	Environmental Radioactivity 2010	24	2012	0	0
Hagedorn et al.	Estimating Recharge In Fractured Aquifers Of A Temperate Humid To Semiarid Volcanic Island (Jeju, Korea) From Water Table Fluctuations, and Cl, CFC-12 and H-3 Chemistry	Journal of Hydrology	409	2011	1	0
Tosaki et al.	Estimation Of Groundwater Residence Time Using The Cl-36 Bomb Pulse	Ground Water	49	2011	1	0
Datta et al.	Perennial Ponds Are Not An Important Source Of Water Or Dissolved Organic Matter To Groundwaters With High Arsenic Concentrations In West Bengal, India	Geophysical Research Letters	38	2011	0	0
Massoudieh and Ginn	The Theoretical Relation Between Unstable Solutes And Groundwater Age	Water Resources Research	47	2011	0	0
Brown et al.	Impacts Of Agricultural Irrigation Recharge On Groundwater Quality In A Basalt Aquifer (Washington, USA): A Multi-Tracer Approach	Hydrogeology Journal	19	2011	0	0
Qin et al.	Assessing Impact Of Irrigation Water On Groundwater Recharge And Quality In Arid Environment Using Cfc, Tritium And Stable Iso-topes, In The Zhangye Basin, Northwest China	Journal of Hydrology	405	2011	0	0
Rinaldo et al.	Catchment Travel Time Distributions And Water Flow In Soils	Water Resources Research	47	2011	0	0
Botter et al.	Catchment Residence And Travel Time Distributions: The Master Equation	Geophysical Research Letters	38	2011	0	0
McMahon et al.	A Comparison Of Recharge Rates In Aquifers Of The United States Based On Groundwater-Age Data	Hydrogeology Journal	19	2011	0	0
Bretzler et al.	Groundwater Origin And Flow Dynamics In Active Rift Systems - A Multi-Isotope Approach In The Main Ethiopian Rift	Journal of Hydrology	402	2011	0	0
Van Stempvoort et al.	Artificial Sweeteners As Potential Tracers In Groundwater In Urban Environments	Journal of Hydrology	401	2011	0	0
Momoshima et al.	Application Of Kr-85 Dating To Groundwater In Volcanic Aquifer Of Kumamoto Area, Japan	J. Of Radioanalytical And Nuclear Chemistry	287	2011	0	0
Tosaki et al.	Distribution Of Cl-36 In The Yoro River Basin, Central Japan, and Its Relation to the Residence Time Of The Regional Groundwater Flow System	Water	3	2011	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Zongyu et al.	Identifying The Recharge Sources And Age Of Groundwater In The Songnen Plain (North-east China) Using Environmental Isotopes	Hydrogeology Journal	19	2011	0	0
Zuber et al.	On Some Methodological Problems In The Use Of Environmental Tracers To Estimate Hydrogeologic Parameters And To Calibrate Flow And Transport Models	Hydrogeology Journal	19	2011	0	0
Murphy et al.	Tritium-Helium Groundwater Age Used To Constrain A Groundwater Flow Model Of A Valley-Fill Aquifer Contaminated With Trichloroethylene (Quebec, Canada)	Hydrogeology Journal	19	2011	0	0
Zouari et al.	Using Geochemical Indicators To Investigate Groundwater Mixing And Residence Time In The Aquifer System Of Djefara Of Medenine (Southeastern Tunisia)	Hydrogeology Journal	19	2011	0	0
Sueltenfuss et al.	Age Structure And Recharge Conditions Of A Coastal Aquifer (Northern Germany) Investigated With Ar-39, C-14, H-3, He Isotopes And Ne	Hydrogeology Journal	19	2011	0	0
Kagabu et al.	Groundwater Flow System Under A Rapidly Urbanizing Coastal City As Determined By Hydrogeochemistry	Journal Of Asian Earth Sciences	40	2011	0	0
Asai et al.	Impact Of Natural And Local Anthropogenic SF6 Sources On Dating Springs And Groundwater Using SF6 In Central Japan	Hydrological Research Letters	5	2011	0	0
Kagabu et al.	Groundwater Flow System In Aso Caldera	Journal Of Japanese Association Of Hydrological Sciences	41	2011	0	0
Fourre et al.	Dissolved Helium Distribution In The Oxfordian And Dogger Deep Aquifers Of The Meuse/Haute-Marne Area	Physics And Chemistry Of The Earth	36	2011	0	0
Liao and Cirpka	Shape-Free Inference Of Hyporheic Traveltime Distributions From Synthetic Conservative And “Smart” Tracer Tests In Streams	Water Resources Research	47	2011	1	1
Knee et al.	Using Radium Isotopes To Characterize Water Ages And Coastal Mixing Rates: A Sensitivity Analysis	Limnol. Oceanogr. Methods	9	2011	1	1
Singleton, and Moran	Dissolved Noble Gas And Isotopic Tracers Reveal Vulnerability Of Groundwater In A Small, High-Elevation Catchment To Predicted Climate Changes	Water Resources Research	46	2010	0	0
Starn et al.	Using Atmospheric Tracers To Reduce Uncertainty In Groundwater Recharge Areas	Ground Water	48	2010	1	0
Koh et al.	Land-Use Controls On Sources And Fate Of Nitrate In Shallow Groundwater Of An Agricultural Area Revealed By Multiple Environmental Tracers	Journal Of Contaminant Hydrology	118	2010	0	0
Stolp et al.	Age Dating Base Flow At Springs And Gaining Streams Using Helium-3 And Tritium: Fischadagnitz System, Southern Vienna Basin, Austria	Water Resources Research	46	2010	0	0
Darling et al.	Using Environmental Tracers To Assess The Extent Of River-Groundwater Interaction In A Quarried Area Of The English Chalk	Applied Geochemistry	25	2010	1	0

Authors	Title	Place of publication	Vol.	year	A	B
Kirchner et al.	Comparing Chloride And Water Isotopes As Hydrological Tracers In Two Scottish Catchments	Hydrological Processes	24	2010	0	0
McMahon et al.	Use Of Geochemical, Isotopic, And Age Tracer Data To Develop Models Of Groundwater Flow For The Purpose Of Water Management, Northern High Plains Aquifer, USA	Applied Geochemistry	25	2010	0	0
Aeppli et al.	Quantifying In Situ Transformation Rates Of Chlorinated Ethenes By Combining Compound-Specific Stable Isotope Analysis, Groundwater Dating, And Carbon Isotope Mass Balances	Environmental Science & Technology	44	2010	0	0
Fantong et al.	Hydrochemical And Isotopic Evidence Of Recharge, Apparent Age, And Flow Direction Of Groundwater In Mayo Tsanaga River Basin, Cameroon: Barings On Contamination	Environmental Earth Sciences	60	2010	0	0
Daughney et al.	Discriminant Analysis For Estimation Of Groundwater Age From Hydrochemistry And Well Construction: Application To New Zealand Aquifers	Hydrogeology Journal	18	2010	0	0
Land and Huff	Multi-Tracer Investigation of Groundwater Residence Time in a Karstic Aquifer: Bitter Lakes National Wildlife Refuge, New Mexico	Hydrogeology Journal	18	2010	1	0
Cartwright	Using Groundwater Geochemistry And Environmental Isotopes To Assess The Correction Of C-14 Ages In A Silicate-Dominated Aquifer System	Journal of Hydrology	382	2010	0	0
Lavastre et al.	Establishing Constraints On Groundwater Ages With Cl-36, C-14, H-3, And Noble Gases: A Case Study In The Eastern Paris Basin, France	Applied Geochemistry	25	2010	0	0
Newman et al.	Dating Of 'Young' Groundwaters Using Environmental Tracers: Advantages, Applications, And Research Needs	Isotopes In Environmental And Health Studies	46	2010	0	0
von Rohden et al.	Accumulation Of Natural SF ₆ In The Sedimentary Aquifers Of The North China Plain As A Restriction On Groundwater Dating	Isotopes In Environmental And Health Studies	46	2010	0	0
Seebach et al.	Dating Problems With Selected Mining Lakes And The Adjacent Groundwater Body In Lusatia, Germany	Isotopes In Environmental And Health Studies	46	2010	0	0
Kluge et al.	Assessing The Use Of 3H-3He Dating To Determine The Subsurface Transit Time Of Cave Drip Waters	Isotopes In Environmental And Health Studies	46	2010	0	0
Stadler et al.	Linking Chloride Mass Balance Infiltration Rates With Chlorofluorocarbon And SF ₆ Groundwater Dating In Semi-Arid Settings: Potential And Limitations	Isotopes In Environmental And Health Studies	46	2010	1	0
Hasegawa et al.	Verification Of 4He And ³⁶ Cl Dating Of Very Old Groundwater In The Great Artesian Basin, Australia.	Groundwater Response To Changing Climate		2010	0	0
Bouchaou et al.	Origin And Residence Time Of Groundwater In The Tadla Basin (Morocco) Using Multiple Isotopic And Geochemical Tools	Journal of Hydrology	379	2009	0	0
Gattacceca et al.	Isotopic And Geochemical Characterization Of Salinization In The Shallow Aquifers Of A Reclaimed Subsiding Zone: The Southern Venice Lagoon Coastland	Journal of Hydrology	378	2009	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Gillon et al.	Open To Closed System Transition Traced Through The TDIC Isotopic Signature at the Aquifer Recharge Stage, Implications For Groundwater C-14 Dating	Geochimica Et Cosmochimica Acta	73	2009	1	0
Liu et al.	Origin Of Methane In High-Arsenic Groundwater Of Taiwan - Evidence From Stable Isotope Analyses And Radiocarbon Dating	Journal Of Asian Earth Sciences	36	2009	0	0
Amaral et al.	Assessing TNT And DNT Groundwater Contamination By Compound-Specific Isotope Analysis And H-3-He-3 Groundwater Dating: A Case Study In Portugal	Chemosphere	77	2009	0	0
Mali and Urbanc	Isotope Oxygen-18 As Natural Tracer Of Water Movement In A Coarse Gravel Unsaturated Zone	Water Air And Soil Pollution	203	2009	0	0
Mahara et al.	Groundwater Dating By Estimation Of Groundwater Flow Velocity And Dissolved He-4 Accumulation Rate Calibrated By Cl-36 In The Great Artesian Basin, Australia	Earth And Planetary Science Letters	287	2009	1	0
Gourcy et al.	Improving The Knowledge Of Pesticide And Nitrate Transfer Processes Using Age-Dating Tools (CFC, SF6, H-3) In A Volcanic Island (Martinique, French West Indies)	Journal Of Contaminant Hydrology	108	2009	0	0
Genereux et al.	Chemical And Isotopic Signature Of Old Groundwater And Magmatic Solutes In A Costa Rican Rain Forest: Evidence From Carbon, Helium, And Chlorine	Water Resources Research	45	2009	0	0
Schwientek et al.	Effect Of The Unsaturated Zone Thickness On The Distribution Of Water Mean Transit Times In A Porous Aquifer	Journal of Hydrology	373	2009	0	0
Trabelsi et al.	Quantifying Regional Groundwater Flow between Continental Intercalaire And Djeffara Aquifers in Southern Tunisia Using Isotope Methods	Environmental Geology	58	2009	0	0
Bartlett and Morrison	Tracer Method To Determine Residence Time In A Permeable Reactive Barrier	Ground Water	47	2009	0	0
Heilweil et al.	Oxygen, Hydrogen, And Helium Isotopes For Investigating Groundwater Systems Of The Cape Verde Islands, West Africa	Hydrogeology Journal	17	2009	0	0
Boehlke and Michel	Contrasting Residence Times And Fluxes Of Water And Sulfate In Two Small Forested Watersheds In Virginia, USA	Science Of The Total Environment	407	2009	0	0
Althaus et al.	Noble Gas Tracers For Characterisation Of Flow Dynamics And Origin Of Groundwater: A Case Study In Switzerland	Journal of Hydrology	370	2009	0	0
Raiber et al.	Strontium Isotopes As Tracers To Delineate Aquifer Interactions And The Influence Of Rainfall In The Basalt Plains Of Southeastern Australia	Journal of Hydrology	367	2009	0	0
Kaown et al.	Effects Of Groundwater Residence Time And Recharge Rate On Nitrate Contamination Deduced From Delta O-18, Delta D, H-3/He-3 And Cfc3 In A Small Agricultural Area In Chuncheon, Korea	Journal of Hydrology	366	2009	0	0
Yechieli et al.	The Inter-Relationship Between Coastal Sub-Aquifers And The Mediterranean Sea, Deduced From Radioactive Isotopes Analysis	Hydrogeology Journal	17	2009	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Bayari et al.	Radiocarbon Age Distribution Of Groundwater In The Konya Closed Basin, Central Anatolia, Turkey	Hydrogeology Journal	17	2009	0	0
Dobrzynski	Geochemistry And Age Of Groundwater In A Hydrochemically Diversified Aquifer (Permo-Carboniferous, The Intra-Sudetic Synclinorium, SW Poland) Derived From Geochemical Modelling And Isotopic Studies	Acta Geologica Polonica	59	2009	0	0
Su et al.	Chemical Evolution Of Shallow Groundwater And The Residence Time In The Ejina Basin.	Arid Land Geography	32	2009	0	0
Amaral et al.	Assessing TNT And DNT Groundwater Contamination By Compound-Specific Isotope Analysis And 3H - 3He Groundwater Dating: A Case Study In Portugal.	Chemosphere	77	2009	0	0
Gattacceca et al.	Isotopic And Geochemical Characterization Of Salinization In The Shallow Aquifers Of A Reclaimed Subsiding Zone: The Southern Venice Lagoon Coastland.	Journal of Hydrology (Amsterdam)	378	2009	0	0
Matsumoto et al.	Groundwater - Surface Water Interaction Analysis Using A Groundwater Flow Model And Radioactive Isotopes.	Journal Of Japan Society Of Hydrology And Water Resources	22	2009	0	0
Fenton et al.	Variations In Travel Time For N Loading To Groundwaters In Four Case Studies In Ireland: Implications For Policy Makers And Regulators	Tearmann	7	2009	0	0
Genereux et al.	Chemical And Isotopic Signature Of Old Groundwater And Magmatic Solutes In A Costa Rican Rain Forest: Evidence From Carbon, Helium, And Chlorine.	Water Resources Research	45	2009	0	0
Edmunds	Palaeoclimate And Groundwater Evolution In Africa - Implications For Adaptation And Management.	Hydrological Sciences Journal	54	2009	0	0
Fenton et al.	Variations In Travel Time For N Loading To Groundwaters In Four Case Studies In Ireland: Implications For Policy Makers And Regulators.	Tearmann		2009	0	0
Gates et al.	Conceptual Model Of Recharge To South-eastern Badain Jaran Desert Groundwater And Lakes From Environmental Tracers	Applied Geochemistry	23	2008	0	0
Horst et al.	Evaluation Of The Recharge Processes And Impacts Of Irrigation On Groundwater Using Cfc's And Radiogenic Isotopes In The Silao-Romita Basin, Mexico	Hydrogeology Journal	16	2008	0	0
Mahlknecht et al.	Groundwater Geochemistry Of The Chihuahua City Region In The Rio Conchos Basin (Northern Mexico) And Implications For Water Resources Management	Hydrological Processes	22	2008	0	0
Meillier et al.	Groundwater Dating And Flow-Model Calibration In The Kern Water Bank, California	Journal Of Hydrologic Engineering	13	2008	0	0
Fleishman	Cosmogenic Na-^{22} As An Index Of The Residence Time Of Water In Freshwater Basins: A Review	Journal Of Environmental Radioactivity	99	2008	0	0
Engle et al.	Application Of Environmental Groundwater Tracers At The Sulphur Bank Mercury Mine, California, USA	Hydrogeology Journal	16	2008	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Bouchaou et al.	Application Of Multiple Isotopic And Geochemical Tracers For Investigation Of Recharge, Salinization, And Residence Time Of Water In The Souss-Massa Aquifer, Southwest Of Morocco	Journal of Hydrology	352	2008	0	0
Massmann et al.	Investigation Of Groundwater A Residence Times During Bank Filtration In Berlin: Multi-Tracer Approach	Hydrological Processes	22	2008	0	0
Busenberg, and Plummer	Dating Groundwater With Trifluoromethyl Sulfurpentafluoride (SF ₅ CF ₃), Sulfur Hexafluoride (SF ₆), CF ₃ Cl (CFC-13), And CF ₂ Cl ₂ (CFC-12)	Water Resources Research	44	2008	0	0
Ozyurt	Residence Time Distribution In The Kirkgoz Karst Springs (Antalya-Turkey) As A Tool For Contamination Vulnerability Assessment	Environmental Geology	53	2008	0	0
Kebede et al.	Groundwater Origin And Flow Along Selected Transects In Ethiopian Rift Volcanic Aquifers	Hydrogeology Journal	16	2008	0	0
Mohrlok et al.	Quantification Of Infiltration Processes In Urban Areas By Accounting For Spatial Parameter Variability	Journal Of Soils And Sediments	8	2008	0	0
Innocent and Negrel	U-Series Constraints On Aquifer Groundwater Residence Time: The Adour-Garonne District Case (Southwest France)	Mineralogical Magazine	72	2008	0	0
Santella et al.	Widespread Elevated Atmospheric SF ₆ Mixing Ratios In The Northeastern United States: Implications For Groundwater Dating	Journal of Hydrology	349	2008	1	0
Hori et al.	Seasonal Patterns Of Carbon Chemistry And Isotopes In Tufa Depositing Groundwaters Of Southwestern Japan	Geochimica Et Cosmochimica Acta	72	2008	0	0
Bethke et al.	Groundwater Age And Groundwater Age Dating	Annual Review Of Earth And Planetary Sciences	36	2008	0	0
Kulongoski et al.	Helium-4 Characteristics Of Groundwaters From Central Australia: Comparative Chronology With Chlorine-36 And Carbon-14 Dating Techniques	Journal of Hydrology	348	2008	0	0
Koh et al.	Estimation Of Mixing Properties And Mean Residence Time Using 3H For Groundwater In Typical Geothermal And CO ₂ -Rich Areas In South Korea	Journal Of The Geological Society Of Korea	44	2008	0	0
Sik et al.	A Review Of Groundwater Dating With Environmental Tracers	J. Of The Geological Society Of Korea	44	2008	0	0
Konikow et al.	The Use Of Groundwater Age As A Calibration Target.	Calibration & Reliability In Ground-water Modelling: Credibility Of Modelling		2008	0	0
Stewart et al.	Hydrometric And Natural Tracer (Oxygen-18, Silica, Tritium And SF ₆) Evidence For A Dominant Groundwater Contribution To Pukemanga Stream, New Zealand	Hydrological Processes	21	2007	0	0
Darling and Goody	Assessing The Applicability Of Global CFC And SF ₆ Input Functions To Groundwater Dating In The UK	Science Of The Total Environment	387	2007	0	0
Koh et al.	Evidence For Terrigenous SF ₆ In Groundwater From Basaltic Aquifers, Jeju Island, Korea: Implications For Groundwater Dating	Journal of Hydrology	339	2007	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Treutler et al.	Radon As A Tracer To Determine The Mean Residence Times Of Groundwater In Decontamination Reactors	Journal Of Radioanalytical And Nuclear Chemistry	272	2007	0	0
Tosaki et al.	Application Of Cl-36 As A Dating Tool For Modern Groundwater	Nuclear Instruments & Methods In Physics Research Section B-Beam Interactions With Materials And Atoms	259	2007	0	0
Mahara et al.	Can The He-4 Clock Be Calibrated By Cl-36 For Groundwater Dating?		259	2007	0	0
Zhou et al.	Testing Method And Application Of Dating Shallow Groundwater With SF6	Geological Science & Technology Inform.	26	2007	1	0
Manning et al.	Groundwater Noble Gas, Age, And Temperature Signatures In An Alpine Watershed: Valuable Tools In Conceptual Model Development	Water Resources Research	43	2007	0	0
Worthington	Groundwater Residence Times In Unconfined Carbonate Aquifers	Journal Of Cave And Karst Studies	69	2007	0	0
Alvarado et al.	Constraining The Age Distribution Of Highly Mixed Groundwater Using 39 Ar: A Multiple Environmental Tracer (H-3/He-3, Kr-85, Ar-39, And C-14) Study In The Semiconfined Fontainebleau Sands Aquifer (France)	Water Resources Research	43	2007	0	0
Ingram et al.	Noble Gas Excess Air Applied To Distinguish Groundwater Recharge Conditions	Environmental Science & Technology	41	2007	0	0
Soulsby et al.	Inferring Groundwater Influences On Surface Water In Montane Catchments From Hydrochemical Surveys Of Springs & Streamwater	Journal of Hydrology	333	2007	0	0
Swarzenski et al.	Ra And Rn Isotopes As Natural Tracers Of Submarine Groundwater Discharge In Tampa Bay, Florida	Marine Chemistry	104	2007	0	0
Kabeya et al.	Estimation Of Mean Residence Times Of Subsurface Waters Using Seasonal Variation In Deuterium Excess In A Small Headwater Catchment In Japan	Hydrological Processes	21	2007	0	0
Han et al.	Residence Times And Age Distributions Of Spring Waters At The Semmering Catchment Area, Eastern Austria, Inferred From Tritium, Cfcs And Stable Isotopes	Isotopes In Environmental And Health Studies	43	2007	0	0
Kennedy et al.	C-14 Groundwater Age And The Importance Of Chemical Fluxes Across Aquifer Boundaries In Confined Cretaceous Aquifers Of North Carolina, USA	Radiocarbon	49	2007	0	0
Cirpka et al.	Analyzing Bank Filtration By Deconvoluting Time Series Of Electric Conductivity.	Groundwater	45	2007	1	1
Zhou et al.	Dating Shallow Groundwater With SF6 In Shijiazhuang, Hebei, China	Water-Rock Interaction, Vols 1 And 2, Proceedings		2007	0	0
Goody et al.	Using Chlorofluorocarbons (Cfcs) And Sulphur Hexafluoride (SF6) To Characterise Groundwater Movement And Residence Time In A Lowland Chalk Catchment	Journal of Hydrology	330	2006	0	0
Guendouz and Michelot	Chlorine-36 Dating Of Deep Groundwater From Northern Sahara	Journal of Hydrology	328	2006	0	0
Leybourne et al.	Stable Isotope Geochemistry Of Ground And Surface Waters Associated With Undisturbed Massive Sulfide Deposits; Constraints On Origin Of Waters And Water-Rock Reactions	Chemical Geology	231	2006	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Koh et al.	Application Of Environmental Tracers To Mixing, Evolution, And Nitrate Contamination Of Ground Water In Jeju Island, Korea	Journal of Hydrology	327	2006	0	0
LaBolle et al.	Diffusive Fractionation Of H-3 And He-3 In Groundwater And Its Impact On Groundwater Age Estimates	Water Resources Research	42	2006	1	0
Soulsby et al.	Runoff Processes, Stream Water Residence Times And Controlling Landscape Characteristics In A Mesoscale Catchment: An Initial Evaluation	Journal of Hydrology	325	2006	0	0
Mahlknecht et al.	Geochemical And Isotopic Investigations On Groundwater Residence Time And Flow In The Independence Basin, Mexico	Journal of Hydrology	324	2006	0	0
Moore et al.	Sources Of Groundwater Nitrate Revealed Using Residence Time And Isotope Methods	Applied Geochemistry	21	2006	0	0
Sukhija et al.	Characterisation Of Recharge Processes And Groundwater Flow Mechanisms In Weathered-Fractured Granites Of Hyderabad (India) Using Isotopes	Hydrogeology Journal	14	2006	0	0
Trettin et al.	Flooding Of Lignite Mines: Isotope Variations And Processes In A System Influenced By Saline Groundwater	Isotopes In Environmental And Health Studies	42	2006	0	0
Bennetts et al.	Understanding The Salinisation Process For Groundwater In An Area Of South-Eastern Australia, Using Hydrochemical And Isotopic Evidence	Journal of Hydrology	323	2006	0	0
McIntosh and Walter	Paleowaters In Silurian-Devonian Carbonate Aquifers: Geochemical Evolution Of Groundwater In The Great Lakes Region Since The Late Pleistocene	Geochimica Et Cosmochimica Acta	70	2006	0	0
Reddy et al.	Characterization Of Surface And Ground Water Delta O-18 Seasonal Variation And Its Use For Estimating Groundwater Residence Times	Hydrological Processes	20	2006	1	0
Leybourne and Cameron	Composition Of Groundwaters Associated With Porphyry-Cu Deposits, Atacama Desert, Chile: Elemental And Isotopic Constraints On Water Sources And Water-Rock Reactions	Geochimica Et Cosmochimica Acta	70	2006	0	0
Onnis et al.	Simulating Environmental Tracer Transport In Unsaturated-Saturated Porous Media	Calibration & Reliability In Groundwater Modelling: From Uncertainty To Decision Making	304	2006	0	0
Bayari et al.	Groundwater Age: A Vital Information In Protecting Groundwater Dependent Ecosystem	Groundwater And Ecosystems	70	2006	0	0
Hoehn and Cirpka	Assessing Residence Times Of Hyporheic Ground Water In Two Alluvial Flood Plains Of The Southern Alps Using Water Temperature And Tracers	Hydrology And Earth System Sciences	10	2006	0	0
Oudijk	The Use Of Atmospheric Contaminants To Estimate The Minimum Age Of Environmental Releases Impacting Groundwater	Environmental Forensics	6	2005	0	0
Rueedi et al.	Estimating Amount And Spatial Distribution Of Groundwater Recharge In The Iullemmeden Basin (Niger) Based On H-3, He-3 And CFC-11 Measurements	Hydrological Processes	19	2005	1	0

Authors	Title	Place of publication	Vol.	year	A	B
Katz et al.	Using Multiple Chemical Indicators To Assess Sources Of Nitrate And Age Of Groundwater In A Karstic Spring Basin	Environmental & Engineering Geoscience	11	2005	0	0
Malcolm et al.	Catchment-Scale Controls On Groundwater-Surface Water Interactions In The Hyporheic Zone: Implications For Salmon Embryo Survival	River Research And Applications	21	2005	0	0
Tolstikhin et al.	Helium Transfer From Water Into Quartz Crystals: A New Approach For Porewater Dating	Earth And Planetary Science Letters	238	2005	0	0
Qin et al.	Isotopes Of Geothermal Water In Xi'an Area And Implications On Its Relation To Karstic Groundwater In North Mountains	Acta Petrologica Sinica	21	2005	0	0
Cook et al.	Groundwater Ages In Fractured Rock Aquifers	Journal of Hydrology	308	2005	0	0
Boronina et al.	Application Of Tritium In Precipitation And In Groundwater Of The Kouris Catchment (Cyprus) For Description Of The Regional Groundwater Flow	Applied Geochemistry	20	2005	0	0
Zuber et al.	Groundwater Dating With H-3 And SF6 In Relation To Mixing Patterns, Transport Modelling And Hydrochemistry	Hydrological Processes	19	2005	0	0
Rodgers et al.	Stable Isotope Tracers As Diagnostic Tools In Upscaling Flow Path Understanding And Residence Time Estimates In A Mountainous Mesoscale Catchment	Hydrological Processes	19	2005	0	0
Ozyurt and Bayari	LUMPED Unsteady: A Visual Basic (R) Code Of Unsteady-State Lumped-Parameter Models For Mean Residence Time Analyses Of Groundwater Systems	Computers & Geosciences	31	2005	0	0
Alvarado et al.	Cl-36 In Modern Groundwater Dated By A Multi-Tracer Approach (H-3/He-3, SF ₆ , CFC-12 and Kr-85): A Case Study In Quaternary Sand Aquifers In The Odense Pilot River Basin, Denmark	Applied Geochemistry	20	2005	0	0
Kim and Jeong	Factors Influencing Natural Occurrence of Fluoride-Rich Groundwaters: A Case Study In The Southeastern Part Of The Korean Peninsula	Chemosphere	58	2005	0	0
Tesoriero et al.	Nitrogen Transport And Transformations In A Coastal Plain Watershed: Influence Of Geomorphology On Flow Paths And Residence Times	Water Resources Research	41	2005	0	0
Morikawa et al.	Estimation Of Groundwater Residence Time In A Geologically Active Region By Coupling He-4 Concentration With He Isotopic Ratios	Geophysical Research Letters	32	2005	0	0
Patterson et al.	Cosmogenic, Radiogenic, And Stable Isotopic Constraints On Groundwater Residence Time In The Nubian Aquifer, Western Desert Of Egypt	Geochemistry Geophysics Geosystems	6	2005	0	0
Rodgers et al.	Using Stable Isotope Tracers To Assess Hydrological Flow Paths, Residence Times And Landscape Influences In A Nested Mesoscale Catchment	Hydrology And Earth System Sciences	9	2005	0	0
Tesoriero et al.	Nitrogen Transport And Transformations In A Coastal Plain Watershed: Influence Of Geomorphology On Flow Paths & Residence Times.	Water Resources Research	41	2005	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Laier	Nitrate Monitoring And CFC-Age Dating Of Shallow Groundwaters - An Attempt To Check The Effect Of Restricted Use Of Fertilizers.	Nitrates In Groundwater: Selected Papers From The European Meeting Of The International Association Of Hydrogeologists, Wisla, Poland, 4-7 Jun 2002		2005	0	0
Kilchmann et al.	Natural Tracers In Recent Groundwaters From Different Alpine Aquifers	Hydrogeology Journal	12	2004	0	0
Broers	The Spatial Distribution Of Groundwater Age For Different Geohydrological Situations In The Netherlands: Implications For Groundwater Quality Monitoring At The Regional Scale	Journal of Hydrology	299	2004	0	0
Katz et al.	Use Of Chemical And Isotopic Tracers To Assess Nitrate Contamination And Ground-Water Age, Woodville Karst Plain, USA	Journal of Hydrology	289	2004	0	0
Gascoyne	Hydrogeochemistry, Groundwater Ages And Sources Of Salts In A Granitic Batholith On The Canadian Shield, Southeastern Manitoba	Applied Geochemistry	19	2004	0	0
Carey et al.	Alabama Gulf Coast Groundwaters : He-4 And C-14 As Groundwater-Dating Tools	Geology	32	2004	0	0
Bockgard et al.	Accuracy Of CFC Groundwater Dating In A Crystalline Bedrock Aquifer: Data From A Site In Southern Sweden	Hydrogeology Journal	12	2004	0	0
Maloszewski et al.	Interpretation Of Environmental Tracers In Groundwater Systems With Stagnant Water Zones	Isotopes In Environmental And Health Studies	40	2004	0	0
Zuber et al.	Age And Flow Pattern Of Groundwater In A Jurassic Limestone Aquifer And Related Tertiary Sands Derived From Combined Isotope, Noble Gas And Chemical Data	Journal of Hydrology	286	2004	0	0
Zhang	Numerical Simulations of Dating Young Ground-water With Multiple Atmospheric Tracers: CFC-11, CFC-12, SF6, H-3/He-3 And Kr-85	Computational Methods In Water Resources, Vols 1 And 2	55	2004	1	0
Buttle and McDonnell	Isotope Tracers In Catchment Hydrology In The Humid Tropics.	Forests, Water And People In The Humid Tropics: Past, Present And Future Hydrological Research For Integrated Land & Water Management		2004	0	0
Yui et al.	Geostatistical And Geochemical Classification Of Groundwaters Considered In Safety Assessment Of A Deep Geologic Repository For High-Level Radioactive Wastes In Japan	Geochemical Journal	38	2004	0	0
Eaton et al.	Tritium-Helium-3 Age-Dating Of Groundwater In The Livermore Valley Of California	Radioanalytical Methods In Interdisciplinary Research: Fundamentals in Cutting-Edge Applications	868	2004	0	0
Taylor	Time-Dependent Factors Inherent In The Age Equation For Determining Residence Times Of Groundwater Using C-14: A Procedure To Compensate For The Past Variability Of C-14 In Atmospheric Carbon Dioxide, With Application To The Wairau Deep Aquifer, Marlborough, New Zealand	Radiocarbon	46	2004	1	0

Authors	Title	Place of publication	Vol.	year	A	B
Kulongoski et al.	Helium Isotope Studies In The Mojave Desert, California: Implications For Groundwater Chronology And Regional Seismicity	Chemical Geology	202	2003	0	0
Ojiambo et al.	Strontium Isotopes And Rare Earth Elements As Tracers Of Groundwater-Lake Water Interactions, Lake Naivasha, Kenya	Applied Geochemistry	18	2003	0	0
Price et al.	Use Of Tritium And Helium To Define Groundwater Flow Conditions In Everglades National Park	Water Resources Research	39	2003	0	0
Happell et al.	Evidence For The Removal Of CFC-11, CFC-12, And CFC-113 At The Groundwater-Surface Water Interface In The Everglades	Journal of Hydrology	279	2003	0	0
Lehmann et al.	A Comparison Of Groundwater Dating With Kr-81, Cl-36 And He-4 In Four Wells Of The Great Artesian Basin, Australia	Earth And Planetary Science Letters	211	2003	1	0
Hogan and Blum	Boron And Lithium Isotopes As Groundwater Tracers: A Study At The Fresh Kills Landfill, Staten Island, New York, USA	Applied Geochemistry	18	2003	0	0
Darling et al.	The O & H Stable Isotopic Composition Of Fresh Waters In The British Isles. 2. Surface Waters And Groundwater	Hydrology And Earth System Sciences	7	2003	1	0
Flury and Wai	Dyes As Tracers For Vadose Zone Hydrology	Reviews Of Geophysics	41	2003	0	0
Oudijk	Estimating The Minimum Age Of A Chlorinated Solvent Plume In Groundwater With Chlorofluorocarbon (CFC) And Tritium Methodologies: A Case Study	Environmental Forensics	4	2003	0	0
Neretnieks and Moreno	Prediction Of Some In Situ Tracer Tests With Sorbing Tracers Using Independent Data	Journal Of Contaminant Hydrology	61	2003	0	0
Ozyurt and Bayari	LUMPED: A Visual Basic Code Of Lumped-Parameter Models For Mean Residence Time Analyses Of Groundwater Systems	Computers & Geosciences	29	2003	0	0
Rademacher et al.	Groundwater Residence Times And Flow Paths In Fractured Rock Determined Using Environmental Tracers In The Mission Tunnel; Santa Barbara County, California, USA	Environmental Geology	43	2003	0	0
Peeters et al.	Improving Noble Gas Based Paleoclimate Reconstruction And Groundwater Dating Using Ne-20/Ne-22 Ratios	Geochimica Et Cosmochimica Acta	67	2003	0	0
Hohener et al.	Worldwide Occurrence And Fate Of Chlorofluorocarbons In Groundwater	Critical Reviews In Environmental Science And Technology	33	2003	0	0
Rademacher et al.	Groundwater Residence Times And Flow Paths In Fractured Rock Determined Using Environmental Tracers In The Mission Tunnel; Santa Barbara County, California, USA.	Environmental Geology	44	2003	0	0
Waugh et al.	Transit Time Distributions In Lake Issyk-Kul	Geophysical Research Letters	29	2002	0	0
Weissmann et al.	Dispersion Of Groundwater Age In An Alluvial Aquifer System	Water Resources Research	38	2002	0	0
Puckett et al.	Using Chemical, Hydrologic, And Age Dating Analysis To Delineate Redox Processes And Flow Paths In The Riparian Zone Of A Glacial Outwash Aquifer-Stream System	Water Resources Research	38	2002	0	0
Bottomley et al.	Iodine-129 Constraints On Residence Times Of Deep Marine Brines In The Canadian Shield	Geology	30	2002	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Bayari	TRACER: An EXCEL Workbook To Calculate Mean Residence Time In Groundwater By Use Of Tracers CFC-11, CFC-12 And Tritium	Computers & Geosciences	28	2002	0	0
Burton et al.	Influence Of Fracture Anisotropy On Ground Water Ages And Chemistry, Valley And Ridge Province, Pennsylvania	Ground Water	40	2002	0	0
Park et al.	Transport Modeling Applied To The Interpretation Of Groundwater Cl-36 Age	Water Resources Research	38	2002	0	0
McGuire et al.	Evaluation Of Mean Residence Time In Subsurface Waters Using Oxygen-18 Fluctuations During Drought Conditions In The Mid-Appalachians	Journal of Hydrology	261	2002	0	0
Asano et al.	Residence Times And Flow Paths Of Water In Steep Unchannelled Catchments, Tanakami, Japan	Journal of Hydrology	261	2002	0	0
Bouhlassa and Aiachi	Groundwater Dating With Radiocarbon: Appli-cation to an Aquifer under Semi-Arid Condi-tions In The South Of Morocco (Guelmime)	Applied Radiation And Isotopes	56	2002	0	0
Neretnieks	A Stochastic Multi-Channel Model For Solute Transport - Analysis Of Tracer Tests In Fractured Rock	Journal Of Contaminant Hydrology	55	2002	0	0
Hohener et al.	Occurrence And Fate Of Chlorofluorocarbon Plumes In Groundwater	Groundwater Quality: Natural And Enhanced Restoration of Groundwater Pollution		2002	0	0
Puckett et al.	Using Chemical, Hydrologic, And Age Dating Analysis To Delineate Redox Processes And Flow Paths In The Riparian Zone Of A Glacial Outwash Aquifer-Stream System.	Water Resources Research	38	2002	0	0
Buttle et al.	Prediction Of Groundwater Characteristics In Forested And Harvested Basins During Spring Snowmelt Using A Topographic Index	Hydrological Processes	15	2001	0	0
Plummer et al.	Groundwater Residence Times In Shenandoah National Park, Blue Ridge Mountains, Virginia, USA: A Multi-Tracer Approach	Chemical Geology	179	2001	1	0
Katz et al.	Timescales For Nitrate Contamination Of Spring Waters, Northern Florida, USA	Chemical Geology	179	2001	0	0
Sauter et al.	Sampling Of Sub-Sea-floor Aquifers By A Temporary Well For CFC Age Dating And Natural Tracer Investigations	Journal Of Sea Research	46	2001	0	0
Qin and Wang	Chlorofluorocarbons And H-3/He-3 In Groundwater - Applications In Tracing And Dating Young Groundwater	Science In China Series E-Technological Sciences	44	2001	0	0
Bauer et al.	A Multi-Tracer Study In A Shallow Aquifer Using Age Dating Tracers H-3, Kr-85, CFC-113 And SF6 - Indication For Retarded Transport Of CFC-113	Journal of Hydrology	248	2001	0	0
Ojiambo et al.	Ground Water/Surface Water Interactions In Lake Naivasha, Kenya, Using Delta O-18, Delta D, And H-3/He-3 Age-Dating	Ground Water	39	2001	0	0
Zoellmann et al.	Environmental Tracer Transport (H-3 And SF6) In The Saturated And Unsaturated Zones And Its Use In Nitrate Pollution Management	Journal of Hydrology	240	2001	0	0
Authors	Title	Place of publication	Vol.	year	A	B

Zuhair	Use Of Hydrochemistry And Environmental Isotopes For Evaluation Of Groundwater In The Paleogene Limestone Aquifer Of The Ras Al-Ain Area (Syrian Jezireh).	Environmental Geology	41	2001	0	0
Stewart and Morgenstern	Age And Source Of Groundwater From Isotope Tracers.	Groundwaters Of New Zealand		2001	0	0
Brantley et al.	Interpreting Kinetics Of Groundwater-Mineral Interaction Using Major Element, Trace Element, And Isotopic Tracers	Water-Rock Interaction, Vols 1 And 2		2001	0	0
Thomas et al.	Age Dating Groundwater Using Dissolved Organic Carbon - An Example From Southern Nevada, USA	Water-Rock Interaction, Vols 1 And 2		2001	0	0
Negrel and Lachassagne	Geochemistry Of The Maroni River (French Guiana) During The Low Water Stage: Implications For Water-Rock Interaction And Groundwater Characteristics	Journal of Hydrology	237	2000	0	0
Gibson et al.	Runoff Generation In A Hypermaritime Bog-Forest Upland	Hydrological Processes	14	2000	0	0
Collon et al.	Kr-81 In The Great Artesian Basin, Australia: A New Method For Dating Very Old Groundwater	Earth And Planetary Science Letters	182	2000	1	0
Iwatsuki et al.	Estimation Of Relative Groundwater Age In The Granite At The Tono Research Site, Central Japan	Nuclear Instruments & Methods In Physics Research Section B-Beam Interactions With Materials And Atoms	172	2000	0	0
Edmunds and Smedley	Residence Time Indicators In Groundwater: The East Midlands Triassic Sandstone Aquifer	Applied Geochemistry	15	2000	0	0
Buckau et al.	C-14 Dating Of Gorleben Groundwater	Applied Geochemistry	15	2000	0	0
Bohlke and Horan	Strontium Isotope Geochemistry Of Groundwaters And Streams Affected By Agriculture, Locust Grove, MD	Applied Geochemistry	15	2000	0	0
Arnorsson and Sveinbjornsdottir	Age And Chemical Evolution Of Groundwaters In Skagafjordur, Iceland	Journal Of Geochemical Exploration	69	2000	0	0
Etcheverry and Perrochet	Direct Simulation Of Groundwater Transit-Time Distributions Using The Reservoir Theory	Hydrogeology Journal	8	2000	0	0
Collins et al.	The Contribution Of Old And New Water To A Storm Hydrograph Determined By Tracer Addition To A Whole Catchment	Hydrological Processes	14	2000	0	0
Spurlock et al.	Chlorofluorocarbon Dating Of Herbicide-Containing Well Waters In Fresno And Tulare Counties, California	Journal Of Environmental Quality	29	2000	0	0
Scanlon	Uncertainties In Estimating Water Fluxes And Residence Times Using Environmental Tracers In An Arid Unsaturated Zone	Water Resources Research	36	2000	1	0
Talma et al.	CFC Tracing Of Groundwater In Fractured Rock Aided With C-14 And H-3 To Identify Water Mixing	Groundwater: Past Achievements And Future Challenges		2000	0	0
Gallagher et al.	Performance Of Models For Radiocarbon Dating Of Groundwater: An Appraisal Using Selected Irish Aquifers	Radiocarbon	42	2000	0	0
Uhlenbrook et al.	Natural Tracers For Investigating Residence Times, Runoff Components And Validation Of A Rainfall-Runoff Model	Tracers And Modelling In Hydrogeology		2000	0	0
Authors	Title	Place of publication	Vol.	year	A	B

Schlosser et al.	Tritium/He-3 Measurements In Young Groundwater: Progress In Applications To Complex Hydrogeological Systems	Tracers And Modelling In Hydrogeology		2000	0	0
Schlosser et al.	Pathways And Mean Residence Times Of Dissolved Pollutants In The Ocean Derived From Transient Tracers And Stable Isotopes	Science Of The Total Environment	238	1999	0	0
Trotignon et al.	Equilibrium Geochemical Modelling Of Aspo Groundwaters: A Sensitivity Study Of Thermodynamic Equilibrium Constants	Applied Geochemistry	14	1999	0	0
Beyerle et al.	Infiltration Of River Water To A Shallow Aquifer Investigated With H-3/He-3, Noble Gases And Cfc3	Journal of Hydrology	220	1999	0	0
Liem et al.	Residence Time Distribution Analysis As Related To The Effective Contact Time	Canadian Journal Of Civil Engineering	26	1999	0	0
Plummer et al.	Flow Of River Water Into A Karstic Limestone Aquifer - 2. Dating The Young Fraction In Groundwater Mixtures In The Upper Floridan Aquifer Near Valdosta, Georgia	Applied Geochemistry	13	1998	1	0
Clark et al.	Noble Gases, Stable Isotopes, And Radiocarbon As Tracers Of Flow In The Dakota Aquifer, Colorado And Kansas	Journal of Hydrology	211	1998	0	0
Ho et al.	Variability In Atmospheric Chlorofluorocarbons (Ccl3f And Ccl2f2) Near A Large Urban Area: Implications For Groundwater Dating	Environmental Science & Technology	32	1998	1	0
Kloppmann et al.	Residence Time Of Chalk Groundwaters In The Paris Basin And The North German Basin: A Geochemical Approach	Applied Geochemistry	13	1998	0	0
Burns and McDonnell	Effects Of A Beaver Pond On Runoff Processes: Comparison Of Two Headwater Catchments	Journal of Hydrology	205	1998	0	0
Hoehn	Radionuclides In Groundwaters: Contaminants And Tracers	Groundwater Quality: Remediation And Protection		1998	0	0
Hoehn	Solute Exchange Between River Water And Groundwater In Headwater Environments	Hydrology, Water Resources And Ecology In Headwaters		1998	0	0
Loosli et al.	Age Structure Of Groundwaters Determined By Isotope Methods	Scientific Basis For Nuclear Waste Management Xxi	506	1998	0	0
Edmunds and Smedley	Trace Elements As Residence Time Indicators In Groundwaters: The East Midlands Triassic Sandstone Aquifer, England	Water-Rock Interaction		1998	0	0
Bajjali et al.	The Artesian Thermal Groundwaters Of Northern Jordan: Insights Into Their Recharge History And Age	Journal of Hydrology	192	1997	0	0
Brennan and Quade	Reliable Late-Pleistocene Stratigraphic Ages And Shorter Groundwater Travel Times From C-14 In Fossil Snails From The Southern Great Basin	Quaternary Research	47	1997	0	0
Cook and Solomon	Recent Advances In Dating Young Groundwater: Chlorofluorocarbons, H-3/He-3 and Kr-85	Journal of Hydrology	191	1997	0	0
Balderer and Synal	Use Of Chlorine-36 As Tracer For The Evolution Of Waters In Geothermal And Tectonically Active Areas In Western Turkey	Nuclear Instruments & Methods In Physics Research Section B- Beam Interactions With Materials And Atoms	123	1997	0	0
Authors	Title	Place of publication	Vol.	year	A	B

Pezdic	Recharge And Retention Time Study Of A Partly Karstified Area Of Boc (Eastern Slovenia) Using Hydrogen, Oxygen And Carbon Isotope Composition As Natural Tracers	Isotopes In Environmental And Health Studies	33	1997	0	0
Snow and Spalding	Short-Term Aquifer Residence Times Estimated From Rn-222 Disequilibrium In Artificially-Recharged Ground Water	Journal Of Environmental Radioactivity	37	1997	0	0
Marjoua et al.	Contribution Of Chemical And Isotopic Tools To The Identification Of Water Salinization Origins: The Case Of Coastal Chaouia Aquifer (Morocco)	Revue Des Sciences De l'Eau	10	1997	0	0
Treskatis and Hartsch	Environmental Isotope Studies And Tracer Testing To Determine Capture And Protection Zones In The Zechstein-Karst On The Northern Verge Of The Thuringian Forest	Tracer Hydrology 97		1997	0	0
Oster et al.	Groundwater Age Dating With Chlorofluorocarbons	Water Resources Research	32	1996	0	0
Lange et al.	Water Flow Paths And Residence Times In A Small Headwater Catchment At Gardsjon, Sweden, During Steady State Storm Flow Conditions	Water Resources Research	32	1996	0	0
Solomon et al.	Source Of Radiogenic Helium 4 In Shallow Aquifers: Implications For Dating Young Groundwater	Water Resources Research	32	1996	0	0
LaSalle et al.	Geochemistry And C-14 Dating Of Groundwaters From Jurassic Aquifers Of North Aquitaine Basin (France)	Applied Geochemistry	11	1996	0	0
Szabo et al.	Age Dating Of Shallow Groundwater With Chlorofluorocarbons, Tritium Helium 3, And Flow Path Analysis, Southern New Jersey Coastal Plain	Water Resources Research	32	1996	1	0
Ivanovich et al.	Isotopic Characterization Of Humic Colloids And Other Organic And Inorganic Dissolved Species In Selected Groundwaters From Sand Aquifers At Gorleben, Germany	Humic And Fulvic Acids: Isolation, Structure, And Environmental Role	651	1996	0	0
Seiler and Maloszewski	Age Distribution In Near Surface And Deep Groundwaters Using Environmental Tracers And Numerical Models	Isotopes In Water Resources Management	2	1996	0	0
Aravena et al.	Estimating C-14 Groundwater Ages In A Methanogenic Aquifer	Water Resources Research	31	1995	0	0
Bohlke and Denver	Combined Use Of Groundwater Dating, Chemical, And Isotopic Analyses To Resolve The History And Fate Of Nitrate Contamination In two Agricultural Watersheds, Atlantic Coastal-Plain, Maryland	Water Resources Research	31	1995	0	0
Pinti and Marty	Noble-Gases In Crude Oils From The Paris Basin, France - Implications For The Origin Of Fluids And Constraints On Oil-Water-Gas Interactions	Geochimica Et Cosmochimica Acta	59	1995	0	0
Katz et al.	Chemical Evolution Of Groundwater Near A Sinkhole Lake, Northern Florida .1. Flow Patterns, Age Of Groundwater, And Influence Of Lake Water Leakage	Water Resources Research	31	1995	0	0
Turner et al.	Chlorine-36 In Hypersaline Palaeochannel Groundwaters Of Western Australia	Application Of Tracers In Arid Zone Hydrology		1995	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Cook and Solomon	Transport Of Atmospheric Trace Gases To The WaterTable- Implications For Groundwater Da-ting with Chlorofluorocarbons And Krypton-85	Water Resources Research	31	1995	1	0
Hussein	RIETHM: Radioisotope Environmental Tracer Hydrology Model Using Exponential And Dispersion Methods	Application Of Tracers In Arid Zone Hydrology		1995	1	0
Neretnieks and Moreno	Some Basic Difficulties In Predicting Sorbing Tracer Migration In Fractured Rocks From Tracer Experiments Using Non-Interacting Tracers	Proceedings Of The 5th International Conference On Radioactive Waste Management And Environmental Remediation. ICEM '95		1995	0	
Byegard et al.	The Use Of Some Ion-Exchange Sorbing Tracer Cations In Insitu Experiments In High Saline Groundwaters	Scientific Basis For Nuclear Waste Management Xviii, Pts 1 And 2	353	1995	0	0
Ekwurzel et al.	Dating Of Shallow Groundwater - Comparison Of The Transient Tracers H-3 /H-E-3 Chlorofluorocarbons, And Kr-85	Water Resources Research	30	1994	0	0
Matray et al.	Stable-Isotope Conservation And Origin Of Saline Waters From The Middle Jurassic Aquifer Of The Paris Basin, France	Applied Geochemistry	9	1994	0	0
Reilly et al.	The Use Of Simulation And Multiple Environmental Tracers To Quantify Groundwater-Flow In A Shallow Aquifer	Water Resources Research	30	1994	1	0
Dunkle et al.	Chlorofluorocarbons (Ccl3f And Ccl2f2) As Dating Tools And Hydrologic Tracers in Shallow Groundwater Of The Delmarva Peninsula, Atlantic Coastal-Plain, USA	Water Resources Research	29	1993	0	0
Matsutani et al.	Residence Times Of Soil, Ground, And Discharge Waters In A Mountainous Headwater Basin, Central Japan, Traced By Tritium	Tracers In Hydrology		1993	0	0
Stauffer and Wittchen	Hydrogeochemistry Of Maine Seepage Lakes And Related Groundwaters	J. Hydrol.	138	1992	0	0
Busenberg and Plummer	Use Of Chlorofluorocarbons (Ccl3f And Ccl2f2) As Hydrologic Tracers And Age-Dating Tools - The Alluvium And Terrace System Of Central Oklahoma	Water Resources Research	28	1992	1	0
Held et al.	A Simplified Method Of Kr-85 Measurement For Dating Young Groundwaters	Applied Radiation And Isotopes	43	1992	0	0
Fehn et al.	I-129 And Cl-36 Concentrations In Waters Of The Eastern Clear Lake Area, California - Residence Times And Source Ages Of Hydrothermal Fluids	Geochimica Et Cosmochimica Acta	56	1992	0	0
Hoehn et al.	Rn-222 As A Groundwater Tracer - A Laboratory Study	Environmental Science & Technology	26	1992	0	0
Solomon et al.	Tritium And He-3 As Groundwater Age Tracers In The Borden Aquifer	Water Resources Research	28	1992	0	0
Miko and Marton	Application Of Isotope Geochemistry To Hydrogeological And Environmental-Geological Investigations	Magyar Allami Foldtani Intezet Evi Jelentese	1990	1992	0	0
Kamensky et al.	H-3 He-3 Dating - A Case For Mixing Of Young And Old Groundwaters	Geochimica Et Cosmochimica Acta	55	1991	0	0
Wassenaar et al.	Radiocarbon In Dissolved Organic-Carbon, A Possible Groundwater Dating Method - Case-Studies From Western Canada	Water Resources Research	27	1991	0	0

Authors	Title	Place of publication	Vol.	year	A	B
Calf et al.	Recharge Mechanism And Groundwater Age In The Ti-Tree Basin, Northern-Territory	Australian Journal Of Earth Sciences	38	1991	0	0
Frohlich et al.	Application Of Isotopic Methods To Dating Of Very Old Groundwaters - Milk River Aquifer, Alberta, Canada	Applied Geochemistry	6	1991	0	0
Banner et al.	U-234 U-238 Th-230 Th-232 Systematics In Saline Groundwaters From Ceentral Missouri	Earth And Planetary Science Letters	101	1990	0	0
Thiele and Sarmiento	Tracer Dating And Ocean Ventilation	Journal Of Geophysical Research-Oceans	95	1990	0	0
Frohlich	On Dating Of Old Groundwater	Isotopenpraxis	26	1990	0	0
Andrews et al.	Atmospheric And Radiogenic Gases In Groundwaters From The Stripa Granite	Geochimica Et Cosmochimica Acta	53	1989	0	0
Bentley et al.	Cl-36 Dating Of Very Old Groundwater .1. The Great Artesian Basin, Australia	Water Resources Research	22	1986	0	0
Mazor et al.	Tritium Corrected C-14 And Atmospheric Noble-Gas Corrected He-4 Applied To Deduce Ages Of Mixed Groundwaters - Examples From The Baden Region, Switzerland	Geochimica Et Cosmochimica Acta	50	1986	0	0
Drost	Groundwater Measurements By Means Of Radioactive-Tracers	Atomkernenergie-Kerntechnik	48	1986	0	0
Dincer and Davis	Application Of Environmental Isotope Tracers To Modeling In Hydrology	J. Hydrol.	68	1984	0	0
Gupta et al.	An Approach To Determining Pathways And Residence Time Of Groundwaters - Dual Radiotracer Dating	Journal Of Geophysical Research-Oceans And Atmospheres	86	1981	1	0
Neretnieks	Age Dating Of Groundwater In Fissured Rock - Influence Of Water Volume In Micropores	Water Resources Research	17	1981	0	0
Sudicky and Frind	C-14 Dating Of Groundwater In Confined Aquifers - Implications Of Aquitard Diffusion	Water Resources Research	17	1981	1	0
Geyh	Interpretation Of Environmental Isotopic Groundwater Data: Arid And Semi-Arid Zones.	Arid-Zone Hydrology: Investigations With Isotope Techniques.		1980	0	0
Simard	C-14 And T Measurements Of Groundwaters In Eaton River Basin And In Mirabel Area, Quebec	Canadian Journal Of Earth Sciences	14	1977	0	0

C2 Detailed model description

In the following a more detailed model description is presented. Details on the MC simulation (number of MC runs and parameter boundaries), specifications of input functions and their convolution to minimize numerical uncertainty are given. Details on the considered model input uncertainties are also presented.

C2.1 MC Simulation details

To minimize numerical uncertainty an adequately large number of MC realizations were used. Generally a higher the number of MC simulations the closer the model output will get to the actual 'real' solution in expense of modelling time and processor memory. If an inadequately low number of simulations are run, misleading result may be obtained. However, in this inverse problem not only the number of simulations is crucial, but also the number of 'behavioural' models. When, e.g. only three behavioural models are obtained even at 1 million MC simulations, this low number of behavioural models does not allow an adequate assessment of the inferred parameter distribution. The following three solutions may be applicable: 1) the number of MC runs needs to be increased, 2) a smaller parameter range (i.e. narrower boundaries) needs to be resampled or 3) the objective function needs to be adjusted to allow more behavioural models (e.g. using a higher cut-off threshold or using the best 10% of models with regard to their objective function value) or a combination of these.

In this study the behavioural models (i.e. LPM parameter range and probability distribution and most likely parameter value) were assessed at 1,000, 10,000, 20,000, 50,000 and 100,000 MC runs (Fig. C1 and C2) to identity the most adequate number of MC simulations (most appropriate number of MC runs refers to an adequate large number of MC runs to reduce numeric uncertainty, but one that also allow for a practicable amount of model run time and processor memory). It was found that above 50,000 runs MC runs the behavioural models were independent of the number of MC runs for any location (example Fig. C1). The exceptions were two sites (Well 5 and 6), where a larger number of MC runs was necessary to allow for stabilization of the behavioural LPM parameter range (Fig. C3) and to allow for a larger number of behavioural models, i.e. a relatively smooth LPM parameter distribution.

To increase the number of behavioural models for these two sites, but keep model run time and processor memory at a minimum, 100,000 MC runs and a smaller MRT range (an MRT of 10 to 30 years for Well 5 and 0 to 15 years for Well 6) were used. For Well 5 the smaller MRT range resulted a higher number of behavioural models and with that a smoother LPM parameter distribution. For Well 6, however, the narrower MRT range, did not significantly improve the smoothness of the behavioural LPM parameter probability plots. This may be due to outliers in the observations or a generally high sensitivity towards uncertainties in tracer recharge (e.g. seasonality) due to its location in the unconfined area. To improve the model outcome of Well 6, the number of MC runs were increased to

1 million (with the same MRT boundaries of 0 to 15 years). To save time and processor memory, 50,000 MC simulations were run for the remaining sites. As a result between 130 and 4,200 behavioural models were obtained when using average inputs, the EPM and the monthly atmospheric tritium record which resulted in a relatively smooth and well defined distribution with identifiable parameters (e.g. Fig. C2). It is suggested to assess the most appropriate number of MC runs and adjust the LPM parameter boundaries if necessary to allow for relatively smooth, representative LPM parameter distributions.

Figure C1: Change in behavioural model number and MRT range (max-min) as function of MC run, when using monthly atmospheric data without consideration of uncertainty with tritium (UPPER) and SF6 (LOWER); * for Well 5 the MRT range had been adjusted to 15-30 years; for Well 6 the MRT range had been adjusted to 0-15 years

Figure C2: Effect of model runs at EPM on behavioural MRT and E/PM populations for Well 4 when using tritium observations and average input (tritium recharge equivalent to monthly atmospheric record, average half-life, without consideration of input uncertainty)

Figure C3: Effect of model runs on behavioural MRT and E/PM populations for Well 5 (UPPER) and Well 6 (LOWER) when using tritium observations and average input (tritium recharge equivalent to monthly atmospheric record, average half-life, without consideration of input uncertainty and the EPM); the large MRT range for both well 5 and 6 refer to 0-100 years; the small MRT range refers to 0-15 years (for Well 6) and 10-30 years (for Well 5).

C2.2 Input functions, input uncertainties and their convolution and integration

In this section the uncertainties deemed irrelevant or insignificant in this study are listed. It is also described which LPM type(s), recharge estimates and the decay function (if applicable) was used and how these functions were convolved and integrated to minimize numerical uncertainty.

Uncertainties deemed irrelevant or insignificant in this study

The following uncertainties have been deemed not relevant or insignificant in this study:

- Uncertainty in tracer decay – this could be excluded for SF₆ only, since SF₆ is not known to degrade in groundwater, even under anoxic conditions [e.g. Busenberg and Plummer, 2000].
- Uncertainty in tracer recharge estimate - this could be excluded for SF₆, since SF₆ is a gaseous tracer with a steadily increasing atmospheric concentration with lack of significant seasonality (see e.g. Bullister, (2014)).
- Uncertainty due to incomplete sampling of the entire age distribution is believed to be insignificant in this study: The well screens in the chosen study area were designed to sample the entire aquifer layer, which ensures sampling of the entire age distribution.
- Uncertainty in tracer observations in groundwater as a result of retardation, non-conservativeness (such as degradation) of the tracer in the groundwater environment or inadequate sampling,

storage/ analysis procedures is excluded. Retardation of tritium is negligible (tritium is part of the water molecule), and has been shown to be negligible for SF₆ [e.g. Watson et al., 1991; Wilson and Mackay, 1996]. SF₆ is sometimes found in tritium free groundwater, which is commonly attributed to problems during sampling, storage and/or analysis. This uncertainty was minimized in this study by following standard procedures for storage, sampling and analysis of SF₆ (and Halon-1301) [e.g. Busenberg and Plummer, 2008; van der Raaij and Beyer, 2015].

- Uncertainty in tracer input to groundwater as a result of spatially variable tracer recharge induced from spatially variable rainfall is deemed insignificant for SF₆ in the study, due to spatially invariable atmospheric SF₆ concentrations at the relatively small spatial scale of the study area. Tritium recharge may vary spatially, particularly at locations close to the ocean, due to differences in tritium concentration over oceans and continents driven by re-evaporation of tritium from land masses [Ehhalt, 1971]. These may affect the amount, timing and location of tritium being recharged, in addition to seasonally variable recharge. It was assumed that the effect of spatially variable rainfall and spatially variable tritium concentration on the tritium recharge in this study was minor, because the Lower Hutt Groundwater Zone is mainly river recharged (the river smoothed spatial variability in the catchment) and spatial variability in the relatively small and flat recharge area (of ca. 5 km² [Gyopari, 2014]) is expected to be insignificant.
- Uncertainty in time series tracer observations induced by non-steady state conditions is relevant for both tritium and SF₆, but insignificant as confirmed by an absence of apparent trends in major hydrochemistry for the time period where tracer observations were taken (Appendix C2) and absence of outliers in the time series tracer observations.

Transfer function or LPM

Three LPM types, namely the exponential piston flow model (EPM), piston flow model (PEM) and dispersion model (DM) were used as described in Eqn. C1, C2 and C3 and illustrated in Fig. C4, respectively (after Maloszewski and Zuber (1982) and Jurgens et al. (2012)).

$$\text{EPM: for } t' > \text{MRT}(1 - \frac{1}{n}), f_{\text{EPM}} = \frac{n}{\text{MRT}} * \exp(-n * \frac{t'}{\text{MRT}} + n - 1); \text{ else } f_{\text{EPM}} = 0. \quad \text{Eqn. C1}$$

MRT is the mean residence time; n=the reciprocal of the ratio of exponential in total flow, which is referred to as E/PM=1/n, the ratio of exponential in total flow in the following (n had been defined as ratio of total to exponential flow by after Maloszewski and Zuber, 1982). At E/PM = 0 for pure piston flow is obtained and at E/PM=1 for pure exponential flow is obtained.

$$\text{PEM: for } t' > \text{MRT}_{aq} * \ln(m), f_{\text{PEM}} = \frac{m}{\text{MRT}_{aq}} * \exp(\frac{-t'}{\text{MRT}_{aq}}) ; \text{ else } f_{\text{PEM}} = 0. \quad \text{Eqn. C2}$$

$\text{MRT}_{aq} = \frac{\text{MRT}_s}{\ln(m)+1}$, MRT_s is the MRT of the sample and m as the reciprocal of the ratio of sampled to total volume (P/EM). This version of the PEM conceptualises mixing of water in an aquifer that can be

described by the exponential model (EM), but only part of the well is screened and therefore sampled. At $n = 1$ (for wells screened across the entire aquifer) the EMM is obtained.

$$\text{DM: } f_{DM} = \frac{1}{MRT} \times \frac{1}{\sqrt{4\pi DP \frac{t'}{MRT}}} \times e^{-\frac{\left(1 - \frac{t'}{MRT}\right)^2}{4DP \frac{t'}{MRT}}} \quad \text{Eqn. C3}$$

The DM conceptualizes 1-dimensional advection-dispersion with DP as dispersion parameter, which is defined as $DP = \frac{D}{Vx}$ with dispersion coefficient D , velocity V and outlet position x . When $DP=0$, piston flow behaviour is obtained.

Figure C4: Schematic diagram of idealized aquifer in which the dispersion model (DM) (panel A) exponential piston-flow model (EPM) (panel B) and partial exponential model (PEM) (panel C) can be applied. DM: mixing occurs within the aquifer due to heterogeneities that cause variations in groundwater velocity. EPM: a partly confined aquifer with a recharge area of length x and a confined part of length x^* . PEM: an unconfined aquifer receiving uniform recharge with a partially screened well of length (z) and screen length $z-z^*$. The age distribution is illustrated below the schematic aquifer diagram assuming a MRT of 25 years (all 3 models), a dispersion parameter of 0.5 (DM), an EPM and PEM ratio of 1 (EPM and PEM) [after Jurgens et al, 2012].

Decay

Decay (applicable for tritium) is defined as: $f_{decay} = \exp(-\frac{\log 2}{t_{1/2}} * (t'))$, Eqn. C4

where $t_{1/2}$ is half-life, for tritium=12.32 +/-0.02 years (± 1 SD) [Lucas and Unterweger, 2000], t' is the transit time.

Atmospheric tracer records

For estimation of the tracers input/recharge, atmospheric tritium and SF₆ records from Kaitoke (located 50 km north of Wellington) [Taylor, 1966; Morgenstern and Taylor, 2009] and Cape Grim (Australia) [Bullister, 2014], respectively, were used. For Halon-1301 atmospheric records from Cape Grim were used [Newland et al., 2013]. Atmospheric records and uncertainty are illustrated in Fig. C5. Uncertainty in monthly atmospheric tracer concentrations is reported to be about 2-10 % of its median for tritium and 1-10% for SF₆. Where measurement uncertainty had not been reported (particularly true for data before 1920 for tritium and before 1950 for SF₆), uncertainties were approximated from existing data of similar magnitude (tritium) or were assumed to be within 10 % of its estimated concentration (for SF₆) [Rigby et al., 2010]. To the authors knowledge it has not been assessed if uncertainty in atmospheric record is biased or random. Figure C6 illustrates random and biased uncertainty in the tritium input.

Commonly discrete (monthly) tracer input data are used in groundwater age modelling studies. However, considerable uncertainty can be introduced by integration of discrete data. To reduce errors introduced by integration of vectorised data, studies in related areas have shown that either the time increment needs to be minimized or the data need to be interpolated [e.g. Hrachowitz et al., 2011 and references therein]. In this study atmospheric tracer records were interpolated to reduce numerical uncertainty. For tritium, piecewise cubic interpolation [Fritsch and Carlson, 1980] was found to best interpolate the data compared to polynomial or cubic spline fit (Fig. C7). To allow for adequate interpolation of the input data up to an upper integration limit of 300 times MRT, atmospheric tritium data were artificially extrapolated from 1943 until 1500 BC to background concentration (with average concentration from 1943 to 1955 equal to 1.5 tritium units (TU)). Tritium concentrations close to background (natural) concentrations were most representative for this time period, due to a lack of anthropogenic tritium sources. It should be noted that the actual extrapolated concentration, e.g. 1 or 10 TU, did not significantly change the age estimation, since only a very small portion of water is contained in waters with MRT up to 100 or 150 years.

Figure C5: Monthly and yearly (Dec-Nov) atmospheric tritium concentration in the southern hemisphere (Kaitoke) [Taylor, 1966, Morgenstern and Taylor, 2009], monthly atmospheric concentration of SF_6 in southern hemisphere (Cape Grim) [Bullister, 2014], with blow up of concentration between 2000 and 2010 to assess seasonality includes uncertainties

For SF_6 and Halon-1301, monthly atmospheric records were interpolated using piecewise cubic interpolation (Fig. C8). Atmospheric SF_6 records have been monitored since 1994. For the period 1953.5-1994.5 industrial production and release estimates were used to estimate annual atmospheric concentrations of SF_6 [Maiss and Brenninkmeijer, 1998]. Atmospheric concentrations prior to 1953.5 are assumed to be 0, based on the solubility of SF_6 in seawater [Bullister et al., 2002], which results in a concentration below the current limit of detection [e.g. Bullister and Wisegarver, 2008; van der Raaij and Beyer, 2015]. Halon-1301 concentrations prior to 1960 are assumed to be 0 based on Arctic and Antarctic firn air analysis [Butler et al., 1999] which showed absence of Halon-1301 prior to 1960.

It should be noted that additional uncertainty in the tracers recharge may be introduced due to artificially extending atmospheric tracer records for time periods with unknown concentration. The effect of this additional uncertainty on the age estimation is dependent on the transfer function and its parameters used, but will generally affect a wide age distribution with large MRT more than a narrower distribution with low MRT [Hrachowitz et al., 2011 and references therein].

Figure C6: Examples for biased and random uncertainty in tritium input, average denotes the fir through tritium observations, error bars display ± 1 SD

Figure C7: Interpolation of monthly (left) and yearly (right) atmospheric tritium data with pchip (piecewise cubic spline) and cubic spline – both fitting methods result in an insignificantly different fit for tritium

Integration

Integration of the convolved functions LPM, tracer input and decay (if applicable) was carried out with the Matlab build in function 'integral', which is a global adaptive quadrature numerical integration function based on 'quadva' [Shampine, 2008]. It adjusts the quadrature integration steps according to

the shape/discontinuity of the function and ensures an absolute/relative error of integration to a minimum of $10^{-10}/10^{-6}$ (default value) by comparison to Gaussian and Kronrod integration.

Figure C8: Interpolation of monthly atmospheric SF_6 concentration with pchip (piecewise cubic spline) and a spline (a cubic spline fit) – both fitting methods result in an insignificantly different fit for either tracer

Tracer observations

Measurement uncertainties for SF_6 (data before 2014) and tritium data had been provided by GNS Science (with a measurement uncertainty (1 SD) of 7- 15 % for SF_6 and 2- 10 % for tritium). Uncertainty reported for SF_6 includes correction for excess air, headspace, recharge temperature and elevation. Where the measurement uncertainty had not been reported (relevant for SF_6 only), an uncertainty of 10 % of the observed SF_6 concentration (equivalent to the average uncertainty in determination reported by van der Raaij and Beyer (2015)) was assumed. For Halon-1301 uncertainties have been determined in Chapter 4 of this thesis. Please note that in Chapter 4 determined analytical uncertainties were presented as uncertainty including and excluding uncertainty in solubility. Both uncertainty measures were considered in this study to assess their effect on uncertainty in inferred age.

To allow for a more comprehensive (and theoretical) assessment of the value that Halon-1301 added to the currently used tracers (SF_6 and tritium) with regard to uncertainty in inferred age and identification of LPM type, artificial Halon-1301 data were generated. To allow for (a more direct) comparison of the performance of SF_6 and Halon-1301, the observation times for the artificial Halon-1301 data were set to the observation times of SF_6 (specific for each site, the Hutt River was left out since it had also only one available SF_6 observation). To generate the artificial Halon-1301 concentrations it was assumed that the Halon-1301 input to groundwater follows monthly atmospheric Halon-1301 records at Cape Grim (Australia) with biased uncertainty. It was also assumed that groundwater flow can be conceptualized by the EPM (as formerly identified and confirmed with SF_6 and tritium in this study). The EPM parameters were randomly sampled inferred from one Halon-1301 observation.

The median and standard deviation of the generated population of possible Halon-1301 concentrations were then used as artificial Halon-1301 observations and their uncertainty, respectively. Since three of the five sites with an available Halon-1301 observation (excluding Hutt River) were degraded in Halon-1301 (as shown in Chapter 4), artificial Halon-1301 observations were only generated for the two remaining sites (namely Well 6 and 11).

Uncertainty in tritium recharge

Atmospheric tritium records:

Uncertainty in yearly average atmospheric tritium concentrations (as estimated from the standard deviation of average monthly atmospheric concentrations) was significantly larger compared to uncertainty in monthly average atmospheric tritium, induced by its seasonally changing signal, which may have overestimated uncertainties for yearly average atmospheric tritium concentrations. Taylor et al. (1992) reports the seasonality of tritium determined in rivers was considerably smoothed compared to atmospheric concentrations. They suggested that the smoothing is similar to that found for the oxygen isotope (O18), which is about 10% of the total seasonal variance. Ten % of uncertainty in yearly averaged tritium data equals a value close to the measurement uncertainty in monthly data and is therefore not considered as a separate case in this study.

Recharge weighted atmospheric tritium records:

Figure C9 illustrates the average monthly recharge estimated using a) precipitation and evapotranspiration data from selected stations in the recharge area and b) using a more complex recharge model by Butcher (1993). Both recharge estimates showed a similar pattern of higher recharge during spring, winter and autumn months (Ap. to Oct.) and very little to no recharge during summer (Nov. to Feb.). Total amounts vary significantly over time, which was taken into account with the 3rd time variable recharge estimate (not included in Fig. C9). All recharge weighting techniques increased the effect of seasonality significantly compared to yearly average concentrations of tritium in rain, illustrated in Fig. C10.

Figure C9: Comparison of recharge estimated using precipitation and evapotranspiration data from selected locations in the recharge area (data include 1 SD error bars) and recharge estimated by Butcher (1993) for the LHWZ

Locations of precipitation and evapo-transpiration data [CliFlo database (NIWA)] for recharge estimate method 2 are illustrated in Fig. C11. Data from 1975 to 1991 (this was the only time range with available monthly precipitation and potential evapo-transpiration data) were used. For recharge estimation method 3, actual (not average) monthly precipitation and potential evapo-transpiration data (time

range 1975-1991) were used. For calendar years with unavailable precipitation and potential evapo-transpiration data average monthly precipitation and potential evapo-transpiration data (determined from time range 1975-1991) were used.

Figure C10: Monthly averaged tritium input and monthly weighted tritium input

Figure C11: Locations of precipitation and evapo-transpiration data [CliFlo database (NIWA)]; solid line represents the outline of the Hutt River catchment

C2.3 Hydrochemistry trends for assessment of steady state flow

To confirm steady state flow conditions in the study area during measurement of age tracers in groundwater, a variety of hydrochemistry parameter (with lowest potential to be affected anthropogenically) were assessed for apparent trends and seasonality for the time range: 1992-2013 (time range where most tracer measurements were taken) at all sites with available age tracer data. Trend analysis was carried with the Mann-Kendall test and Sen's slope estimator, where a significant trend was characterized by $p < 0.05$ and an increase/year $>10\%$ [Helsel and Hirsch 1992; Daughney 2005]. Seasonality was assessed with the Kruskal-Wallis test. Trend and seasonality analysis results are summarized in Tab. C2 and C3, respectively.

A significant trend ($>10\%$ /year) was only found for Well 4, which showed a significant decrease in DO ($>10\%$). DO had been determined in the field with a probe, which had been submerged into the water sample. Due to that procedure, the DO measurement is sensitive towards the sampling procedure (adequate flushing of the well and submerging of the probe into fresh, unexposed groundwater) and to the calibration of the probe. The decrease found for the anoxic site (Well 4) may have been an artefact of better sampling and analysis procedures in recent years. Since no other parameters showed significant trends in Well 4, it was assumed that the trend observed for DO was a result of sampling procedure rather than non-steady state.

It should be noted that for some parameters insufficient data were available, so trend analysis could not be carried out (stated as ND in Table C1). Similarly some observations were below LOD, which were substituted according to a method by Helsel and Cohn (1988) [Daughney, 2007]. These parameters may have exhibited significant trends over the assessed time period, which were removed by substitution of below detection limits. However significant trends for these parameters seemed unlikely due to the absence of significant trends in the remaining hydrochemistry parameters.

Significant seasonality of the parameters alkalinity, B, Ca, Mg and K flowed by Fe, Na, TDS, Zn and pH was found in two shallow wells located in the recharge area (Well 6 and 2). The seasonality observed in these shallow wells may have been a result of seasonally changing recharge (varying proportions of river and rain recharge), because the Hutt River did only indicate significant seasonality of DO and Zn.

Table C2: Trends (N, ND, INCR/DECR in units/year) for Hutt aquifer sites; Sen's slope estimator data [%], data from 1993 to 2012; * above 10% (but below 15%) from median

Well	Alk. tot	Br	Ca	Cl	Cond. field	DO	F	Hard-ness	Fe	Mg	Mn	K	SiO ₂	Na	TDS	Zn	pH field
6	N	N	INCR 0.03	N	DECR -1.3	DECR -0.24	N	INCR 0.09	N	N	N	DECR -0.01	INCR 0.05	N	DECR -0.25	N	INCR 0.03
3	INCR 0.22	N	INCR 0.12	INCR 0.10	N	N	N	INCR 0.5	N	INCR 0.04	INCR 0.0005	INCR 0.007	N	INCR 0.12	N	N	N
4	N	N	N	N	N	DECR -0.04*	N	N	N	N	N	DECR -0.0003	N	INCR 0.08	N	N	N
5	N	N	INCR 0.15	DECR -0.08	N	N	N	N	N	N	N	N	N	N	N	N	N
8	N	N	N	N	N	N	N	ND	N	N	N	N	N	N	N	ND	N
1	N	N	DECR -0.21	N	ND	ND	N	N	ND	N	ND	N	ND	N	N	ND	ND
2	N	N	INCR 0.02	INCR 0.05	N	N	N	INCR 0.12	N	N	ND	DECR -0.005	INCR 0.05	N	N	N	INCR 0.03
10	N	N	N	N	ND	ND	N	N	N	N	N	N	ND	N	N	N	ND
7	N	N	N	N	N	N	N	ND	N	N	N	N	N	N	N	ND	N
9	N	N	N	N	N	N	N	ND	N	N	N	N	N	N	N	ND	N
11	N	N	N	N	ND	ND	N	N	N	N	N	N	ND	N	N	ND	ND
13	N	N	N	N	ND	ND	N	N	N	N	N	N	ND	N	N	N	ND
12	N	DECR -0.003	N	N	ND	ND	N	DEC 1.56	ND	N	ND	N	N	N	DECR -3.35	ND	ND
14	N	N	N	N	ND	ND	N	N	N	N	ND	N	ND	N	N	ND	ND
15	N	ND	N	N	INCR 0.11	INCR -0.03	ND	ND	N	N	N	N	ND	N	ND	DECR -0.004	N

Table C3: Seasonality test (Y, N or ND) for Hutt aquifer sites, concentrations given as total concentration in mg/L, TDS as conductivity in uS/cm, data from 1993 to 2012

Well #	Alkal. tot	Ca	Cl	Cond. field	DO	F	Hard-ness	Fe	Mg	Mn	K	SiO ₂	Na	TDS	Zn	pH field
15	N	N	N	N	Y	ND	ND	N	N	N	N	ND	N	ND	Y	N
1	N	N	N	ND	ND	N	N	ND	N	ND	N	ND	N	N	ND	N
10	N	N	N	ND	ND	N	N	N	N	N	N	ND	N	N	N	N
11	N	N	N	ND	ND	N	N	N	N	N	N	ND	N	N	ND	N
12	N	N	N	ND	ND	N	N	ND	N	ND	N	N	N	N	ND	N
13	N	N	N	ND	ND	N	N	N	N	N	N	ND	N	N	N	N
14	N	N	N	ND	ND	N	N	N	N	ND	N	ND	N	N	ND	N
2	Y	Y	Y	Y	Y	N	Y	Y	Y	ND	Y	Y	Y	Y	Y	Y
3	Y	N	N	N	N	Y	N	N	N	N	N	N	N	N	N	N
4	N	N	N	N	N	Y	N	N	N	N	N	N	N	N	N	N
5	N	Y	N	N	N	Y	N	N	N	Y	N	N	N	N	N	N
6	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y
7	N	N	N	N	N	N	ND	N	N	N	N	N	N	N	ND	N
8	N	N	N	N	N	N	ND	N	N	N	N	N	N	N	ND	N
9	N	N	N	N	N	N	ND	N	N	N	N	N	N	N	ND	N

C3 Detailed model outcome

C3.1 Details on the objective function

A variety of objective functions currently commonly used for hydrological model calibration or other curve fitting exercises was assessed in this study. The objective function that produced behavioural concentrations closest to observed tracer concentrations (with the lowest RMSE and bias) was the 'goodness of fit' or Chi² statistic (Eqn. C5 and C6). The Chi² statistic may have been more suitable for

this study's data because the LPMs, which were fit to the data, were relatively simple and the tracer's inputs were relatively 'smooth'. Highly variable or sudden changes in the fit, such as often encountered when using rainfall runoff models, can be accounted for by application of more complex objective functions, such as Nash-Sutcliffe or Kling-Gupta efficiency.

When using the χ^2 statistic, optimally simulated concentrations lie within the measurement error of the tracer observations, i.e. the 'optimal' variance of observed and simulated concentrations is less than or equal to 1. Hence models can be considered as adequately representing observations (i.e. behavioural), when the variance of simulated and observed concentrations does not significantly differ from the 'optimal' variance at a specific confidence level, i.e. the normalized observed χ^2 is below or equal to the normalized 'optimal' χ^2 (Eqn. C6) (after Helsel and Hirsch (2002)).

$$\text{normalized } \chi^2(\text{observed}) = \frac{\sum \frac{(obs-sim)^2}{\epsilon^2}}{df}, \quad \text{Eqn. C5}$$

where *obs* and *sim* are the observed and simulated tracer concentration, respectively; *df* is the degrees of freedom ($df = \# \text{ observations} - \# \text{ relations}$ e.g. when using the EPM, # relations is two (MRT and E/PM)), ϵ is the measurement error, e.g. 1 standard deviation (SD)

$$\text{normalized } \chi^2(\text{optimal}) = \frac{\chi^2(\alpha, df)}{df}, \quad \text{Eqn. C6}$$

where $\chi^2(\alpha, df)$ = χ^2 distribution at significance level α of e.g. 0.05 (or 95% confidence).

The χ^2 approach presumes normally distributed measurement errors and can only be applied on a relatively large dataset which allows at least one degree of freedom. For example a minimum number of three time series tracer observations is necessary, to fit an Exponential Piston flow Model (EPM) to tracer observations when using the χ^2 statistic. To ensure a consistent objective comparison of time series tracer simulations and observations for all sites in this study (independent of the number of tracer observations) several combinations of the following 'custom' objective function (Eqn. C7) are assessed with the aim to find a combination, which leads to similar behavioural models to those found with the χ^2 approach (assessed for sites with > 3 tracer observations).

$$\text{custom obj. fct.} = \frac{(x_1*a)+(x_2*b)+(x_3*c)+...+(x_{n-1}*y)+(x_n*z)}{o}, \quad \text{Eqn. C7}$$

where *o* is total number of observations, x_1 as number of simulations within 1 SD of observation(s), x_2 as number of simulations within 1-2 SDs of observations, x_3 as number of simulations within 2-3 SDs of observations, etc., x_n as number of simulations greater than *n* SDs from observations. Variables *a*, *b*, *c*, ..., *y*, *z* are assigned values (e.g. +0.5 or -1) to reward/penalize simulations that comply/do not comply with simulations within the considered level of uncertainty. A specific threshold (e.g. 0.5) is assigned to distinguish between behavioural and non-behavioural models.

When assessing the performance of a variety of custom objective functions at sites with more than three observations, consistent behavioural models with the χ^2 approach (at 99 % confidence, ≤ 2

SDs) in terms of number of behavioural models and range (max-min) of behavioural model parameters were obtained with the following custom objective function at threshold of 0.5

$$\text{custom obj. fct.} = \frac{(x_1*1)+(x_2*0.5)+(x_3*0.25)+(x_4*-0.25)+(x_5*-0.5)+(x_6*-1)}{o} \quad \text{Eqn. C8}$$

Although there were generally more empty spaces in the behavioural parameter cloud when the custom objective function was used (compared to Chi^2), both objective functions led to similar behavioural LPM parameter ranges and shape of uncertainty distribution of behavioural tracer concentrations (Fig. C13 to B14). The empty spaces may have been induced by the more rigorous approach of distinguishing behavioural from non-behavioural models at a certain uncertainty threshold. In contrast the Chi^2 is a ‘smoother’ approach which does not apply rigorous thresholds or cut offs, but assesses if the overall variance of simulations and observations is statistically similar. The Chi^2 approach may have therefore appeared the more appropriate objective function when an adequate number of tracer time series observations were available. However, note that the Chi^2 approach presumes normally distributed measurement errors, but the actual shape of uncertainty in tracer observations is often unknown, because an adequately large data set of tracer measurements at point in time is rarely available to study the shape of uncertainty distribution in tracer observations in groundwater. Some studies had assumed normally distributed errors [e.g. Green et al., 2014]. Others had assumed log-normally distributed errors [e.g. Massoudieh et al., 2014]). Assuming a specific uncertainty distribution shape can often not be justified and may lead to significant errors in the model outcome, as shown in other areas of hydrological modelling [Stedinger et al., 2008].

As can be seen in Fig. C12 and C13, when using the custom objective function, the behavioural tracer simulations followed relatively well defined distributions, which did not necessarily agree with the normal distribution. When assessing uncertainty distribution of the inferred LPM parameters (e.g. Fig. C13 to C15), one can observe that the distribution of behavioural LPM parameters was often relatively well-defined (i.e. a relatively narrow most likely range), but was not of a specific shape (e.g. Gaussian, or log-normal). It can also be seen that the most likely LPM parameter did not (necessarily) occur at the best objective function value. This indicated that the commonly inferred and reported best fitting LPM parameters may not necessarily reflect the most likely LPM parameters.

Figure C12: Example of behavioural model parameters when using χ^2 different uncertainty levels (UPPER) or a custom objective function (LOWER) at different threshold levels for Well 4 inferred from multiple tritium observations

Figure C12 to C14 also illustrate that the behavioural LPM parameters were dependent on the considered measurement error (e.g. 1 or 2 SDs) and probability (e.g. 99 and 80%) for the χ^2 objective function or the measurement error (e.g. 1 or 2 SDs) and the threshold (e.g. 0.5 or 0.6) for the custom objective function. However, the shape of the distribution of behavioural LPM parameters was not altered. This indicated that the most likely LPM parameters inferred when using the custom objective function or χ^2 objective function was not sensitive to the chosen thresholds (measurement error or confidence level), but the range (max-min) of the behavioural LPM parameters was sensitive to this. Depending on the tracer observations (and analytical uncertainty) or purpose of the study, the

confidence, uncertainty level or objective function threshold can be adjusted if appropriate. This implies if one was only interested in the most likely age estimation it does not matter which objective function (custom and χ^2) and uncertainty level or objective function threshold is used. For assessment of the entire uncertainty distribution, however, appropriate threshold(s) need to be identified.

Figure C13: Example of behavioural model parameters when using Chi² different uncertainty levels (UPPER) or a custom objective function (LOWER) at different threshold levels for Well 5 inferred from multiple tritium observations

C3.2 Detailed assessment of input uncertainties on the behavioural LPM parameter populations

In the following details on the performance of the chosen framework components (the LPM type, tracer recharge estimate) are presented and the behavioural LPM parameters inferred when using one

of the three LPM types (the PEM, EPM and DM), uncertainty in tracer input (monthly, yearly, recharge weighted atmospheric concentrations), uncertainty in the shape of uncertainty distribution in atmospheric tracer records and uncertainty in tritium decay are shown.

Figure C14: Example of behavioural model parameters when using the custom objective function at different threshold levels for Well 5 inferred from one SF₆ observations (UPPER) and for Well 4 inferred from 2 SF₆ observations (LOWER)

LPM type

Figure C15 illustrates Box and Whisker plots of the behavioural LPM parameters ranges (max-min) obtained for all sites in the LHGWZ when using three different LPM types (EPM, DM and PEM). It can be seen that the choice of LPM type significantly affected the LPM parameter range. This indicated that it is important to evaluate the best LPM type or a use multi-model approach to account for uncertainties in model structure.

Figure C15: Behavioural MRT and E/PM range inferred when using three LPM types (EPM = exponential piston flow model; DM= dispersion model and PEM=partial exponential model) for tritium (UPPER) and SF₆ (LOWER)

Decay

Figure C16 illustrates Box and Whisker plots of the behavioural LPM parameter ranges (max-min) obtained for all sites in the LHGWZ when using average half-life, half-life + 1 SD and half-life – 1 SD. As can be seen the behavioural MRT and EPM range as well as the model number did not vary significantly which indicated that the effect of uncertainty in decay on the behavioural LPM parameter population was negligible.

Table C4: Performance criteria for the EPM, DM and PEM when using Halon-1301

criterion	LPM type		
	EPM	DM	PEM
Use all sites with one observation, except two sites (Well 6 and 11) with artificial data			
RMSE [^]	0.25 (0.06/0.40)	0.25 (0.08/0.40)	0.25 (0.06/0.40)
Bias [^]	0.24 (0.06/0.36)	0.24 (0.08/0.36)	0.24 (0.06/0.36)
CV (MRT/ mix.p.)	0.45 (0.52/0.38)	0.51 (0.61/0.40)	0.45 (0.53/0.36)
# behav. mod.	16107	20981	15946
Sum points	7	2	6
With artificial data using Well 6 and 11 only			
Bias [^]	0.184 (0.06/0.40)	0.183 (0.08/0.40)	0.182 (0.06/0.40)
RMSE [^]	0.223 (0.06/0.36)	0.219 (0.08/0.36)	0.217 (0.06/0.36)
CV (MRT/ mix.p.)	0.417/0.565	0.588/0.668	0.419/0.562
# behav. mod.	4759	2753	4796
Sum points	7	2	6
Without artificial data using Well 6 and 11 (only)			
RMSE [^] , Bias [^]	0.432 (0.577/0.288)	0.430 (0.575/0.284)	0.432 (0.575/0.288)
CV (MRT/ mix.p.)	0.524/0.596	0.648/0.712	0.520/0.591
# behav. mod.	15299	8051	14980
Sum points	2	6	2

Figure C16: Max MRT and E/PM inferred from tritium observations and number of behavioural models when using average half-life and half-life $\pm$ 1 SD

Recharge estimate

Table C5 summarizes the performance criteria and corresponding score for each recharge estimated used in this study showing that the monthly and yearly average atmospheric concentrations performed better than the recharge weighted estimates for tritium. Figure C17 illustrates Box and Whisker plots of the behavioural LPM parameter populations obtained for all sites in the LHGWZ when using different tracer (tritium) recharge estimates. As can be seen the LPM parameter populations were significantly affected by the choice of tracer recharge estimate. Interestingly the difference in behavioural MRT and EPM range was insignificant for the majority of sites (below 3%) when recharge estimates 1 and 2 were

used, except three sites with only 1-2 observations. Recharge estimate 3 led to larger changes in the behavioural MRT and EPM range between 10 and 65% for all assessed locations.

Figure C17: Max, min MRT and max E/PM inferred from tritium observations when using different tritium input estimates, 12m denotes 12 monthly average (Dec-Nov) and 12m 2 denotes yearly average (Jul-Jun), for all sites

Table C5: Average criteria at all sites to assess the most representative tritium recharge: median RMSE (root mean square error) and median bias of behavioural simulations and observation; median coefficient of variation (CV) of behavioural MRT and E/PM range (max-min); median number of behavioural models; median=median at all sites, *data given as median (25/75 percentile), ^ median bias and median RMSE for observation number 9 (in 1972) before the arrival of the bomb peak and observation number 8 (in 1997) after arrival of the bomb peak at Well 5; detailed box whisker plots can be found in Appendix C3; colour code: dark grey = 2 points; medium grey=1 point; light grey=0 points

Recharge estimate	Monthly average	Yearly (Jul-Jun) average	Yearly (Dec-Nov) average	Recharge method 1	Recharge Method 2	Recharge Method 3
CV (MRT/E/PM)	0.55/0.50	0.73/0.42	0.45/0.57	0.46/0.50	0.43/0.44	0.72/0.45
RMSE *	0.67 (0.60/0.93)	0.78 (0.60/0.96)	0.78 (0.60/0.96)	0.91 (0.59/0.96)	0.92 (0.60/0.97)	0.92 (0.63/1.00)
Bias *	-0.006 (-0.004 /-0.020)	-0.005 (-0.003 /-0.018)	-0.005 (-0.003 /-0.018)	-0.005 (-0.003 /-0.022)	-0.008 (-0.003 /-0.021)	-0.011 (-0.003 /-0.027)
# behav. models	886	1020	994	692	813	997
RMSE; bias import.obs.^	1.49; 0.009	1.50; 0.014	1.46; 0.012	1.54; -0.012	1.51; -0.026	1.28; -0.038
Sum points	8	6	7	4	4	1

Uncertainty in atmospheric trends

Table C6 summarizes the performance criteria and corresponding score when using random and biased uncertainty in the atmospheric tritium and SF₆ trend showing best performance with biased uncertainty for tritium and SF₆. Figure C18 illustrates Box and Whisker plots of the behavioural LPM parameter ranges (max, min) obtained for all sites in the LHGWZ when using random and biased uncertainty in atmospheric tracer records. No difference in behavioural models was obtained when using single Halon-1301 observations as illustrated in Fig. C19.

As expected, the range of behavioural EPM parameters was significantly wider for all sites when monthly/yearly averaged atmospheric data including ± 1 SD uncertainty was used, compared to monthly/yearly average data alone. For tritium a wider behavioural MRT and E/PM range was obtained when yearly atmospheric records (with biased or random uncertainty) were used compared to the one obtained when using monthly records (with biased or random uncertainty). This can be explained by the seasonally varying atmospheric signal, which may have led to a higher uncertainty in yearly average

atmospheric records (due to averaging of monthly records) compared to monthly average records. However, this may have overestimated uncertainty in yearly average tritium concentrations as discussed earlier (in section C2.2).

*Table C6: Criteria to assess the most representative uncertainty shape in atmospheric tritium and SF₆ data average RMSE (root mean square error) and average bias of behavioural simulations and observation; average CV (coefficient of variation) of behavioural MRT and E/PM range; average number of behavioural models; *data given as median (25/75 percentile); ^ average bias and average RMSE for observation number 9 (in 1972) before the arrival of the bomb peak and observation number 8 (in 1997) after arrival of the bomb peak at Well 5; detailed box whisker plots can be found in Appendix C3; average = average of all sites; dark grey = 2 points; medium grey=1 point; light grey=0 points*

Shape of uncertainty		Monthly biased	Monthly random
Tritium monthly input	CV (MRT/ E/PM)	0.47/0.56	0.44/0.50
	RMSE*	0.65 (0.58/0.96)	0.67 (0.58/0.96)
	Bias*	-0.009 (-0.004/ -0.021)	-0.007 (-0.003/ -0.019)
	# behav. models	849	907
	RMSE; bias import.obs.^	1.08; -0.0001	no behav. model
	Sum points	7	7
Tritium yearly input	CV (MRT/ E/PM)	0.55/0.44	0.51/0.52
	RMSE*	0.65 (0.59/0.97)	0.70 (0.63/1.0)
	Bias*	-0.009 (-0.005/ -0.019)	-0.008 (-0.003/ -0.012)
	# behav. models	657	851
	RMSE; bias import.obs.^	1.22; -0.01	no behav. model
	Sum points	6	3
SF ₆	CV (MRT/ E/PM)	0.41/0.45	0.39/0.43
	RMSE*	1.17 (0.51/2.10)	1.12 (0.49/2.08)
	Bias*	1.05 (0.41/1.81)	1.05 (0.43/1.78)
	# behav. models	7442	7430
	Sum points	5	6
Halon-1301	CV (MRT/ E/PM)	0.41/0.53	0.39/0.52
	RMSE*	0.23 (0.05/0.42)	0.23 (0.05/0.42)
	Bias*	0.23 (0.05/0.42)	0.23 (0.05/0.42)
	# behav. models	13989	13961
	Sum points	5	5
Halon-1301 with artificially generated data			
Average of data from all sites with one observation and two sites (Well 6 and 11) with artificial data	CV (MRT/ E/PM)	0.43/0.47	0.44/0.51
	RMSE*	0.28 (0.06/0.51)	0.29 (0.06/0.51)
	Bias*	0.28 (0.06/0.48)	0.29 (0.06/0.48)
	# behav. models	148795	19190
	Sum points	7	4
Average of data from Well 6 and 11 with artificial data	CV (MRT/ E/PM)	0.184 (0.16/0.21)	0.156 (0.11/0.20)
	RMSE*	0.223 (0.18/0.26)	0.185 (0.11/0.26)
	Bias*	0.417/0.565	0.397/0.584
	# behav. models	4759	4384
	Sum points	7	2

Figure C18: Behavioural MRT and E/PM range (max, min) under consideration of measurement uncertainties in tracer input for tritium (UPPER) and SF6 (LOWER)

Figure C19: Behavioural MRT and E/PM inferred from single Halon-1301 observations

C4 Detailed age estimation

In the following the effect of bin size on the LPM parameter distribution is presented. A discussion on factors that influence how well the age estimation can be constrained and a discussion on the combination of the age estimation obtained from three tracers (here SF₆, Halon-1301 and tritium) are also given.

C4.1 Probability plots

The population of behavioural LPM parameter are illustrated in probability plots. These probability plots were established by binning the behavioural LPM parameter population into bins and normalizing the binned data by the sum of all behavioural models (under the assumption that all behavioural models fit observations adequately well). Since the bin size had an effect on the shape of the probability distribution, the most appropriate bin size of the following bin sizes: 10, 20 and 40 was identified when assessing 1) a relatively narrow MRT range (Well 4), 2) a relatively wide MRT range

(Well 8) and 3) relatively few behavioural models (Well 5). Results, as illustrated in Fig. C20 to C22, indicated that when 10 bins were used detailed features of the LPM parameter distribution could not be captured, such as two ranges with highly likely MRTs (e.g. Well 8, Fig. C20). However when 40 bins were used the probability plots were over-fit (leading to artificial features in the distribution), particularly for locations with very few behavioural models (e.g. Well 5, Fig. C21). To avoid both over- and under-fitting, a bin size of 20 was chosen as a compromise.

Figure C20: Effect on bin size on the distribution of behavioural LPM parameters inferred from SF₆ for Well 4

Figure C21: Effect on bin size on the distribution of behavioural LPM parameters inferred from tritium for Well 8

Figure C22: Effect on bin size on the distribution of behavioural LPM parameters inferred from tritium for Well 5

C4.2 Age estimation at 90 and 95% confidence

Table C7 summarizes the inferred age estimation at 90 and 95% confidence in comparison to the entire range (max-min) presented in Tab. 5-4 in Chapter 5 for tritium and SF₆.

Table C7: Inferred age estimation at 90 and 95% confidence for tritium and SF₆

Well #	% tile	inferred from Tritium				inferred from SF ₆			
		MRT min	MRT max	E/PM min	E/PM max	MRT min	MRT max	E/PM min	E/PM max
1	100	6.9	63.7	0.0	1.0	8.6	19.9	0.0	1.0
	90	11.8	49.2	0.1	0.9	9.6	15.6	0.1	0.9
	95	10.9	54.3	0.1	0.9	9.3	16.8	0.1	1.0
2	100	0.7	50.9	0.0	1.0	0.2	5.5	0.0	1.0
	90	1.0	47.0	0.2	0.8	0.8	4.3	0.1	0.9
	95	0.9	47.9	0.1	0.9	0.6	4.5	0.1	1.0
3	100	2.9	58.3	0.0	1.0	3.3	10.9	0.0	1.0
	90	7.7	21.9	0.3	0.9	4.1	8.2	0.1	0.9
	95	7.0	24.5	0.2	1.0	3.8	8.9	0.1	1.0
4	100	19.1	51.1	0.4	0.8	8.2	21.3	0.0	1.0
	90	24.4	42.0	0.4	0.6	9.4	16.2	0.2	0.9
	95	22.7	44.3	0.4	0.6	8.9	17.8	0.1	1.0
5	100	17.7	29.8	0.0	0.7	25.4	100.0	0.0	0.9
	90	19.7	22.0	0.2	0.3	29.6	87.4	0.2	0.9
	95	19.4	22.4	0.2	0.4	28.5	93.5	0.1	0.9
6	100	0.5	2.5	0.0	1.0	0.1	2.9	0.0	1.0
	90	1.0	1.8	0.2	0.8	0.3	2.2	0.1	0.9
	95	1.0	1.9	0.1	0.9	0.2	2.4	0.0	0.9
7	100	26.7	40.4	0.0	0.4	-	-	-	-
	90	29.4	36.3	0.2	0.3	-	-	-	-
	95	28.7	37.2	0.1	0.4	-	-	-	-
8	100	7.3	55.8	0.0	1.0	2.7	8.5	0.0	1.0
	90	8.6	50.6	0.2	1.0	3.3	6.7	0.1	0.9
	95	8.3	52.3	0.1	1.0	3.1	7.2	0.1	1.0
9	100	55.7	99.9	0.0	0.5	-	-	-	-
	90	63.2	94.2	0.1	0.4	-	-	-	-
	95	61.0	96.9	0.0	0.5	-	-	-	-
10	100	0.1	50.8	0.0	1.0	-	-	-	-
	90	2.0	47.5	0.1	0.9	-	-	-	-
	95	1.2	49.3	0.1	0.9	-	-	-	-
11	100	0.9	56.6	0.0	1.0	2.34	6.38	0.00	1.00
	90	6.7	49.7	0.1	0.9	2.92	5.30	0.11	0.92
	95	6.2	52.1	0.1	1.0	2.76	5.57	0.06	0.96
12	100	7.1	64.5	0.0	1.0	-	-	-	-
	90	12.6	51.3	0.1	0.9	-	-	-	-
	95	11.5	56.2	0.1	0.9	-	-	-	-
13	100	0.1	51.8	0.0	1.0	-	-	-	-
	90	2.5	46.9	0.1	0.9	-	-	-	-
	95	2.0	49.3	0.1	0.9	-	-	-	-
14	100	0.4	51.1	0.0	1.0	-	-	-	-
	90	4.5	47.2	0.3	0.5	-	-	-	-
	95	1.2	48.5	0.2	0.7	-	-	-	-
15	100	49.8	1.0	0.2	0.0	-	-	-	-
	90	44.9	0.9	0.6	0.1	-	-	-	-
	95	47.9	1.0	0.4	0.1	-	-	-	-

C4.3 Factors that influence uncertainty of the age estimation

In general how well the age estimation can be constrained (in terms of its uncertainty) is dependent on various factors. A compendium can be found in the following:

- The tracers input concentration. This is more ambiguous for tritium than SF₆ and Halon-1301.
- Sensitivity of the tracer observation to external processes/factors. Such processes/factors include sampling procedure and estimate of recharge temperature applicable for SF₆ and Halon-1301 and actual recharge to the groundwater (mainly) applicable for tritium.
- The time interval between the observations. For example for Well 4 vs Well 14, despite Well 14 having more observations (11) than Well 4 (9), Well 14 data could not be fit very well, because tritium data have been obtained with a monthly time interval. Data obtained with a small time interval (< 1year) are expected to be sensitive towards seasonality of the tritium signal and actual tritium recharge.
- The timing of the observation. Ambiguous results with tritium can still be obtained with multiple observations, e.g. as found for Well 8 with three observations. An additional measurement, taken at a later time, may annihilate the effect of radioactive decay and similarly decreasing atmospheric concentration.
- The number of observations. Fig. C23 shows the objective function and behavioural EPM parameter range (max, min and mean) as function of number of observations (by removing observations backward in time) for Well 4. The wider range of max, min and mean MRT found at lower number of tracer observations confirm a higher likelihood of an ambiguous MRT and E/PM prediction with a lower number of observations.
- Heterogeneities in the subsurface and/or a more complex flow, which cannot be explained by the simplified LPM. This can cause poorer fits with increasing number of tracer observations. Fig. C20 illustrates Well 4, where best results (highest objective function, least ambiguous results) were obtained with at least six observations. However more data do not necessarily improve the fit (as also shown in Fig. C23 with a slightly decreased objective function value with more than eight observations), because additional observations may capture that mixing is more complex than can be represented by a simplified LPM. A reduced objective function may also indicate outlier(s), induced by erroneous determination or changing groundwater flow (non-steady state) (e.g. observation 9 in Fig. C23).
- Transient groundwater flow conditions, due to e.g. seasonal variability in pumping, may influence the tracer's concentration in groundwater and may result in a larger uncertainty in the age estimation.

Figure C23: Objective function as a function of number of observations for Well 4, tritium data using monthly average atmospheric concentrations with the custom objective function (UPPER) and Chi² objective function (LOWER)

C4.4 Tracer combination methods from a combined age estimation inferred from tritium, Halon-1301 and SF₆

To infer a combined age estimation from multiple tracers, the following four tracer combination methods were suggested in Chapter 5 of this thesis. Overall the age estimation could be better constrained when combining age estimations inferred from Halon-1301, SF₆ and tritium when using any of the three methods (as illustrated in Fig. C24 and C25). For example for Well 4, the relatively unconstrained, wide E/PM range obtained with SF₆ alone could be better constrained when a combination of tritium, Halon-1301 and SF₆ was used. For Well 8, the MRT of 40-50 years of the ambiguous age estimation inferred from tritium could be excluded with consideration of SF₆. In the following it is commented on how well the age estimation could be constrained when inferred from combinations of SF₆, tritium and Halon-1301 (compared to the ones inferred from each individual tracers) using any of the four methods. Since assessment of the performance of Halon-1301 (the new groundwater age tracer presented in Chapter 4) was of particular focus of this study, the relative

change in the age estimation when including/excluding Halon-1301 is summarized in Tab. C8 and illustrated in Fig. C26.

Method 1: average of behavioural LPM parameter populations inferred from each individual tracer:

The simple combination (average) of the behavioural EPM parameters inferred from any tracer implied equal weighting of all tracers' age estimation resulted in a large uncertainty of the inferred MRT and E/PM (Fig. C24 and C25). Because in the majority of cases, the behavioural population of EPM parameters inferred from Halon-1301 and SF₆ were significantly larger than inferred from tritium, this approach resulted in artificially higher weighting of the LPM parameters inferred from Halon-1301 and SF₆ compared to the ones inferred from tritium.

Method 2: All tracers' objective function > threshold:

This method implied that LPM parameters were considered as behavioural if the objective function for all tracers was met. Figure C24 and C25 illustrate that method 2 resulted in a reduced number of behavioural models and reduced uncertainty in the MRT and E/PM compared to the ones inferred from method 1. This method may be too strict, particularly when e.g. some tracer observations were erroneous. This can be resolved with tracer combination method 3.

Method 3: Average objective function of all tracers > threshold:

This method implied that LPM parameters were considered as behavioural if the average of all tracers' objective function was met (with equal weight for all tracers' objective function). Figure C24 and C25 illustrate that method 3 led to a narrower range of behavioural models than obtained with method 1, but a larger range than obtained with method 2.

When using method 1 to 3, the EPM parameters inferred from all tracers were weighted equally. This appears inappropriate, since the LPM parameters can be better constrained with a larger number of observations as accounted for by method 4.

Method 4: Weighted average objective function of all tracers > threshold:

This method implied that LPM parameters were considered as behavioural if the weighted average of all tracers' objective function was met. Weighting was carried out according to the number of (time series) observations, i.e. the tracer with a larger number of observations was given a higher weight compared to the tracer with a lower number of tracer observations. As a result a narrower LPM parameter range and lower number of behavioural models was obtained compared to method 1 and 3 (Fig. C24 and C25).

Because the presented methods did not take into account each tracers' individual performance (i.e. magnitude of uncertainty in behavioural LPM parameter), it was also considered to weight the objective function with uncertainty in LPM parameters. However this is complicated, because

uncertainty in LPM parameters is dependent on the tracers input shape (i.e. higher uncertainty with flatter input curve) and uncertainty in the tracers observation (i.e. higher uncertainty with higher uncertainty in observation) and for tritium also the time of observation in relation to the time of recharge (i.e. higher uncertainty when tritium is decayed to background levels). It is hoped that further studies will develop a tracer combination method that can account for this uncertainty.

Figure C24: MRT range (max, min) and behavioural model number inferred by combining SF_6 and tritium for Well 4

Figure C25: Probability as function of MRT (LEFT) and E/PM (RIGHT) inferred from tritium, Halon-1301 and SF_6 combined for Well 11 = Shandon GC (UPPER) and Well 6= Avalon (LOWER)

Table C8: Average relative change in uncertainty in the MRT and E/PM when including Halon-1301- all changes were statistically insignificant ($p > 0.05$) which is probably a result of the small number of available data, data highlighted in orange/yellow refer to a increase/decrease in uncertainty when including Halon-1301, respectively; the colour green indicates no significant change when including Halon-1301

Combination method #	Relative change in uncertainty for MRT when using			Relative change in uncertainty for E/PM when using		
	All 3	Halon-1301 and SF ₆	Halon-1301 and tritium	All 3	Halon-1301 and SF ₆	Halon-1301 and tritium
Only non-degraded sites (Well 6, 11 and 15)						
1	0.02	-0.01	0.01	<0.01	<0.01	<0.01
2	0	1827.6	561.3	0	545.6	539.9
3	15.8	60.2	16.7	0.02	0.04	<0.01
4	29.1	215.9	49.2	0.7	1.4	-0.02
Only non-degraded sites (Well 6, 11 and 15) plus artificial data for Well 6 and 11						
1	0.02	-2.5	0.02	0.0	0.0	0.0
2	-8.6	2429.6	730.5	-16.5	727.5	703.4
3	24.3	67.3	-4.7	0.04	0.1	0.0
4	45.1	305.4	50.3	1.8	1.9	1.6

Figure C26: Relative range in uncertainty in MRT and E/PM when considering Halon-1301 in addition to tritium and/or SF₆ compared to using tritium and/or SF₆ alone; bars symbolize the median relative change obtained when assessing all sites; error bars symbolize the maximum and minimum change obtained; Table 5-5 in Chapter 5 shows whether the average change was significant.

C5 References of Appendix C

Bullister, J. L.; Wisegarver, D.P. and F. A. Menzia (2002) The solubility of sulphur hexafluoride in water and seawater, Deep Sea Research Part I: Oceanographic Research Papers 49(1), 175-187, ISSN 0967-0637, http://dx.doi.org/10.1016/S0967-0637(01)00051-6 .
Bullister, J.L. (2014) Atmospheric CFC-11, CFC-12, CFC-113, CCl4 and SF6 Histories. http://cdiac.ornl.gov/ftp/oceans/CFC_ATM_Hist/CFC_ATM_Hist_2014 . Carbon Dioxide Information Analysis Center, Oak Ridge National Laboratory, US Department of Energy, Oak Ridge, Tennessee. Doi: 10.3334/CDIAC/otg.CFC_ATM_Hist_2014
Bullister, J.L. and D.P. Wisegarver (2008): The shipboard analysis of trace levels of sulfur hexafluoride, chlorofluorocarbon-11 and chlorofluorocarbon-12 in seawater. Deep-Sea Res. I, 55, doi: 10.1016/j.dsr.2008.03.014, 1063–1074.
Butcher, G.M. (1993) Estimate of potential rainfall recharge to the Hutt Aquifer System. Wellington Regional Council, Technical Report WRC/CI-T-93/52.
Daughney, C.J. (2007) Spreadsheet for automatic processing of water quality data: 2007 update, GNS science report, 2007/17, 18p.
Daughney, C.J. (2005) Spreadsheet for automatic processing of water quality data: Theory, use and implementation in excel, GNS science report, 2005/35, 84p.
Ehhalt, D. H. (1971) Vertical profiles and transport of HTO in the troposphere. Journal of Geophysical Research 76: 7351-7367.
Fritsch, F.N. and R.E. Carlson (1980) Monotone Piecewise Cubic Interpolation, SIAM J. Numerical Analysis, 17, pp.238-246.
Helsel, D R. and Cohn, T.A. (1988) Estimation of descriptive statistics for multiply censored water quality data. Wat. Resources Res. 24, 1997-2004.
Helsel, D.R. and Hirsch, R.M., 1992, Statistical Methods in Water Resources, Elsevier, 522 p.
Hrachowitz, M.; Soulsby, C.; Tetzlaff, D. and I.A. Malcolm (2011) Sensitivity of mean transit time estimates to model conditioning and data availability. Hydrol. Process., 25: 980–990. doi: 10.1002/hyp.7922
Lucas, L.L. and M.P. Unterweger (2000) Comprehensive Review and Critical Evaluation of the Half-Life of Tritium, Journal of Research of the National Institute of Standards and Technology 105(4), 541. doi:10.6028/jres.105.043.
Maiss, M., and C.A.M. Brenninkmeijer (1998) Atmospheric SF ₆ , trends sources and prospects, Environ. Sci. Tech., 32, 3077-3086.
Morgenstern, U. and C.B. Taylor (2009) Ultra Low-level tritium measurement using electrolytic enrichment and LSC, Isotopes in Environmental and Health Studies, 45, 96–117.
Rigby, M.; Mühle, J.; Miller, B.R.; Prinn, R.G.; Krummel, P.B.; Steele, L.P.; Fraser, P.J.; Salameh, P.K.; Harth, C.M.; Weiss, R.F.; Grealley, B.R.; O'Doherty, S.; Simmonds, P.G.; Vollmer, M.K.; Reimann, S.; Kim, J.; Kim, K.-R.; Wang, H.J.; Olivier, J.G.J.; Dlugokencky, E.J.; Dutton, G.S.; Hall, B.D. and J. W. Elkins (2010) History of atmospheric SF ₆ from 1973 to 2008, Atmos. Chem. Phys., 10, 10305–10320, doi:10.5194/acp-10-10305-2010.
Shampine, L. F. (2008) Vectorized adaptive quadrature in MATLAB, Journal of Computational and Applied Mathematics, v.211 n.2, p.131-140, January 2008 [doi>10.1016/j.cam.2006.11.021]
Taylor, C. B. (1966) Tritium in Southern Hemisphere precipitation 1953–1964. Tellus, 18: 105–131. doi: 10.1111/j.2153-3490.1966.tb01449.x
Taylor, C.B., L.J. Brown, J.J. Cunliffe, P.W. Davidson (1992) Environmental tritium and 18O applied in a hydrological study of the Wairau Plain and its contributing mountain catchments, Marlborough, New Zealand, J. Hydrol., 138, pp. 269–319.
Van der Raaij, R. and Beyer, M. (2015) Use of CFCs and SF ₆ as groundwater age tracers in New Zealand, J. Hydrol. New Zealand 54(1), in press.

Appendix D – for Chapter 6

This Appendix consists of five parts. In the first part details on the study area (LHGWZ) are summarized which includes information on the structure of the groundwater zone (alternating aquifer and aquiclude layer) and information on the composition of the aquifer material. The second and third parts give detailed results on the hydrochemistry and aquifer material analysis, respectively, obtained in this study. In the fourth and fifth part detailed results and discussion on the inferred hydrochemistry-PT relationships and age information are presented, respectively.

D1- Details on aquifer composition (LHGWZ)

D2 - Detailed assessment of hydrochemistry in the LHGWZ

D3 - Detailed assessment of aquifer material in the LHGWZ

D4 - Detailed hydrochemistry-PT modelling results

D5 - Detailed results on constrained age information with inferred hydrochemistry-PT relationships

D6 References of Appendix D

D1 Detailed assessment of hydrochemistry in the LHGWZ

D1.1 Statistical and graphical tools for assessment of the consistency of hydrochemistry data

Various statistical tools, such as hierarchical cluster analysis (HCA) and visualization methods, such as the Piper diagram or box plots [e.g. Freeze and Cherry, 1979; Langmuir, 1997] have been used to identify homogeneity or stratification of the aquifer, steady state and recharge source based on hydrochemistry (which may indicate the same potential drivers and controlling factors affecting hydrochemistry in that aquifer). Other statistical tools such as principal component analysis (PCA) and inverse mass balance modelling have been used to study the hydrochemistry altering processes and reactions, respectively [e.g. Parkhurst and Appelo, 1999; Gueler et al., 2002].

D1.2 Data Analysis

Before using the historical hydrochemistry data (time range: 1992-2013) available data are assessed to identify and correct or remove erroneous and missing data. The following was included in the data analysis:

- Total vs dissolved concentrations: Due to a change in sampling method, concentrations prior to 2003 have been reported as total (unfiltered sample), after 2003 concentration are reported as dissolved (filtered sample). Dissolved and total concentrations were summarized (used interchangeably), since no significant differences in (median) concentration for filtered and unfiltered samples was found, which had also been indicated by Daughney (2007) (except for Fe and Mn).

- Outliers: Data above 4 MAD (median absolute deviation) from the median were considered as outliers and are excluded from the dataset on a per site per sample basis.
- Lab vs field estimates: Where possible field determined data were used as these reflect the groundwater environment better. During storage and transport hydrochemistry may alter e.g. due to dissolution of air (O_2), which disturbs the carbonate equilibrium (H_2CO_3 , CO_2 and their dissolved ions), which affects for example the redox equilibrium and microbial activity.
- Missing data: For some hydrochemistry parameters data were missing or are below limit of detection (LOD), as summarized in Table D1. If the data were too few to allow determination of a median, the missing data were inferred from regression analysis (if possible, e.g. conductivity and pH (Field) were inferred from Conductivity and pH (Lab), respectively as illustrated in Fig. D1) or in the last instance inferred from other groundwater wells of similar age to allow for further analysis.
- Data below detection limit: Data below detection limit were generally not a problem, because the log probability regression method was used when determining the median and SD [Gilliom and Helsel, 1986; Sanford et al., 1993]. If the median was below detection limit (because all historical data were below detection limit), the median was replaced by 0.5 times the detection limit (a common procedure [Helsel, 1990]) to allow for further analysis. For some hydrochemistry parameters too many data were missing or below the detection limit at the majority of groundwater sites and are therefore excluded from further analysis. These are: Cd, As, Nitrite, Ni, B, Cr and Cu.

No site had a charge balance error (CBE) >7% when using median hydrochemistry data after this data 'cleaning', so it was assumed that no bias had been introduced by the data 'cleaning'.

Table D1: Summary of hydrochemistry data availability

Available for all sites	tot. hardness ($CaCO_3$), TOC, Fe, F, SO_4 , Na, SiO_2 , tot. alkalinity, Ca, TDS, Cl, K, Mg, Br, TDS
Some data < LOD	NH_4 -N, Pb, DRP, Mn, Zn, Al, NO_3 -N
Not enough data (excluded)	Cr, As, Cd, Ni, Cu, B, F, Al, NO_2 -N

Figure D1: Regression analysis of field and lab measurement of conductivity and pH to surrogate missing data

D1.3 Determination of median and standard deviation

The median of the historical hydrochemistry data (for the time range 1992 - 2013) are summarized in Tab. D2. It is acknowledged that for sites where hydrochemistry had only been determined two to four times within the time range 1992 – 2013 (for sites: Well 8 (four observations), Well 10 (three observations), Well 7 and 9 (two observations each)), the median and SD are less robust. However, since the difference between the available data sets was within or close to the measurement error and the charge balance error when using the median hydrochemistry was below 7%, it was assumed that the median adequately reflected the real median at the specific site. For a more robust determination of the median and SD additional data should be obtained.

D1.4 Trends and seasonality

Details of seasonality and trend analysis of all groundwater and river water sites (upstream and downstream sites) are summarized in Table D3 and D4, respectively. Significant trends ($>10\%/year$, $>0.1\text{mg/L}$ for $\text{NO}_3\text{-N}$ and $p < 0.05$) were only observed for DO at Well 4 (decrease), $\text{NH}_4\text{-N}$ at site Well 3 (decrease), $\text{NO}_3\text{-N}$ at site Well 14 (decrease) and Zn in the River (decrease). The oxygen concentration (DO) had been determined in the field with a probe that is submerged into the freshly sampled water. This method is sensitive to adequate flushing of the well, complete exposure of the probe with fresh well water and to the calibration of the probe. The decrease in DO found at Well 4 (an anoxic site) may therefore be an artefact of improved sampling and analysis and/or better probes in recent years. The decrease in Zn in the river is believed to have been caused by improved detection limit over the past years being able to detect lower concentrations. Because the decrease in DO, $\text{NH}_4\text{-N}$ and $\text{NO}_3\text{-N}$ were only observed at one site each, their relative change was below 15% and no other (anthropogenic) hydrochemistry parameter showed significant trends at these sites, these trends were not considered as indication for non-steady state or anthropogenic effect on the groundwater. It should be noted that for some parameters insufficient data were available that did not allow for trend analysis (stated as ND in Tab. D3). Significant trends in these wells, may have been possible but seemed unlikely because of lacking (unexplained) significant trends in hydrochemistry at any other site, particularly the lack of significant trends in anthropogenic compounds, such as sulphate and nitrate.

Significant seasonality ($p < 0.05$ and relative SD $>10\%$) was observed for two shallow wells located in the recharge area (Well 2 and 6) for the parameters DO, DRP, TOC and Zn and at Well 6 also for F and $\text{NO}_3\text{-N}$. Because the Hutt River did indicate significant seasonality only for $\text{NO}_3\text{-N}$ and Zn, the seasonality observed for these parameters in the shallow groundwater wells may have resulted from seasonally changing recharge (rain vs. river recharge). Significant seasonality in the remaining older wells (located in the confined area) was only observed for site Well 3 for F and Well 5 for Ca (note it was found that the Ca concentration in Well 5 may have been affected by ion exchange, see C 1.5).

Table D2: Detailed hydrochemistry median data (unit mg/L, except for Conductivity - unit is uS/cm, and pH – no unit); yellow highlight refers to field data that had been inferred from lab determined data; orange refers to data that had been estimated from data from the youngest GW sites (Well 2 and 6); grey refers to data that were at detection limit and had been assigned 0.5 times the detection limit; green refers to data were the SD had been surrogated

Well #	Alkal tot	Al	NH ₄ -N	Br	Ca	Cl	Cond. Field	DO	DRP	F	Fe	Pb	Mg	Mn	NO ₃ -N	K	SiO ₂	Na	SO ₄	TDS	Zn	pH Field
15	19.8	0.0385	0.0058	0.02	5.0	13.8	96.3	10.7	0.005	0.06	0.06	0.0001	1.8	0.0016	0.24	0.86	11.2	10	4.1	61.6	0.002	7.29
6	22.0	0.02	0.01	0.04	5.2	13.5	99.8	4.82	0.009	0.07	0.01	0.0003	1.9	0.0022	0.34	0.92	11.0	9.9	4.3	65.0	0.005	6.23
2	32.0	0.02	0.01	0.06	8.1	15.6	137.0	1.72	0.011	0.06	0.01	0.0006	3.1	0.005	0.95	1.1	16.0	12	7.6	88.0	0.009	5.93
14	24.7	0.01	0.05	0.06	5.2	13.0	102.6	ND	0.01	0.10	0.05	0.03	2.2	0.01	0.42	0.86	13.9	10.3	4.6	69.0	0.03	6.05
10	29.0	0.48	0.006	0.2	5.9	13.1	104.6	1.58	0.01	0.08	0.1	0.03	2.5	0.005	0.41	0.79	13.6	10.8	4.6	147.0	0.03	7.09
13	24.0	0.01	0.05	0.06	5.3	13.6	108.8	9.07	0.01	0.08	0.05	0.05	2.3	0.02	0.35	0.91	13.5	10.1	5.4	71.0	0.031	6.63
11	41.4	0.0006	0.05	0.08	9.1	15.0	163.3	0.11	0.01	0.08	0.14	0.05	4.1	7.6E-05	1.09	1.1	18.0	13	7.8	100	0.03	5.87
8	51.0	0.01	0.02	0.09	10.4	16.6	171.4	3.71	0.005	0.09	0.94	0.0001	4.6	0.0413	1.15	1.15	17.2	14.3	7.0	112.1	0.004	6.50
12	34.9	0.04	0.05	0.06	6.4	13.0	116.0	0.14	0.01	0.14	0.03	0.05	3.3	0.03	0.51	1.1	16.0	13	6.9	79.0	0.03	6.22
3	59.0	0.02	0.024	0.1	11.0	18.0	203.0	0.22	0.008	0.08	0.18	2.7E-06	6.0	0.0518	0.82	1.7	18.4	18	8.8	120.0	0.002	6.19
1	40.0	0.01	0.05	0.06	4.3	12.9	111.2	0.26	0.01	0.16	0.03	0.03	2.3	0.01	0.36	0.98	17.3	19.4	4.8	86.0	0.03	6.52
5	54.0	0.02	0.32	0.08	4.8	15.0	152.0	0.17	0.12	0.16	1.22	4.9E-07	4.6	0.24	0.001	1.7	24.0	18	0.04	99.0	0.008	6.37
4	28.0	0.01	0.05	0.06	4.2	14.0	118.0	0.31	0.016	0.18	0.13	5.6E-07	2.4	0.021	0.16	0.98	18.4	13.95	4.4	76.0	0.004	6.51
7	29.5	0.01	0.01	0.08	4.4	14.1	112.0	1.8	0.012	0.19	0.15	0.0001	2.6	0.0185	0.18	0.87	18.1	13.55	4.3	72.96	0.006	6.58
9	73.0	0.01	0.815	0.09	0.8	15.7	180.0	0.94	0.94	0.16	0.8	0.0006	0.7	0.0405	0.75	2.75	27.5	35.5	0.4	160.8	0.02	6.94

Table D3: Trends (N, ND, INCR/DECR in units/year) for Hutt aquifer sites; Sen's slope estimator data [%], data from 1993 to 2012; * above 10% (but below 15%) from median

Well #	Alk. tot	Al	NH ₄ -N	Br	Ca	Cl	Cond . Field	DO	DRP	F	Hardn.	Fe	Mg	Mn	NO ₃ -N	K	SiO ₂	Na	SO ₄	TDS	Zn	pH Field
6	N	ND	ND	N	INCR 0.5	N	DECR -1.3	DECR -5.1	N	N	INCR 0.4	N	N	N	DECR -1.2	DECR -0.6	INCR 0.5	N	N	DECR -0.4	N	INCR 0.4
3	INCR 0.4	ND	DECR -10.5*	N	INCR 1.1	INCR 0.6	N	N	N	N	INCR 1.0	N	INCR 0.6	INCR 1.0	DECR -0.6	INCR 0.4	N	INCR 0.7	INCR 0.6	N	N	N
4	N	ND	DECR -4.4	N	N	N	N	DECR -14.1*	INCR 5.5	N	N	N	N	N	INCR 4.1	DECR -0.3	N	INCR 0.6	N	N	N	N
5	N	N	N	N	INCR 3.2	DECR -0.5	N	N	INCR 9.7	N	N	N	N	N	N	N	N	N	DECR >-0.1	N	N	N
8	N	ND	N	N	N	N	N	N	ND	N	ND	N	N	N	N	N	N	N	N	N	ND	N
1	N	ND	N	N	DECR -5.0	N	ND	ND	N	N	N	ND	N	ND	N	N	ND	N	N	N	ND	ND
2	N	ND	ND	N	INCR 0.3	INCR 0.3	N	N	N	N	INCR 0.4	N	N	ND	DECR -1.2	DECR -0.4	INCR 0.3	N	N	N	N	INCR 0.5
10	N	N	N	N	N	N	ND	ND	N	N	N	N	N	N	N	N	ND	N	N	N	N	ND
7	N	ND	N	N	N	N	N	N	ND	N	ND	N	N	N	N	N	N	N	N	N	ND	N
9	N	ND	N	N	N	N	N	N	ND	N	ND	N	N	N	N	N	N	N	N	N	ND	N
11	N	ND	N	N	N	N	ND	ND	ND	N	N	N	N	N	N	N	ND	N	N	N	ND	ND
13	N	ND	N	N	N	N	ND	ND	ND	N	N	N	N	N	N	N	ND	N	N	N	N	ND
12	N	ND	N	DECR -4.3	N	N	ND	ND	ND	N	DECR -5.8	ND	N	ND	N	N	N	N	DECR -6.9	DECR -4.2	ND	ND
14	N	ND	N	N	N	N	ND	ND	N	N	N	N	N	ND	DECR -14.4*	N	ND	N	N	N	ND	ND
15	N	N	N	ND	N	N	INCR 1.4	INCR -0.6	N	ND	ND	N	N	N	DECR -4.0	N	ND	N	N	ND	DECR -22.5*	N

Table D4: Seasonality test (Y, N or ND) of historical hydrochemistry data from 1993 to 2012 for Hutt aquifer sites

Well #	Alkalinity tot	Al	Ca	Cl	Cond. Field	DO	DRP	F	Hardness	Fe	Mg	Mn	NO ₃ -N	K	SiO ₂	Na	SO ₄	TDS	TOC	Zn	pH (field)
2	Y 0.9%	ND	Y, 5.7%	Y 3.2%	Y 2.9%	Y 24%	Y 18%	N	Y 3.0%	ND	Y 3.2%	ND	Y 7.4%	Y 9.1%	Y 3.1%	Y 3.3%	Y 3.9%	Y 1.1%	Y 45%	Y 82%	Y 2.5%
5	N	N	Y, 12%	N	N	N	N	Y 6.3%	N	N	N	Y 4.6%	N	N	N	N	N	N	N	N	N
3	Y 3.4%	ND	N	N	N	N	N	Y 13%	N	N	N	N	N	N	N	N	N	N	N	N	N
6	Y 9.1%	ND	Y 5.8%	Y 3.7%	Y 8.2%	Y 29%	Y 15%	Y 13%	Y 4.8%	ND	Y 5.3%	N	Y 16%	Y 7.6%	Y 5.5%	Y 5.1%	Y 4.7%	Y 4.6%	Y 43%	Y 98%	Y 1.3%
4	N	ND	N	N	N	N	N	Y 5.6%	N	N	N	N	N	N	N	N	N	N	N	N	N
13	N	ND	N	N	ND	ND	ND	N	N	N	N	N	N	N	ND	N	N	N	ND	N	N
11	N	ND	N	N	ND	ND	ND	N	N	N	N	N	N	N	ND	N	N	N	ND	ND	N
1	N	ND	N	N	ND	ND	N	N	N	ND	N	ND	N	N	ND	N	N	N	ND	ND	N
12	N	ND	N	N	ND	ND	ND	N	N	ND	N	ND	N	N	N	N	N	N	ND	ND	N
14	N	ND	N	N	ND	ND	N	N	N	N	N	ND	N	N	ND	N	N	N	ND	ND	N
10	N	N	N	N	ND	ND	N	N	N	N	N	N	N	N	ND	N	N	N	ND	N	N
8	N	ND	N	N	N	N	ND	N	ND	N	N	N	N	N	N	N	N	N	ND	ND	N
7	N	ND	N	N	N	N	ND	N	ND	N	N	N	N	N	N	N	N	N	ND	ND	N
9	N	ND	N	N	N	N	ND	N	ND	N	N	N	N	N	N	N	N	N	ND	ND	N
15	N	N	N	N	N	Y 7.5%	N	ND	ND	N	N	N	Y 31%	N	ND	N	N	ND	N	Y 43%	N

D1.5 Hierarchical Cluster Analysis (HCA) and Principal Component Analysis (PCA)

HCA⁹⁵ indicated that hydrochemistry at two groundwater sites (Well 5 and Well 9) was significantly different from the hydrochemistry at any other site (see Fig. D2) Assessment of their individual hydrochemical composition showed that water from Well 5 was reduced in SO₄ as indicated by a significantly lower concentration in SO₄ in Well 5 compared to all other sites (0.04 mg/L for Well 5 vs. 5.1 mg/L on average for all sites) in combination with elevated Fe and Mn concentrations. Water from Well 9 had an extremely low Ca concentration (0.8 mg/L), but high alkalinity (73 mg/L) in combination with elevated Na and K concentrations compared to all other sites (Ca is on average 5.9 mg/L, alkalinity was on average 41 mg/L) indicating significant contribution of ion exchange at this site.

Figure D2: HCA (nearest neighbour) scree plot (LEFT) and dendrogram (RIGHT) considering: using Alkalinity tot, NH₄-N, Br, Ca, Cl, Cond. (field), DO, Fe, Mg, NO₃-N, K, SiO₂, Na, SO₄, pH (field)

Figure D3: Principle component analysis of selected Lower Hutt aquifer hydrochemistry

PCA⁹⁵ illustrated in Fig. D3 shows two components (with Eigenvalue >1) explained 76% of the variation in the data. PC 1 (explaining 45% of the variation in the data) showed positive loading for almost all major ions and was therefore attributed to mineral weathering. PC 2 (explaining 31% of the variation in the data PC 1) showed positive loading for oxidized species NO₃ and SO₄ and negative loading for reduced species NH₄ and Fe and was therefore attributed to redox reactions. Of the two important drivers of hydrochemistry identified by PCA, mineral weathering was likely more strongly correlated with groundwater residence time, due to relatively homogenous aquifer layers in regard to aquifer

⁹⁵ using Total Alkalinity, NH₄-N, Br, Ca, Cl, Conductivity (field), DO, Fe, Mg, NO₃-N, K, SiO₂, Na, SO₄, pH (field) because these parameters were available at all sites and were above the Limit of Detection (LOD)

material and aquifer geometry in the study area. In contrast, microbial processes were expected to be dependent on for example the residence time in addition to the presence of specific microbes, substrate and respiratory nutrients. Due to these findings, assumptions and the general understanding of aquifer processes, dominant mineral weathering reactions were assessed and their consistency across the entire aquifer confirmed by using a inverse mass balance model.

D1.6 Inverse mass balance mineral weathering model

Mineral weathering is generally strongly dependent on the pH [e.g. Knaus and Wolery, 1986; Blum and Stillings, 1995; Brantley, 2008]. Figure D4 (upper) indicates that the pH in the LHGWZ was around neutral to slightly acidic (pH 5.9 to 7.3) and fairly constant across the studied sites. Mineral weathering around this neutral pH is the slowest and a change in pH should only have a minor effect on weathering kinetics compared to a higher/lower pH [Knaus and Wolery, 1986; Blum and Stillings, 1995; Brantley, 2008]. It was therefore expected that weathering kinetics in this study were fairly consistent across the studied sites. To confirm this and assess the specific mineral weathering reactions that have led to the change in hydrochemistry, inverse mass balance modelling was used.

Figure D4: pH average for all sites (UPPER) and saturation state given by the saturation index (SI) of groundwater wells with respect to minerals present, where each bar represents one studied site (LOWER)

The inverse mass balance mineral weathering model was kept as simple as possible with least possible mineral phases. As input, minerals present in 'parent' rock (in this study greywacke) were considered as determined by [Rowe, 1980] and confirmed in this study by aquifer material analysis (details in Appendix D3). These were albite, anorthite, quartz, K-feldspar, biotite and the weathering products kaolinite and gibbsite. The presence of trace minerals was neglected. Quartz was constrained to precipitate and calcite, albite and anorthite were constrained to weather based on their general stability/weatherability [Bowen, 1928] and assessment of their saturation index (SI) illustrated in Fig. D4 (lower), which indicated oversaturation with respect to kaolinite, K-mica, goethite, gibbsite Fe-oxide, under-saturation for albite, anorthite, calcite and close to equilibrium for K-feldspar, Silica(amorphous) and quartz. The saturation states were fairly similar across the aquifer which also indicated consistent weathering processes in the entire aquifer.

The outcome of the inverse mass balance model is illustrated in Fig. D5 showing that K-feldspar weathering and albite/anorthite dissolution occurred in concert with precipitation of kaolinite/gibbsite and quartz. Very few models considered gibbsite as weathering product (precipitating). These findings may have indicated a fairly weathered aquifer material, since one would expect higher amounts of albite and anorthite to dissolve, due to their lower stability compared to all other minerals present in the aquifer material (greywacke). Similar amounts of chlorite and biotite weathered and precipitated, respectively, which may have indicated that the phase transition of biotite and chlorite had no significant active contribution to the change in hydrochemistry in this study. Figure 6-3 also shows a decreasing trend of mineral weathering/precipitation with residence time (the sites are sorted in increasing order of the previously inferred most likely MRT), which confirmed a slower reaction rate with time (i.e. power law weathering kinetics) generally found in lab and field environments [e.g. Luce et al., 1972; Paces, 1973; Downes, 1985; Taylor and Blum, 1995; Katz et al., 1995; Rademacher et al., 2001 and 2005; Morgenstern et al., 2009 and 2010].

Figure D5: Inverse model output PHREEQC showing mineral dissolution during weathering decreases with MRT (LEFT) and mineral precipitation during weathering (illustrated as positive rates) (RIGHT), note wells are sorted with increasing MRT

D1.6 Groundwater environments

Water that contained more than 0.5 mg/L DO was considered oxic and water with a DO below 0.5 mg/L was considered anoxic based on the recommendation of [McMahon and Chapelle, 2008; Jurgens et al., 2009]. This threshold split the dataset into half (seven oxic and seven anoxic sites, Well 14 was left out due to unavailable DO data) and concurred with a significantly larger variation in ion concentrations below 0.5 mg/L DO than above 0.5 mg/L as illustrated in Fig. D6.

Figure D6: Ion concentrations as a function of dissolved oxygen (DO), y axis crosses at 0.5 mg/L DO

D1.7 Assessment of normal distribution of data

The χ^2 objective function used in this study requires normally distributed data. To assess if the historical hydrochemistry data were normally distributed (or required transformation to follow the normal distribution), their distribution was assessed graphically and their skewness and kurtosis was determined. Data were considered as normally distributed if their kurtosis and skewness agreed with the critical value equivalent to two times their standard error (*sek* and *ses*, respectively), which were estimated as: $ses = \sqrt{6/N}$ and $sek = \sqrt{24/N}$ (after Tabachnick and Fidell, 1996). The normality was assessed using the historical data for Ca, Cl, F, Fe, Mg, K, Si, Na and TDS (since these parameters were used in this study to assess hydrochemistry-PT relationships and infer age information from hydrochemistry) at five sites with a rich dataset (Well 2 to 6 with 54- 78 data from 1992 to 2012). It was assumed that the outcome of this assessment was representative for all remaining sites with fewer available data. As summarized in Tab. D5, data are insignificantly different from normally distributed data at the majority of sites, except for Fe and F. Fe is very sensitive to sampling (contact with air) and F is below detection limit for the majority of sites.

Table D5: Percentage of sites for which skewness and kurtosis are insignificantly different from the normal distribution

% of sites for which	Ca	Cl	F	Fe	Mg	K	Si	Na	TDS
Skewness is not sig. different than normal distribution	100%	60%	40%	40%	100%	80%	100%	80%	80%
Kurtosis is not sig. different than normal distribution	100%	60%	20%	40%	100%	100%	60%	80%	100%

D1.8 Relationships between hydrochemistry and the tritium-inferred MRT in the Lower Hutt Groundwater Zone

Figure D7 illustrates the previously found relationships between hydrochemistry and the tritium-inferred MRT in the Lower Hutt Groundwater Zone.

Figure D7: Promising relationships found between hydrochemistry and tritium-inferred groundwater age in the Lower Hutt Groundwater zone

D2 Detailed assessment of aquifer material

D2.1 Details on aquifer composition of the LHGWZ by Rowe (1980)

Figure D7 summarizes the composition of greywacke rock (the source of the aquifer material) in the Wellington Region determined by Rowe (1980).

Figure D8: Geochemistry of greywacke basement rock, the source of the aquifer material in the LHGWZ [Rowe, 1980]

D2.2 Location of the Gravel pebbles

The Hutt River sample was taken from the central river bed in the unconfined aquifer part and the 68m sample was taken from a bore in the confined area of the aquifer that tapped into the lower aquifer layer (lower Waiwhetu aquifer). The gravel sample locations in regard to the groundwater wells are illustrated in Fig. 3-2 in Chapter 3.

D2.3 Details on WDS and EDs analysis

Thin sections of the two gravel samples are shown in Fig. D9. The electron beam was set to zonally analyse squares of 50x50um in a 0.4 mm wide and 20.25 mm long strip going from rim to centre of the gravel samples (illustrated in Fig. D10) with a dwell time of 20s at 15kV and 12nA (typical settings for EDS/WDS [e.g. Reed, 1975]). This approach averaged the signal over each 250um² square, but is a much faster approach compared to single point analysis. The obtained elemental signals (e.g. Al, Si, Na, K and Ca), equivalent to relative abundances of each element, were assessed as a function of distance to the rim of the aquifer material. Because each element could be associated with the abundance of specific mineral(s) (e.g. Na is contained in /can be associated with the mineral albite), a different elemental compositions in the rim and bulk of the aquifer material may have indicated mineral weathering. To identify apparent changes between rim and bulk chemistry in the aquifer material, trend analysis was carried out on EDS and WDS median signals for each row (of 8 x 250um² squares) using the Mann-Kendall test and Sen's slope estimation, where a significant trend was characterized by $p < 0.05$ and $> 10\%$ increase/unit [Helsel and Cohn, 1988; Daughney, 2005 and 2006].

Additionally a student t-test (for small sample volumes) was performed on these data to assess if the EDS and WDS signals at the rim and bulk were significantly different.

Figure D9: Thin section of Hutt River and 68m b.s. sample

Figure D10: schematic setup of the EDS/WDS strip analysis

D2.4 Detailed results of aquifer material analysis

The cut of the 68m deep gravel sample (illustrated in Fig. D9) showed a visible difference between rim and centre of the gravel pebble and was expected to show a good indication of which minerals and how much of the minerals weathered. Results of mineral identification carried out using EDS point and area analyses are presented in Fig. D11 and D12 of the 68m gravel sample showing the mineral abundance close to the rim and the centre/bulk of the gravel pebble, respectively. As can be seen mainly quartz (qrtz.), K-feldspar (K-f.) and albite (alb.) as well as smaller amounts of chlorite/biotite (chl./bio.), anorthite (an.) and gibbsite/kaolinite and perhaps some higher silicates (hs.) were present in the 68m gravel pebbles. Similar results were obtained when analysing the Hutt River gravel pebble (results are not presented here).

Median elemental EDS signals and signal ratios (for each row of eight times 50um squares) are illustrated in Fig. D13 as a function of distance from the rim for both gravel samples indicating an increase in O, Na, Si, Al, K and Fe from rim to bulk in the 68 m sample during the first 4 mm. Trend analysis revealed the highest increase of Si and Al. In contrast to the 68 m sample, EDS analysis of the Hutt River gravel sample indicated a much narrower weathering rind with a sudden increase in all elements identified with EDS (except for oxygen) during the first 500 um from the pebble edge. Trend analysis of the first 500 um revealed increasing trends for all elements except Si and Al. Overall, EDS and WDS analysis revealed that both gravel samples were depleted in lighter elements (Ca, Na, K, Fe, etc.) close to the rim, which may have indicated weathering. Ratios of the EDS signals (Fig. D13, lower) confirmed the rim was enriched in Si in relation to Al, Na and K and depleted in Al in relation to Si, Na and K, which may be linked to K-feldspar, anorthite and albite weathering and quartz and kaolinite precipitation, as indicated during inverse mass balance modelling. These findings also support that the aquifer material was fairly weathered, as indicated by inverse mass balance modelling, and agree with reaction path modelling of silicate weathering in the general sense [e.g. Langmuir, 1997; White and Buss, 2013].

Figure D11: EDS example 1, sample number 1, close to rim. Backscatter image with EDS spectra of selected locations

Figure D12: EDS example 2, sample number 8, central gravel pebble. Backscatter image with EDS spectra of selected locations

Figure D13: Elemental EDS signals (UPPER) and EDS signal ratios (LOWER) of 68m (left) and Hutt River (right) gravel pebble

D2.5 Determination of differences and apparent trend in mineral abundance within the studied aquifer pebbles

The difference in mineral abundance within the aquifer pebble (with distance from rim) was assessed by trend analysis using the Man-Kendall test. Results are summarized in Tab. D9 and D10 for the 68m sample and the Hutt River sample, respectively, indicating a significant increase in O, Na, Si, Al, K and Fe from rim to bulk in the 68 m sample during the first 4 mm with the highest increase of Si and Al. In contrast to the 68 m sample, EDS analysis of the Hutt River gravel sample indicated a much narrower weathering rind with a sudden increase in all elements identified with EDS (except for oxygen) during the first 500 μm from the pebble edge. Trend analysis of the first 500 μm revealed increasing trends for all elements except Si and Al.

Table D9: Trend analysis of WDS and EDS data 68m

		WDS					CP	EDS					
		Ca	Na	Mg	K	Si		O	Na	Al	Si	K	Fe
trend	average	N	DECR	N	N	INCR	INCR	INCR	INCR	INCR	INCR	INCR	INCR
	median	N	DECR	N	N	INCR	INCR	INCR	INCR	INCR	INCR	INCR	INCR
Sen's slope	average	28.0	-59.4	15.1	39.2	84.1	6.5	68.3	79.8	852.7	454.2	100.6	40.1
	median	0.9	-73.8	4.8	6.6	58.6	4.0	57.4	74.5	707.4	436.6	92.9	36.1
Linear regression	average	13.0	-71.9	18.1	65.0	108.5	12.6	100.6	80.1	1510.4	556.0	102.0	43.3
	median	29.1	-97.2	7.4	46.4	101.4	10.7	89.1	74.6	1505	568.8	98.2	40.0
potential outliers (>4 MAD)	average	24	0	9	12	10	16	38	0	55	19	6	13
	median	21	8	10	19	17	22	41	0	56	32	8	55

Table D10: Trend analysis of WDS and EDS data Hutt River sample [signal/um]

	Trend for the entire 200um sample										
Element and method	Ca WDS	Na WDS	Mg WDS	K WDS	Si WDS	CP	O EDS	Na EDS	Al EDS	Si EDS	K EDS
T trend?	INCR	N	N	N	INCR	N	N	N	INCR	INCR	N
Sen's slope	524.5	281.3	20.7	70.5	362.7	0.0	-67.1	81.49	280.7	394.6	66.9
Linear regression	952.6	310.4	47.1	-9.61	1292	0.0	-200	192.16	2769	2666	125.9
	Trend for the first 500 um										
Trend?	INCR	INCR	INCR	INCR	N	N	DECR	INCR	N	N	INCR
Sen's slope	3723	8824	1397	11154	3079	0.0	-3127	3876	1411	3787	3420
Linear regression	4332	7359	1610	10498	15526	0.0	-4136	3926	37157	34456	3387

D3 Detailed results hydrochemistry-time modelling

D3.1 Equations of LPMs used

The three LPM types, EPM, DM and PEM were used as described in Eqn. D1, D2 and D3, respectively [after Maloszewski and Zuber, 1982 and Jurgens et al. 2012].

$$\text{EPM: for } t' > \text{MRT}(1 - \frac{1}{n}), f_{\text{EPM}} = \frac{n}{\text{MRT}} * \exp(-n * \frac{t'}{\text{MRT}} + n - 1); \text{ else } f_{\text{EPM}} = 0. \quad \text{Eqn. D1}$$

MRT is the mean residence time; n=the reciprocal of the ratio of exponential in total flow, which is referred to as E/PM=1/n, the ratio of exponential in total flow in the following. (n had been defined as ratio of total to exponential flow by after Maloszewski and Zuber, 1982). At E/PM = 0 for pure piston flow is obtained and at E/PM=1 for pure exponential flow is obtained.

$$\text{DM: } f_{\text{DM}} = \frac{1}{\text{MRT}} \times \frac{1}{\sqrt{4\pi\text{DP}\frac{t'}{\text{MRT}}}} \times e^{-\frac{\left(1 - \frac{t'}{\text{MRT}}\right)^2}{4\text{DP}\frac{t'}{\text{MRT}}}} \quad \text{Eqn. D2}$$

The DM conceptualizes 1-dimensional advection-dispersion with DP as dispersion parameter, which is defined as $\text{DP} = \frac{D}{Vx}$ with D as the dispersion coefficient, V as velocity and x as outlet position. When DP=0, piston flow behaviour is obtained.

$$\text{PEM: for } t' > \text{MRT}_{\text{aq}} * \ln(m), f_{\text{PEM}} = \frac{m}{\text{MRT}_{\text{aq}}} * \exp\left(\frac{-t'}{\text{MRT}_{\text{aq}}}\right) ; \text{ else } f_{\text{PEM}} = 0. \quad \text{Eqn. D3}$$

$\text{MRT}_{\text{aq}} = \frac{\text{MRT}_s}{\ln(m)+1}$, MRT_s is the MRT of the sample and m as the reciprocal of the ratio of sampled to total volume (P/EM). This version of the PEM conceptualises mixing of water in an aquifer that can be described by the exponential model (EM), but only part of the well is screened and therefore sampled. At n = 1 (for wells screened across the entire aquifer) the EMM is obtained.

D3.2 Median of considered hydrochemistry parameters

Table D11 summarizes median concentrations and standard deviations of the assessed hydrochemistry parameters at each site. These data were used to assess hydrochemistry-PT relationships and inference of age information from hydrochemistry.

Table D11: Summary of median and standard deviation data for each site, ** uncertainty could not be determined from existing historical data, but is interpolated from uncertainty determined at other sites, which is * 5% and + 10%

Well #	TDS		Mg		K		Ca		Si		Na		F		Cl		Fe	
	median [mg/L]	SD	median [mg/L]	SD	median [mg/L]	SD	median [mg/L]	SD	median [mg/L]	SD	median [mg/L]	SD	median [mg/L]	SD	median [mg/L]	SD	median [mg/L]	SD
6	65.0	4.53	1.90	0.16	0.92	0.12	5.2	0.44	11	0.81	9.9	0.69	0.069	0.008	13.5	0.69	0.01	0.001 ⁺
3	120.0	5.56	6.00	0.32	1.7	0.11	11	1.06	18.4	0.48	18	1.08	0.080	0.013	18.0	0.81	0.18	0.099
4	76.0	5.62	2.40	0.16	0.98	0.07	4.21	0.32	18.35	0.57	13.95	1.33	0.180	0.014	14.0	0.21	0.13	0.055
5	99.0	2.93	4.60	0.27	1.7	0.16	4.8	0.66	24	0.24	18	0.55	0.160	0.014	15.0	1.16	1.22	0.144
8	111.4	2.02	4.60	0.99	1.15	0.07	10.6	0.99	17	0.28	14.1	1.56	0.094	0.037	17.0	0.85 [*]	1.18	1.582
1	86.0	6.27	2.30	0.00	0.98	0.03	4.3	0.36	17.3	0.87 [*]	19.4	0.97	0.160	0.005	12.9	0.19	0.03	0.003
2	88.0	3.17	3.10	0.18	1.1	0.12	8.1	0.49	16	0.74	12	0.61	0.060	0.011	15.6	0.69	0.01	0.001
10	147.0	6.36	4.30	1.25	2.2	0.14	18	0.00	13.6	0.68 [*]	19	1.41	0.160	0.007	23.4	1.63	7.60	0.636
7	73.0	1.36	2.60	0.28	0.87	0.11	4.35	0.35	18.1	0.14	13.55	0.78	0.185	0.007	14.1	0.07	0.15	0.076
9	160.8	69.6	0.73	0.09	2.75	0.21	0.755	0.22	27.5	0.71	35.5	2.12	0.155	0.049	15.7	1.91	0.80	0.113
11	100.0	2.19	4.10	0.08	1.1	0.00	9.05	0.82	18	0.90 [*]	13	0.09	0.080	0.008	15.0	0.16	0.14	0.114
13	71.0	1.44	2.30	0.00	0.91	0.02	5.3	0.35	13.5	0.68 [*]	10.1	0.10	0.080	0.008	13.6	0.27	0.05	0.048
12	79.0	6.08	3.30	0.30	1.1	0.07	6.4	0.72	16	0.80 [*]	13	0.79	0.140	0.014 ⁺	13.0	0.65 [*]	0.03	0.003
14	69.0	2.71	2.20	0.14	0.86	0.03	2.5	0.67	13.9	0.70 [*]	10.3	0.40	0.100	0.010 ⁺	13.0	0.23	0.05	0.011
15	66.0	5.02	0.01	0.00	0.7	0.11	4.685	4.69	9.085	4.27	7.6	1.46	0.070	0.018	12.6	1.08	0.06	0.050

D3.4 Chi² objective function and the effect of uncertainty threshold on behavioural hydrochemistry-time relationships

In this study, simulated hydrochemistry is defined as behavioural if they lie within uncertainty (e.g. 1 SD) of the observed hydrochemistry, i.e. the 'optimal' variance of observed and simulated hydrochemistry is equal to 1. Hence simulations were considered as behavioural when the variance of simulated and observed concentrations was not significantly different from the 'optimal' variance at the considered confidence (e.g. 99%), i.e. the normalized observed Chi² is below or equal to the normalized 'optimal' Chi²:

$$\text{normalized } \chi^2(\text{observed}) = \sum \frac{(\text{obs}-\text{sim})^2}{\varepsilon^2} / df, \quad \text{Eqn. D4}$$

where *obs* is the observed hydrochemistry (the median of historical data was used if no trends in hydrochemistry records had been identified); *sim* is the simulated hydrochemistry; *df* is the degrees of freedom, which are defined as difference between the # of observations and the # of relations between observations (which is dependent on the independent variables of the model, in this study the EPM, so *df* = 3); ε is the uncertainty in observations, which was estimated from the standard deviation (SD) of the historical data or the measurement uncertainty whichever is larger. If historical data did not allow the determination of the SD (e.g. too few data) uncertainty was assumed to be 10% of the median. $\varepsilon > 5$ SD was considered as too large to allow adequate constraining of the hydrochemistry time relationship.

$$\text{normalized } \chi^2(\text{optimal}) = \chi^2(\alpha, df) / df, \quad \text{Eqn. D5}$$

where $\chi^2(\alpha, df)$ is the Chi square distribution at significance level α of e.g. 0.01 (or 99% confidence). It was observed that with increasing uncertainty threshold (e.g. 1 or 2 SD with SD referring to the standard deviation/measurement error of the hydrochemistry observations which is reflecting analytical uncertainty, repeatability and the variability of the historical hydrochemistry data) the number of behavioural models increased. An example is illustrated in Fig. D14. Firstly a larger behavioural process parameter range (i.e. uncertainty) and an increasingly smoother probability distribution were obtained with increasing uncertainty threshold. Secondly the increase in behavioural process parameter range plateaued and thirdly increased further until the considered uncertainty threshold was so large that ambiguous process parameters were obtained (i.e. a negative minimum for process parameter *a* at an uncertainty of >3.5 SD as illustrated in Fig. D14).

To ensure the full development of the probability distribution (smooth distribution), but avoid ambiguous interpretations, uncertainty threshold was considered as appropriate the following criteria were fulfilled:

1. To ensure a 'fully developed' behavioural process parameter range (the 'plateau' is reached) an insignificant difference in behavioural process parameter range between the tested uncertainty threshold and a 0.1 SD higher uncertainty threshold was required. A change of <10% of the max,

min and most probable a, b, c for at least six out of the nine parameters (max, min, most probable for each process parameter a, b and c) was considered insignificant.

2. To ensure a relatively smooth distribution of behavioural process parameters when binning the behavioural process parameter population into 15 bins, the number of behavioural models obtained at the tested uncertainty threshold was required to be large enough (> 100 behavioural models relative smoothness was achieved).
3. If multiple uncertainty thresholds fulfilled the above criteria, the lowest of these uncertainty thresholds was considered as appropriate to minimize the risk of ambiguous behavioural process parameter ranges.

Figure D14: Effect of uncertainty threshold on the behavioural process parameter range

D3.5 Effect of number of MC runs on behavioural hydrochemistry-time relationships

When assessing the effect of MC runs on the behavioural process parameter range (illustrated in Fig. D15), no significant differences in model outcome (i.e. behavioural hydrochemistry-time relationships) were observed when using 1 million or 0.9 million MC runs. With 0.7 million MC runs no significantly different hydrochemistry-time relationships were obtained, except for oxic sites, where a significant change in appropriate uncertainty threshold resulted in significantly different behavioural process parameter ranges. Based on these findings, 1 million MC runs were used throughout this study.

Figure D15: Differences in behavioural process parameter range when using 0.7, 0.9 and 1 million (in legend referred to as million) MC runs for Na, Ca, Si and TDS

D3.6 Effect of binning on the probability distribution of behavioural hydrochemistry-PT relationships

The effect of binning and the number of bins on the shape of the process parameter distribution is illustrated in Fig. D16 shows that five bins were too few (lumps information together), 30 bins were too many (individual information counts more so that the shape of distribution was lost) and best results were obtained with 10 to 20 bins. Based on these findings 10 bins are used throughout this study.

Figure D16: Probability distribution of 100 binned behavioural models when using 5, 10, 20 or 30 bins

D3.7 Determination of equivalent piston flow time

The time dependent mixing function and hydrochemistry-PT relationships overlay (convolve), see Eqn. 6-1 in Chapter 6. The time equivalent to piston flow time can be determined as the mean of these convolved functions. An example is given in Eqn. D6 and D7 using the EPM and a logarithmic hydrochemistry-PT relationship. The convolved functions of LPM and kinetics are normalized by their

integral to obtain a probability function (all add up to 1) (Eqn. D6). The mean time is then simply the time at probability 0.5 (50%) (Eqn. D7).

$$\text{convolved probabaility function} = \int_0^{\infty} \frac{EPM * at^b}{\int_0^{\infty} (EPM * at^b)}, \quad \text{Eqn. D6}$$

where EPM symbolizes the exponential piston flow model (Eqn. C1), at^b is the logarithmic kinetics with variable a, b and time t.

$$\text{convolved probabaility function}(MRT_{PM \text{ equivalent}}) = 0.5 \quad \text{Eqn. D7}$$

D4 Detailed results on constrained age information with hydrochemistry-time relationships

In the following summary figures that illustrate the inferred behavioural process parameters and age information when using unconstrained/floating age information and tracer-inferred age information are presented to support the results summarized in the main part of the publication.

D4.1 Inferred hydrochemistry-time relationships

Figure D17 illustrates the behavioural process parameter population for a, b and c inferred when using tracer-inferred age information. Figure D18 and D19 illustrate the behavioural process parameter populations when using unconstrained/floating age information and the DM and PEM (results using the EPM are illustrated in the main part of the publication). Table D12 contains detailed information on the number of behavioural models and uncertainty threshold when using unconstrained age data and any of the three LPM types (EPM, DM, PEM).

Figure D17: Behavioural process parameter ranges when using age information inferred from tritium, bars indicate the most probable inferred process parameters and error bars indicate the maximum and minimum inferred process parameters; * aquifer layer specific analysis excluded Well 9 from the dataset

Figure D18: Behavioural process parameter *a* inferred when using unconstrained age information using and the EPM, DM and PEM; bars illustrate the most likely value for *a* and the errors bars illustrate the max and min of *a* (i.e. its uncertainty range); * aquifer layer specific analysis excluded Well 9 from the dataset

Table D12: Determined (most appropriate) uncertainty threshold and number of behavioural models when using unconstrained age information and the LPMs EM, DM and PEM at different groundwater environments

	Oxic sites			Anoxic sites			Anoxic sites layer *			All sites			All sites layer*		
	PEM	EPM	DM	PEM	EPM	DM	PEM	EPM	DM	PEM	EPM	DM	PEM	EPM	DM
Si	2.7 (109)	2.7 (105)	2.7 (121)	3.9 (118)	4 (122)	4.2 (163)	3 (104)	3.2 (109)	3.3 (108)	5 (93)	5 (67)	5 (63)	4.6 (104)	4.8 (148)	4.9 (188)
Na	2.3 (203)	2.1 (107)	2.2 (115)	4.3 (181)	4.1 (102)	4.2 (110)	3.5 (148)	3.4 (109)	3.4 (111)	4.5 (135)	4.5 (131)	4.8 (187)	4 (105)	4.1 (137)	4.2 (124)
Ca	3.1 (1492)	3.1 (1498)	2.8 (256)	3.7 (161)	3.6 (124)	3.6 (117)	2.4 (142)	2.4 (135)	2.4 (124)	4.5 (1053)	4.6 (1505)	4.2 (177)	3.1 (1026)	3.1 (1227)	3.2 (1881)
K	3.4 (103)	3.6 (111)	3.6 (111)	-	-	-	-	-	-	-	-	-	-	-	-
Mg, Fe, F	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Cl	-	-	-	2.5 (106)	2.6 (172)	2.6 (159)	2.7 (110)	2.8 (176)	2.8 (160)	-	-	-	-	-	-
TDS	4.1 (125)	4.2 (150)	4.2 (113)	2.2 (372)	1.9 (121)	2.1 (209)	2 (113)	2 (104)	2.1 (120)	4.2 (249)	4.2 (258)	4.1 (138)	4.2 (162)	4.3 (239)	4.2 (130)

Figure D19: Behavioural *b* and *c* with unconstrained age information using the EPM, DM and PEM; * aquifer layer specific analysis excludes Well 9 from the dataset

D4.2 Inferred age information

The constraining of the tracer-inferred age parameters (MRT and E/PM min, max and best) when inferred from hydrochemistry is illustrated in Fig. D20. It can be seen that E/PM min was most constrained, followed by MRT min. This may be due to the tracer-inferred min(E/PM) and min(MRT) are in most cases close to or at 0. Figure D21 illustrates the average change (constraining) of the unconstrained age parameters (MRT and E/PM min, max and best) when inferred from hydrochemistry when using the DM, EPM and PEM.

Figure D20: Relative constraining of the age parameters at different locations (UPPER) and for each hydrochemistry parameter (LOWER), * ambiguous age estimation inferred from tritium

Figure D21: Average change in age estimation with each hydrochemistry parameter when using unconstrained age and the EPM, DM and PEM; E/PM stands for the mixing parameter of any LPM type

Figure D22 and D23 illustrate the range in change (max-min) of the age information and the most probable age information when using unconstrained age information and the DM and PEM, respectively (results obtained with the EPM are illustrated in the main part of the paper).

Figure D22: Range in change (max-min) of age estimation with each hydrochemistry parameter when using unconstrained age and the DM; DP stands for dispersion parameter

Figure D23: Range in change (max-min) of age estimation with each hydrochemistry parameter when using unconstrained age and the PEM; P/EM stands for the ratio of sampled to total volume

D4.3 Including/excluding tritium/hydrochemistry

Table D13 shows the correlation matrix of the most likely MRT and E/PM, uncertainty in tracer-inferred MRT and E/PM hydrochemistry and the constraining of the age estimation when replacing unstrained age data with tritium-inferred age at one site ($\Delta\epsilon\%(E/PM)_{hc}$ and $\epsilon\%(MRT)_h$) and when replacing tritium-inferred age with unconstrained age at one site ($\Delta\epsilon\%(E/PM)_t$ and $\Delta\epsilon\%(MRT)_t$). Data are presented as average correction coefficient, i.e. the average of correlation coefficients when using Na, Si, K, Cl and TDS. Table D13 indicates that the tracer-inferred age information (at one point in the dataset) would need to be relatively well constrained and in the older age range to successfully constrain the hydrochemistry-inferred age estimation absolutely (and constrain uncertainty in the MRT inferred from hydrochemistry further). These findings were supported by the correlation of $\Delta\epsilon\%(E/PM)_t$, $\Delta\epsilon\%(MRT)_t$, with uncertainty in tracer-inferred MRT (statistically significant) and E/PM (statistically insignificant).

Table D13: Correlation matrix of tracer-inferred LPM parameters (i.e. uncertainty in MRT and E/PM and most likely MRT and E/PM) and the constraining of the MRT and E/PM with the aid of hydrochemistry when replacing unstrained age at one site with tritium-inferred age and tracer-inferred ($\Delta\epsilon\%(E/PM)_h$ and $\Delta\epsilon\%(MRT)_h$) and when replacing tritium-inferred age at one site with unconstrained age ($\Delta\epsilon\%(E/PM)_t$ and $\Delta\epsilon\%(MRT)_t$); a correlation coefficient of > 0.55 is considered as statistically significant at 80% confidence

Correlation matrix	Un-certainty* in MRT	Most likely MRT	Un-certainty* in E/PM	Most likely E/PM	$\Delta\epsilon\%(MRT)_{hc}$	$\Delta\epsilon\%(E/PM)_{hc}$	$\Delta\epsilon\%(MRT)_t$	$\Delta\epsilon\%(E/PM)_t$
All behavioural hydrochemistry-PT relationships								
Uncertainty* in MRT	1							
most likely MRT	-0.17	1						
Uncertainty* in E/PM	0.75	-0.72	1					
most likely E/PM	-0.32	0.02	-0.17	1				
$\Delta\epsilon\%(MRT)_{hc}$	0.44	0.03	0.22	-0.57	1			
$\Delta\epsilon\%(E/PM)_{hc}$	0.26	-0.60	0.63	0.29	-0.01	1		
$\Delta\epsilon\%(MRT)_t$	-0.92	-0.14	-0.49	0.26	-0.50	-0.04	1	
$\Delta\epsilon\%(E/PM)_t$	-0.10	-0.02	-0.21	0.00	-0.05	-0.55	0.08	1
Only considering positive hydrochemistry-PT relationships								
Uncertainty* in MRT	1							
most likely MRT	-0.17	1						
Uncertainty* in E/PM	0.75	-0.72	1					
most likely E/PM	-0.32	0.02	-0.17	1				
$\Delta\epsilon\%(MRT)_{hc}$	0.58	-0.24	0.47	-0.59	1			
$\Delta\epsilon\%(E/PM)_{hc}$	0.27	-0.60	0.65	0.29	0.07	1		
$\Delta\epsilon\%(MRT)_t$	-0.91	-0.15	-0.47	0.25	-0.53	-0.04	1	
$\Delta\epsilon\%(E/PM)_t$	-0.06	-0.06	-0.15	0.07	0.05	-0.52	0.09	1

D4.4 Constraining of inferred hydrochemistry of recharge with known relationships of hydrochemistry parameters

In the following the relationships found between K, Cl, Na, Si and/or TDS to explain Ca are presented including relevant statistics. All found relationships were statistically significant at the 95% confidence level (with $p < 0.05$ using the ANOVA test).

For all sites: $\text{Ca} = -1.40393 + 0.233872 \cdot \text{TDS} - 0.922262 \cdot \text{Na}$

$R^2 = 81.6385 \%$; R^2 (adjusted for d.f.) = 78.5783 %; Standard Error of Est. = 1.96054; Mean absolute error = 1.42839; Durbin-Watson statistic = 1.7671 ($P=0.3732$); Lag 1 residual autocorrelation = 0.05415

For all sites excluding Well 9: $\text{Ca} = -0.214764 + 0.228489 \cdot \text{TDS} - 0.119278 \cdot \text{Si} - 0.835252 \cdot \text{Na}$

$R^2 = 82.1731 \%$; R^2 (adjusted for d.f.) = 77.3112 %; Standard Error of Est. = 2.01769; Mean absolute error = 1.39374; Durbin-Watson statistic = 1.6832 ($P=0.3093$); Lag 1 residual autocorrelation = 0.0737961

For oxic sites: $\text{Ca} = -0.733212 + 0.246418 \cdot \text{TDS} - 1.38501 \cdot \text{K} - 0.120043 \cdot \text{Si} - 0.795653 \cdot \text{Na}$

$R^2 = 82.4666 \%$; R^2 (adjusted for d.f.) = 75.4532 %; Standard Error of Est. = 2.09868; Mean absolute error = 1.44997; Durbin-Watson statistic = 1.68259 ($P=0.3206$); Lag 1 residual autocorrelation = 0.0718791

For anoxic sites (including and excluding Well 9): $\text{Ca} = -9.62105 + 0.061941 \cdot \text{TDS} - 0.0340028 \cdot \text{Si} - 0.4399 \cdot \text{Na} + 1.17042 \cdot \text{Cl}$

$R^2 = 91.0283 \%$; R^2 (adjusted for d.f.) = 87.4397 %; Standard Error of Est. = 1.50124; Mean absolute error = 0.921459; Durbin-Watson statistic = 2.4997 ($P=0.8367$); Lag 1 residual autocorrelation = -0.268624

D5 References of Appendix

- Blum A. E. and L. L. Stillings (1995) Feldspar dissolution kinetics. In *Chemical Weathering Rates of Silicate Minerals* (eds. A. F. White and S. L. Brantley); *Reviews in Mineralogy*, Vol. 31, pp. 291–351. Mineral. Soc. Amer
- Bowen, N. L. (1928) *The evolution of the igneous rocks*: Princeton, New Jersey, Princeton University Press, 334 p.; second edition, 1956, New York, Dover.
- Brantley S.L. (2008) Kinetics of mineral dissolution. In: *Kinetics of Water–Rock Interaction* (eds Brantley S.F., Kubicki J.D., White A.F.). Springer Science Business Media LLC, New York, NY, pp. 151–210.
- Brantley, S.L. and N.P. Mellott (2000) Surface area and porosity of primary silicate minerals, *American Mineralogist*, Volume 85, pages 1767–178.
- Brown, L.J. and A. Jones (2000) *Moera Gravel Investigation Bore WRC Well Number 6386 Marsden Street, Lower Hutt*. A report prepared for GWRC, Publication No. WRC/RINV-T-00/30.
- Daughney, C.J.; Baker, T.; Jones, A.; Hanson, C.; Davidson, P.W.; Thompson, M.; Reeves, R.R. and G.M. Zemansky (2007) Comparison of groundwater sampling methods for State of the Environment monitoring in New Zealand. *J. Hydrol., New Zealand*, 46(1): 19-3
- Gilliom, R. J. and D.R. Helsel (1986) Estimation of distributional parameters for censored trace level water quality data, 1. Estimation techniques: *Water Res. Res.*, 22, p. 135–146.
- Grant-Taylor, T.L. (1967) *Groundwater in New Zealand*. NZGS report 24, presented at “Water of Peace” conference, 1967, Washington.

Gyopari, M. (2014) Lower Hutt Aquifer Model Revision (Ham3): Sustainable Management Of The Waiwhetu Aquifer, A Report Prepared For Greater Wellington Regional Council, June 2014.

Helsel D.R.(1990) Less than obvious—statistical treatment of data below the detection limit. *Environ Sci Technol.* 24, 1766–1774.

Knauss, I.G. and T.J. Wolery (1986) Dependence of albite dissolution kinetics on pH and time at 25 f and 70 'C. *Geochimica et Cosmo-chimica Acta*, 50, 2481-2497

Parkhurst, D.L. and C.A.J. Appelo (1999) User's guide to PHREEQC (Version 2)—A computer program for speciation, batch-reaction, one-dimensional transport, and inverse geochemical calculations: U.S. Geological Survey Water-Resources Investigations Report 99–4259, 312 pp.

Reynolds, T.I. (1993) Computer modelling of groundwater and evaluation of scenarios for pumping from the Waiwhetu Aquifer, Lower Hutt basin. Wellington Regional Council Publication No. WRC/CI-G-93/45. Vols 1-3, 142p + 4 apps.

Rowe, G.H. (1980) Applied Geology of Wellington Rocks for Aggregate and Concrete, PhD, Victoria University of Wellington.

Sanford, R.F.; Pierson, C.T. and R.A. Crovelli (1993) An objective replacement method for censored geochemical data, *Mathematical Geology* 25, pp. 59-80, Doi:10.1007/BF00890676

Tabachnick, B.G. and L.S. Fidell (1996). *Using multivariate statistics* (3rd ed.). New York: Harper Collins